

General		Unit
User terminal type	-	Typ-60cm
Carrier designator	-	3M16G7W
Data rate (kbps)	(kbps)	1023
Coding rate	-	1/2
Modulation	-	BPSK
Occupied bandwidth	(kHz)	2630.3
Allocated bandwidth	(kHz)	3156.3
Uplink		
Beam		User-Spot
Frequency	(GHz)	29.75
User Terminal EIRP	(dBW)	49.2
Antenna tx gain	dBi	43.6
Uplink power	(dBW)	5.6
<i>Uplink p.s.d.</i>	(dBW/Hz)	-58.6
Path loss	(dB)	213.6
Rain loss	(dB)	7.0
Mean Atmospheric loss	(dB)	1.7
Satellite G/T (EOC)	(dB/K)	9.6
Up-path C/No	(dBHz)	65.0
Up-path C/N	(dB)	0.8
Downlink		
Beam		Feeder
Frequency	(GHz)	18.95
Beam Peak to Edge of Coverage	(dB)	3.0
<i>Max pfd per crx @ earth surface(EOC)</i>	(dBW/m ² /1MHz)	-147.0
Satellite EIRP (EOC)	(dBW)	19.3
Satellite EIRP density (EOC)	(dBW/Hz)	-44.9
Path loss	(dB)	209.7
Rain loss	(dB)	5.6
Mean Atmospheric loss	(dB)	0.7
Earth Station G/T	(dB/K)	42.0
G/T degradation due to rain	(dB)	2.4
Rx terminal Pointing loss	(dB)	0
Co-Channel / adj . beam interf. (dn)	(dBHz)	164.2
Down-path C/No	(dBHz)	71.5
Down-path C/N	(dB)	7.3
Total		
Mean satellite C/Imo	(dBHz)	76.2
Mean Overall C/No	(dBHz)	63.9
Total C/I (adjacent satellite interference)	(dB)	15.3
Mean Overall C/N (incl. a.s.i)	(dB)	-0.4
Margin		
C/N required	(dB)	-1.0
C/N margin	(dB)	0.6

C/I calculations

Orbital separation (interferor 1)	degree	2.0
Worst case topocentric angle (1)	degree	2.09
Uplink C/I		
Interferor 1		
Max. uplink p.s.d	(dBW/Hz)	-56.5
Other's sidelobe at 2 deg. sep X-25log(t)		29.0
Tx Sidelobe gain at 2 deg sep	dBi	21.0
<i>Inm-Ka C/I up1</i>	<i>dB</i>	<i>17.5</i>
Downlink C/I		
Interferor 1		
Max. ground PFD	(dBW/m2/MHz)	-121.1
Max. downlink EIRP s.d	(dBW/Hz)	-19.0
Inm Rx sidelobe gain at 2 deg sep	dBi	21.0
Inm-Ka C/I dn1	dB	19.3
Total C/I (adjacent satellite interference)	dB	15.3