

## **Analysis of Non-Ionizing Radiation for a 2.4 m Earth Station Antenna System**

This report analyzes the non-ionizing radiation levels for a 2.4 m Ka-band earth station antenna system employing a 20 W power amplifier.

The FCC's Office of Engineering Technology's Bulletin No. 65 specifies that there are two separate tiers of exposure limits that are dependant upon the situation in which the exposure takes place and/or the status of the individuals who are subject to the exposure. The two tiers are General Population / Uncontrolled environment, and an Occupational / Controlled environment.

The applicable exposure limit for the General Population / Uncontrolled environment, i.e., areas that people may enter freely, at this frequency of operation is  $1 \text{ mW/cm}^2$  average power density over a 30 minute period.

The applicable exposure limit for the Occupational / Controlled environment, i.e., areas that only authorized / trained personnel have access to, at this frequency of operation is  $5 \text{ mW/cm}^2$  average power density over a 6 minute period.

### **Summary of expected radiation levels for a controlled environment**

<b><u>Region</u></b>	<b><u>Maximum Power Density</u></b>	<b><u>Hazard Assessment</u></b>
Far field ( $R_{ff}$ ) = 345.839 m	0.167 $\text{mW/cm}^2$	Satisfies FCC MPE
Near field ( $R_{nf}$ ) = 144.1 m	0.814 $\text{mW/cm}^2$	Satisfies FCC MPE
Transition region ( $R_t$ ) ( $R_t$ ) = $R_{nf} < R_t < R_{ff}$	0.232 $\text{mW/cm}^2$	Satisfies FCC MPE
Main Reflector Surface ( $S_{surface}$ )	1.252 $\text{mW/cm}^2$	Satisfies FCC MPE

Note, power density level in the area between the feed and the reflector surface is greater than the reflector surface and is assumed to be a potential hazard.

## **Summary of expected radiation levels for an uncontrolled environment**

<b><u>Region</u></b>	<b><u>Maximum Power Density</u></b>	<b><u>Hazard Assessment</u></b>
Far field ( $R_{ff}$ ) = 325.839 m	0.167 mW/cm <sup>2</sup>	Satisfies FCC MPE
Near field ( $R_{nf}$ ) = 144.1 m	0.814 mW/cm <sup>2</sup>	Satisfies FCC MPE
Transition region ( $R_t$ ) ( $R_t$ ) = $R_{nf} < R_t < R_{ff}$	0.232 mW/cm <sup>2</sup>	Satisfies FCC MPE
Main Reflector Surface ( $S_{surface}$ )	1.252 mW/cm <sup>2</sup>	Potential Hazard

Note, power density level in the area between the feed and the reflector surface is greater than the reflector surface and is assumed to be a potential hazard.

## **Conclusions**

The proposed earth station system will be located on a secured rooftop at a commercial satellite communications gateway facility with controlled access and will be serviced by trained personnel.

While the power level at the reflector surface is below the threshold for uncontrolled or occupational access, levels between the reflector and the feed area are presumed to be a potential hazard; therefore, no access to this area will be permitted when the transmitter is turned on.

Based on the above analysis it is concluded that no hazard exists for the public or for trained personnel.

## Analysis

The analysis and calculations that follow in this report are performed in compliance with the methods described in the OET Bulletin No. 65.

## Definition of terms

The terms are used in the formulas here are defined as follows:

$S_{\text{surface}}$  = maximum power density at the antenna surface

$S_{\text{nf}}$  = maximum near-field power density

$S_{\text{t}}$  = power density in the transition region

$S_{\text{ff}}$  = power density (on axis)

$R_{\text{nf}}$  = extent of near-field

$R_{\text{ff}}$  = distance to the beginning of the far-field

$R$  = distance to point of interest

$P_{\text{a}}$  = 20 W maximum power amplifier output

$L_{\text{fs}}$  = 1.5 dB loss between power amplifier and antenna feed

$P$  = 14.159 W power fed to the antenna in Watts

$A$  = 4.254 m<sup>2</sup> physical area of the aperture antenna

$G$  = 3.7 x 10<sup>5</sup> power gain relative to an isotropic radiator

$D$  = 2.4 m diameter of antenna in meters

$F$  = 30,000 frequency in MHz

$\lambda$  = 0.01 cm wavelength in meters (300/ $F_{\text{MHz}}$ )

$\eta$  = 0.65 aperture efficiency

**Antenna Surface.** The maximum power density directly in front of an antenna (e.g., at the antenna surface) can be approximated by the following equation:

$$\begin{aligned} S_{\text{surface}} &= (4 * P) / A && (1.1) \\ &= (4 * 14.159 \text{ W}) / 4.524 \text{ m}^2 \\ &= 1.252 \text{ mW/cm}^2 \end{aligned}$$

**Near Field Region.** In the near-field or Fresnel region, of the main beam, the power density can reach a maximum before it begins to decrease with distance. The extent of the near field can be described by the following equation ( $D$  and  $\lambda$  in same units):

$$\begin{aligned} R_{\text{nf}} &= D^2 / (4 * \lambda) && (1.2) \\ &= (2.4 \text{ m})^2 / (4 * 0.01 \text{ m}) \\ &= 144.1 \text{ m} \end{aligned}$$

The magnitude of the on-axis (main beam) power density varies according to location in the near field. However, the maximum value of the near-field, on-axis, power density can be expressed by the following equation:

$$\begin{aligned}
 S_{nf} &= (16 * \eta * P) / (\pi * D^2) & (1.3) \\
 &= (16 * 0.65 * 14.159 \text{ W}) / (\pi * (2.4 \text{ m})^2) \\
 &= 0.814 \text{ mW/cm}^2
 \end{aligned}$$

**Transition Region.** Power density in the transition region decreases inversely with distance from the antenna, while power density in the far field (Fraunhofer region) of the antenna decreases inversely with the *square* of the distance. The transition region will then be the region extending from  $R_{nf}$  to  $R_{ff}$ . If the location of interest falls within this transition region, the on-axis power density can be determined from the following equation:

$$\begin{aligned}
 S_t &= (S_{nf} * R_{nf}) / R & (1.4) \\
 &= (0.814 \text{ mW/cm}^2 * 144.1 \text{ m}) / R \\
 &= (117.261 \text{ m} * \text{mW/cm}^2) / R \quad \text{where R is the location of interest in meters}
 \end{aligned}$$

**Far-Field Region.** The power density in the far-field or Fraunhofer region of the antenna pattern decreases inversely as the square of the distance. The distance to the start of the far field can be calculated by the following equation:

$$\begin{aligned}
 R_{ff} &= (0.6 * D^2) / \lambda & (1.5) \\
 &= (0.6 * (2.4 \text{ m})^2) / 0.01 \text{ m} \\
 &= 345.839 \text{ m}
 \end{aligned}$$

The power density at the start of the far-field region of the radiation pattern can be estimated by the equation:

$$\begin{aligned}
 S_{ff} &= (P * G) / (4 * \pi * R_{ff}^2) & (1.6) \\
 &= (14.159 \text{ W} * 3.7 * 10^5) / (4 * \pi * (345.839 \text{ m})^2) \\
 &= 0.232 \text{ mW/cm}^2
 \end{aligned}$$