

FCC OET-65 RF Exposure Study - Satellite Uplink Facility

NBC Digital Ku-band transportable uplink - "LOWBOY-R"

Antenna Vendor/Model	AVL 2410K
Antenna Size:	2.4m
Amplifier Make/Model:	MCL MT3400
Amplifier Max Output Power at flange:	310w.
Feed Flange Power after system loss of 0.1 dB	303w

FCC Maximum Permissible Exposure Levels	Source	Units
Public/uncontrolled area exposure limit	47CFR §1.1310	1 mW/cm ²
Occupational/controlled area exposure limit	47CFR §1.1310	5 mW/cm ²

Input Data

Antenna Diameter	datasheet	240.0 cm
Antenna surface area	calculated	45239 cm ²
Feed flange diameter	estimated	6.350 cm ²
Feed flange area	calculated	32
Frequency	(entry)	14125 MHz
Wavelength (speed of light = 299,792,458 m/s)	calculated	2.122 cm
Transmit power at flange	Application	303000 milliwatts
Antenna gain	datasheet	49 dBi
Antenna gain factor	calculated	79433
Height of base of antenna above ground	measured	3.81 m
Height of center of antenna above ground	measured	5.01 m
Minimum Elevation Angle	(entry)	5 degrees
Minimum Elevation Angle	calculated	0.08727 radians

Results calculated using FCC Bulletin OET-65 (Edition 97-01 August 1997)

			FCC Maximum Permissible Exposure (MPE)	
			Uncontrolled	Controlled
Maximum power density at antenna surface	Eq. 11 Pg 27	26.79 mW/cm ²	Potential Hazard	Potential Hazard
Power density at feed flange	Eq. 11 Pg 27	38270.6 mW/cm ²	Potential Hazard	Potential Hazard
Extent of near-field	Eq. 12 Pg 27	6785 cm		
Maximum near-field power density	Eq. 13 Pg 28	16.86 mW/cm ²	Potential Hazard	Potential Hazard
Aperture efficiency	Eq. 14 Pg 28	0.63		
Distance to beginning of far-field	Eq. 16 Pg 29	16283.26 cm		
Power density at end of the transition region	Eq. 17 Pg 29	7.03 mW/cm ²	Potential Hazard	Potential Hazard
Maximum far-field power density	Eq. 18 Pg 29	7.224 mW/cm ²	Potential Hazard	Potential Hazard

Main Beam Far-field region safe exposure distances

Minimum distance for public/uncontrolled exposure	Eq. 18 Pg 29	437.64 meters
Height at minimum antenna elevation angle	calculated	43.15 meters
Horizontal distance	calculated	435.97 meters
Minimum distance for occupational/controlled exposure	Eq. 18 Pg 29	195.72 meters
Height at minimum antenna elevation angle	calculated	22.07 meters
Horizontal distance	calculated	194.97 meters

Off-Axis Near Field/Transition Region safe exposure distances from antenna

(20 dB reduction in power density at distances greater than one antenna diameter from the main beam center.)	OET-65 Pg 30			
Maximum off-axis near field power density	Eq. 13 Pg 28	0.1686 mW/cm ²	Below FCC MPE	Below FCC MPE
Public/uncontrolled exposure off-axis distance	Diam/or Eq 17	2.4 meters		
Occupational/controlled exposure off-axis distance	Diam/or Eq 17	2.4 meters		

Off-Axis Far Field safe exposure distances from the antenna

(Based on side lobe attenuation required by FCC 25.209(a)(2))			
Angle off main beam axis (1 to 48 degrees)	(entry)	5 degree(s)	
Off-axis antenna gain factor	OET-65 Pg 30*	28	
Minimum distance for public/uncontrolled exposure	Eq. 18 Pg 29 **	162.83 meters	

* Gain converted from dBi to linear multiple

** If calculated distance is less than the start of the far field region, the distance to the start of the far field region is used.