

FCC OET-65 RF Exposure Study - Satellite Uplink Facility  
 Telemundo Digital Ku-band transportable uplink - "Hurricane"

FCC Maximum Permissible Exposure Levels	Source	Units
Public/uncontrolled area exposure limit	47CFR §1.1310	1 mW/cm <sup>2</sup>
Occupational/controlled area exposure limit	47CFR §1.1310	5 mW/cm <sup>2</sup>

**Input Data**

Antenna Diameter	datasheet	240.0 cm
Antenna surface area	calculated	45239 cm <sup>2</sup>
Sub-reflector diameter	measured	51.440 cm
Sub-reflector area	calculated	2078 cm <sup>2</sup>
Feed flange diameter	estimated	13.340 cm <sup>2</sup>
Feed flange area	calculated	140
Frequency	(entry)	14250 MHz
Wavelength (speed of light = 299,792,458 m/s)	calculated	2.104 cm
Transmit power at flange	Application	250000 milliwatts
Antenna gain	datasheet	48.7 dBi
Antenna gain factor	calculated	74131
Height of base of antenna above ground	measured	3.25 m
Height of center of antenna above ground	measured	5.35 m
Minimum Elevation Angle	(entry)	15 degrees
Minimum Elevation Angle	calculated	0.26180 radians

**Results calculated using FCC Bulletin OET-65 (Edition 97-01 August 1997)**

			FCC Maximum Permissible Exposure (MPE)	
			Uncontrolled	Controlled
Maximum power density at antenna surface	Eq. 11 Pg 27	22.1 mW/cm <sup>2</sup>	Potential Hazard	Potential Hazard
Power density at subreflector	Eq. 11 Pg 27	481.18 mW/cm <sup>2</sup>	N/A	N/A
Power density at feed flange	Eq. 11 Pg 27	7154.82 mW/cm <sup>2</sup>	Potential Hazard	Potential Hazard
Extent of near-field	Eq. 12 Pg 27	6845 cm		
Maximum near-field power density	Eq. 13 Pg 28	12.76 mW/cm <sup>2</sup>	Potential Hazard	Potential Hazard
Aperture efficiency	Eq. 14 Pg 28	0.58		
Distance to beginning of far-field	Eq. 16 Pg 29	16427.36 cm		
Power density at end of the transition region	Eq. 17 Pg 29	5.32 mW/cm <sup>2</sup>	Potential Hazard	Potential Hazard
Maximum far-field power density	Eq. 18 Pg 29	5.465 mW/cm <sup>2</sup>	Potential Hazard	Potential Hazard

**Main Beam Far-field region safe exposure distances**

Minimum distance for public/uncontrolled exposure	Eq. 18 Pg 29	384.03 meters
Height at minimum antenna elevation angle	calculated	104.74 meters
Horizontal distance	calculated	370.94 meters
Minimum distance for occupational/controlled exposure	Eq. 18 Pg 29	171.74 meters
Height at minimum antenna elevation angle	calculated	49.8 meters
Horizontal distance	calculated	165.89 meters

**Off-Axis Near Field/Transition Region safe exposure distances from antenna**

(20 dB reduction in power density at distances greater than one antenna diameter from the main beam center.)				
	OET-65 Pg 30			
Maximum off-axis near field power density	Eq. 13 Pg 28	0.1276 mW/cm <sup>2</sup>	Below FCC MPE	Below FCC MPE
Public/uncontrolled exposure off-axis distance	Diam/or Eq 17	2.4 meters		
Occupational/controlled exposure off-axis distance	Diam/or Eq 17	2.4 meters		

**Off-Axis Far Field safe exposure distances from the antenna**

(Based on side lobe attenuation required by FCC 25.209(a)(2))				
Angle off main beam axis (1 to 48 degrees)	(entry)	15 degree(s)		
Off-axis antenna gain factor	OET-65 Pg 30*	2		
Minimum distance for public/uncontrolled exposure	Eq. 18 Pg 29 **	164.27 meters		

\* Gain converted from dBi to linear multiple

\*\* If calculated distance is less than the start of the far field region, the distance to the start of the far field region is used.