

General	Unit	
User terminal type	-	Typ-150cm
Carrier designator	-	4M78G7W
Data rate (kbps)	(kbps)	5140
Coding rate	-	3/4
Modulation	-	QPSK
Occupied bandwidth	(kHz)	3981.1
Allocated bandwidth	(kHz)	4777.3
Uplink		User-Spot
Beam		
Frequency	(GHz)	29.75
User Terminal EIRP	(dBW)	59.5
Antenna tx gain	dBi	51.5
Uplink power	(dBW)	8.0
<i>Uplink p.s.d.</i>	<i>(dBW/Hz)</i>	<i>-58.0</i>
Path loss	(dB)	213.6
Rain loss	(dB)	7.0
Mean Atmospheric loss	(dB)	1.7
Satellite G/T (EOC)	(dB/K)	9.6
Up-path C/No	(dBHz)	74.9
Up-path C/N	(dB)	8.9
Downlink		Feeder
Beam		
Frequency	(GHz)	18.95
Beam Peak to Edge of Coverage	(dB)	3.0
<i>Max pfd per crx @ earth surface(EOC)</i>	<i>(dBW/m2/1MHz)</i>	<i>-141.5</i>
Satellite EIRP (EOC)	(dBW)	26.6
Satellite EIRP density (EOC)	(dBW/Hz)	-39.4
Path loss	(dB)	209.7
Rain loss	(dB)	5.6
Mean Atmospheric loss	(dB)	0.7
Earth Station G/T	(dB/K)	42.0
G/T degradation due to rain	(dB)	2.4
Rx terminal Pointing loss	(dB)	0
Co-Channel / adj . beam interf. (dn)	(dBHz)	166.0
Down-path C/No	(dBHz)	78.8
Down-path C/N	(dB)	12.8
Total		
Mean satellite C/Imo	(dBHz)	83.5
Mean Overall C/No	(dBHz)	73.0
Total C/I (adjacent satellite interference)	(dB)	22.3
Mean Overall C/N (incl. a.s.i)	(dB)	6.9
Margin		
C/N required	(dB)	5.6
C/N margin	(dB)	1.3

C/I calculations

Orbital separation (interferor 1)	degree	2.0
Worst case topocentric angle (1)	degree	2.09

Uplink C/I

Interferor 1		
Max. uplink p.s.d	(dBW/Hz)	-56.5
Other's sidelobe at 2 deg. sep X-25log(t)		29.0
Tx Sidelobe gain at 2 deg sep	dBi	21.0
Inm-Ka C/I up1	<i>dB</i>	26.0

Downlink C/I

Interferor 1		
Max. ground PFD	(dBW/m2/MHz)	-121.1
Max. downlink EIRP s.d	(dBW/Hz)	-19.0
Inm Rx sidelobe gain at 2 deg sep	dBi	21.0
Inm-Ka C/I dn1	dB	24.8
Total C/I (adjacent satellite interference)	dB	22.3