

FREQUENCY COORDINATION AND INTERFERENCE ANALYSIS REPORT

Prepared for
UltiSat
EILSON, AK
Satellite Earth Station

Prepared By:
COMSEARCH
19700 Janelia Farm Boulevard
Ashburn, VA 20147
March 18, 2016

TABLE OF CONTENTS

| | |
|---|----|
| 1. CONCLUSIONS | 3 |
| 2. SUMMARY OF RESULTS | 4 |
| 3. SUPPLEMENTAL SHOWING | 5 |
| 4. EARTH STATION COORDINATION DATA..... | 6 |
| 5. CERTIFICATION..... | 10 |

1. CONCLUSIONS

An interference study considering all existing, proposed and prior coordinated microwave facilities within the coordination contours of the proposed earth station demonstrates that this site will operate satisfactorily with the common carrier microwave environment. Further, there will be no restrictions of its operation due to interference considerations.

2. SUMMARY OF RESULTS

A number of great circle interference cases were identified during the interference study of the proposed earth station. Each of the cases, which exceeded the interference objective on a line-of-sight basis, was profiled and the propagation losses estimated using NBS TN101 (Revised) techniques. The losses were found to be sufficient to reduce the signal levels to acceptable magnitudes in every case.

The following companies reported potential great circle interference conflicts that did not meet the objectives on a line-of-sight basis. When over-the-horizon losses are considered on the interfering paths, sufficient blockage exists to negate harmful interference from occurring with the proposed transmit-receive earth station.

Company

Alascom Inc
Golden Valley Electric Association, Inc.
State of Alaska

No other carriers reported potential interference cases.

3. SUPPLEMENTAL SHOWING

Pursuant to Part 25.203(c) of the FCC Rules and Regulations, the satellite earth station proposed in this application was coordinated by Comsearch using computer techniques and in accordance with Part 25 of the FCC Rules and Regulations.

Coordination data for this earth station was sent to the below listed carriers with a letter dated 01/28/2016.

Company

ACS of the Northland License Sub, LLC
Alascom Inc
DRS Technical Services
Golden Valley Electric Association, Inc.
New Cingular Wireless PCS LLC - Alaska
SUMMIT TELEPHONE COMPANY
State of Alaska

4. EARTH STATION COORDINATION DATA

This section presents the data pertinent to frequency coordination of the proposed earth station that was circulated to all carriers within its coordination contours.

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Date: 03/18/2016
Job Number: 160128COMSGE08

Administrative Information

Status ENGINEER PROPOSAL
Call Sign
Licensee Code ULITSA
Licensee Name UltiSat

Site Information EILSON, AK

Venue Name
Latitude (NAD 83) 64° 38' 8.3" N
Longitude (NAD 83) 147° 2' 47.4" W
Climate Zone A
Rain Zone 2
Ground Elevation (AMSL) 168.03 m / 551.3 ft

Link Information

Satellite Type Geostationary
Mode TR - Transmit-Receive
Modulation Digital
Satellite Arc 177° W to 177° West Longitude
Azimuth Range 212.5° to 212.5°
Corresponding Elevation Angles 13.3° / 13.3°
Antenna Centerline (AGL) 24.08 m / 79.0 ft

Antenna Information

| | | Receive - FCC32 | | Transmit - FCC32 | |
|--------------------------|-------------|------------------|-------|------------------|---------|
| Manufacturer | | Prodelin | | Prodelin | |
| Model | | 1251 | | 1251 | |
| Gain / Diameter | | 38.0 dBi / 2.4 m | | 42.0 dBi / 2.4 m | |
| 3-dB / 15-dB Beamwidth | | 2.30° / 4.60° | | 1.36° / 2.72° | |
| Max Available RF Power | (dBW/4 kHz) | | | -10.0 | |
| | (dBW/MHz) | | | 14.0 | |
| Maximum EIRP | (dBW/4 kHz) | | | 32.0 | |
| | (dBW/MHz) | | | 56.0 | |
| Interference Objectives: | Long Term | -156.0 dBW/MHz | 20% | -154.0 dBW/4 kHz | 20% |
| | Short Term | -146.0 dBW/MHz | 0.01% | -131.0 dBW/4 kHz | 0.0025% |

Frequency Information

| | Receive 4.0 GHz | Transmit 6.1 GHz |
|--|-------------------------------------|--|
| Emission / Frequency Range (MHz) | 87K0G7D - 100KG7D / 3700.0 - 4200.0 | 87K0G7D - 100KG7D / 6061.0 - 6067.0 87K0G7D - 100KG7D / 6182.0 - 6230.0 87K0G7D - 100KG7D / 6283.0 - 6289.0 87K0G7D - 100KG7D / 6341.0 - 6359.0 |
| Max Great Circle Coordination Distance | 385.7 km / 239.6 mi | 195.4 km / 121.4 mi |
| Precipitation Scatter Contour Radius | 525.1 km / 326.2 mi | 100.0 km / 62.1 mi |

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Coordination Values

EILSON, AK

Licensee Name UltiSat
Latitude (NAD 83) 64° 38' 8.3" N
Longitude (NAD 83) 147° 2' 47.4" W
Ground Elevation (AMSL) 168.03 m / 551.3 ft
Antenna Centerline (AGL) 24.08 m / 79.0 ft
Antenna Model Prodelin 2.4 Meter
Antenna Mode Receive 4.0 GHz Transmit 6.1 GHz
Interference Objectives: Long Term -156.0 dBW/MHz 20% -154.0 dBW/4 kHz 20%
Short Term -146.0 dBW/MHz 0.01% -131.0 dBW/4 kHz 0.0025%
Max Available RF Power -10.0 (dBW/4 kHz)

| Azimuth (°) | Horizon Elevation (°) | Antenna Discrimination (°) | Receive 4.0 GHz | | Transmit 6.1 GHz | |
|-------------|-----------------------|----------------------------|--------------------|----------------------------|--------------------|----------------------------|
| | | | Horizon Gain (dBi) | Coordination Distance (km) | Horizon Gain (dBi) | Coordination Distance (km) |
| 0 | 0.00 | 145.13 | -10.00 | 285.28 | -10.00 | 143.12 |
| 5 | 0.00 | 149.65 | -10.00 | 285.28 | -10.00 | 143.12 |
| 10 | 0.00 | 154.01 | -10.00 | 285.28 | -10.00 | 143.12 |
| 15 | 0.25 | 158.26 | -10.00 | 278.62 | -10.00 | 138.29 |
| 20 | 0.39 | 162.07 | -10.00 | 261.94 | -10.00 | 128.01 |
| 25 | 0.43 | 165.10 | -10.00 | 257.38 | -10.00 | 124.81 |
| 30 | 0.57 | 167.01 | -10.00 | 245.00 | -10.00 | 115.99 |
| 35 | 0.63 | 167.07 | -10.00 | 241.21 | -10.00 | 113.18 |
| 40 | 0.52 | 165.20 | -10.00 | 248.60 | -10.00 | 118.62 |
| 45 | 0.89 | 162.46 | -10.00 | 226.30 | -10.00 | 101.66 |
| 50 | 1.00 | 158.73 | -10.00 | 220.18 | -10.00 | 100.00 |
| 55 | 1.16 | 154.60 | -10.00 | 215.27 | -10.00 | 100.00 |
| 60 | 1.30 | 150.20 | -10.00 | 211.31 | -10.00 | 100.00 |
| 65 | 1.80 | 145.75 | -10.00 | 199.82 | -10.00 | 100.00 |
| 70 | 1.93 | 141.08 | -10.00 | 196.35 | -10.00 | 100.00 |
| 75 | 1.89 | 136.30 | -10.00 | 197.63 | -10.00 | 100.00 |
| 80 | 1.47 | 131.41 | -10.00 | 206.51 | -10.00 | 100.00 |
| 85 | 0.92 | 126.50 | -10.00 | 224.80 | -10.00 | 100.45 |
| 90 | 0.36 | 121.60 | -10.00 | 265.69 | -10.00 | 130.61 |
| 95 | 0.00 | 116.72 | -10.00 | 285.28 | -10.00 | 143.12 |
| 100 | 0.00 | 111.89 | -10.00 | 285.28 | -10.00 | 143.12 |
| 105 | 0.00 | 107.04 | -10.00 | 285.28 | -10.00 | 143.12 |
| 110 | 0.28 | 102.20 | -10.00 | 275.16 | -10.00 | 135.84 |
| 115 | 0.00 | 97.32 | -10.00 | 285.28 | -10.00 | 143.12 |
| 120 | 0.00 | 92.46 | -10.00 | 285.28 | -10.00 | 143.12 |
| 125 | 0.00 | 87.59 | -10.00 | 285.28 | -10.00 | 143.12 |
| 130 | 0.00 | 82.73 | -10.00 | 285.28 | -10.00 | 143.12 |
| 135 | 0.23 | 77.85 | -10.00 | 281.29 | -10.00 | 140.20 |
| 140 | 0.35 | 72.99 | -10.00 | 267.32 | -10.00 | 131.73 |
| 145 | 0.37 | 68.13 | -10.00 | 264.29 | -10.00 | 129.64 |
| 150 | 0.85 | 63.23 | -10.00 | 228.38 | -10.00 | 103.32 |
| 155 | 0.39 | 58.45 | -10.00 | 261.97 | -10.00 | 128.03 |
| 160 | 0.00 | 53.70 | -10.00 | 285.28 | -10.00 | 143.12 |
| 165 | 0.00 | 48.92 | -10.00 | 285.28 | -10.00 | 143.12 |
| 170 | 0.00 | 44.18 | -9.13 | 290.87 | -9.13 | 145.87 |
| 175 | 0.00 | 39.49 | -7.91 | 298.91 | -7.91 | 149.89 |
| 180 | 0.00 | 34.87 | -6.56 | 308.10 | -6.56 | 154.55 |
| 185 | 0.00 | 30.35 | -5.05 | 319.29 | -5.05 | 160.00 |

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Coordination Values


EILSON, AK

| | | | | |
|------------------------------------|---------------------|-------|-------------------|---------|
| Licensee Name | UltiSat | | | |
| Latitude (NAD 83) | 64° 38' 8.3" N | | | |
| Longitude (NAD 83) | 147° 2' 47.4" W | | | |
| Ground Elevation (AMSL) | 168.03 m / 551.3 ft | | | |
| Antenna Centerline (AGL) | 24.08 m / 79.0 ft | | | |
| Antenna Model | Prodelin 2.4 Meter | | | |
| Antenna Mode | Receive 4.0 GHz | | Transmit 6.1 GHz | |
| Interference Objectives: Long Term | -156.0 dBW/MHz | 20% | -154.0 dBW/4 kHz | 20% |
| Short Term | -146.0 dBW/MHz | 0.01% | -131.0 dBW/4 kHz | 0.0025% |
| Max Available RF Power | | | -10.0 (dBW/4 kHz) | |

| Azimuth (°) | Horizon Elevation (°) | Antenna Discrimination (°) | Receive 4.0 GHz | | Transmit 6.1 GHz | |
|-------------|-----------------------|----------------------------|--------------------|----------------------------|--------------------|----------------------------|
| | | | Horizon Gain (dBi) | Coordination Distance (km) | Horizon Gain (dBi) | Coordination Distance (km) |
| 190 | 0.00 | 25.99 | -3.37 | 331.41 | -3.37 | 168.04 |
| 195 | 0.00 | 21.89 | -1.50 | 345.20 | -1.50 | 175.30 |
| 200 | 0.00 | 18.21 | 0.49 | 360.39 | 0.49 | 183.03 |
| 205 | 0.00 | 15.27 | 2.40 | 375.34 | 2.40 | 190.40 |
| 210 | 0.00 | 13.56 | 3.70 | 385.67 | 3.70 | 195.35 |
| 215 | 0.00 | 13.55 | 3.70 | 385.72 | 3.70 | 195.37 |
| 220 | 0.00 | 15.24 | 2.42 | 375.48 | 2.42 | 190.46 |
| 225 | 0.00 | 18.18 | 0.51 | 360.55 | 0.51 | 183.11 |
| 230 | 0.00 | 21.85 | -1.49 | 345.35 | -1.49 | 175.38 |
| 235 | 0.00 | 25.95 | -3.35 | 331.53 | -3.35 | 168.11 |
| 240 | 0.00 | 30.31 | -5.04 | 319.40 | -5.04 | 160.06 |
| 245 | 0.00 | 34.82 | -6.55 | 308.20 | -6.55 | 154.60 |
| 250 | 0.00 | 39.44 | -7.90 | 298.99 | -7.90 | 149.93 |
| 255 | 0.00 | 44.13 | -9.12 | 290.94 | -9.12 | 145.91 |
| 260 | 0.00 | 48.87 | -10.00 | 285.28 | -10.00 | 143.12 |
| 265 | 0.00 | 53.65 | -10.00 | 285.28 | -10.00 | 143.12 |
| 270 | 0.00 | 58.45 | -10.00 | 285.28 | -10.00 | 143.12 |
| 275 | 0.00 | 63.28 | -10.00 | 285.28 | -10.00 | 143.12 |
| 280 | 0.00 | 68.11 | -10.00 | 285.28 | -10.00 | 143.12 |
| 285 | 0.00 | 72.96 | -10.00 | 285.28 | -10.00 | 143.12 |
| 290 | 0.00 | 77.82 | -10.00 | 285.28 | -10.00 | 143.12 |
| 295 | 0.00 | 82.68 | -10.00 | 285.28 | -10.00 | 143.12 |
| 300 | 0.00 | 87.54 | -10.00 | 285.28 | -10.00 | 143.12 |
| 305 | 0.00 | 92.41 | -10.00 | 285.28 | -10.00 | 143.12 |
| 310 | 0.00 | 97.27 | -10.00 | 285.28 | -10.00 | 143.12 |
| 315 | 0.00 | 102.13 | -10.00 | 285.28 | -10.00 | 143.12 |
| 320 | 0.00 | 106.99 | -10.00 | 285.28 | -10.00 | 143.12 |
| 325 | 0.00 | 111.84 | -10.00 | 285.28 | -10.00 | 143.12 |
| 330 | 0.00 | 116.68 | -10.00 | 285.28 | -10.00 | 143.12 |
| 335 | 0.00 | 121.50 | -10.00 | 285.28 | -10.00 | 143.12 |
| 340 | 0.00 | 126.30 | -10.00 | 285.28 | -10.00 | 143.12 |
| 345 | 0.00 | 131.08 | -10.00 | 285.28 | -10.00 | 143.12 |
| 350 | 0.00 | 135.82 | -10.00 | 285.28 | -10.00 | 143.12 |
| 355 | 0.00 | 140.51 | -10.00 | 285.28 | -10.00 | 143.12 |

5. CERTIFICATION

I HEREBY CERTIFY THAT I AM THE TECHNICALLY QUALIFIED PERSON RESPONSIBLE FOR THE PREPARATION OF THE FREQUENCY COORDINATION DATA CONTAINED IN THIS APPLICATION, THAT I AM FAMILIAR WITH PARTS 101 AND 25 OF THE FCC RULES AND REGULATIONS, THAT I HAVE EITHER PREPARED OR REVIEWED THE FREQUENCY COORDINATION DATA SUBMITTED WITH THIS APPLICATION, AND THAT IT IS COMPLETE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

BY: 

Gary K. Edwards
Senior Manager
COMSEARCH
19700 Janelia Farm Boulevard
Ashburn, VA 20147

DATED: March 18, 2016