

# FCC OET-65 RF Exposure Study - Satellite Uplink Facility

## NBC Digital Ku-band transportable uplink - "Blue"

<b>Antenna Vendor/Model</b>	Vislink-Advent
<b>Antenna Size:</b>	1.9m
<b>Amplifier Make/Model:</b>	Xicom XTD-400K
<b>Amplifier Max Output Power:</b>	400w
<b>Maximum operating power at flange:</b>	100w

FCC Maximum Permissible Exposure Levels	Source	Units
Public/uncontrolled area exposure limit	47CFR §1.1310	1 mW/cm <sup>2</sup>
Occupational/controlled area exposure limit	47CFR §1.1310	5 mW/cm <sup>2</sup>

### Input Data

Antenna Diameter	datasheet	190.0 cm
Antenna surface area	calculated	28353 cm <sup>2</sup>
Feed flange diameter	estimated	4.200 cm
Feed flange area	calculated	13.85 cm <sup>2</sup>
Frequency	(entry)	14250 MHz
Wavelength (speed of light = 299,792,458 m/s)	calculated	2.104 cm
Transmit power at flange	Application	100000 milliwatts
Antenna gain	datasheet	47.2 dBi
Antenna gain factor	calculated	52481
Height of base of antenna above ground	measured	1.2 m
Height of center of antenna above ground	measured	1.5 m
Minimum Elevation Angle	(entry)	5 degrees
Minimum Elevation Angle	calculated	0.08727 radians

### Results calculated using FCC Bulletin OET-65 (Edition 97-01 August 1997)

			FCC Maximum Permissible Exposure (MPE)	
			Uncontrolled	Controlled
Maximum power density at antenna surface	Eq. 11 Pg 27	14.11 mW/cm <sup>2</sup>	Potential Hazard	Potential Hazard
Power density at feed flange	Eq. 11 Pg 27	28871.65 mW/cm <sup>2</sup>	Potential Hazard	Potential Hazard
Extent of near-field	Eq. 12 Pg 27	4290 cm		
Maximum near-field power density	Eq. 13 Pg 28	9.2 mW/cm <sup>2</sup>	Potential Hazard	Potential Hazard
Aperture efficiency	Eq. 14 Pg 28	0.65		
Distance to beginning of far-field	Eq. 16 Pg 29	10295.62 cm		
Power density at end of the transition region	Eq. 17 Pg 29	3.83 mW/cm <sup>2</sup>	Potential Hazard	Below FCC MPE
Maximum far-field power density	Eq. 18 Pg 29	3.940 mW/cm <sup>2</sup>	Potential Hazard	Below FCC MPE

### Main Beam Far-field region safe exposure distances

Minimum distance for public/uncontrolled exposure	Eq. 18 Pg 29	204.36 meters
Height at minimum antenna elevation angle	calculated	19.31 meters
Horizontal distance	calculated	203.58 meters
Minimum distance for occupational/controlled exposure	Eq. 18 Pg 29	91.39 meters
Height at minimum antenna elevation angle	calculated	9.47 meters
Horizontal distance	calculated	91.04 meters

### Off-Axis Near Field/Transition Region safe exposure distances from antenna

(20 dB reduction in power density at distances greater than one antenna diameter from the main beam center.)				
	OET-65 Pg 30			
Maximum off-axis near field power density	Eq. 13 Pg 28	0.0920 mW/cm <sup>2</sup>	Below FCC MPE	Below FCC MPE
Public/uncontrolled exposure off-axis distance	Diam/or Eq 17	1.9 meters		
Occupational/controlled exposure off-axis distance	Diam/or Eq 17	1.9 meters		

### Off-Axis Far Field safe exposure distances from the antenna

(Based on side lobe attenuation required by FCC 25.209(a)(2))				
Angle off main beam axis (1 to 48 degrees)	(entry)	5 degree(s)		
Off-axis antenna gain factor	OET-65 Pg 30*	28		
Minimum distance for public/uncontrolled exposure	Eq. 18 Pg 29 **	102.96 meters		

\* Gain converted from dBi to linear multiple  
 \*\* If calculated distance is less than the start of the far field region, the distance to the start of the far field region is used.