# Ka-Band Earth Station – Gilman, VT Frequency Coordination Report 28 GHz



Prepared on Behalf of SPACE EXPLORATION HOLDINGS

February 18, 2021





## **Table of Contents**

1.	Summary of Results	- 1 -
2.	28 GHz Common Carrier and LTTS Coordination	- 1 -
3.	28 GHz UMFUS Coordination	- 2 -
4.	Earth Station Coordination Data	- 3 -
5.	Contact Information	- 7 -



#### 1. Summary of Results

On behalf of SPACE EXPLORATION HOLDINGS, Comsearch performed a coordination notice under Section 25.203(c) and Section 25.136(a)(4) of the FCC's rules for all existing and proposed terrestrial licenses within the coordination contours of their proposed Ka-Band earth station in Gilman, VT, which will transmit at 28 GHz<sup>1</sup>. Prior-notification letters were sent to the licensees and a copy of the notification data is provided in section four of this report. The earth station coordination was finalized on February 18, 2021.

No objections were received from any of the incumbent 28 GHz licensees.

#### 2. 28 GHz Common Carrier and LTTS Coordination

In accordance with FCC Rules and Regulations, the Ka-Band earth station in Gilman, VT was prior-coordinated by Comsearch. A notification letter and datasheets for this earth station were sent to the following 28 GHz common carrier fixed microwave licensees. These licensees are authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis or local basis.

Licensee	Authorized Geographic Area
Frontier	Nationwide

A notification letter and datasheets for the Ka-Band earth station in Gilman, VT were also sent to the following 28 GHz local television transmission licensee. This licensee is authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis.

Licensee	Authorized Geographic Area
Information Super Station, LLC	Continental US

No objections were received from the common carrier or local television transmission service incumbents.

 $<sup>^{\</sup>rm 1}$  The proposed earth station will operate in the 27.5 – 29.1 GHz & 29.5 – 30.0 GHz portion of the Ka-Band.



#### **3.** 28 GHz UMFUS Coordination

There were three 28 GHz UMFUS licensees identified within the coordination distance of the proposed earth station. The proposed earth station will operate on frequencies that overlap Channel L1 & L2 of the UMFUS service. The total frequency allocation for Channels L1 & L2 of the UMFUS spectrum appears below.

Channel:	L1	27.500 - 27.925 GHz
	L2	27.925 - 28.350 GHz

Licensee	Authorized Geographic Area
T-Mobile	Market Based
US Cellular	Market Based
Verizon	Market Based

No objections were received from the UMFUS incumbents within coordination distance.



## 4. Earth Station Coordination Data

This section presents the data pertinent to the proposed Ka-Band earth station in Gilman, VT. This data was circulated to all incumbent licensees in the shared 28 GHz frequency ranges.



Job Number:		210112COMSGE08				
Administrative Informa	ation					
		ENGINEER PROPOSAL				
Call Sign		SPACEX				
Licensee Code Licensee Name		Space Exploration Holding	c			
		-	9			
Site Information		GILMAN, VT				
Venue Name		110 241 42 25 11				
Latitude (NAD 83)		44° 24' 43.3" N				
Longitude (NAD 83)		71° 43' 54.6" W				
Climate Zone		A				
Rain Zone	13	2				
Ground Elevation (AMS	L)	265.54 m / 871.2 ft				
Link Information		5. 5. 1.80				
Satellite Type		Low Earth Orbit				
Mode		TR - Transmit-Receive				
Modulation		Digital				
Minimum Elevation Ang	le	25.0°				
Azimuth Range		0.0° to 360°				
Antenna Centerline (AG	L)	0.91 m / 3.0 ft				
Antenna Information		Receive - FCC32		Transmit - FCC32		
Manufacturer		SpaceX		SpaceX		
Model		1.47 meter		1.47 meter		
Gain / Diameter		46.9 dBi / 1.5 m		49.5 dBi / 1.5 m		
3-dB / 15-dB Beamwidth	n	0.77° / 1.70°		0.49° / 1.17°		
Max Available RF Power	(dBW/4 kH	7)		-39.8		
	(dBW/MHz			-15.8		
Maximum EIRP	(dBW/4 kH	7)		97		
	(dBW/MHz	A. C.		33.7		
Interference Objectives:	Long Term	-156.0 dBW/MHz	20%	-151.0 dBW/4 kHz 20%		
and seems a second	Short Term	-146.0 dBW/MHz	0.01%	-128.0 dBW/4 kHz 0.0025%		
Frequency Information		Receive 18.0 GHz		Transmit 28.0 GHz		
Emission / Frequency Range (MHz)		62M5D7W - 480MD7W / 17800 62M5D7W - 480MD7W / 18800		62M5D7W - 480MD7W / 27500.0 - 29100.0 62M5D7W - 480MD7W / 29500.0 - 30000.0		
Max Great Circle Coordinatio	n Distance	262.0 km / 162.8 m	ī	125.0 km / 77.7 mi		
Precipitation Scatter Contour	Radius	100.0 km / 62.1 mi		100.0 km / 62.1 mi		



#### SPACE EXPLORATION HOLDINGS Ka-Band Earth Station – Gilman, VT Frequency Coordination Report 28 GHz

Coordination Values Licensee Name Latitude (NAD 83) Longitude (NAD 83) Ground Elevation (AMSL) Antenna Centerline (AGL)		Space Exploration Holdin 44° 24' 43.3" N 71° 43' 54.6" W 265.54 m / 871.2 ft 0.91 m / 3.0 ft	71° 43' 54.6" W 265.54 m / 871.2 ft 0.91 m / 3.0 ft			
Antenna Mod Antenna Mod		SpaceX 1.47 meter Receive 18.0 GHz		Trope	mit 20 0 CH+	
	e Objectives: Long Tei		Transmit 28.0 GHz 20% -151.0 dBW/4 kHz 20%			
interierence (	Short		0.01%		0 dBW/4 kHz 0.0025%	
Max Availabl		140.0 00100002		BW/4 kHz)	0 0010 4 1012 0.0023 70	
			Receiv	ve 18.0 GHz	Transmit 28.0 GHz	
	Horizon	Antenna	Horizon	Coordination	Horizon	Coordinati
Azimuth (°)	Elevation (°)	Discrimination (°)	Gain (dBi)	Distance (km)	Gain (dBi)	Distance (
0	5.23	103.01	-3.00	262.00	-3.00	125.00
5	5.24	98.01	-3.00	262.00	-3.00	125.00
10	5.22	93.01	-3.00	262.00	-3.00	125.00
15	5.40	88.01	-3.00	262.00	-3.00	125.00
20	4.62	83.01	-3.00	262.00	-3.00	125.00
25	4.02	78.01	-3.00	262.00	-3.00	125.00
30	3.45	73.01	-3.00	262.00	-3.00	125.00
35	3.11	68.01	-3.00	262.00	-3.00	125.00
40	3.16	63.02	-3.00	262.00	-3.00	125.00
45	3.51	58.01	-3.00	262.00	-3.00	125.00
50	3.33	53.02	-3.00	262.00	-3.00	125.00
55	2.80	48.03	-3.00	262.00	-3.00	125.00
60	1.94	43.06	-3.00	262.00	-3.00	125.00
65	1.64	38.09	-3.00	262.00	-3.00	125.00
70	1.47	33.11	-3.00	262.00	-3.00	125.00
75	1.30	28.15	-3.00	262.00	-3.00	125.00
80	1.09	23.22	-3.00	262.00	-3.00	125.00
85	1.55	18.21	-3.00	262.00	-3.00	125.00
90	1.77	13.24	-3.00	262.00	-3.00	125.00
95	2.00	8.32	-3.00	262.00	-3.00	125.00
100	2.91	3.30	-3.00	262.00	-3.00	125.00
105	3.64	2.09	-3.00	262.00	-3.00	125.00
110	3.71	7.01	-3.00	262.00	-3.00	125.00
115	4.18	11.99	-3.00	262.00	-3.00	125.00
120	4.74	17.00	-3.00	262.00	-3.00	125.00
125	4.16	21.99	-3.00	262.00	-3.00	125.00
130	3.59	27.00	-3.00	262.00	-3.00	125.00
135	3.01	32.01	-3.00	262.00	-3.00	125.00
140	3.06	37.01	-3.00	262.00	-3.00	125.00
145 150	3.55	41.99	-3.00	262.00	-3.00	125.00
	3.97	46.99	-3.00	262.00	-3.00	125.00
155 160	3.70	51.99 57.00	-3.00	262.00 262.00	-3.00	
165	2.93 2.64	62.00	-3.00	262.00	-3.00 -3.00	125.00 125.00
			-3.00			125.00
170 175	2.74 2.60	67.00 72.00	-3.00 -3.00	262.00 262.00	-3.00 -3.00	125.00
180	3.03	76.99	-3.00	262.00	-3.00	125.00
185	3.53	81.99	-3.00	262.00	-3.00	125.00



#### SPACE EXPLORATION HOLDINGS Ka-Band Earth Station – Gilman, VT Frequency Coordination Report 28 GHz

Coordination Values Licensee Name Latitude (NAD 83) Longitude (NAD 83) Ground Elevation (AMSL) Antenna Centerline (AGL) Antenna Model Antenna Mode Interference Objectives: Long Term Short Ten Max Available RF Power			20% 0.01%	-151	smit 28.0 GHz .0 dBW/4 kHz 20% .0 dBW/4 kHz 0.0025%	
			Receiv	e 18.0 GHz	Transmit 28.0 GHz	
	Horizon	Antenna	Horizon	Coordination	Horizon	Coordination
Azimuth (°)	Elevation (°)	Discrimination (°)	Gain (dBi)	Distance (km)	Gain (dBi)	Distance (km
190	4.04	86.99	-3.00	262.00	-3.00	125.00
195	4.25	91.99	-3.00	262.00	-3.00	125.00
200	4.10	96.99	-3.00	262.00	-3.00	125.00
205	4.26	101.99	-3.00	262.00	-3.00	125.00
210	4.22	106.99	-3.00	262.00	-3.00	125.00
215	3.48	111.99	-3.00	262.00	-3.00	125.00
220	2.99	116.98	-3.00	262.00	-3.00	125.00
225	2.50	121.97	-3.00	262.00	-3.00	125.00
230	1.87	126.95	-3.00	262.00	-3.00	125.00
235	1.49	131.93	-3.00	262.00	-3.00	125.00
240	2.17	136.95	-3.00	262.00	-3.00	125.00
245	2.61	141.96	-3.00	262.00	-3.00	125.00
250	2.84	146.96	-3.00	262.00	-3.00	125.00
255	3.21	151.97	-3.00	262.00	-3.00	125.00
260	3.41	156.97	-3.00	262.00	-3.00	125.00
265	3.54	161.98	-3.00	262.00	-3.00	125.00
270	3.56	166.97	-3.00	262.00	-3.00	125.00
275	3.46	171.95	-3.00	262.00	-3.00	125.00
280	3.25	176.82	-3.00	262.00	-3.00	125.00
285	3.13	177.71	-3.00	262.00	-3.00	125.00
290	2.56	172.81	-3.00	262.00	-3.00	125.00
295	2.22	167.84	-3.00	262.00	-3.00	125.00
300	1.43	162.78	-3.00	262.00	-3.00	125.00
305	1.06	157.79	-3.00	262.00	-3.00	125.00
310	1.36	152.87	-3.00	262.00	-3.00	125.00
315	1.15	147.88	-3.00	262.00	-3.00	125.00
320 325	1.29	142.91 137.93	-3.00	262.00 262.00	-3.00 -3.00	125.00 125.00
325 330	1.32	132.94	-3.00	262.00	-3.00	125.00
335	2.23	127.98	-3.00	262.00	-3.00	125.00
335 340	3.20	127.98	-3.00	262.00	-3.00	125.00
340	4.13	123.00	-3.00	262.00	-3.00	125.00
345 350	4.15	113.01	-3.00	262.00	-3.00	125.00
550	5.11	108.01	-3.00	262.00	-3.00	125.00



## 5. Contact Information

For questions or information regarding the 28 GHz Frequency Coordination Report, please contact:

Contact person:	Dennis Jimeno
Title:	Engineer III, Telecommunications
Company:	Comsearch
Address:	19700 Janelia Farm Blvd., Ashburn, VA 20147
Telephone:	703-726-5858
Fax:	703-726-5599
Email:	DJimeno@Comsearch.com
Web site:	www.comsearch.com