

Ka-Band Earth Station – Sheffield, IL

Frequency Coordination Report

28 GHz



Prepared on Behalf of
SPACE EXPLORATION
HOLDINGS

April 11, 2022



Table of Contents

1.	Summary of Results	- 1 -
2.	28 GHz Common Carrier and LTTS Coordination	- 1 -
3.	28 GHz UMFUS Coordination	- 2 -
4.	Earth Station Coordination Data	- 3 -
5.	Contact Information	- 7 -

1. Summary of Results

On behalf of SPACE EXPLORATION HOLDINGS, Comsearch performed a coordination notice under Section 25.203(c) and Section 25.136(a)(4) of the FCC's rules for all existing and proposed terrestrial licenses within the coordination contours of their proposed Ka-Band earth station in Sheffield, IL, which will transmit at 28 GHz¹. Prior-notification letters were sent to the licensees and a copy of the notification data is provided in section four of this report. The earth station coordination was finalized on April 11, 2022.

There are no unresolved objections from any of the incumbent 28 GHz licensees.

2. 28 GHz Common Carrier and LTTS Coordination

In accordance with FCC Rules and Regulations, the Ka-Band earth station in Sheffield, IL was prior-coordinated by Comsearch. A notification letter and datasheets for this earth station were sent to the following 28 GHz common carrier fixed microwave licensees. These licensees are authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis or local basis.

Licensee	Authorized Geographic Area
AT&T	Statewide: IL

A notification letter and datasheets for the Ka-Band earth station in Sheffield, IL were also sent to the following 28 GHz local television transmission licensee. This licensee is authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis.

Licensee	Authorized Geographic Area
None Identified	

No objections were received from the common carrier or local television transmission service incumbents.

¹ The proposed earth station will operate in the 27.5 – 29.1 GHz & 29.5 – 30.0 GHz portion of the Ka-Band.

3. 28 GHz UMFUS Coordination

There were eight 28 GHz UMFUS licensees identified within the coordination distance of the proposed earth station. The proposed earth station will operate on frequencies that overlap Channel L1 & L2 of the UMFUS service. The total frequency allocation for Channels L1 & L2 of the UMFUS spectrum appears below.

Channel: **L1** 27.500 - 27.925 GHz
 L2 27.925 - 28.350 GHz

Licensee	Authorized Geographic Area
Broadband One	Market Based
David Behanna (Aries)	Market Based
Mary J Kuiken Partnership	Market Based
T-Mobile	Market Based
US Cellular	Market Based
Verizon	Market Based
Verso LMDS	Market Based
Windstream	Market Based

There are no unresolved objections from the UMFUS incumbents within coordination distance.



4. Earth Station Coordination Data

This section presents the data pertinent to the proposed Ka-Band earth station in Sheffield, IL. This data was circulated to all incumbent licensees in the shared 28 GHz frequency ranges.

Job Number:		220312COMSGE08		
Administrative Information				
Status	ENGINEER PROPOSAL			
Call Sign				
Licensee Code	SPACEX			
Licensee Name	Space Exploration Holdings			
Site Information				
Venue Name	SHEFFIELD, IL			
Latitude (NAD 83)	41° 21' 40.4" N			
Longitude (NAD 83)	89° 44' 35.9" W			
Climate Zone	A			
Rain Zone	2			
Ground Elevation (AMSL)	201.9 m / 662.4 ft			
Link Information				
Satellite Type	Low Earth Orbit			
Mode	TR - Transmit-Receive			
Modulation	Digital			
Minimum Elevation Angle	25.0°			
Azimuth Range	0.0° to 360°			
Antenna Centerline (AGL)	1.7 m / 5.6 ft			
Antenna Information		Receive - FCC32	Transmit - FCC32	
Manufacturer		SpaceX	SpaceX	
Model		1.85 meter	1.85 meter	
Gain / Diameter		49.1 dBi / 1.9 m	52.6 dBi / 1.9 m	
3-dB / 15-dB Beamwidth		0.63° / 1.27°	0.41° / 0.81°	
Max Available RF Power	(dBW/4 kHz) (dBW/MHz)		-40.8 -16.8	
Maximum EIRP	(dBW/4 kHz) (dBW/MHz)		11.8 35.8	
Interference Objectives:	Long Term	-156.0 dBW/MHz	20%	-151.0 dBW/4 kHz 20%
	Short Term	-146.0 dBW/MHz	0.01%	-128.0 dBW/4 kHz 0.0025%
Frequency Information		Receive 18.0 GHz	Transmit 28.0 GHz	
Emission / Frequency Range (MHz)		60M5D7W - 480MD7W / 17800.0 - 18600.0 60M5D7W - 480MD7W / 18800.0 - 19300.0	60M5D7W - 480MD7W / 27500.0 - 29100.0 60M5D7W - 480MD7W / 29500.0 - 30000.0	
Max Great Circle Coordination Distance		225.0 km / 139.8 mi	100.0 km / 62.1 mi	
Precipitation Scatter Contour Radius		100.0 km / 62.1 mi	100.0 km / 62.1 mi	

Coordination Values	SHEFFIELD, IL		
Licensee Name	Space Exploration Holdings		
Latitude (NAD 83)	41° 21' 40.4" N		
Longitude (NAD 83)	89° 44' 35.9" W		
Ground Elevation (AMSL)	201.9 m / 662.4 ft		
Antenna Centerline (AGL)	1.7 m / 5.6 ft		
Antenna Model	SpaceX 1.85 meter		
Antenna Mode	Receive 18.0 GHz		
Interference Objectives: Long Term	-156.0 dBW/MHz	20%	Transmit 28.0 GHz -151.0 dBW/4 kHz 20%
Short Term	-146.0 dBW/MHz	0.01%	-128.0 dBW/4 kHz 0.0025%
Max Available RF Power	-40.8 (dBW/4 kHz)		

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 18.0 GHz		Transmit 28.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
0	0.41	90.17	-10.00	225.00	-10.00	100.00
5	0.42	85.23	-10.00	225.00	-10.00	100.00
10	0.47	80.29	-10.00	225.00	-10.00	100.00
15	0.55	75.36	-10.00	225.00	-10.00	100.00
20	0.45	70.42	-10.00	225.00	-10.00	100.00
25	0.44	65.49	-10.00	225.00	-10.00	100.00
30	0.56	60.57	-10.00	225.00	-10.00	100.00
35	0.54	55.66	-10.00	225.00	-10.00	100.00
40	0.37	50.73	-10.00	225.00	-10.00	100.00
45	0.30	45.83	-10.00	225.00	-10.00	100.00
50	0.30	40.95	-10.00	225.00	-10.00	100.00
55	0.32	36.10	-10.00	225.00	-10.00	100.00
60	0.33	31.30	-10.00	225.00	-10.00	100.00
65	0.31	26.55	-10.00	225.00	-10.00	100.00
70	0.28	21.89	-10.00	225.00	-10.00	100.00
75	0.26	17.43	-10.00	225.00	-10.00	100.00
80	0.25	13.33	-10.00	225.00	-10.00	100.00
85	0.23	10.06	-10.00	225.00	-10.00	100.00
90	0.22	8.63	-10.00	225.00	-10.00	100.00
95	0.21	9.87	-10.00	225.00	-10.00	100.00
100	0.38	13.16	-10.00	225.00	-10.00	100.00
105	0.53	17.26	-10.00	225.00	-10.00	100.00
110	0.46	21.65	-10.00	225.00	-10.00	100.00
115	0.49	26.28	-10.00	225.00	-10.00	100.00
120	0.57	31.03	-10.00	225.00	-10.00	100.00
125	0.77	35.87	-10.00	225.00	-10.00	100.00
130	0.76	40.70	-10.00	225.00	-10.00	100.00
135	0.75	45.56	-10.00	225.00	-10.00	100.00
140	0.73	50.44	-10.00	225.00	-10.00	100.00
145	0.76	55.34	-10.00	225.00	-10.00	100.00
150	0.70	60.25	-10.00	225.00	-10.00	100.00
155	0.67	65.17	-10.00	225.00	-10.00	100.00
160	0.68	70.09	-10.00	225.00	-10.00	100.00
165	0.68	75.02	-10.00	225.00	-10.00	100.00
170	0.64	79.96	-10.00	225.00	-10.00	100.00
175	0.85	84.90	-10.00	225.00	-10.00	100.00
180	0.94	89.83	-10.00	225.00	-10.00	100.00
185	0.93	94.76	-10.00	225.00	-10.00	100.00

Coordination Values	SHEFFIELD, IL		
Licensee Name	Space Exploration Holdings		
Latitude (NAD 83)	41° 21' 40.4" N		
Longitude (NAD 83)	89° 44' 35.9" W		
Ground Elevation (AMSL)	201.9 m / 662.4 ft		
Antenna Centerline (AGL)	1.7 m / 5.6 ft		
Antenna Model	SpaceX 1.85 meter		
Antenna Mode	Receive 18.0 GHz		
Interference Objectives:	Long Term	-156.0 dBW/MHz	20%
	Short Term	-146.0 dBW/MHz	0.01%
Max Available RF Power	-40.8 (dBW/4 kHz)		
			Transmit 28.0 GHz
			-151.0 dBW/4 kHz 20%
			-128.0 dBW/4 kHz 0.0025%

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 18.0 GHz		Transmit 28.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
190	0.82	99.70	-10.00	225.00	-10.00	100.00
195	0.73	104.64	-10.00	225.00	-10.00	100.00
200	0.65	109.57	-10.00	225.00	-10.00	100.00
205	0.65	114.50	-10.00	225.00	-10.00	100.00
210	0.61	119.42	-10.00	225.00	-10.00	100.00
215	0.61	124.34	-10.00	225.00	-10.00	100.00
220	0.62	129.24	-10.00	225.00	-10.00	100.00
225	0.61	134.13	-10.00	225.00	-10.00	100.00
230	0.57	139.00	-10.00	225.00	-10.00	100.00
235	0.67	143.82	-10.00	225.00	-10.00	100.00
240	0.69	148.61	-10.00	225.00	-10.00	100.00
245	0.76	153.31	-10.00	225.00	-10.00	100.00
250	0.70	157.94	-10.00	225.00	-10.00	100.00
255	0.78	162.32	-10.00	225.00	-10.00	100.00
260	0.76	166.34	-10.00	225.00	-10.00	100.00
265	0.60	169.62	-10.00	225.00	-10.00	100.00
270	0.43	171.15	-10.00	225.00	-10.00	100.00
275	0.37	169.99	-10.00	225.00	-10.00	100.00
280	0.20	166.96	-10.00	225.00	-10.00	100.00
285	0.00	163.00	-10.00	225.00	-10.00	100.00
290	0.00	158.53	-10.00	225.00	-10.00	100.00
295	0.00	153.87	-10.00	225.00	-10.00	100.00
300	0.00	149.11	-10.00	225.00	-10.00	100.00
305	0.00	144.30	-10.00	225.00	-10.00	100.00
310	0.00	139.44	-10.00	225.00	-10.00	100.00
315	0.00	134.56	-10.00	225.00	-10.00	100.00
320	0.00	129.65	-10.00	225.00	-10.00	100.00
325	0.00	124.74	-10.00	225.00	-10.00	100.00
330	0.00	119.81	-10.00	225.00	-10.00	100.00
335	0.00	114.88	-10.00	225.00	-10.00	100.00
340	0.00	109.95	-10.00	225.00	-10.00	100.00
345	0.21	105.00	-10.00	225.00	-10.00	100.00
350	0.29	100.05	-10.00	225.00	-10.00	100.00
355	0.39	95.11	-10.00	225.00	-10.00	100.00



5. Contact Information

For questions or information regarding the 28 GHz Frequency Coordination Report, please contact:

Contact person:	Gary Edwards
Title:	Senior Manager, Satellite Services
Company:	Comsearch
Address:	19700 Janelia Farm Blvd., Ashburn, VA 20147
Telephone:	703-726-5662
Fax:	703-726-5599
Email:	GEdwards@Comsearch.com
Web site:	www.comsearch.com