

Ka-Band Earth Station – Wichita Falls, TX

Frequency Coordination Report

28 GHz



Prepared on Behalf of
SPACE EXPLORATION
HOLDINGS

April 18, 2022



Table of Contents

1.	Summary of Results	- 1 -
2.	28 GHz Common Carrier and LTTS Coordination	- 1 -
3.	28 GHz UMFUS Coordination	- 2 -
4.	Earth Station Coordination Data	- 3 -
5.	Contact Information	- 7 -



1. Summary of Results

On behalf of SPACE EXPLORATION HOLDINGS, Comsearch performed a coordination notice under Section 25.203(c) and Section 25.136(a)(4) of the FCC's rules for all existing and proposed terrestrial licenses within the coordination contours of their proposed Ka-Band earth station in Wichita Falls, TX, which will transmit at 28 GHz¹. Prior-notification letters were sent to the licensees and a copy of the notification data is provided in section four of this report. The earth station coordination was finalized on April 18, 2022.

No objections were received from any of the incumbent 28 GHz licensees.

2. 28 GHz Common Carrier and LTTS Coordination

In accordance with FCC Rules and Regulations, the Ka-Band earth station in Wichita Falls, TX was prior-coordinated by Comsearch. A notification letter and datasheets for this earth station were sent to the following 28 GHz common carrier fixed microwave licensees. These licensees are authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis or local basis.

Licensee	Authorized Geographic Area
None Identified	

A notification letter and datasheets for the Ka-Band earth station in Wichita Falls, TX were also sent to the following 28 GHz local television transmission licensee. This licensee is authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis.

Licensee	Authorized Geographic Area
None Identified	

No objections were received from the common carrier or local television transmission service incumbents.

¹ The proposed earth station will operate in the 27.5 – 29.1 GHz & 29.5 – 30.0 GHz portion of the Ka-Band.

3. 28 GHz UMFUS Coordination

There were six 28 GHz UMFUS licensees identified within the coordination distance of the proposed earth station. The proposed earth station will operate on frequencies that overlap Channel L1 & L2 of the UMFUS service. The total frequency allocation for Channels L1 & L2 of the UMFUS spectrum appears below.

Channel: **L1** 27.500 - 27.925 GHz
 L2 27.925 - 28.350 GHz

Licensee	Authorized Geographic Area
Chickasaw Nation	Market Based
McBride Spectrum Partners	Market Based
T-Mobile	Market Based
US Cellular	Market Based
Verizon	Market Based
Windstream	Market Based

No objections were received from the UMFUS incumbents within coordination distance.



4. Earth Station Coordination Data

This section presents the data pertinent to the proposed Ka-Band earth station in Wichita Falls, TX. This data was circulated to all incumbent licensees in the shared 28 GHz frequency ranges.

Job Number:		220316COMSGE08	
Administrative Information			
Status	ENGINEER PROPOSAL		
Call Sign			
Licensee Code	SPACEX		
Licensee Name	Space Exploration Holdings		
Site Information			
Venue Name	WICHITA FALLS, TX		
Latitude (NAD 83)	33° 51' 8.1" N		
Longitude (NAD 83)	98° 36' 14.8" W		
Climate Zone	A		
Rain Zone	2		
Ground Elevation (AMSL)	304.71 m / 999.7 ft		
Link Information			
Satellite Type	Low Earth Orbit		
Mode	TR - Transmit-Receive		
Modulation	Digital		
Minimum Elevation Angle	25.0°		
Azimuth Range	0.0° to 360°		
Antenna Centerline (AGL)	1.7 m / 5.6 ft		
Antenna Information		Receive - FCC32	Transmit - FCC32
Manufacturer		SpaceX	SpaceX
Model		1.85 meter	1.85 meter
Gain / Diameter		49.1 dBi / 1.9 m	52.6 dBi / 1.9 m
3-dB / 15-dB Beamwidth		0.63° / 1.27°	0.41° / 0.81°
Max Available RF Power	(dBW/4 kHz) (dBW/MHz)		-40.8 -16.8
Maximum EIRP	(dBW/4 kHz) (dBW/MHz)		11.8 35.8
Interference Objectives:	Long Term Short Term	-156.0 dBW/MHz -146.0 dBW/MHz	20% 0.01%
			-151.0 dBW/4 kHz 20% -128.0 dBW/4 kHz 0.0025%
Frequency Information		Receive 18.0 GHz	Transmit 28.0 GHz
Emission / Frequency Range (MHz)		60M5D7W - 480MD7W / 17800.0 - 18600.0 60M5D7W - 480MD7W / 18800.0 - 19300.0	60M5D7W - 480MD7W / 27500.0 - 29100.0 60M5D7W - 480MD7W / 29500.0 - 30000.0
Max Great Circle Coordination Distance		225.0 km / 139.8 mi	100.0 km / 62.1 mi
Precipitation Scatter Contour Radius		100.0 km / 62.1 mi	100.0 km / 62.1 mi



SPACE EXPLORATION HOLDINGS
Ka-Band Earth Station – Wichita Falls, TX
Frequency Coordination Report
28 GHz

Coordination Values	WICHITA FALL, TX			
Licensee Name	Space Exploration Holdings			
Latitude (NAD 83)	33° 51' 8.1" N			
Longitude (NAD 83)	98° 36' 14.8" W			
Ground Elevation (AMSL)	304.71 m / 999.7 ft			
Antenna Centerline (AGL)	1.7 m / 5.6 ft			
Antenna Model	SpaceX 1.85 meter			
Antenna Mode	Receive 18.0 GHz			
Interference Objectives: Long Term	-156.0 dBW/MHz	20%	Transmit 28.0 GHz	-151.0 dBW/4 kHz 20%
Short Term	-146.0 dBW/MHz	0.01%		-128.0 dBW/4 kHz 0.0025%
Max Available RF Power	-40.8 (dBW/4 kHz)			

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 18.0 GHz		Transmit 28.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
0	0.39	85.37	-10.00	225.00	-10.00	100.00
5	0.43	80.57	-10.00	225.00	-10.00	100.00
10	0.57	75.78	-10.00	225.00	-10.00	100.00
15	0.43	70.98	-10.00	225.00	-10.00	100.00
20	0.43	66.20	-10.00	225.00	-10.00	100.00
25	0.46	61.45	-10.00	225.00	-10.00	100.00
30	0.50	56.72	-10.00	225.00	-10.00	100.00
35	0.57	52.03	-10.00	225.00	-10.00	100.00
40	0.54	47.36	-10.00	225.00	-10.00	100.00
45	0.48	42.74	-10.00	225.00	-10.00	100.00
50	0.36	38.18	-10.00	225.00	-10.00	100.00
55	0.27	33.72	-10.00	225.00	-10.00	100.00
60	0.24	29.43	-10.00	225.00	-10.00	100.00
65	0.26	25.41	-10.00	225.00	-10.00	100.00
70	0.28	21.78	-10.00	225.00	-10.00	100.00
75	0.24	18.69	-10.00	225.00	-10.00	100.00
80	0.24	16.57	-10.00	225.00	-10.00	100.00
85	0.26	15.78	-10.00	225.00	-10.00	100.00
90	0.00	16.23	-10.00	225.00	-10.00	100.00
95	0.00	18.30	-10.00	225.00	-10.00	100.00
100	0.00	21.33	-10.00	225.00	-10.00	100.00
105	0.00	24.97	-10.00	225.00	-10.00	100.00
110	0.00	29.00	-10.00	225.00	-10.00	100.00
115	0.00	33.28	-10.00	225.00	-10.00	100.00
120	0.00	37.71	-10.00	225.00	-10.00	100.00
125	0.00	42.26	-10.00	225.00	-10.00	100.00
130	0.00	46.88	-10.00	225.00	-10.00	100.00
135	0.00	51.56	-10.00	225.00	-10.00	100.00
140	0.00	56.27	-10.00	225.00	-10.00	100.00
145	0.00	61.02	-10.00	225.00	-10.00	100.00
150	0.00	65.79	-10.00	225.00	-10.00	100.00
155	0.00	70.58	-10.00	225.00	-10.00	100.00
160	0.00	75.38	-10.00	225.00	-10.00	100.00
165	0.00	80.19	-10.00	225.00	-10.00	100.00
170	0.00	85.00	-10.00	225.00	-10.00	100.00
175	0.00	89.82	-10.00	225.00	-10.00	100.00
180	0.23	94.63	-10.00	225.00	-10.00	100.00
185	0.25	99.44	-10.00	225.00	-10.00	100.00

Coordination Values	WICHITA FALL, TX		
Licensee Name	Space Exploration Holdings		
Latitude (NAD 83)	33° 51' 8.1" N		
Longitude (NAD 83)	98° 36' 14.8" W		
Ground Elevation (AMSL)	304.71 m / 999.7 ft		
Antenna Centerline (AGL)	1.7 m / 5.6 ft		
Antenna Model	SpaceX 1.85 meter		
Antenna Mode	Receive 18.0 GHz		
Interference Objectives: Long Term	-156.0 dBW/MHz	20%	Transmit 28.0 GHz
Short Term	-146.0 dBW/MHz	0.01%	-151.0 dBW/4 kHz 20%
Max Available RF Power		-40.8 (dBW/4 kHz)	-128.0 dBW/4 kHz 0.0025%

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 18.0 GHz		Transmit 28.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
190	0.25	104.25	-10.00	225.00	-10.00	100.00
195	0.27	109.04	-10.00	225.00	-10.00	100.00
200	0.31	113.82	-10.00	225.00	-10.00	100.00
205	0.33	118.58	-10.00	225.00	-10.00	100.00
210	0.31	123.32	-10.00	225.00	-10.00	100.00
215	0.29	128.03	-10.00	225.00	-10.00	100.00
220	0.27	132.71	-10.00	225.00	-10.00	100.00
225	0.23	137.33	-10.00	225.00	-10.00	100.00
230	0.22	141.87	-10.00	225.00	-10.00	100.00
235	0.21	146.31	-10.00	225.00	-10.00	100.00
240	0.20	150.59	-10.00	225.00	-10.00	100.00
245	0.31	154.56	-10.00	225.00	-10.00	100.00
250	0.41	158.13	-10.00	225.00	-10.00	100.00
255	0.34	161.22	-10.00	225.00	-10.00	100.00
260	0.29	163.39	-10.00	225.00	-10.00	100.00
265	0.29	164.20	-10.00	225.00	-10.00	100.00
270	0.26	163.53	-10.00	225.00	-10.00	100.00
275	0.24	161.50	-10.00	225.00	-10.00	100.00
280	0.21	158.52	-10.00	225.00	-10.00	100.00
285	0.20	154.90	-10.00	225.00	-10.00	100.00
290	0.33	150.83	-10.00	225.00	-10.00	100.00
295	0.76	146.39	-10.00	225.00	-10.00	100.00
300	0.79	142.00	-10.00	225.00	-10.00	100.00
305	0.79	137.49	-10.00	225.00	-10.00	100.00
310	0.79	132.91	-10.00	225.00	-10.00	100.00
315	0.79	128.26	-10.00	225.00	-10.00	100.00
320	0.79	123.57	-10.00	225.00	-10.00	100.00
325	0.79	118.85	-10.00	225.00	-10.00	100.00
330	0.79	114.11	-10.00	225.00	-10.00	100.00
335	0.79	109.34	-10.00	225.00	-10.00	100.00
340	0.78	104.56	-10.00	225.00	-10.00	100.00
345	0.67	99.78	-10.00	225.00	-10.00	100.00
350	0.49	94.98	-10.00	225.00	-10.00	100.00
355	0.37	90.18	-10.00	225.00	-10.00	100.00



5. Contact Information

For questions or information regarding the 28 GHz Frequency Coordination Report, please contact:

Contact person:	Gary Edwards
Title:	Senior Manager, Satellite Services
Company:	Comsearch
Address:	19700 Janelia Farm Blvd., Ashburn, VA 20147
Telephone:	703-726-5662
Fax:	703-726-5599
Email:	GEdwards@Comsearch.com
Web site:	www.comsearch.com