

Micronet Communications, Inc.

812 Lexington Dr
Plano, Texas 75075
972-422-7200

SUPPLEMENTAL SHOWING PART 101.103(D)

File Number: B2203418
Licensee: SHELL COMMUNICATIONS INC

5.93 GHz

Page 1

Pursuant to Parts 25.203 and 101.103(d) of the FCC Rules and Regulations, a frequency coordination study was conducted by Micronet Communications, Inc. for the following proposed earth station:

Salsa, GM

The results of the study indicate that no unacceptable interference will result with existing, proposed or prior coordinated radio facilities.

Coordination was performed with existing, proposed and prior coordinated carriers within coordination range on the following dates:

02/17/2022 Original PCN

There were no unresolved interference objections.

The attached coordination data was forwarded on the latest date to the following parties within coordination range or their authorized coordination agents:

CHEVRON USA INC.
COMSEARCH INC
MICRONET COMMUNICATIONS INC
RIGNET SATCOM, INC.
STRATOS OFFSHORE SERVICES COMPANY
TAMPNET LICENSEE LLC

Respectfully Submitted,



Jeremy Lewis
Systems Engineer

Attached: 1 data sheet

Micronet Communications, Inc.
812 Lexington Dr
Plano, Texas 75075
972-422-7200

File: B2203418

TECHNICAL CHARACTERISTICS OF TRANSMIT RECEIVE EARTH STATION

Company:	SHELL COMMUNICATIONS INC		
Site Name, State:	Salsa, GM		
Call Sign:			
Latitude	(NAD83)	27 50	25.2 N
Longitude	(NAD83)	91 59	15.6 W
Elevation AMSL	(ft/m)	0.00	0.00
Receive Frequency Range	(MHz)	3700-4200	
Transmit Frequency Range	(MHz)	5925-6242.84/6270.24-6300.665/6360.665-6425	
Range of Satellite Orbital Long.	(deg W)	60.00	143.00
Range of Azimuths from North	(deg)	126.79	249.29
Antenna Centerline	(ft/m)	198.75	60.58
Antenna Elevation Angles	(deg)	42.17	26.01

Equipment Parameters		Receive	Transmit
----------------------	--	---------	----------

Antenna Gain, Main Beam	(dbI)	38.50	42.00
15 DB Half Beamwidth	(deg)	4.20	2.60

Antennas Receive: ASC SIGNAL CORPORATION 243 (2.4M)
Transmit: ASC SIGNAL CORPORATION 243 (2.4M)

Max Transmitter Power	(dbW/4KHz)	-19.60
Max EIRP Main Beam	(dbW/4KHz)	22.40
Modulation / Emission Designator	DIGITAL 4M30G7W 2M03G7W	

Coordination Parameters		Receive	Transmit
-------------------------	--	---------	----------

Max Greater Circle Distances	(km)	387.51	130.01
Max Rain Scatter Distances	(km)	559.55	100.00
Max Interference Power Long Term	(dbW)	-158.60	-154.80
Max Interference Power Short Term	(dbW)	-153.90	-126.80
Rain Zone / Radio Zone		1	A