

Ka-Band Earth Station – Hawthorne 1, CA

Frequency Coordination Report

28 GHz



Prepared on Behalf of
SPACE EXPLORATION
HOLDINGS

March 31, 2023



Table of Contents

1.	Summary of Results	- 1 -
2.	28 GHz Common Carrier, LTTS and LMDS Coordination	- 1 -
3.	28 GHz UMFUS Coordination	- 2 -
4.	Earth Station Coordination Data	- 3 -
5.	Contact Information	- 7 -



1. Summary of Results

On behalf of SPACE EXPLORATION HOLDINGS, Comsearch performed a coordination notice under Section 25.203(c) and Section 25.136(a)(4) of the FCC's rules for all existing and proposed terrestrial licenses within the coordination contours of their proposed Ka-Band earth station in Hawthorne 1, CA, which will transmit at 28 GHz¹. Prior-notification letters were sent to the licensees and a copy of the notification data is provided in section four of this report. The earth station coordination was finalized on March 31, 2023.

There were no reported objections from any of the incumbent 28 GHz licensees.

2. 28 GHz Common Carrier, LTTS and LMDS Coordination

In accordance with FCC Rules and Regulations, the Ka-Band earth station in Hawthorne 1, CA was prior-coordinated by Comsearch. A notification letter and datasheets for this earth station were sent to the following 28 GHz common carrier fixed microwave licensees. These licensees are authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis or local basis.

Licensee	Authorized Geographic Area
AT&T	Statewide: CA

A notification letter and datasheets for the Ka-Band earth station in Hawthorne 1, CA were also sent to the following 28 GHz local television transmission or LMDS licensees. These licensees are authorized to operate temporary fixed operations from 27.5 – 29.5 GHz (LTTS) or 29.1 – 29.25 GHz (LMDS).

Licensee	Authorized Geographic Area
Alta	Market Based
GeoLinks	Market Based

No objections were received from the common carrier, local television transmission service or LMDS incumbents.

¹ The proposed earth station will operate in the 27.5 – 29.1 GHz & 29.5 – 30.0 GHz portion of the Ka-Band.

3. 28 GHz UMFUS Coordination

There were three 28 GHz UMFUS licensees identified within the coordination distance of the proposed earth station. The proposed earth station will operate on frequencies that overlap Channel L1 & L2 of the UMFUS service. The total frequency allocation for Channels L1 & L2 of the UMFUS spectrum appears below.

Channel: **L1** 27.500 - 27.925 GHz
 L2 27.925 - 28.350 GHz

Licensee	Authorized Geographic Area
Alta	Market Based
T-Mobile	Market Based
Verizon	Market Based

There were no objections from the UMFUS incumbents within coordination distance.



4. Earth Station Coordination Data

This section presents the data pertinent to the proposed Ka-Band earth station in Hawthorne 1, CA. This data was circulated to all incumbent licensees in the shared 28 GHz frequency ranges.

Job Number:		230316COMSGE01	
Administrative Information			
Status	ENGINEER PROPOSAL		
Call Sign			
Licensee Code	SPACEX		
Licensee Name	Space Exploration Holdings		
Site Information			
Venue Name	HAWTHORNE 1, CA		
Latitude (NAD 83)	33° 55' 12.5" N		
Longitude (NAD 83)	118° 19' 56.7" W		
Climate Zone	A		
Rain Zone	4		
Ground Elevation (AMSL)	18.13 m / 59.5 ft		
Link Information			
Satellite Type	Low Earth Orbit		
Mode	TR - Transmit-Receive		
Modulation	Digital		
Minimum Elevation Angle	25.0°		
Azimuth Range	0.0° to 360°		
Antenna Centerline (AGL)	11.1 m / 36.4 ft		
Antenna Information		Receive - FCC32	Transmit - FCC32
Manufacturer		SpaceX	SpaceX
Model		1.85 meter	1.85 meter
Gain / Diameter		49.1 dBi / 1.9 m	52.6 dBi / 1.9 m
3-dB / 15-dB Beamwidth		0.63° / 1.27°	0.41° / 0.81°
Max Available RF Power	(dBW/4 kHz) (dBW/MHz)		-40.8 -16.8
Maximum EIRP	(dBW/4 kHz) (dBW/MHz)		11.8 35.8
Interference Objectives:	Long Term	-156.0 dBW/MHz	20%
	Short Term	-146.0 dBW/MHz	0.01%
			-151.0 dBW/4 kHz 20%
			-128.0 dBW/4 kHz 0.0025%
Frequency Information		Receive 18.0 GHz	Transmit 28.0 GHz
Emission / Frequency Range (MHz)		60M0D7W - 480MD7W / 17800.0 - 18600.0 60M0D7W - 480MD7W / 18800.0 - 19300.0	60M0D7W - 480MD7W / 27500.0 - 29100.0 60M0D7W - 480MD7W / 29500.0 - 30000.0
Max Great Circle Coordination Distance		262.0 km / 162.8 mi	125.0 km / 77.7 mi
Precipitation Scatter Contour Radius		100.0 km / 62.1 mi	100.0 km / 62.1 mi

Coordination Values		HAWTHORNE 1, CA		
Licensee Name		Space Exploration Holdings		
Latitude (NAD 83)		33° 55' 12.5" N		
Longitude (NAD 83)		118° 19' 56.7" W		
Ground Elevation (AMSL)		18.13 m / 59.5 ft		
Antenna Centerline (AGL)		11.1 m / 36.4 ft		
Antenna Model		SpaceX 1.85 meter		
Antenna Mode		Receive 18.0 GHz		Transmit 28.0 GHz
Interference Objectives: Long Term		-156.0 dBW/MHz	20%	-151.0 dBW/4 kHz 20%
Short Term		-146.0 dBW/MHz	0.01%	-128.0 dBW/4 kHz 0.0025%
Max Available RF Power			-40.8 (dBW/4 kHz)	

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 18.0 GHz		Transmit 28.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
0	0.53	75.73	-3.00	262.00	-3.00	125.00
5	0.51	71.52	-3.00	262.00	-3.00	125.00
10	0.57	67.37	-3.00	262.00	-3.00	125.00
15	0.64	63.29	-3.00	262.00	-3.00	125.00
20	0.73	59.29	-3.00	262.00	-3.00	125.00
25	0.73	55.37	-3.00	262.00	-3.00	125.00
30	0.76	51.58	-3.00	262.00	-3.00	125.00
35	0.73	47.91	-3.00	262.00	-3.00	125.00
40	0.77	44.48	-3.00	262.00	-3.00	125.00
45	0.77	41.28	-3.00	262.00	-3.00	125.00
50	0.79	38.40	-3.00	262.00	-3.00	125.00
55	0.84	35.94	-3.00	262.00	-3.00	125.00
60	0.84	33.92	-3.00	262.00	-3.00	125.00
65	0.85	32.47	-3.00	262.00	-3.00	125.00
70	0.81	31.63	-3.00	262.00	-3.00	125.00
75	0.55	31.26	-3.00	262.00	-3.00	125.00
80	0.65	31.96	-3.00	262.00	-3.00	125.00
85	0.53	33.12	-3.00	262.00	-3.00	125.00
90	0.42	34.91	-3.00	262.00	-3.00	125.00
95	0.35	37.24	-3.00	262.00	-3.00	125.00
100	0.00	39.81	-3.00	262.00	-3.00	125.00
105	0.00	42.99	-3.00	262.00	-3.00	125.00
110	0.00	46.43	-3.00	262.00	-3.00	125.00
115	0.00	50.07	-3.00	262.00	-3.00	125.00
120	0.00	53.88	-3.00	262.00	-3.00	125.00
125	0.00	57.82	-3.00	262.00	-3.00	125.00
130	0.00	61.86	-3.00	262.00	-3.00	125.00
135	0.00	65.97	-3.00	262.00	-3.00	125.00
140	0.00	70.15	-3.00	262.00	-3.00	125.00
145	0.00	74.37	-3.00	262.00	-3.00	125.00
150	0.00	78.62	-3.00	262.00	-3.00	125.00
155	0.00	82.90	-3.00	262.00	-3.00	125.00
160	0.00	87.20	-3.00	262.00	-3.00	125.00
165	0.00	91.50	-3.00	262.00	-3.00	125.00
170	0.00	95.80	-3.00	262.00	-3.00	125.00
175	0.00	100.08	-3.00	262.00	-3.00	125.00
180	0.00	104.35	-3.00	262.00	-3.00	125.00
185	0.00	108.58	-3.00	262.00	-3.00	125.00

Coordination Values		HAWTHORNE 1, CA		
Licensee Name		Space Exploration Holdings		
Latitude (NAD 83)		33° 55' 12.5" N		
Longitude (NAD 83)		118° 19' 56.7" W		
Ground Elevation (AMSL)		18.13 m / 59.5 ft		
Antenna Centerline (AGL)		11.1 m / 36.4 ft		
Antenna Model		SpaceX 1.85 meter		
Antenna Mode		Receive 18.0 GHz		Transmit 28.0 GHz
Interference Objectives: Long Term		-156.0 dBW/MHz	20%	-151.0 dBW/4 kHz 20%
Short Term		-146.0 dBW/MHz	0.01%	-128.0 dBW/4 kHz 0.0025%
Max Available RF Power			-40.8 (dBW/4 kHz)	

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 18.0 GHz		Transmit 28.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
190	0.00	112.77	-3.00	262.00	-3.00	125.00
195	0.00	116.91	-3.00	262.00	-3.00	125.00
200	0.00	120.97	-3.00	262.00	-3.00	125.00
205	0.00	124.94	-3.00	262.00	-3.00	125.00
210	0.00	128.79	-3.00	262.00	-3.00	125.00
215	0.00	132.49	-3.00	262.00	-3.00	125.00
220	0.00	135.99	-3.00	262.00	-3.00	125.00
225	0.00	139.26	-3.00	262.00	-3.00	125.00
230	0.26	142.01	-3.00	262.00	-3.00	125.00
235	0.25	144.56	-3.00	262.00	-3.00	125.00
240	0.00	146.85	-3.00	262.00	-3.00	125.00
245	0.00	148.34	-3.00	262.00	-3.00	125.00
250	0.00	149.18	-3.00	262.00	-3.00	125.00
255	0.00	149.29	-3.00	262.00	-3.00	125.00
260	0.00	148.67	-3.00	262.00	-3.00	125.00
265	0.00	147.37	-3.00	262.00	-3.00	125.00
270	0.00	145.45	-3.00	262.00	-3.00	125.00
275	0.00	143.03	-3.00	262.00	-3.00	125.00
280	0.00	140.19	-3.00	262.00	-3.00	125.00
285	0.00	137.01	-3.00	262.00	-3.00	125.00
290	0.00	133.57	-3.00	262.00	-3.00	125.00
295	0.00	129.93	-3.00	262.00	-3.00	125.00
300	0.00	126.12	-3.00	262.00	-3.00	125.00
305	0.00	122.18	-3.00	262.00	-3.00	125.00
310	0.00	118.14	-3.00	262.00	-3.00	125.00
315	0.00	114.03	-3.00	262.00	-3.00	125.00
320	0.00	109.85	-3.00	262.00	-3.00	125.00
325	0.00	105.63	-3.00	262.00	-3.00	125.00
330	0.00	101.38	-3.00	262.00	-3.00	125.00
335	0.00	97.10	-3.00	262.00	-3.00	125.00
340	0.33	92.79	-3.00	262.00	-3.00	125.00
345	0.48	88.51	-3.00	262.00	-3.00	125.00
350	0.35	84.22	-3.00	262.00	-3.00	125.00
355	0.46	79.97	-3.00	262.00	-3.00	125.00



5. Contact Information

For questions or information regarding the 28 GHz Frequency Coordination Report, please contact:

Contact person:	Gary Edwards
Title:	Senior Manager, Satellite Services
Company:	Comsearch
Address:	21515 Ridgetop Circle, Suite 300, Sterling, VA 20166
Telephone:	703-726-5662
Fax:	703-726-5599
Email:	GEdwards@Comsearch.com
Web site:	www.comsearch.com