

Ka,Q/V-Band Earth Station – Sherman, TX.

Frequency Coordination Report

Ka, Q/V-Band

Receive: 37.5 – 42.5 GHz Transmit: 27.5 – 31.0 GHz, 47.2 – 50.2, 50.4 – 52.4 GHz



Prepared on Behalf of
SPACE EXPLORATION
HOLDINGS

July 20, 2026



Table of Contents

1.	Summary of Results	- 1 -
2.	40/50 GHz Common Carrier and LTTS Coordination	- 1 -
3.	28/40/50 GHz UMFUS Coordination	- 2 -
4.	Earth Station Coordination Data	- 3 -
5.	Contact Information	- 7 -



1. Summary of Results

On behalf of SPACE EXPLORATION HOLDINGS, Comsearch performed a coordination notice under Section 25.203(c) of the FCC's rules for all existing and proposed terrestrial licenses within the coordination contours of their proposed Ka, Q/V-band earth station in Sherman, TX which will receive at 40 GHz and transmit at 28 and 50 GHz¹. Prior-notification letters were sent to the licensees and a copy of the notification data is provided in section four of this report. The earth station coordination was finalized on July 20, 2026.

There are no unresolved objections from any of the incumbent 28/40/50 GHz licensees.

2. 28/40/50 GHz Common Carrier and LTTS Coordination

In accordance with FCC Rules and Regulations, the Ka, Q/V-band earth station in Sherman, TX was prior-coordinated by Comsearch. A notification letter and datasheets for this earth station were sent to the following 28/40/50 GHz common carrier fixed microwave licensees. These licensees are authorized to operate temporary fixed operations from 38.6 – 40.0 GHz on a nationwide basis or local basis.

Licensee	Authorized Geographic Area
None Identified	

A notification letter and datasheets for the Ka, Q/V-band earth station in Sherman, TX were also sent to the following 40 GHz LTTS licensee. This licensee is authorized to operate temporary fixed operations from 38.6 – 40.0 GHz on a market basis.

Licensee	Authorized Geographic Area
Broadcast Sports International, LLC	Nationwide
DCI II Inc	Nationwide
Remote Facilities Consulting Services Inc	Nationwide

No objections were received from the common carrier or LTTS incumbents.

¹ The proposed earth station will receive in the 37.5 – 42.5 GHz & transmit in the 47.2-50.2 GHz / 50.4-52.4 GHz portion of the Q/V-Band. Ka-band transmissions will be in the 27.5 – 31.0 GHz band.

3. 28/40/50 GHz UMFUS Coordination

There were eleven 28/40/50 GHz UMFUS licensees identified within the coordination distance of the proposed earth station. The proposed earth station will operate on frequencies that overlap portions of the UMFUS service which includes the following frequency ranges:

27.5 GHz – 31.0 GHz
37.5 GHz – 42.5 GHz
47.2 GHz – 50.2 GHz

Licensee	Authorized Geographic Area
AT&T	Market Based
Broadband One	Market Based
GeoLinks	Market Based
Chickasaw Nation	Market Based
Columbia Capital	
DISH Network	Market Based
US Cellular	Market Based
Pine Cellular	Market Based
T-Mobile	Market Based
Verizon	Market Based
Scientel Solutions	Market Based

There were no objections from the UMFUS incumbents within the coordination distance at the end of the coordination period.



4. Earth Station Coordination Data

This section presents the data pertinent to the proposed Ka, Q/V-band earth station in Sherman, TX. This data was circulated to all incumbent licensees in the shared 28/40/50 GHz frequency ranges.

SPACE EXPLORATION HOLDINGS
Ka, Q/V-Band Earth Station – Sherman, TX
Frequency Coordination Report
28/40/50 GHz

Date: 06/23/2026
Job Number: 260623COMSGE04

Administrative Information

Status: ENGINEER PROPOSAL
Call Sign:
Licensee Code: SPACEX
Licensee Name: SpaceX Services, Inc

Site Information

SHERMAN, TX
Venue Name: ATHENS OF TEXAS
Latitude (NAD 83): 33° 41' 10.0" N
Longitude (NAD 83): 96° 35' 12.6" W
Climate Zone: A
Rain Zone: 2
Ground Elevation (AMSL): 238.0 m / 780.8 ft

Link Information

Satellite Type: Low Earth Orbit
Mode: TR - Transmit-Receive
Antenna Count: 40
Modulation: Digital
Minimum Elevation Angle: 10.0°
Azimuth Range: 0.0° to 360°
Antenna Centerline (AGL): 1.7 m / 5.6 ft

Antenna Information

Manufacturer:
Model:
Gain / Diameter:
3-dB / 15-dB Beamwidth:

Receive - FCC32

SpaceX
1.99 meter
50.0 dBi / 2.0 m
0.50° / 1.00°

Transmit - FCC32

SpaceX
1.99 meter
53.9 dBi / 2.0 m
0.30° / 0.60°

Max Available RF Power (dBW/4 kHz)
(dBW/MHz)

-40.8
-16.8

Maximum EIRP (dBW/4 kHz)
(dBW/MHz)

13.1
37.1

Aggregate EIRP (dBW/MHz)

37.1

Interference Objectives: Long Term -156.0 dBW/MHz 20%
Short Term -146.0 dBW/MHz 0.01%

-151.0 dBW/4 kHz 20%
-128.0 dBW/4 kHz 0.0025%

Frequency Information

Emission / Frequency Range (MHz)

Receive 18.0 GHz

60M0D7W - 480MD7W / 17300.0 - 17800.0
60M0D7W - 480MD7W / 17800.0 - 18600.0
60M0D7W - 480MD7W / 18600.0 - 18800.0
60M0D7W - 480MD7W / 18800.0 - 19300.0
60M0D7W - 480MD7W / 19300.0 - 19700.0
60M0D7W - 480MD7W / 19700.0 - 20200.0
60M0D7W - 480MD7W / 20200.0 - 21200.0

Transmit 28.0 GHz

60M0D7W - 480MD7W / 27500.0 - 29100.0
60M0D7W - 480MD7W / 29100.0 - 29500.0
60M0D7W - 480MD7W / 29500.0 - 30000.0
60M0D7W - 480MD7W / 30000.0 - 31000.0

Max Great Circle Coordination Distance
Precipitation Scatter Contour Radius

225.0 km / 139.8 mi
100.0 km / 62.1 mi

100.0 km / 62.1 mi
100.0 km / 62.1 mi

SPACE EXPLORATION HOLDINGS
Ka, Q/V-Band Earth Station – Sherman, TX
Frequency Coordination Report
28/40/50 GHz

Coordination Values			SHERMAN, TX			
Licensee Name			SpaceX Services, Inc			
Latitude (NAD 83)			33° 41' 10.0" N			
Longitude (NAD 83)			96° 35' 12.6" W			
Ground Elevation (AMSL)			238.0 m / 780.8 ft			
Antenna Centerline (AGL)			1.4 m / 4.6 ft			
Antenna Model			SpaceX 1.99 meter			
Antenna Mode			Receive 18.0 GHz		Transmit 28.0 GHz	
Interference Objectives: Long Term			-156.0 dBW/MHz	20%	-151.0 dBW/4 kHz	20%
Short Term			-146.0 dBW/MHz	0.01%	-128.0 dBW/4 kHz	0.0025%
Max Available RF Power			-40.8 (dBW/4 kHz)			
Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 18.0 GHz		Transmit 28.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
0	0.00	86.45	0.00	225.00	0.00	100.00
5	0.00	81.59	0.00	225.00	0.00	100.00
10	0.00	76.75	0.00	225.00	0.00	100.00
15	0.00	71.91	0.00	225.00	0.00	100.00
20	0.00	67.07	0.00	225.00	0.00	100.00
25	0.37	62.30	0.00	225.00	0.00	100.00
30	0.47	57.53	0.00	225.00	0.00	100.00
35	0.71	52.81	0.00	225.00	0.00	100.00
40	0.96	48.15	0.00	225.00	0.00	100.00
45	1.26	43.56	0.00	225.00	0.00	100.00
50	1.61	39.09	0.00	225.00	0.00	100.00
55	1.51	34.58	0.00	225.00	0.00	100.00
60	1.69	30.33	0.00	225.00	0.00	100.00
65	1.69	26.22	0.00	225.00	0.00	100.00
70	1.75	22.49	0.00	225.00	0.00	100.00
75	1.50	19.06	0.00	225.00	0.00	100.00
80	1.28	16.44	0.00	225.00	0.00	100.00
85	1.16	15.14	0.00	225.00	0.00	100.00
90	1.16	15.51	0.00	225.00	0.00	100.00
95	1.11	17.30	0.00	225.00	0.00	100.00
100	1.10	20.19	0.00	225.00	0.00	100.00
105	1.12	23.80	0.00	225.00	0.00	100.00
110	1.14	27.81	0.00	225.00	0.00	100.00
115	1.00	32.02	0.00	225.00	0.00	100.00
120	1.00	36.46	0.00	225.00	0.00	100.00
125	0.80	40.96	0.00	225.00	0.00	100.00
130	0.69	45.57	0.00	225.00	0.00	100.00
135	0.49	50.23	0.00	225.00	0.00	100.00
140	0.49	54.98	0.00	225.00	0.00	100.00
145	0.50	59.76	0.00	225.00	0.00	100.00
150	0.51	64.55	0.00	225.00	0.00	100.00
155	0.51	69.37	0.00	225.00	0.00	100.00
160	0.48	74.19	0.00	225.00	0.00	100.00
165	0.47	79.02	0.00	225.00	0.00	100.00
170	0.48	83.86	0.00	225.00	0.00	100.00
175	0.54	88.70	0.00	225.00	0.00	100.00
180	0.42	93.55	0.00	225.00	0.00	100.00
185	0.25	98.40	0.00	225.00	0.00	100.00

SPACE EXPLORATION HOLDINGS
Ka, Q/V-Band Earth Station – Sherman, TX
Frequency Coordination Report
28/40/50 GHz

Coordination Values		SHERMAN, TX				
Licensee Name		SpaceX Services, Inc				
Latitude (NAD 83)		33° 41' 10.0" N				
Longitude (NAD 83)		96° 35' 12.6" W				
Ground Elevation (AMSL)		238.0 m / 780.8 ft				
Antenna Centerline (AGL)		1.4 m / 4.6 ft				
Antenna Model		SpaceX 1.99 meter				
Antenna Mode		Receive 18.0 GHz		Transmit 28.0 GHz		
Interference Objectives:		Long Term	-156.0 dBW/MHz	20%	-151.0 dBW/4 kHz	20%
		Short Term	-146.0 dBW/MHz	0.01%	-128.0 dBW/4 kHz	0.0025%
Max Available RF Power		-40.8 (dBW/4 kHz)				
Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 18.0 GHz		Transmit 28.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
190	0.24	103.24	0.00	225.00	0.00	100.00
195	0.22	108.08	0.00	225.00	0.00	100.00
200	0.23	112.90	0.00	225.00	0.00	100.00
205	0.33	117.70	0.00	225.00	0.00	100.00
210	0.50	122.47	0.00	225.00	0.00	100.00
215	0.59	127.21	0.00	225.00	0.00	100.00
220	0.56	131.95	0.00	225.00	0.00	100.00
225	0.54	136.64	0.00	225.00	0.00	100.00
230	0.55	141.26	0.00	225.00	0.00	100.00
235	0.63	145.76	0.00	225.00	0.00	100.00
240	0.66	150.15	0.00	225.00	0.00	100.00
245	0.64	154.36	0.00	225.00	0.00	100.00
250	0.55	158.31	0.00	225.00	0.00	100.00
255	0.54	161.70	0.00	225.00	0.00	100.00
260	0.58	164.20	0.00	225.00	0.00	100.00
265	0.56	165.46	0.00	225.00	0.00	100.00
270	0.50	165.13	0.00	225.00	0.00	100.00
275	0.44	163.28	0.00	225.00	0.00	100.00
280	0.42	160.29	0.00	225.00	0.00	100.00
285	0.64	156.49	0.00	225.00	0.00	100.00
290	0.47	152.52	0.00	225.00	0.00	100.00
295	0.39	148.24	0.00	225.00	0.00	100.00
300	0.32	143.78	0.00	225.00	0.00	100.00
305	0.39	139.17	0.00	225.00	0.00	100.00
310	0.39	134.51	0.00	225.00	0.00	100.00
315	0.33	129.80	0.00	225.00	0.00	100.00
320	0.00	125.11	0.00	225.00	0.00	100.00
325	0.00	120.32	0.00	225.00	0.00	100.00
330	0.00	115.51	0.00	225.00	0.00	100.00
335	0.00	110.68	0.00	225.00	0.00	100.00
340	0.00	105.85	0.00	225.00	0.00	100.00
345	0.00	101.00	0.00	225.00	0.00	100.00
350	0.00	96.15	0.00	225.00	0.00	100.00
355	0.00	91.30	0.00	225.00	0.00	100.00

Date: 06/23/2026
Job Number: 260623COMSGE04

Administrative Information

Status: ENGINEER PROPOSAL
Call Sign:
Licensee Code: SPACEX
Licensee Name: SpaceX Services, Inc

Site Information

SHERMAN, TX
Venue Name: ATHENS OF TEXAS
Latitude (NAD 83): 33° 41' 10.0" N
Longitude (NAD 83): 96° 35' 12.6" W
Climate Zone: A
Rain Zone: 2
Ground Elevation (AMSL): 238.0 m / 780.8 ft

Link Information

Satellite Type: Low Earth Orbit
Mode: TR - Transmit-Receive
Antenna Count: 40
Modulation: Digital
Minimum Elevation Angle: 10.0°
Azimuth Range: 0.0° to 360°
Antenna Centerline (AGL): 1.7 m / 5.6 ft

Antenna Information

Manufacturer: SpaceX
Model: 1.99 meter
Gain / Diameter: 55.9 dBi / 2.0 m
3-dB / 15-dB Beamwidth: 0.25° / 0.50°

Receive - FCC32

SpaceX
1.99 meter
55.9 dBi / 2.0 m
0.25° / 0.50°

Transmit - FCC32

SpaceX
1.99 meter
58.1 dBi / 2.0 m
0.20° / 0.40°

Max Available RF Power (dBW/4 kHz): -47.8
(dBW/MHz): -23.8

Maximum EIRP (dBW/4 kHz): 10.3
(dBW/MHz): 34.3

Aggregate EIRP (dBW/MHz): 34.3

Interference Objectives:	Long Term	-156.0 dBW/MHz	20%	-151.0 dBW/4 kHz 20%
	Short Term	-146.0 dBW/MHz	0.01%	-128.0 dBW/4 kHz 0.0025%

Frequency Information

Emission / Frequency Range (MHz)	Receive 40.0 GHz	Transmit 50.0 GHz
	60M0D7W - 480MD7W / 37500.0 - 42500.0	60M0D7W - 480MD7W / 47200.0 - 50200.0
		60M0D7W - 480MD7W / 50400.0 - 51400.0
		60M0D7W - 480MD7W / 51400.0 - 52400.0

Max Great Circle Coordination Distance	225.0 km / 139.8 mi	100.0 km / 62.1 mi
Precipitation Scatter Contour Radius	100.0 km / 62.1 mi	100.0 km / 62.1 mi

SPACE EXPLORATION HOLDINGS
Ka, Q/V-Band Earth Station – Sherman, TX
Frequency Coordination Report
28/40/50 GHz

Coordination Values			SHERMAN, TX			
Licensee Name			SpaceX Services, Inc			
Latitude (NAD 83)			33° 41' 10.0" N			
Longitude (NAD 83)			96° 35' 12.6" W			
Ground Elevation (AMSL)			238.0 m / 780.8 ft			
Antenna Centerline (AGL)			1.4 m / 4.6 ft			
Antenna Model			SpaceX 1.99 meter			
Antenna Mode			Receive 40.0 GHz		Transmit 50.0 GHz	
Interference Objectives: Long Term			-156.0 dBW/MHz	20%	-151.0 dBW/4 kHz	20%
			Short Term	-146.0 dBW/MHz	0.01%	-128.0 dBW/4 kHz
Max Available RF Power			-47.8 (dBW/4 kHz)			
Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 40.0 GHz		Transmit 50.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
0	0.00	86.45	0.00	225.00	0.00	100.00
5	0.00	81.59	0.00	225.00	0.00	100.00
10	0.00	76.75	0.00	225.00	0.00	100.00
15	0.00	71.91	0.00	225.00	0.00	100.00
20	0.00	67.07	0.00	225.00	0.00	100.00
25	0.37	62.30	0.00	225.00	0.00	100.00
30	0.47	57.53	0.00	225.00	0.00	100.00
35	0.71	52.81	0.00	225.00	0.00	100.00
40	0.96	48.15	0.00	225.00	0.00	100.00
45	1.26	43.56	0.00	225.00	0.00	100.00
50	1.61	39.09	0.00	225.00	0.00	100.00
55	1.51	34.58	0.00	225.00	0.00	100.00
60	1.69	30.33	0.00	225.00	0.00	100.00
65	1.69	26.22	0.00	225.00	0.00	100.00
70	1.75	22.49	0.00	225.00	0.00	100.00
75	1.50	19.06	0.00	225.00	0.00	100.00
80	1.28	16.44	0.00	225.00	0.00	100.00
85	1.16	15.14	0.00	225.00	0.00	100.00
90	1.16	15.51	0.00	225.00	0.00	100.00
95	1.11	17.30	0.00	225.00	0.00	100.00
100	1.10	20.19	0.00	225.00	0.00	100.00
105	1.12	23.80	0.00	225.00	0.00	100.00
110	1.14	27.81	0.00	225.00	0.00	100.00
115	1.00	32.02	0.00	225.00	0.00	100.00
120	1.00	36.46	0.00	225.00	0.00	100.00
125	0.80	40.96	0.00	225.00	0.00	100.00
130	0.69	45.57	0.00	225.00	0.00	100.00
135	0.49	50.23	0.00	225.00	0.00	100.00
140	0.49	54.98	0.00	225.00	0.00	100.00
145	0.50	59.76	0.00	225.00	0.00	100.00
150	0.51	64.55	0.00	225.00	0.00	100.00
155	0.51	69.37	0.00	225.00	0.00	100.00
160	0.48	74.19	0.00	225.00	0.00	100.00
165	0.47	79.02	0.00	225.00	0.00	100.00
170	0.48	83.86	0.00	225.00	0.00	100.00
175	0.54	88.70	0.00	225.00	0.00	100.00
180	0.42	93.55	0.00	225.00	0.00	100.00
185	0.25	98.40	0.00	225.00	0.00	100.00

SPACE EXPLORATION HOLDINGS
Ka, Q/V-Band Earth Station – Sherman, TX
Frequency Coordination Report
28/40/50 GHz

Coordination Values		SHERMAN, TX				
Licensee Name		SpaceX Services, Inc				
Latitude (NAD 83)		33° 41' 10.0" N				
Longitude (NAD 83)		96° 35' 12.6" W				
Ground Elevation (AMSL)		238.0 m / 780.8 ft				
Antenna Centerline (AGL)		1.4 m / 4.6 ft				
Antenna Model		SpaceX 1.99 meter				
Antenna Mode		Receive 40.0 GHz		Transmit 50.0 GHz		
Interference Objectives:		Long Term	-156.0 dBW/MHz	20%	-151.0 dBW/4 kHz	20%
		Short Term	-146.0 dBW/MHz	0.01%	-128.0 dBW/4 kHz	0.0025%
Max Available RF Power		-47.8 (dBW/4 kHz)				
Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 40.0 GHz		Transmit 50.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
190	0.24	103.24	0.00	225.00	0.00	100.00
195	0.22	108.08	0.00	225.00	0.00	100.00
200	0.23	112.90	0.00	225.00	0.00	100.00
205	0.33	117.70	0.00	225.00	0.00	100.00
210	0.50	122.47	0.00	225.00	0.00	100.00
215	0.59	127.21	0.00	225.00	0.00	100.00
220	0.56	131.95	0.00	225.00	0.00	100.00
225	0.54	136.64	0.00	225.00	0.00	100.00
230	0.55	141.26	0.00	225.00	0.00	100.00
235	0.63	145.76	0.00	225.00	0.00	100.00
240	0.66	150.15	0.00	225.00	0.00	100.00
245	0.64	154.36	0.00	225.00	0.00	100.00
250	0.55	158.31	0.00	225.00	0.00	100.00
255	0.54	161.70	0.00	225.00	0.00	100.00
260	0.58	164.20	0.00	225.00	0.00	100.00
265	0.56	165.46	0.00	225.00	0.00	100.00
270	0.50	165.13	0.00	225.00	0.00	100.00
275	0.44	163.28	0.00	225.00	0.00	100.00
280	0.42	160.29	0.00	225.00	0.00	100.00
285	0.64	156.49	0.00	225.00	0.00	100.00
290	0.47	152.52	0.00	225.00	0.00	100.00
295	0.39	148.24	0.00	225.00	0.00	100.00
300	0.32	143.78	0.00	225.00	0.00	100.00
305	0.39	139.17	0.00	225.00	0.00	100.00
310	0.39	134.51	0.00	225.00	0.00	100.00
315	0.33	129.80	0.00	225.00	0.00	100.00
320	0.00	125.11	0.00	225.00	0.00	100.00
325	0.00	120.32	0.00	225.00	0.00	100.00
330	0.00	115.51	0.00	225.00	0.00	100.00
335	0.00	110.68	0.00	225.00	0.00	100.00
340	0.00	105.85	0.00	225.00	0.00	100.00
345	0.00	101.00	0.00	225.00	0.00	100.00
350	0.00	96.15	0.00	225.00	0.00	100.00
355	0.00	91.30	0.00	225.00	0.00	100.00



5. Contact Information

For questions or information regarding the Ka, Q/V-band Frequency Coordination Report, please contact:

Contact person:	Gary Edwards
Title:	Senior Manager, Satellite Services
Company:	Comsearch
Address:	21515 Ridgetop Circle, Suite 300, Sterling, VA 20166
Telephone:	703-726-5662
Email:	GEdwards@Comsearch.com
Web site:	www.comsearch.com

FREQUENCY COORDINATION AND INTERFERENCE ANALYSIS REPORT

Prepared for
SpaceX Services, Inc
SHERMAN, TX
Satellite Earth Station

Prepared By:
COMSEARCH
21515 Ridgetop Circle, Suite 300
Sterling, VA 20166
July 20, 2026

TABLE OF CONTENTS

1. CONCLUSIONS 3

2. SUMMARY OF RESULTS 4

3. SUPPLEMENTAL SHOWING 5

4. EARTH STATION COORDINATION DATA..... 8

5. CERTIFICATION..... 15

1. CONCLUSIONS

An interference study considering all existing, proposed and prior coordinated microwave facilities within the coordination contours of the proposed earth station demonstrates that this site will operate satisfactorily with the common carrier microwave environment. Further, there will be no restrictions of its operation due to interference considerations.

2. SUMMARY OF RESULTS

A number of great circle interference cases were identified during the interference study of the proposed earth station. Each of the cases, which exceeded the interference objective on a line-of-sight basis, was profiled and the propagation losses estimated using NBS TN101 (Revised) techniques. The losses were found to be sufficient to reduce the signal levels to acceptable magnitudes in every case.

3. SUPPLEMENTAL SHOWING

Pursuant to Part 25.203(c) of the FCC Rules and Regulations, the satellite earth station proposed in this application was coordinated by Comsearch using computer techniques and in accordance with Part 25 of the FCC Rules and Regulations.

Coordination data for this earth station was sent to the below listed carriers with a letter dated 06/23/2026.

Company

3 Rooms Communications LLC
360 Broadband, LLC
AMA Communications, LLC
AMG Technology Investment Group LLC
AT&T Enterprises, LLC
AT&T Mobility Spectrum LLC - North Texas
AT&T Mobility Spectrum LLC - South Texas
ATLink Services, LLC
Above All Satellite Systems L.L.C
Air Canopy Internet Services, Inc.
Airosurf Communications, Inc.
Arbuckle Communications, LLC
Audacy License, LLC
BNSF Railway Company
BelWave Communications
Business Only Broadband, LLC
Carrollton City of Texas/ACS
Cellco Partnership-C TX/LA/AR/OK
Chickasaw Personal Communications
City of Allen, Texas
City of Dallas
City of Denton Water Production Division
City of Farmers Branch Texas
City of Frisco
City of Gainesville (Texas)
City of Grand Prairie
City of Grapevine
City of Lewisville
City of McKinney
City of North Richland Hills
City of Oklahoma City
City of Plano
City of Richardson
City of University Park
City of Wichita Falls, Texas
Cobalt Ridge LLC
Collin, County of
Community Telephone Company
Conterra Ultra Broadband, LLC
County of Wichita Falls

Dallas Area Rapid Transit Authority
Denison, City of
Denton Commercial Internet, Inc
Denton County Sheriffs Office
Digitex.com
Dish Wireless LLC
ECTISP Inc.
ElektraFI N-TX LLC
ExxonMobil
Fort Worth, City of
Genco, Inc.
Global Telecom & Technology Americas
Granbury, City of
Griffin Licensing, LLC
HILCO Electric Cooperative, Inc.
Hood County Sheriffs Department
Kaufman County Sheriff Department
Legacy ISP, LLC
Legacy Texas Bank
Linux Internet, LLC
MHO Networks
NW Communications of Texas, Inc.
New Cingular Wireless PCS LLC - N Texas
New Cingular Wireless PCS LLC - S Texas
New Source Broadband I LLC
Nexstar Media Inc.
Nokia of America Corporation
Ohio/Oklahoma Hearst Argyle TV Inc.
Olympic Wireless, LLC
One Ring Networks, Inc.
PB Wireless Asset Entity, LLC
PRWireless PR, LLC
Peoples Electric Cooperative
Plains Internet, LLC
Prosper, City of
Rayburn Country Electric Cooperative Inc
Resonance Broadband LLC
Resound Networks
Rhino Communications, Inc
Silvers, Neal
Skyriver Communications
SmartBurst LLC
Sprint Spectrum LLC
Syntrio Solutions, LLC
T-Mobile MW LLC
TMN, Inc.
TTS-Linx
Targa Midstream Services LLC
Tarrant Regional Water District
Texas A&M University - Commerce Ketr
Texas New Mexico Power Company
Texas RSA 7B1 Limited Partnership
Texas RSA 7B3, LLC
Texoma Communications, LLC
The City of Princeton
Towerstream Corp.

UniMas Dallas LLC
Union Pacific Railroad Company
Upper Trinity Regional Water District
Vistra Corporate Services Company
WiFires Communications LLC
WireStar, Inc.
XO Communications, LLC

4. EARTH STATION COORDINATION DATA

This section presents the data pertinent to frequency coordination of the proposed earth station that was circulated to all carriers within its coordination contours.

COMSEARCH

Earth Station Data Sheet

21515 Ridgetop Circle, Suite 300, Sterling, VA 20166
(703)726-5662 <http://www.comsearch.com>

Date: 06/23/2026
Job Number: 260623COMSGE04

Administrative Information

Status ENGINEER PROPOSAL
Call Sign
Licensee Code SPACEX
Licensee Name SpaceX Services, Inc

Site Information

SHERMAN, TX
Venue Name ATHENS OF TEXAS
Latitude (NAD 83) 33° 41' 10.0" N
Longitude (NAD 83) 96° 35' 12.6" W
Climate Zone A
Rain Zone 2
Ground Elevation (AMSL) 238.0 m / 780.8 ft

Link Information

Satellite Type Low Earth Orbit
Mode TR - Transmit-Receive
Antenna Count 40
Modulation Digital
Minimum Elevation Angle 10.0°
Azimuth Range 0.0° to 360°
Antenna Centerline (AGL) 1.7 m / 5.6 ft

Antenna Information

Manufacturer
Model
Gain / Diameter
3-dB / 15-dB Beamwidth

Receive - FCC32

SpaceX
1.99 meter
50.0 dBi / 2.0 m
0.50° / 1.00°

Transmit - FCC32

SpaceX
1.99 meter
53.9 dBi / 2.0 m
0.30° / 0.60°

Max Available RF Power (dBW/4 kHz) -40.8
(dBW/MHz) -16.8

Maximum EIRP (dBW/4 kHz) 13.1
(dBW/MHz) 37.1

Aggregate EIRP (dBW/MHz) 37.1

Interference Objectives:	Long Term	-156.0 dBW/MHz	20%	-151.0 dBW/4 kHz 20%
	Short Term	-146.0 dBW/MHz	0.01%	-128.0 dBW/4 kHz 0.0025%

Frequency Information

Emission / Frequency Range (MHz)

Receive 18.0 GHz

60M0D7W - 480MD7W / 17300.0 - 17800.0
60M0D7W - 480MD7W / 17800.0 - 18600.0
60M0D7W - 480MD7W / 18600.0 - 18800.0
60M0D7W - 480MD7W / 18800.0 - 19300.0
60M0D7W - 480MD7W / 19300.0 - 19700.0
60M0D7W - 480MD7W / 19700.0 - 20200.0
60M0D7W - 480MD7W / 20200.0 - 21200.0

Transmit 28.0 GHz

60M0D7W - 480MD7W / 27500.0 - 29100.0
60M0D7W - 480MD7W / 29100.0 - 29500.0
60M0D7W - 480MD7W / 29500.0 - 30000.0
60M0D7W - 480MD7W / 30000.0 - 31000.0

Max Great Circle Coordination Distance	225.0 km / 139.8 mi	100.0 km / 62.1 mi
Precipitation Scatter Contour Radius	100.0 km / 62.1 mi	100.0 km / 62.1 mi

COMSEARCH**Earth Station Data Sheet**

21515 Ridgetop Circle, Suite 300, Sterling, VA 20166
 (703)726-5662 <http://www.comsearch.com>

Coordination Values		SHERMAN, TX			
Licensee Name		SpaceX Services, Inc			
Latitude (NAD 83)		33° 41' 10.0" N			
Longitude (NAD 83)		96° 35' 12.6" W			
Ground Elevation (AMSL)		238.0 m / 780.8 ft			
Antenna Centerline (AGL)		1.4 m / 4.6 ft			
Antenna Model		SpaceX 1.99 meter			
Antenna Mode		Receive 18.0 GHz		Transmit 28.0 GHz	
Interference Objectives:	Long Term	-156.0 dBW/MHz	20%	-151.0 dBW/4 kHz	20%
	Short Term	-146.0 dBW/MHz	0.01%	-128.0 dBW/4 kHz	0.0025%
Max Available RF Power		-40.8 (dBW/4 kHz)			

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 18.0 GHz		Transmit 28.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
0	0.00	86.45	0.00	225.00	0.00	100.00
5	0.00	81.59	0.00	225.00	0.00	100.00
10	0.00	76.75	0.00	225.00	0.00	100.00
15	0.00	71.91	0.00	225.00	0.00	100.00
20	0.00	67.07	0.00	225.00	0.00	100.00
25	0.37	62.30	0.00	225.00	0.00	100.00
30	0.47	57.53	0.00	225.00	0.00	100.00
35	0.71	52.81	0.00	225.00	0.00	100.00
40	0.96	48.15	0.00	225.00	0.00	100.00
45	1.26	43.56	0.00	225.00	0.00	100.00
50	1.61	39.09	0.00	225.00	0.00	100.00
55	1.51	34.58	0.00	225.00	0.00	100.00
60	1.69	30.33	0.00	225.00	0.00	100.00
65	1.69	26.22	0.00	225.00	0.00	100.00
70	1.75	22.49	0.00	225.00	0.00	100.00
75	1.50	19.06	0.00	225.00	0.00	100.00
80	1.28	16.44	0.00	225.00	0.00	100.00
85	1.16	15.14	0.00	225.00	0.00	100.00
90	1.16	15.51	0.00	225.00	0.00	100.00
95	1.11	17.30	0.00	225.00	0.00	100.00
100	1.10	20.19	0.00	225.00	0.00	100.00
105	1.12	23.80	0.00	225.00	0.00	100.00
110	1.14	27.81	0.00	225.00	0.00	100.00
115	1.00	32.02	0.00	225.00	0.00	100.00
120	1.00	36.46	0.00	225.00	0.00	100.00
125	0.80	40.96	0.00	225.00	0.00	100.00
130	0.69	45.57	0.00	225.00	0.00	100.00
135	0.49	50.23	0.00	225.00	0.00	100.00
140	0.49	54.98	0.00	225.00	0.00	100.00
145	0.50	59.76	0.00	225.00	0.00	100.00
150	0.51	64.55	0.00	225.00	0.00	100.00
155	0.51	69.37	0.00	225.00	0.00	100.00
160	0.48	74.19	0.00	225.00	0.00	100.00
165	0.47	79.02	0.00	225.00	0.00	100.00
170	0.48	83.86	0.00	225.00	0.00	100.00
175	0.54	88.70	0.00	225.00	0.00	100.00
180	0.42	93.55	0.00	225.00	0.00	100.00
185	0.25	98.40	0.00	225.00	0.00	100.00

COMSEARCH

Earth Station Data Sheet

21515 Ridgetop Circle, Suite 300, Sterling, VA 20166
(703)726-5662 <http://www.comsearch.com>

Coordination Values		SHERMAN, TX			
Licensee Name		SpaceX Services, Inc			
Latitude (NAD 83)		33° 41' 10.0" N			
Longitude (NAD 83)		96° 35' 12.6" W			
Ground Elevation (AMSL)		238.0 m / 780.8 ft			
Antenna Centerline (AGL)		1.4 m / 4.6 ft			
Antenna Model		SpaceX 1.99 meter			
Antenna Mode		Receive 18.0 GHz		Transmit 28.0 GHz	
Interference Objectives: Long Term		-156.0 dBW/MHz	20%	-151.0 dBW/4 kHz	20%
Short Term		-146.0 dBW/MHz	0.01%	-128.0 dBW/4 kHz	0.0025%
Max Available RF Power		-40.8 (dBW/4 kHz)			

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 18.0 GHz		Transmit 28.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
190	0.24	103.24	0.00	225.00	0.00	100.00
195	0.22	108.08	0.00	225.00	0.00	100.00
200	0.23	112.90	0.00	225.00	0.00	100.00
205	0.33	117.70	0.00	225.00	0.00	100.00
210	0.50	122.47	0.00	225.00	0.00	100.00
215	0.59	127.21	0.00	225.00	0.00	100.00
220	0.56	131.95	0.00	225.00	0.00	100.00
225	0.54	136.64	0.00	225.00	0.00	100.00
230	0.55	141.26	0.00	225.00	0.00	100.00
235	0.63	145.76	0.00	225.00	0.00	100.00
240	0.66	150.15	0.00	225.00	0.00	100.00
245	0.64	154.36	0.00	225.00	0.00	100.00
250	0.55	158.31	0.00	225.00	0.00	100.00
255	0.54	161.70	0.00	225.00	0.00	100.00
260	0.58	164.20	0.00	225.00	0.00	100.00
265	0.56	165.46	0.00	225.00	0.00	100.00
270	0.50	165.13	0.00	225.00	0.00	100.00
275	0.44	163.28	0.00	225.00	0.00	100.00
280	0.42	160.29	0.00	225.00	0.00	100.00
285	0.64	156.49	0.00	225.00	0.00	100.00
290	0.47	152.52	0.00	225.00	0.00	100.00
295	0.39	148.24	0.00	225.00	0.00	100.00
300	0.32	143.78	0.00	225.00	0.00	100.00
305	0.39	139.17	0.00	225.00	0.00	100.00
310	0.39	134.51	0.00	225.00	0.00	100.00
315	0.33	129.80	0.00	225.00	0.00	100.00
320	0.00	125.11	0.00	225.00	0.00	100.00
325	0.00	120.32	0.00	225.00	0.00	100.00
330	0.00	115.51	0.00	225.00	0.00	100.00
335	0.00	110.68	0.00	225.00	0.00	100.00
340	0.00	105.85	0.00	225.00	0.00	100.00
345	0.00	101.00	0.00	225.00	0.00	100.00
350	0.00	96.15	0.00	225.00	0.00	100.00
355	0.00	91.30	0.00	225.00	0.00	100.00

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Date: 06/23/2026
Job Number: 260623COMSGE04

Administrative Information

Status: ENGINEER PROPOSAL
Call Sign:
Licensee Code: SPACEX
Licensee Name: SpaceX Services, Inc

Site Information

SHERMAN, TX
Venue Name: ATHENS OF TEXAS
Latitude (NAD 83): 33° 41' 10.0" N
Longitude (NAD 83): 96° 35' 12.6" W
Climate Zone: A
Rain Zone: 2
Ground Elevation (AMSL): 238.0 m / 780.8 ft

Link Information

Satellite Type: Low Earth Orbit
Mode: TR - Transmit-Receive
Antenna Count: 40
Modulation: Digital
Minimum Elevation Angle: 10.0°
Azimuth Range: 0.0° to 360°
Antenna Centerline (AGL): 1.7 m / 5.6 ft

Antenna Information

Manufacturer:
Model:
Gain / Diameter:
3-dB / 15-dB Beamwidth:

Receive - FCC32

SpaceX
1.99 meter
55.9 dBi / 2.0 m
0.25° / 0.50°

Transmit - FCC32

SpaceX
1.99 meter
58.1 dBi / 2.0 m
0.20° / 0.40°

Max Available RF Power (dBW/4 kHz): -47.8
(dBW/MHz): -23.8

Maximum EIRP (dBW/4 kHz): 10.3
(dBW/MHz): 34.3

Aggregate EIRP (dBW/MHz): 34.3

Interference Objectives: Long Term: -156.0 dBW/MHz 20% -151.0 dBW/4 kHz 20%
Short Term: -146.0 dBW/MHz 0.01% -128.0 dBW/4 kHz 0.0025%

Frequency Information

Receive 40.0 GHz

Emission / Frequency Range (MHz): 60M0D7W - 480MD7W / 37500.0 - 42500.0

Transmit 50.0 GHz

60M0D7W - 480MD7W / 47200.0 - 50200.0
60M0D7W - 480MD7W / 50400.0 - 51400.0
60M0D7W - 480MD7W / 51400.0 - 52400.0

Max Great Circle Coordination Distance: 225.0 km / 139.8 mi 100.0 km / 62.1 mi
Precipitation Scatter Contour Radius: 100.0 km / 62.1 mi 100.0 km / 62.1 mi

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Coordination Values		SHERMAN, TX		
Licensee Name		SpaceX Services, Inc		
Latitude (NAD 83)		33° 41' 10.0" N		
Longitude (NAD 83)		96° 35' 12.6" W		
Ground Elevation (AMSL)		238.0 m / 780.8 ft		
Antenna Centerline (AGL)		1.4 m / 4.6 ft		
Antenna Model		SpaceX 1.99 meter		
Antenna Mode		Receive 40.0 GHz	Transmit 50.0 GHz	
Interference Objectives:	Long Term	-156.0 dBW/MHz	20%	-151.0 dBW/4 kHz 20%
	Short Term	-146.0 dBW/MHz	0.01%	-128.0 dBW/4 kHz 0.0025%
Max Available RF Power		-47.8 (dBW/4 kHz)		

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 40.0 GHz		Transmit 50.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
0	0.00	86.45	0.00	225.00	0.00	100.00
5	0.00	81.59	0.00	225.00	0.00	100.00
10	0.00	76.75	0.00	225.00	0.00	100.00
15	0.00	71.91	0.00	225.00	0.00	100.00
20	0.00	67.07	0.00	225.00	0.00	100.00
25	0.37	62.30	0.00	225.00	0.00	100.00
30	0.47	57.53	0.00	225.00	0.00	100.00
35	0.71	52.81	0.00	225.00	0.00	100.00
40	0.96	48.15	0.00	225.00	0.00	100.00
45	1.26	43.56	0.00	225.00	0.00	100.00
50	1.61	39.09	0.00	225.00	0.00	100.00
55	1.51	34.58	0.00	225.00	0.00	100.00
60	1.69	30.33	0.00	225.00	0.00	100.00
65	1.69	26.22	0.00	225.00	0.00	100.00
70	1.75	22.49	0.00	225.00	0.00	100.00
75	1.50	19.06	0.00	225.00	0.00	100.00
80	1.28	16.44	0.00	225.00	0.00	100.00
85	1.16	15.14	0.00	225.00	0.00	100.00
90	1.16	15.51	0.00	225.00	0.00	100.00
95	1.11	17.30	0.00	225.00	0.00	100.00
100	1.10	20.19	0.00	225.00	0.00	100.00
105	1.12	23.80	0.00	225.00	0.00	100.00
110	1.14	27.81	0.00	225.00	0.00	100.00
115	1.00	32.02	0.00	225.00	0.00	100.00
120	1.00	36.46	0.00	225.00	0.00	100.00
125	0.80	40.96	0.00	225.00	0.00	100.00
130	0.69	45.57	0.00	225.00	0.00	100.00
135	0.49	50.23	0.00	225.00	0.00	100.00
140	0.49	54.98	0.00	225.00	0.00	100.00
145	0.50	59.76	0.00	225.00	0.00	100.00
150	0.51	64.55	0.00	225.00	0.00	100.00
155	0.51	69.37	0.00	225.00	0.00	100.00
160	0.48	74.19	0.00	225.00	0.00	100.00
165	0.47	79.02	0.00	225.00	0.00	100.00
170	0.48	83.86	0.00	225.00	0.00	100.00
175	0.54	88.70	0.00	225.00	0.00	100.00
180	0.42	93.55	0.00	225.00	0.00	100.00
185	0.25	98.40	0.00	225.00	0.00	100.00

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Coordination Values

SHERMAN, TX

Licensee Name SpaceX Services, Inc
Latitude (NAD 83) 33° 41' 10.0" N
Longitude (NAD 83) 96° 35' 12.6" W
Ground Elevation (AMSL) 238.0 m / 780.8 ft
Antenna Centerline (AGL) 1.4 m / 4.6 ft
Antenna Model SpaceX 1.99 meter

Antenna Mode Receive 40.0 GHz

Transmit 50.0 GHz

Interference Objectives: Long Term

-156.0 dBW/MHz

20%

-151.0 dBW/4 kHz 20%

Short Term

-146.0 dBW/MHz

0.01%

-128.0 dBW/4 kHz 0.0025%


Max Available RF Power

-47.8 (dBW/4 kHz)

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 40.0 GHz		Transmit 50.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
190	0.24	103.24	0.00	225.00	0.00	100.00
195	0.22	108.08	0.00	225.00	0.00	100.00
200	0.23	112.90	0.00	225.00	0.00	100.00
205	0.33	117.70	0.00	225.00	0.00	100.00
210	0.50	122.47	0.00	225.00	0.00	100.00
215	0.59	127.21	0.00	225.00	0.00	100.00
220	0.56	131.95	0.00	225.00	0.00	100.00
225	0.54	136.64	0.00	225.00	0.00	100.00
230	0.55	141.26	0.00	225.00	0.00	100.00
235	0.63	145.76	0.00	225.00	0.00	100.00
240	0.66	150.15	0.00	225.00	0.00	100.00
245	0.64	154.36	0.00	225.00	0.00	100.00
250	0.55	158.31	0.00	225.00	0.00	100.00
255	0.54	161.70	0.00	225.00	0.00	100.00
260	0.58	164.20	0.00	225.00	0.00	100.00
265	0.56	165.46	0.00	225.00	0.00	100.00
270	0.50	165.13	0.00	225.00	0.00	100.00
275	0.44	163.28	0.00	225.00	0.00	100.00
280	0.42	160.29	0.00	225.00	0.00	100.00
285	0.64	156.49	0.00	225.00	0.00	100.00
290	0.47	152.52	0.00	225.00	0.00	100.00
295	0.39	148.24	0.00	225.00	0.00	100.00
300	0.32	143.78	0.00	225.00	0.00	100.00
305	0.39	139.17	0.00	225.00	0.00	100.00
310	0.39	134.51	0.00	225.00	0.00	100.00
315	0.33	129.80	0.00	225.00	0.00	100.00
320	0.00	125.11	0.00	225.00	0.00	100.00
325	0.00	120.32	0.00	225.00	0.00	100.00
330	0.00	115.51	0.00	225.00	0.00	100.00
335	0.00	110.68	0.00	225.00	0.00	100.00
340	0.00	105.85	0.00	225.00	0.00	100.00
345	0.00	101.00	0.00	225.00	0.00	100.00
350	0.00	96.15	0.00	225.00	0.00	100.00
355	0.00	91.30	0.00	225.00	0.00	100.00

5. CERTIFICATION

I HEREBY CERTIFY THAT I AM THE TECHNICALLY QUALIFIED PERSON RESPONSIBLE FOR THE PREPARATION OF THE FREQUENCY COORDINATION DATA CONTAINED IN THIS APPLICATION, THAT I AM FAMILIAR WITH PARTS 101 AND 25 OF THE FCC RULES AND REGULATIONS, THAT I HAVE EITHER PREPARED OR REVIEWED THE FREQUENCY COORDINATION DATA SUBMITTED WITH THIS APPLICATION, AND THAT IT IS COMPLETE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

BY: 

Gary K. Edwards
Senior Manager
COMSEARCH
21515 Ridgetop Circle, Suite 300
Sterling, VA 20166

DATED: July 20, 2026



E-band Frequency Coordination Report

The “Athens of Texas” Gateway (Sherman, TX)

June 22, 2026



Summary

SpaceX performed a coordination notice under Section 25.203(c), Section 25.251, and Appendix 7 of the ITU's Radio Regulations. Prior-notification letters with earth station details were sent to potentially affected terrestrial licensees; a copy of these details are available in this report. The earth station coordination was finalized on July 07, 2026. No objections were received from any terrestrial licensees.

Methodology

SpaceX has completed an interference analysis based on accepted international and Commission methodologies demonstrating that this satellite earth station will not cause harmful interference to existing terrestrial facilities in the band. Specifically, for each known receiver within the great circle coordination distance surrounding the proposed earth station, SpaceX calculated the expected interference/noise ratio (I/N) to the receiver, assuming the SpaceX antenna properties listed on the following page, SpaceX site layout and design, free-space propagation without terrain or clutter, and actual characteristics of receiver(s) obtained from the 70/80/90 GHz link-registration database. Even under these conservative assumptions, SpaceX's analysis confirms that this earth station will not cause interference exceeding 1.0 dB of degradation to the static threshold of existing 70/80 GHz links within the great circle coordination distance.¹

Operators contacted

Prior-coordination letters were sent to the following operators:

1. 3 Rooms Communications LLC
2. AMG Technology Investment Group, LLC
3. Aviat Networks
4. BNSF Railway Co
5. BOB, LLC
6. BOB, LLC dba Business Only Broadband
7. BelWave Communications, Inc.
8. Charlotte Wi-Fi Inc. dba National Wi-Fi
9. Communications Law Counsel, PLLC
10. Crown Castle Fiber LLC
11. Digis LLC
12. ElektraFI N-TX LLC
13. Fujitsu Network Communications, Inc.
14. Herman & Whiteaker, LLC

¹ If there were any cases in which the interference threshold was exceeded in the conservative free-space analysis for any relevant receiver, SpaceX conducted an additional analysis with more realistic assumptions of terrain and clutter, under which the interference threshold was not exceeded for any relevant receiver. This further ensures that there will be no above-threshold interference to existing receivers.

15. Huffman Communications
16. JTS
17. Kaufman County Sheriff's Office
18. Micronet Communications, Inc.
19. Morgan, Lewis & Bockius LLP
20. Nokia of America Corporation
21. Outpost Plus
22. PB Wireless Asset Entity, LLC
23. REMEC Broadband Wireless Networks LLC DBA Bridgewave Communications
24. Raytheon Company
25. SIAE Microelettronica, Inc.
26. Scientel Solutions LLC
27. Siklu, Inc
28. Skyriver Communications
29. Skywire LLC
30. SpaceX
31. T-MOBILE LICENSE LLC
32. Tarrant Regional Water District
33. Texas RSA 7B3, LLC
34. Towerstream Corp
35. Welink Communications, Inc.
36. WiLine Spectrum Holdings LLC
37. WireStar, Inc.

Earth Station Data

This section presents the data that was circulated to all operators that met the criteria for notification for this earth station.

Site Information:

- Transmitting station name: The "Athens of Texas" Gateway
- Transmitting station coordinates: 33.686121, -96.586836
- Ground Elevation (AMSL): 238.0 m
- Antenna Count: 40
- Aggregate EIRP toward the horizon: -9 dBW/MHz

Frequency Information:

- Transmit: 81-86 GHz
- Receive: 71-76 GHz
- Max Great Circle Coordination Distance: 127 km
- Rain Scatter Coordination Distance Contour: 6 km

Link Information:

- Satellite Type: Low Earth Orbit
- Mode: TR – Transmit-Receive
- Modulation: Digital
- Minimum Elevation Angle: 15.0°
- Azimuth Range: 0.0° to 360.0°
- Antenna Centerline (AGL): 1.4 m

Antenna Information:

- Manufacturer: SpaceX
- Model/Diameter: 1.99m
- Gain: 60.9 dBi at 83.5 GHz
- Max Available RF Power: -20.8 dBW/MHz
- Horizon Gain: 0 dBi
- Maximum EIRP: 40.1 dBW/MHz (main beam)
- Permissible RF Interference Power Level²: I/N ≤ -6 dB
- Antenna Mask: ITU-R S.580

² See 47 CFR § 101.105(a)(5)(i). This I/N value would cause a maximum of 1.0 dB of degradation to the static threshold of the protected receiver.

Horizon Angle by Azimuth:

All values are in degrees

Azimuth	Horizon Angle
0.0	0.02
5.0	-0.02
10.0	-0.07
15.0	-0.01
20.0	-0.03
25.0	-0.02
30.0	-0.11
35.0	-0.13
40.0	-0.12
45.0	-0.07
50.0	-0.14
55.0	-0.16
60.0	-0.08
65.0	-0.13
70.0	-0.20
75.0	-0.25
80.0	-0.23
85.0	-0.25
90.0	-0.20
95.0	-0.17
100.0	-0.08
105.0	-0.01
110.0	-0.03
115.0	-0.06
120.0	-0.09
125.0	-0.05
130.0	0.05
135.0	0.18
140.0	0.24
145.0	0.34
150.0	0.43
155.0	0.49
160.0	0.56
165.0	0.64
170.0	0.74
175.0	0.68
180.0	0.45
185.0	0.32
190.0	0.21
195.0	0.27



Frequency Coordination Report
E-Band Earth Station

200.0	0.27
205.0	0.31
210.0	0.46
215.0	0.52
220.0	0.58
225.0	0.64
230.0	0.70
235.0	0.71
240.0	0.72
245.0	0.59
250.0	0.44
255.0	0.39
260.0	0.35
265.0	0.33
270.0	0.40
275.0	0.33
280.0	0.36
285.0	0.36
290.0	0.28
295.0	0.29
300.0	0.18
305.0	0.22
310.0	0.18
315.0	0.18
320.0	0.11
325.0	-0.05
330.0	0.01
335.0	0.13
340.0	0.13
345.0	0.16
350.0	0.11
355.0	0.11