

Ka, Q/V-Band Earth Station – Centerville, UT.

Frequency Coordination Report

Ka, Q/V-Band

Receive: 37.5 – 42.5 GHz Transmit: 27.5 – 31.0 GHz, 47.2 – 50.2, 50.4 – 52.4 GHz



Prepared on Behalf of
SPACE EXPLORATION
HOLDINGS

April 29, 2026



Table of Contents

1.	Summary of Results	- 1 -
2.	40/50 GHz Common Carrier and LTTS Coordination	- 1 -
3.	28/40/50 GHz UMFUS Coordination	- 2 -
4.	Earth Station Coordination Data	- 3 -
5.	Contact Information	- 7 -



1. Summary of Results

On behalf of SPACE EXPLORATION HOLDINGS, Comsearch performed a coordination notice under Section 25.203(c) of the FCC's rules for all existing and proposed terrestrial licenses within the coordination contours of their proposed Ka, Q/V-band earth station in Centerville, UT, which will receive at 40 GHz and transmit at 28 and 50 GHz¹. Prior-notification letters were sent to the licensees and a copy of the notification data is provided in section four of this report. The earth station coordination was finalized on April 27, 2026.

There are no unresolved objections from any of the incumbent 28/40/50 GHz licensees.

2. 28/40/50 GHz Common Carrier and LTTS Coordination

In accordance with FCC Rules and Regulations, the Ka, Q/V-band earth station in Centerville, UT was prior-coordinated by Comsearch. A notification letter and datasheets for this earth station were sent to the following 28/40/50 GHz common carrier fixed microwave licensees. These licensees are authorized to operate temporary fixed operations from 38.6 – 40.0 GHz on a nationwide basis or local basis.

Licensee	Authorized Geographic Area
Telstar Communications	Statewide: WY

A notification letter and datasheets for the Ka, Q/V-band earth station in Centerville, UT were also sent to the following 40 GHz LTTS licensee. This licensee is authorized to operate temporary fixed operations from 38.6 – 40.0 GHz on a market basis.

Licensee	Authorized Geographic Area
Broadcast Sports International, LLC	Nationwide
Remote Facilities Consulting Services Inc.	Nationwide
DCI II Inc	Nationwide

No objections were received from the common carrier or LTTS incumbents.

¹ The proposed earth station will receive in the 37.5 – 42.5 GHz & transmit in the 47.2-50.2 GHz / 50.4-52.4 GHz portion of the Q/V-Band. Ka-band transmissions will be in the 27.5 – 31.0 GHz band.

3. 28/40/50 GHz UMFUS Coordination

There were nine 28/40/50 GHz UMFUS licensees identified within the coordination distance of the proposed earth station. The proposed earth station will operate on frequencies that overlap portions of the UMFUS service which includes the following frequency ranges:

27.5 GHz – 31.0 GHz
37.5 GHz – 42.5 GHz
47.2 GHz – 50.2 GHz

Licensee	Authorized Geographic Area
AT&T	Market Based
LICT Wireless Broadband Company	Market Based
GeoLinks	Market Based
DISH Network	Market Based
UBET	Market Based
Union Telephone	Market Based
T-Mobile	Market Based
Monarch Wireless	Market Based
Verizon	Market Based

There were no specific objections from the UMFUS incumbents within the coordination distance at the end of the coordination period.



4. Earth Station Coordination Data

This section presents the data pertinent to the proposed Ka, Q/V-band earth station in Centerville, UT. This data was circulated to all incumbent licensees in the shared 28/40/50 GHz frequency ranges.

Date: 03/26/2026
Job Number: 260326COMSGE13

Administrative Information

Status: ENGINEER PROPOSAL
Call Sign:
Licensee Code: SPACEX
Licensee Name: SpaceX Services, Inc

Site Information

CENTERVILLE, UT
Venue Name: SMACK DAB IN IT
Latitude (NAD 83): 40° 54' 56.9" N
Longitude (NAD 83): 111° 53' 38.4" W
Climate Zone: A
Rain Zone: 5
Ground Elevation (AMSL): 1291.01 m / 4235.6 ft

Link Information

Satellite Type: Low Earth Orbit
Mode: TR - Transmit-Receive
Antenna Count: 40
Modulation: Digital
Minimum Elevation Angle: 10.0°
Azimuth Range: 0.0° to 360°
Antenna Centerline (AGL): 8.59 m / 28.2 ft

Antenna Information

Manufacturer: SpaceX
Model: 1.99 meter
Gain / Diameter: 50.0 dBi / 2.0 m
3-dB / 15-dB Beamwidth: 0.50° / 1.00°

Receive - FCC32

SpaceX
1.99 meter
50.0 dBi / 2.0 m
0.50° / 1.00°

Transmit - FCC32

SpaceX
1.99 meter
53.9 dBi / 2.0 m
0.30° / 0.60°

Max Available RF Power (dBW/4 kHz)
(dBW/MHz)

-40.8
-16.8

Maximum EIRP (dBW/4 kHz)
(dBW/MHz)

13.1
37.1

Aggregate EIRP (dBW/MHz)

37.1

Interference Objectives: Long Term -156.0 dBW/MHz 20%
Short Term -146.0 dBW/MHz 0.01%

-151.0 dBW/4 kHz 20%
-128.0 dBW/4 kHz 0.0025%

Frequency Information

Receive 18.0 GHz
Emission / Frequency Range (MHz)
60M0D7W - 480MD7W / 17300.0 - 17800.0
60M0D7W - 480MD7W / 17800.0 - 18600.0
60M0D7W - 480MD7W / 18600.0 - 18800.0
60M0D7W - 480MD7W / 18800.0 - 19300.0
60M0D7W - 480MD7W / 19300.0 - 19700.0
60M0D7W - 480MD7W / 19700.0 - 20200.0
60M0D7W - 480MD7W / 20200.0 - 21200.0

Transmit 28.0 GHz

60M0D7W - 480MD7W / 27500.0 - 29100.0
60M0D7W - 480MD7W / 29100.0 - 29500.0
60M0D7W - 480MD7W / 29500.0 - 30000.0
60M0D7W - 480MD7W / 30000.0 - 31000.0

Max Great Circle Coordination Distance: 225.0 km / 139.8 mi
Precipitation Scatter Contour Radius: 100.0 km / 62.1 mi

100.0 km / 62.1 mi
100.0 km / 62.1 mi

SPACE EXPLORATION HOLDINGS
Ka, Q/V-Band Earth Station – Centerville, UT
Frequency Coordination Report
28/40/50 GHz

Coordination Values		CENTERVILLE, UT				
Licensee Name		SpaceX Services, Inc				
Latitude (NAD 83)		40° 54' 56.9" N				
Longitude (NAD 83)		111° 53' 38.4" W				
Ground Elevation (AMSL)		1291.01 m / 4235.6 ft				
Antenna Centerline (AGL)		8.59 m / 28.2 ft				
Antenna Model		SpaceX 1.99 meter				
Antenna Mode		Receive 18.0 GHz		Transmit 28.0 GHz		
Interference Objectives: Long Term		-156.0 dBW/MHz	20%	-151.0 dBW/4 kHz	20%	
		Short Term	0.01%	-128.0 dBW/4 kHz	0.0025%	
Max Available RF Power		-40.8 (dBW/4 kHz)				
Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 18.0 GHz		Transmit 28.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
0	0.00	76.59	0.00	225.00	0.00	100.00
5	0.00	72.07	0.00	225.00	0.00	100.00
10	1.11	67.78	0.00	225.00	0.00	100.00
15	3.48	63.96	0.00	225.00	0.00	100.00
20	5.19	60.26	0.00	225.00	0.00	100.00
25	6.43	56.66	0.00	225.00	0.00	100.00
30	6.85	52.95	0.00	225.00	0.00	100.00
35	8.05	49.85	0.00	225.00	0.00	100.00
40	8.71	46.78	0.00	225.00	0.00	100.00
45	9.58	44.18	0.00	225.00	0.00	100.00
50	10.23	41.82	0.00	225.00	0.00	100.00
55	10.01	39.20	0.00	225.00	0.00	100.00
60	9.96	37.11	0.00	225.00	0.00	100.00
65	10.02	35.63	0.00	225.00	0.00	100.00
70	9.36	34.01	0.00	225.00	0.00	100.00
75	8.77	33.06	0.00	225.00	0.00	100.00
80	9.68	34.26	0.00	225.00	0.00	100.00
85	8.04	33.61	0.00	225.00	0.00	100.00
90	8.51	35.62	0.00	225.00	0.00	100.00
95	8.96	38.08	0.00	225.00	0.00	100.00
100	8.21	40.01	0.00	225.00	0.00	100.00
105	6.80	41.97	0.00	225.00	0.00	100.00
110	6.81	45.28	0.00	225.00	0.00	100.00
115	6.33	48.57	0.00	225.00	0.00	100.00
120	5.65	52.01	0.00	225.00	0.00	100.00
125	5.96	56.07	0.00	225.00	0.00	100.00
130	5.07	59.79	0.00	225.00	0.00	100.00
135	3.82	63.61	0.00	225.00	0.00	100.00
140	2.89	67.69	0.00	225.00	0.00	100.00
145	3.23	72.12	0.00	225.00	0.00	100.00
150	3.82	76.58	0.00	225.00	0.00	100.00
155	3.61	80.95	0.00	225.00	0.00	100.00
160	2.81	85.32	0.00	225.00	0.00	100.00
165	2.71	89.77	0.00	225.00	0.00	100.00
170	1.81	94.26	0.00	225.00	0.00	100.00
175	1.38	98.77	0.00	225.00	0.00	100.00
180	0.90	103.31	0.00	225.00	0.00	100.00
185	0.37	107.88	0.00	225.00	0.00	100.00

SPACE EXPLORATION HOLDINGS
Ka, Q/V-Band Earth Station – Centerville, UT
Frequency Coordination Report
28/40/50 GHz

Coordination Values		CENTERVILLE, UT				
Licensee Name		SpaceX Services, Inc				
Latitude (NAD 83)		40° 54' 56.9" N				
Longitude (NAD 83)		111° 53' 38.4" W				
Ground Elevation (AMSL)		1291.01 m / 4235.6 ft				
Antenna Centerline (AGL)		8.59 m / 28.2 ft				
Antenna Model		SpaceX 1.99 meter				
Antenna Mode		Receive 18.0 GHz		Transmit 28.0 GHz		
Interference Objectives: Long Term		-156.0 dBW/MHz	20%	-151.0 dBW/4 kHz	20%	
		Short Term	0.01%	-128.0 dBW/4 kHz	0.0025%	
Max Available RF Power		-40.8 (dBW/4 kHz)				
Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 18.0 GHz		Transmit 28.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
190	0.00	112.43	0.00	225.00	0.00	100.00
195	0.00	116.88	0.00	225.00	0.00	100.00
200	0.00	121.30	0.00	225.00	0.00	100.00
205	0.00	125.64	0.00	225.00	0.00	100.00
210	0.00	129.91	0.00	225.00	0.00	100.00
215	0.00	134.07	0.00	225.00	0.00	100.00
220	0.00	138.10	0.00	225.00	0.00	100.00
225	0.00	141.93	0.00	225.00	0.00	100.00
230	0.00	145.52	0.00	225.00	0.00	100.00
235	0.00	148.77	0.00	225.00	0.00	100.00
240	0.00	151.56	0.00	225.00	0.00	100.00
245	0.00	153.75	0.00	225.00	0.00	100.00
250	0.00	155.18	0.00	225.00	0.00	100.00
255	0.00	155.71	0.00	225.00	0.00	100.00
260	0.00	155.28	0.00	225.00	0.00	100.00
265	0.00	153.94	0.00	225.00	0.00	100.00
270	0.00	151.82	0.00	225.00	0.00	100.00
275	0.00	149.08	0.00	225.00	0.00	100.00
280	0.00	145.87	0.00	225.00	0.00	100.00
285	0.00	142.32	0.00	225.00	0.00	100.00
290	0.00	138.50	0.00	225.00	0.00	100.00
295	0.00	134.49	0.00	225.00	0.00	100.00
300	0.00	130.34	0.00	225.00	0.00	100.00
305	0.00	126.09	0.00	225.00	0.00	100.00
310	0.00	121.74	0.00	225.00	0.00	100.00
315	0.00	117.34	0.00	225.00	0.00	100.00
320	0.00	112.89	0.00	225.00	0.00	100.00
325	0.00	108.40	0.00	225.00	0.00	100.00
330	0.00	103.88	0.00	225.00	0.00	100.00
335	0.00	99.34	0.00	225.00	0.00	100.00
340	0.00	94.79	0.00	225.00	0.00	100.00
345	0.00	90.23	0.00	225.00	0.00	100.00
350	0.00	85.68	0.00	225.00	0.00	100.00
355	0.00	81.13	0.00	225.00	0.00	100.00

SPACE EXPLORATION HOLDINGS
Ka, Q/V-Band Earth Station – Centerville, UT
Frequency Coordination Report
28/40/50 GHz

Date: 03/26/2026
Job Number: 260326COMSGE13

Administrative Information

Status: ENGINEER PROPOSAL
Call Sign:
Licensee Code: SPACEX
Licensee Name: SpaceX Services, Inc

Site Information

CENTERVILLE, UT
Venue Name: SMACK DAB IN IT
Latitude (NAD 83): 40° 54' 56.9" N
Longitude (NAD 83): 111° 53' 38.4" W
Climate Zone: A
Rain Zone: 5
Ground Elevation (AMSL): 1291.01 m / 4235.6 ft

Link Information

Satellite Type: Low Earth Orbit
Mode: TR - Transmit-Receive
Antenna Count: 40
Modulation: Digital
Minimum Elevation Angle: 10.0°
Azimuth Range: 0.0° to 360°
Antenna Centerline (AGL): 8.59 m / 28.2 ft

Antenna Information

Manufacturer:
Model:
Gain / Diameter:
3-dB / 15-dB Beamwidth:

Receive - FCC32

SpaceX
1.99 meter
55.9 dBi / 2.0 m
0.25° / 0.50°

Transmit - FCC32

SpaceX
1.99 meter
58.1 dBi / 2.0 m
0.20° / 0.40°

Max Available RF Power (dBW/4 kHz)
(dBW/MHz)

-47.8
-23.8

Maximum EIRP (dBW/4 kHz)
(dBW/MHz)

10.3
34.3

Aggregate EIRP (dBW/MHz)

34.3

Interference Objectives: Long Term -156.0 dBW/MHz 20%
Short Term -146.0 dBW/MHz 0.01%

-151.0 dBW/4 kHz 20%
-128.0 dBW/4 kHz 0.0025%

Frequency Information

Emission / Frequency Range (MHz)

Receive 40.0 GHz

60M0D7W - 480MD7W / 37500.0 - 42500.0

Transmit 50.0 GHz

60M0D7W - 480MD7W / 47200.0 - 50200.0
60M0D7W - 480MD7W / 50400.0 - 51400.0
60M0D7W - 480MD7W / 51400.0 - 52400.0

Max Great Circle Coordination Distance
Precipitation Scatter Contour Radius

225.0 km / 139.8 mi
100.0 km / 62.1 mi

100.0 km / 62.1 mi
100.0 km / 62.1 mi

SPACE EXPLORATION HOLDINGS
Ka, Q/V-Band Earth Station – Centerville, UT
Frequency Coordination Report
28/40/50 GHz

Coordination Values		CENTERVILLE, UT				
Licensee Name		SpaceX Services, Inc				
Latitude (NAD 83)		40° 54' 56.9" N				
Longitude (NAD 83)		111° 53' 38.4" W				
Ground Elevation (AMSL)		1291.01 m / 4235.6 ft				
Antenna Centerline (AGL)		8.59 m / 28.2 ft				
Antenna Model		SpaceX 1.99 meter				
Antenna Mode		Receive 40.0 GHz		Transmit 50.0 GHz		
Interference Objectives: Long Term		-156.0 dBW/MHz	20%	-151.0 dBW/4 kHz	20%	
		Short Term	-146.0 dBW/MHz	0.01%	-128.0 dBW/4 kHz	0.0025%
Max Available RF Power		-47.8 (dBW/4 kHz)				
Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 40.0 GHz		Transmit 50.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
0	0.00	76.59	0.00	225.00	0.00	100.00
5	0.00	72.07	0.00	225.00	0.00	100.00
10	1.11	67.78	0.00	225.00	0.00	100.00
15	3.48	63.96	0.00	225.00	0.00	100.00
20	5.19	60.26	0.00	225.00	0.00	100.00
25	6.43	56.66	0.00	225.00	0.00	100.00
30	6.85	52.95	0.00	225.00	0.00	100.00
35	8.05	49.85	0.00	225.00	0.00	100.00
40	8.71	46.78	0.00	225.00	0.00	100.00
45	9.58	44.18	0.00	225.00	0.00	100.00
50	10.23	41.82	0.00	225.00	0.00	100.00
55	10.01	39.20	0.00	225.00	0.00	100.00
60	9.96	37.11	0.00	225.00	0.00	100.00
65	10.02	35.63	0.00	225.00	0.00	100.00
70	9.36	34.01	0.00	225.00	0.00	100.00
75	8.77	33.06	0.00	225.00	0.00	100.00
80	9.68	34.26	0.00	225.00	0.00	100.00
85	8.04	33.61	0.00	225.00	0.00	100.00
90	8.51	35.62	0.00	225.00	0.00	100.00
95	8.96	38.08	0.00	225.00	0.00	100.00
100	8.21	40.01	0.00	225.00	0.00	100.00
105	6.80	41.97	0.00	225.00	0.00	100.00
110	6.81	45.28	0.00	225.00	0.00	100.00
115	6.33	48.57	0.00	225.00	0.00	100.00
120	5.65	52.01	0.00	225.00	0.00	100.00
125	5.96	56.07	0.00	225.00	0.00	100.00
130	5.07	59.79	0.00	225.00	0.00	100.00
135	3.82	63.61	0.00	225.00	0.00	100.00
140	2.89	67.69	0.00	225.00	0.00	100.00
145	3.23	72.12	0.00	225.00	0.00	100.00
150	3.82	76.58	0.00	225.00	0.00	100.00
155	3.61	80.95	0.00	225.00	0.00	100.00
160	2.81	85.32	0.00	225.00	0.00	100.00
165	2.71	89.77	0.00	225.00	0.00	100.00
170	1.81	94.26	0.00	225.00	0.00	100.00
175	1.38	98.77	0.00	225.00	0.00	100.00
180	0.90	103.31	0.00	225.00	0.00	100.00
185	0.37	107.88	0.00	225.00	0.00	100.00

SPACE EXPLORATION HOLDINGS
Ka, Q/V-Band Earth Station – Centerville, UT
Frequency Coordination Report
28/40/50 GHz

Coordination Values		CENTERVILLE, UT				
Licensee Name		SpaceX Services, Inc				
Latitude (NAD 83)		40° 54' 56.9" N				
Longitude (NAD 83)		111° 53' 38.4" W				
Ground Elevation (AMSL)		1291.01 m / 4235.6 ft				
Antenna Centerline (AGL)		8.59 m / 28.2 ft				
Antenna Model		SpaceX 1.99 meter				
Antenna Mode		Receive 40.0 GHz		Transmit 50.0 GHz		
Interference Objectives: Long Term		-156.0 dBW/MHz	20%	-151.0 dBW/4 kHz	20%	
		Short Term	-146.0 dBW/MHz	0.01%	-128.0 dBW/4 kHz	0.0025%
Max Available RF Power		-47.8 (dBW/4 kHz)				
Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 40.0 GHz		Transmit 50.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
190	0.00	112.43	0.00	225.00	0.00	100.00
195	0.00	116.88	0.00	225.00	0.00	100.00
200	0.00	121.30	0.00	225.00	0.00	100.00
205	0.00	125.64	0.00	225.00	0.00	100.00
210	0.00	129.91	0.00	225.00	0.00	100.00
215	0.00	134.07	0.00	225.00	0.00	100.00
220	0.00	138.10	0.00	225.00	0.00	100.00
225	0.00	141.93	0.00	225.00	0.00	100.00
230	0.00	145.52	0.00	225.00	0.00	100.00
235	0.00	148.77	0.00	225.00	0.00	100.00
240	0.00	151.56	0.00	225.00	0.00	100.00
245	0.00	153.75	0.00	225.00	0.00	100.00
250	0.00	155.18	0.00	225.00	0.00	100.00
255	0.00	155.71	0.00	225.00	0.00	100.00
260	0.00	155.28	0.00	225.00	0.00	100.00
265	0.00	153.94	0.00	225.00	0.00	100.00
270	0.00	151.82	0.00	225.00	0.00	100.00
275	0.00	149.08	0.00	225.00	0.00	100.00
280	0.00	145.87	0.00	225.00	0.00	100.00
285	0.00	142.32	0.00	225.00	0.00	100.00
290	0.00	138.50	0.00	225.00	0.00	100.00
295	0.00	134.49	0.00	225.00	0.00	100.00
300	0.00	130.34	0.00	225.00	0.00	100.00
305	0.00	126.09	0.00	225.00	0.00	100.00
310	0.00	121.74	0.00	225.00	0.00	100.00
315	0.00	117.34	0.00	225.00	0.00	100.00
320	0.00	112.89	0.00	225.00	0.00	100.00
325	0.00	108.40	0.00	225.00	0.00	100.00
330	0.00	103.88	0.00	225.00	0.00	100.00
335	0.00	99.34	0.00	225.00	0.00	100.00
340	0.00	94.79	0.00	225.00	0.00	100.00
345	0.00	90.23	0.00	225.00	0.00	100.00
350	0.00	85.68	0.00	225.00	0.00	100.00
355	0.00	81.13	0.00	225.00	0.00	100.00



5. Contact Information

For questions or information regarding the Ka, Q/V-band Frequency Coordination Report, please contact:

Contact person:	Gary Edwards
Title:	Senior Manager, Satellite Services
Company:	Comsearch
Address:	21515 Ridgetop Circle, Suite 300, Sterling, VA 20166
Telephone:	703-726-5662
Email:	GEdwards@Comsearch.com
Web site:	www.comsearch.com

FREQUENCY COORDINATION AND INTERFERENCE ANALYSIS REPORT

Prepared for
SpaceX Services, Inc
CENTERVILLE, UT
Satellite Earth Station

Prepared By:
COMSEARCH
21515 Ridgetop Circle, Suite 300
Sterling, VA 20166
April 29, 2026

TABLE OF CONTENTS

1. CONCLUSIONS	3
2. SUMMARY OF RESULTS	4
3. SUPPLEMENTAL SHOWING	5
4. EARTH STATION COORDINATION DATA.....	7
5. CERTIFICATION.....	14

1. CONCLUSIONS

An interference study considering all existing, proposed and prior coordinated microwave facilities within the coordination contours of the proposed earth station demonstrates that this site will operate satisfactorily with the common carrier microwave environment. Further, there will be no restrictions of its operation due to interference considerations.

2. SUMMARY OF RESULTS

A number of great circle interference cases were identified during the interference study of the proposed earth station. Each of the cases, which exceeded the interference objective on a line-of-sight basis, was profiled and the propagation losses estimated using NBS TN101 (Revised) techniques. The losses were found to be sufficient to reduce the signal levels to acceptable magnitudes in every case.

3. SUPPLEMENTAL SHOWING

Pursuant to Part 25.203(c) of the FCC Rules and Regulations, the satellite earth station proposed in this application was coordinated by Comsearch using computer techniques and in accordance with Part 25 of the FCC Rules and Regulations.

Coordination data for this earth station was sent to the below listed carriers with a letter dated 03/26/2026.

Company

AT&T Mobility Spectrum LLC - Utah
Alpine School District
Bannock, County of
Bear River Communications, LLC
Beehive Telephone Company, Inc.
Bridger Valley Electric Association
Cache County
Carbon/Emery Telecom, Inc.
Cellco Partnership - CO/ID/MT/WY/UT
Central Utah Telephone, Inc
Community Wireless of Park City (KPCWFM)
Data Solutions Inc
Digis LLC
Dish Wireless LLC
Emery County Sheriff's Office
Enbridge Gas Ohio
Enbridge Gas Utah
ExxonMobil
FIF Utah LLC
InnovativeAir, LLC.
IntelliPOP, LLC
Intermountain Health Care
Jordan School District
Jordan Valley Water Conservancy District
KSB Industries, LLC
Kemmerer Holdings, LLC
Kennebecott Utah Copper LLC
LR Communications, Inc.
Marathon Petroleum Corporation
Mercury Radio Arts
NGL Connection
New Cingular Wireless PCS LLC-Utah
Northwest Pipeline GP
Olympic Wireless, LLC
Omega Networks LLC
Optic Loop Communications
Peak Wireless Services, LLC
Prestige Broadband LLC
Qwest Corporation
RC Wireless Inc.

Royces Electronics Inc
Safelink Internet, LLC
Salt Lake City, City of
Senawave, LLC
Silver Star Telephone Company, Inc.
Snyderville Basin Water Reclamation Dist
Summit County
T-Mobile MW LLC
TPT SpeedConnect, LLC
TXOX Communications LLC
Uintah Basin Elec Telecom dba Strata Net
Union Pacific Railroad Company
Union Telephone Company, Inc.
Utah Communications Authority
Utah Transit Authority
Ventura Media Communications, LLC
Visionary Communications, LLC
Wasatch Utah RSA No. 2 Ltd Partnership
White Cloud Communications
Wi-Fiber, Inc.
Williams Energy Services

4. EARTH STATION COORDINATION DATA

This section presents the data pertinent to frequency coordination of the proposed earth station that was circulated to all carriers within its coordination contours.

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Date: 03/26/2026
Job Number: 260326COMSGE13

Administrative Information

Status: ENGINEER PROPOSAL
Call Sign:
Licensee Code: SPACEX
Licensee Name: SpaceX Services, Inc

Site Information

CENTERVILLE, UT
Venue Name: SMACK DAB IN IT
Latitude (NAD 83): 40° 54' 56.9" N
Longitude (NAD 83): 111° 53' 38.4" W
Climate Zone: A
Rain Zone: 5
Ground Elevation (AMSL): 1291.01 m / 4235.6 ft

Link Information

Satellite Type: Low Earth Orbit
Mode: TR - Transmit-Receive
Antenna Count: 40
Modulation: Digital
Minimum Elevation Angle: 10.0°
Azimuth Range: 0.0° to 360°
Antenna Centerline (AGL): 8.59 m / 28.2 ft

Antenna Information

Manufacturer:
Model:
Gain / Diameter:
3-dB / 15-dB Beamwidth:

Receive - FCC32

SpaceX
1.99 meter
50.0 dBi / 2.0 m
0.50° / 1.00°

Transmit - FCC32

SpaceX
1.99 meter
53.9 dBi / 2.0 m
0.30° / 0.60°

Max Available RF Power (dBW/4 kHz): -40.8
(dBW/MHz): -16.8

Maximum EIRP (dBW/4 kHz): 13.1
(dBW/MHz): 37.1

Aggregate EIRP (dBW/MHz): 37.1

Interference Objectives: Long Term: -156.0 dBW/MHz 20% -151.0 dBW/4 kHz 20%
Short Term: -146.0 dBW/MHz 0.01% -128.0 dBW/4 kHz 0.0025%

Frequency Information

Emission / Frequency Range (MHz)

Receive 18.0 GHz

60M0D7W - 480MD7W / 17300.0 - 17800.0
60M0D7W - 480MD7W / 17800.0 - 18600.0
60M0D7W - 480MD7W / 18600.0 - 18800.0
60M0D7W - 480MD7W / 18800.0 - 19300.0
60M0D7W - 480MD7W / 19300.0 - 19700.0
60M0D7W - 480MD7W / 19700.0 - 20200.0
60M0D7W - 480MD7W / 20200.0 - 21200.0

Transmit 28.0 GHz

60M0D7W - 480MD7W / 27500.0 - 29100.0
60M0D7W - 480MD7W / 29100.0 - 29500.0
60M0D7W - 480MD7W / 29500.0 - 30000.0
60M0D7W - 480MD7W / 30000.0 - 31000.0

Max Great Circle Coordination Distance: 225.0 km / 139.8 mi 100.0 km / 62.1 mi
Precipitation Scatter Contour Radius: 100.0 km / 62.1 mi 100.0 km / 62.1 mi

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Coordination Values

CENTERVILLE, UT

Licensee Name SpaceX Services, Inc
Latitude (NAD 83) 40° 54' 56.9" N
Longitude (NAD 83) 111° 53' 38.4" W
Ground Elevation (AMSL) 1291.01 m / 4235.6 ft
Antenna Centerline (AGL) 8.59 m / 28.2 ft
Antenna Model SpaceX 1.99 meter
Antenna Mode Receive 18.0 GHz Transmit 28.0 GHz
Interference Objectives: Long Term -156.0 dBW/MHz 20% -151.0 dBW/4 kHz 20%
Short Term -146.0 dBW/MHz 0.01% -128.0 dBW/4 kHz 0.0025%
Max Available RF Power -40.8 (dBW/4 kHz)

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 18.0 GHz		Transmit 28.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
0	0.00	76.59	0.00	225.00	0.00	100.00
5	0.00	72.07	0.00	225.00	0.00	100.00
10	1.11	67.78	0.00	225.00	0.00	100.00
15	3.48	63.96	0.00	225.00	0.00	100.00
20	5.19	60.26	0.00	225.00	0.00	100.00
25	6.43	56.66	0.00	225.00	0.00	100.00
30	6.85	52.95	0.00	225.00	0.00	100.00
35	8.05	49.85	0.00	225.00	0.00	100.00
40	8.71	46.78	0.00	225.00	0.00	100.00
45	9.58	44.18	0.00	225.00	0.00	100.00
50	10.23	41.82	0.00	225.00	0.00	100.00
55	10.01	39.20	0.00	225.00	0.00	100.00
60	9.96	37.11	0.00	225.00	0.00	100.00
65	10.02	35.63	0.00	225.00	0.00	100.00
70	9.36	34.01	0.00	225.00	0.00	100.00
75	8.77	33.06	0.00	225.00	0.00	100.00
80	9.68	34.26	0.00	225.00	0.00	100.00
85	8.04	33.61	0.00	225.00	0.00	100.00
90	8.51	35.62	0.00	225.00	0.00	100.00
95	8.96	38.08	0.00	225.00	0.00	100.00
100	8.21	40.01	0.00	225.00	0.00	100.00
105	6.80	41.97	0.00	225.00	0.00	100.00
110	6.81	45.28	0.00	225.00	0.00	100.00
115	6.33	48.57	0.00	225.00	0.00	100.00
120	5.65	52.01	0.00	225.00	0.00	100.00
125	5.96	56.07	0.00	225.00	0.00	100.00
130	5.07	59.79	0.00	225.00	0.00	100.00
135	3.82	63.61	0.00	225.00	0.00	100.00
140	2.89	67.69	0.00	225.00	0.00	100.00
145	3.23	72.12	0.00	225.00	0.00	100.00
150	3.82	76.58	0.00	225.00	0.00	100.00
155	3.61	80.95	0.00	225.00	0.00	100.00
160	2.81	85.32	0.00	225.00	0.00	100.00
165	2.71	89.77	0.00	225.00	0.00	100.00
170	1.81	94.26	0.00	225.00	0.00	100.00
175	1.38	98.77	0.00	225.00	0.00	100.00
180	0.90	103.31	0.00	225.00	0.00	100.00
185	0.37	107.88	0.00	225.00	0.00	100.00

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Coordination Values

CENTERVILLE, UT

Licensee Name	SpaceX Services, Inc				
Latitude (NAD 83)	40° 54' 56.9" N				
Longitude (NAD 83)	111° 53' 38.4" W				
Ground Elevation (AMSL)	1291.01 m / 4235.6 ft				
Antenna Centerline (AGL)	8.59 m / 28.2 ft				
Antenna Model	SpaceX 1.99 meter				
Antenna Mode	Receive 18.0 GHz		Transmit 28.0 GHz		
Interference Objectives: Long Term	-156.0 dBW/MHz	20%	-151.0 dBW/4 kHz	20%	
Short Term	-146.0 dBW/MHz	0.01%	-128.0 dBW/4 kHz	0.0025%	
Max Available RF Power			-40.8 (dBW/4 kHz)		

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 18.0 GHz		Transmit 28.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
190	0.00	112.43	0.00	225.00	0.00	100.00
195	0.00	116.88	0.00	225.00	0.00	100.00
200	0.00	121.30	0.00	225.00	0.00	100.00
205	0.00	125.64	0.00	225.00	0.00	100.00
210	0.00	129.91	0.00	225.00	0.00	100.00
215	0.00	134.07	0.00	225.00	0.00	100.00
220	0.00	138.10	0.00	225.00	0.00	100.00
225	0.00	141.93	0.00	225.00	0.00	100.00
230	0.00	145.52	0.00	225.00	0.00	100.00
235	0.00	148.77	0.00	225.00	0.00	100.00
240	0.00	151.56	0.00	225.00	0.00	100.00
245	0.00	153.75	0.00	225.00	0.00	100.00
250	0.00	155.18	0.00	225.00	0.00	100.00
255	0.00	155.71	0.00	225.00	0.00	100.00
260	0.00	155.28	0.00	225.00	0.00	100.00
265	0.00	153.94	0.00	225.00	0.00	100.00
270	0.00	151.82	0.00	225.00	0.00	100.00
275	0.00	149.08	0.00	225.00	0.00	100.00
280	0.00	145.87	0.00	225.00	0.00	100.00
285	0.00	142.32	0.00	225.00	0.00	100.00
290	0.00	138.50	0.00	225.00	0.00	100.00
295	0.00	134.49	0.00	225.00	0.00	100.00
300	0.00	130.34	0.00	225.00	0.00	100.00
305	0.00	126.09	0.00	225.00	0.00	100.00
310	0.00	121.74	0.00	225.00	0.00	100.00
315	0.00	117.34	0.00	225.00	0.00	100.00
320	0.00	112.89	0.00	225.00	0.00	100.00
325	0.00	108.40	0.00	225.00	0.00	100.00
330	0.00	103.88	0.00	225.00	0.00	100.00
335	0.00	99.34	0.00	225.00	0.00	100.00
340	0.00	94.79	0.00	225.00	0.00	100.00
345	0.00	90.23	0.00	225.00	0.00	100.00
350	0.00	85.68	0.00	225.00	0.00	100.00
355	0.00	81.13	0.00	225.00	0.00	100.00

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Date: 03/26/2026
Job Number: 260326COMSGE13

Administrative Information

Status: ENGINEER PROPOSAL
Call Sign:
Licensee Code: SPACEX
Licensee Name: SpaceX Services, Inc

Site Information

CENTERVILLE, UT
Venue Name: SMACK DAB IN IT
Latitude (NAD 83): 40° 54' 56.9" N
Longitude (NAD 83): 111° 53' 38.4" W
Climate Zone: A
Rain Zone: 5
Ground Elevation (AMSL): 1291.01 m / 4235.6 ft

Link Information

Satellite Type: Low Earth Orbit
Mode: TR - Transmit-Receive
Antenna Count: 40
Modulation: Digital
Minimum Elevation Angle: 10.0°
Azimuth Range: 0.0° to 360°
Antenna Centerline (AGL): 8.59 m / 28.2 ft

Antenna Information

Manufacturer:
Model:
Gain / Diameter:
3-dB / 15-dB Beamwidth:

Receive - FCC32

SpaceX
1.99 meter
55.9 dBi / 2.0 m
0.25° / 0.50°

Transmit - FCC32

SpaceX
1.99 meter
58.1 dBi / 2.0 m
0.20° / 0.40°

Max Available RF Power (dBW/4 kHz): -47.8
(dBW/MHz): -23.8

Maximum EIRP (dBW/4 kHz): 10.3
(dBW/MHz): 34.3

Aggregate EIRP (dBW/MHz): 34.3

Interference Objectives: Long Term: -156.0 dBW/MHz 20% -151.0 dBW/4 kHz 20%
Short Term: -146.0 dBW/MHz 0.01% -128.0 dBW/4 kHz 0.0025%

Frequency Information

Receive 40.0 GHz

Emission / Frequency Range (MHz): 60M0D7W - 480MD7W / 37500.0 - 42500.0

Transmit 50.0 GHz

60M0D7W - 480MD7W / 47200.0 - 50200.0
60M0D7W - 480MD7W / 50400.0 - 51400.0
60M0D7W - 480MD7W / 51400.0 - 52400.0

Max Great Circle Coordination Distance: 225.0 km / 139.8 mi
Precipitation Scatter Contour Radius: 100.0 km / 62.1 mi

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Coordination Values		CENTERVILLE, UT		
Licensee Name		SpaceX Services, Inc		
Latitude (NAD 83)		40° 54' 56.9" N		
Longitude (NAD 83)		111° 53' 38.4" W		
Ground Elevation (AMSL)		1291.01 m / 4235.6 ft		
Antenna Centerline (AGL)		8.59 m / 28.2 ft		
Antenna Model		SpaceX 1.99 meter		
Antenna Mode		Receive 40.0 GHz		Transmit 50.0 GHz
Interference Objectives:	Long Term	-156.0 dBW/MHz	20%	-151.0 dBW/4 kHz 20%
	Short Term	-146.0 dBW/MHz	0.01%	-128.0 dBW/4 kHz 0.0025%
Max Available RF Power		-47.8 (dBW/4 kHz)		

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 40.0 GHz		Transmit 50.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
0	0.00	76.59	0.00	225.00	0.00	100.00
5	0.00	72.07	0.00	225.00	0.00	100.00
10	1.11	67.78	0.00	225.00	0.00	100.00
15	3.48	63.96	0.00	225.00	0.00	100.00
20	5.19	60.26	0.00	225.00	0.00	100.00
25	6.43	56.66	0.00	225.00	0.00	100.00
30	6.85	52.95	0.00	225.00	0.00	100.00
35	8.05	49.85	0.00	225.00	0.00	100.00
40	8.71	46.78	0.00	225.00	0.00	100.00
45	9.58	44.18	0.00	225.00	0.00	100.00
50	10.23	41.82	0.00	225.00	0.00	100.00
55	10.01	39.20	0.00	225.00	0.00	100.00
60	9.96	37.11	0.00	225.00	0.00	100.00
65	10.02	35.63	0.00	225.00	0.00	100.00
70	9.36	34.01	0.00	225.00	0.00	100.00
75	8.77	33.06	0.00	225.00	0.00	100.00
80	9.68	34.26	0.00	225.00	0.00	100.00
85	8.04	33.61	0.00	225.00	0.00	100.00
90	8.51	35.62	0.00	225.00	0.00	100.00
95	8.96	38.08	0.00	225.00	0.00	100.00
100	8.21	40.01	0.00	225.00	0.00	100.00
105	6.80	41.97	0.00	225.00	0.00	100.00
110	6.81	45.28	0.00	225.00	0.00	100.00
115	6.33	48.57	0.00	225.00	0.00	100.00
120	5.65	52.01	0.00	225.00	0.00	100.00
125	5.96	56.07	0.00	225.00	0.00	100.00
130	5.07	59.79	0.00	225.00	0.00	100.00
135	3.82	63.61	0.00	225.00	0.00	100.00
140	2.89	67.69	0.00	225.00	0.00	100.00
145	3.23	72.12	0.00	225.00	0.00	100.00
150	3.82	76.58	0.00	225.00	0.00	100.00
155	3.61	80.95	0.00	225.00	0.00	100.00
160	2.81	85.32	0.00	225.00	0.00	100.00
165	2.71	89.77	0.00	225.00	0.00	100.00
170	1.81	94.26	0.00	225.00	0.00	100.00
175	1.38	98.77	0.00	225.00	0.00	100.00
180	0.90	103.31	0.00	225.00	0.00	100.00
185	0.37	107.88	0.00	225.00	0.00	100.00

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>


Coordination Values		CENTERVILLE, UT		
Licensee Name		SpaceX Services, Inc		
Latitude (NAD 83)		40° 54' 56.9" N		
Longitude (NAD 83)		111° 53' 38.4" W		
Ground Elevation (AMSL)		1291.01 m / 4235.6 ft		
Antenna Centerline (AGL)		8.59 m / 28.2 ft		
Antenna Model		SpaceX 1.99 meter		
Antenna Mode		Receive 40.0 GHz		Transmit 50.0 GHz
Interference Objectives:	Long Term	-156.0 dBW/MHz	20%	-151.0 dBW/4 kHz 20%
	Short Term	-146.0 dBW/MHz	0.01%	-128.0 dBW/4 kHz 0.0025%
Max Available RF Power		-47.8 (dBW/4 kHz)		

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 40.0 GHz		Transmit 50.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
190	0.00	112.43	0.00	225.00	0.00	100.00
195	0.00	116.88	0.00	225.00	0.00	100.00
200	0.00	121.30	0.00	225.00	0.00	100.00
205	0.00	125.64	0.00	225.00	0.00	100.00
210	0.00	129.91	0.00	225.00	0.00	100.00
215	0.00	134.07	0.00	225.00	0.00	100.00
220	0.00	138.10	0.00	225.00	0.00	100.00
225	0.00	141.93	0.00	225.00	0.00	100.00
230	0.00	145.52	0.00	225.00	0.00	100.00
235	0.00	148.77	0.00	225.00	0.00	100.00
240	0.00	151.56	0.00	225.00	0.00	100.00
245	0.00	153.75	0.00	225.00	0.00	100.00
250	0.00	155.18	0.00	225.00	0.00	100.00
255	0.00	155.71	0.00	225.00	0.00	100.00
260	0.00	155.28	0.00	225.00	0.00	100.00
265	0.00	153.94	0.00	225.00	0.00	100.00
270	0.00	151.82	0.00	225.00	0.00	100.00
275	0.00	149.08	0.00	225.00	0.00	100.00
280	0.00	145.87	0.00	225.00	0.00	100.00
285	0.00	142.32	0.00	225.00	0.00	100.00
290	0.00	138.50	0.00	225.00	0.00	100.00
295	0.00	134.49	0.00	225.00	0.00	100.00
300	0.00	130.34	0.00	225.00	0.00	100.00
305	0.00	126.09	0.00	225.00	0.00	100.00
310	0.00	121.74	0.00	225.00	0.00	100.00
315	0.00	117.34	0.00	225.00	0.00	100.00
320	0.00	112.89	0.00	225.00	0.00	100.00
325	0.00	108.40	0.00	225.00	0.00	100.00
330	0.00	103.88	0.00	225.00	0.00	100.00
335	0.00	99.34	0.00	225.00	0.00	100.00
340	0.00	94.79	0.00	225.00	0.00	100.00
345	0.00	90.23	0.00	225.00	0.00	100.00
350	0.00	85.68	0.00	225.00	0.00	100.00
355	0.00	81.13	0.00	225.00	0.00	100.00

5. CERTIFICATION

I HEREBY CERTIFY THAT I AM THE TECHNICALLY QUALIFIED PERSON RESPONSIBLE FOR THE PREPARATION OF THE FREQUENCY COORDINATION DATA CONTAINED IN THIS APPLICATION, THAT I AM FAMILIAR WITH PARTS 101 AND 25 OF THE FCC RULES AND REGULATIONS, THAT I HAVE EITHER PREPARED OR REVIEWED THE FREQUENCY COORDINATION DATA SUBMITTED WITH THIS APPLICATION, AND THAT IT IS COMPLETE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

BY: _



Gary K. Edwards
Senior Manager
COMSEARCH
21515 Ridgetop Circle, Suite 300
Sterling, VA 20166

DATED: April 29, 2026



E-band Frequency Coordination Report

The “Smack Dab In It” Gateway (Centerville, UT)

March 23, 2026



Summary

SpaceX performed a coordination notice under Section 25.203(c), Section 25.251, and Appendix 7 of the ITU's Radio Regulations. Prior-notification letters with earth station details were sent to potentially affected terrestrial licensees; a copy of these details are available in this report. The earth station coordination was finalized on April 07, 2026. No objections were received from any terrestrial licensees.

Methodology

SpaceX has completed an interference analysis based on accepted international and Commission methodologies demonstrating that this satellite earth station will not cause harmful interference to existing terrestrial facilities in the band. Specifically, for each known receiver within the great circle coordination distance surrounding the proposed earth station, SpaceX calculated the expected interference/noise ratio (I/N) to the receiver, assuming the SpaceX antenna properties listed on the following page, SpaceX site layout and design, free-space propagation without terrain or clutter, and actual characteristics of receiver(s) obtained from the 70/80/90 GHz link-registration database. Even under these conservative assumptions, SpaceX's analysis confirms that this earth station will not cause interference exceeding 1.0 dB of degradation to the static threshold of existing 70/80 GHz links within the great circle coordination distance.¹

Operators contacted

Prior-coordination letters were sent to the following operators:

1. 1-800 CONTACTS, INC.
2. 9Stone LLC
3. Aervivo
4. BOB, LLC
5. BOB, LLC dba Business Only Broadband
6. Bear River Communications, LLC
7. Black & Associates
8. Central Utah Telephone, Inc.
9. Digis LLC
10. Echo Broadband LLC
11. FIF Utah LLC
12. Fortius Networks
13. High Speed Utah
14. Intellipop

¹ If there were any cases in which the interference threshold was exceeded in the conservative free-space analysis for any relevant receiver, SpaceX conducted an additional analysis with more realistic assumptions of terrain and clutter, under which the interference threshold was not exceeded for any relevant receiver. This further ensures that there will be no above-threshold interference to existing receivers.

15. Intelpath
16. Intermountain Healthcare
17. LR Communications, Inc.
18. Liberty Broadband LLC
19. Micronet Communications, Inc.
20. REMEC Broadband Wireless Networks LLC DBA Bridgewave Communications
21. SIAE Microelettronica, Inc.
22. Senawave LLC
23. Siklu, Inc
24. Silver Lake Internet, LLC
25. SpaceX
26. Tradlos
27. UTAH TRANSIT AUTHORITY
28. Visionary Communications, LLC
29. Wi-Fiber, Inc.
30. Wicked Fast LLC, dba Wicked Fast Internet.com
31. WirelessGuys Inc.
32. aervivo

Earth Station Data

This section presents the data that was circulated to all operators that met the criteria for notification for this earth station.

Site Information:

- Transmitting station name: The "Smack Dab In It" Gateway
- Transmitting station coordinates: 40.9158, -111.894
- Ground Elevation (AMSL): 1291.0 m
- Antenna Count: 40
- Aggregate EIRP toward the horizon: -9 dBW/MHz

Frequency Information:

- Transmit: 81-86 GHz
- Receive: 71-76 GHz
- Max Great Circle Coordination Distance: 127 km
- Rain Scatter Coordination Distance Contour: 6 km

Link Information:

- Satellite Type: Low Earth Orbit
- Mode: TR – Transmit-Receive
- Modulation: Digital
- Minimum Elevation Angle: 15.0°
- Azimuth Range: 0.0° to 360.0°
- Antenna Centerline (AGL): 8.59 m

Antenna Information:

- Manufacturer: SpaceX
- Model/Diameter: 1.99m
- Gain: 60.9 dBi at 83.5 GHz
- Max Available RF Power: -20.8 dBW/MHz
- Horizon Gain: 0 dBi
- Maximum EIRP: 40.1 dBW/MHz (main beam)
- Permissible RF Interference Power Level²: I/N ≤ -6 dB
- Antenna Mask: ITU-R S.580

² See 47 CFR § 101.105(a)(5)(i). This I/N value would cause a maximum of 1.0 dB of degradation to the static threshold of the protected receiver.

Horizon Angle by Azimuth:

All values are in degrees

Azimuth	Horizon Angle
0.0	2.24
5.0	3.34
10.0	4.61
15.0	5.30
20.0	6.37
25.0	6.87
30.0	7.69
35.0	7.76
40.0	8.53
45.0	9.51
50.0	10.19
55.0	9.81
60.0	9.91
65.0	9.88
70.0	9.25
75.0	8.67
80.0	9.31
85.0	8.45
90.0	8.58
95.0	8.49
100.0	7.80
105.0	7.49
110.0	6.65
115.0	7.09
120.0	7.45
125.0	6.11
130.0	6.06
135.0	5.60
140.0	4.93
145.0	4.59
150.0	4.24
155.0	4.66
160.0	3.92
165.0	3.37
170.0	2.87
175.0	2.83
180.0	2.25
185.0	1.48
190.0	0.48
195.0	0.51



Frequency Coordination Report
E-Band Earth Station

200.0	0.92
205.0	1.41
210.0	1.40
215.0	1.54
220.0	1.35
225.0	1.80
230.0	0.99
235.0	0.62
240.0	0.77
245.0	0.63
250.0	0.11
255.0	0.16
260.0	0.45
265.0	0.60
270.0	0.50
275.0	0.70
280.0	1.13
285.0	0.62
290.0	0.19
295.0	0.11
300.0	-0.14
305.0	-0.14
310.0	0.35
315.0	0.22
320.0	0.14
325.0	-0.04
330.0	-0.00
335.0	0.11
340.0	0.27
345.0	0.31
350.0	0.68
355.0	1.28