

# Ka-Band Earth Station – Los Angeles, CA

## Frequency Coordination Report

28 GHz



Prepared on Behalf of  
SPACE EXPLORATION  
HOLDINGS

April 9, 2020



**COMSEARCH**  
A CommScope Company



## **Table of Contents**

|   |              |
|---|--------------|
| <b>1. Summary of Results</b>                          | <b>- 1 -</b> |
| <b>2. 28 GHz Common Carrier and LTTS Coordination</b> | <b>- 1 -</b> |
| <b>3. 28 GHz UMFUS Coordination</b>                   | <b>- 2 -</b> |
| <b>4. Earth Station Coordination Data</b>             | <b>- 3 -</b> |
| <b>5. Contact Information</b>                         | <b>- 7 -</b> |



## 1. Summary of Results

On behalf of SPACE EXPLORATION HOLDINGS, Comsearch performed a coordination notice under Section 25.203(c) and Section 25.136(a)(4) of the FCC’s rules for all existing and proposed terrestrial licenses within the coordination contours of their proposed Ka-Band earth station in Los Angeles, CA, which will transmit at 28 GHz<sup>1</sup>. Prior-notification letters were sent to the licensees and a copy of the notification data is provided in section four of this report. The earth station coordination was finalized on April 9, 2020.

No objections were received from any of the incumbent 28 GHz licensees.

## 2. 28 GHz Common Carrier and LTTS Coordination

In accordance with FCC Rules and Regulations, the Ka-Band earth station in Los Angeles, CA was prior-coordinated by Comsearch. A notification letter and datasheets for this earth station were sent to the following 28 GHz common carrier fixed microwave licensees. These licensees are authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis or local basis.

| Licensee           | Authorized Geographic Area |
|--------------------|----------------------------|
| AT&T               | California                 |
| Crosslinks Network | California                 |
| Frontier           | Nationwide; CA             |

A notification letter and datasheets for the Ka-Band earth station in Los Angeles, CA were also sent to the following 28 GHz local television transmission licensee. This licensee is authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis.

| Licensee                       | Authorized Geographic Area |
|--------------------------------|----------------------------|
| Information Super Station, LLC | Continental US             |

No objections were received from the common carrier or local television transmission service incumbents.

<sup>1</sup> The proposed earth station will operate in the 27.5 – 29.1 GHz & 29.5 – 30.0 GHz portion of the Ka-Band.

### 3. 28 GHz UMFUS Coordination

There were three 28 GHz UMFUS licensees identified within the coordination distance of the proposed earth station. The proposed earth station will operate on frequencies that overlap Channel L1 & L2 of the UMFUS service. The total frequency allocation for Channels L1 & L2 of the UMFUS spectrum appears below.

**Channel:**    **L1**    27.500 - 27.925 GHz  
                  **L2**    27.925 - 28.350 GHz

| Licensee | Authorized Geographic Area |
|----------|----------------------------|
| Alta     | Market-Based               |
| T-Mobile | Market-Based               |
| Verizon  | Market-Based               |

No objections were received from the UMFUS incumbents.



## **4. Earth Station Coordination Data**

This section presents the data pertinent to the proposed Ka-Band earth station in Los Angeles, CA. This data was circulated to all incumbent licensees in the shared 28 GHz frequency ranges.



**SPACE EXPLORATION HOLDINGS**  
**Ka-Band Earth Station – Los Angeles, CA**  
**Frequency Coordination Report**  
**28 GHz**

Job Number: 200219COMSGE04

**Administrative Information**

Status ENGINEER PROPOSAL  
 Call Sign  
 Licensee Code SPACEX  
 Licensee Name Space Exploration Holdings

**Site Information**

LOS ANGELES, CA  
 Venue Name NEW  
 Latitude (NAD 83) 34° 36' 14.5" N  
 Longitude (NAD 83) 117° 27' 15.7" W  
 Climate Zone B  
 Rain Zone 4  
 Ground Elevation (AMSL) 857.44 m / 2813.1 ft

**Link Information**

Satellite Type Low Earth Orbit  
 Mode TR - Transmit-Receive  
 Modulation Digital  
 Minimum Elevation Angle 25.0°  
 Azimuth Range 0.0° to 360°  
 Antenna Centerline (AGL) 0.91 m / 3.0 ft

**Antenna Information**

|                          |             | Receive - FCC32  |       |                          | Transmit - FCC32 |
|--------------------------|-------------|------------------|-------|--------------------------|------------------|
| Manufacturer             |             | SpaceX           |       |                          | SpaceX           |
| Model                    |             | 1.47 meter       |       |                          | 1.47 meter       |
| Gain / Diameter          |             | 46.9 dBi / 1.5 m |       |                          | 49.5 dBi / 1.5 m |
| 3-dB / 15-dB Beamwidth   |             | 0.77° / 1.70°    |       |                          | 0.49° / 1.17°    |
| Max Available RF Power   | (dBW/4 kHz) |                  |       |                          | -39.8            |
|                          | (dBW/MHz)   |                  |       |                          | -15.8            |
| Maximum EIRP             | (dBW/4 kHz) |                  |       |                          | 9.7              |
|                          | (dBW/MHz)   |                  |       |                          | 33.7             |
| Interference Objectives: | Long Term   | -156.0 dBW/MHz   | 20%   | -151.0 dBW/4 kHz 20%     |                  |
|                          | Short Term  | -146.0 dBW/MHz   | 0.01% | -128.0 dBW/4 kHz 0.0025% |                  |

**Frequency Information**

|  | Receive 18.0 GHz   | Transmit 28.0 GHz  |
|--|--|--|
| Emission / Frequency Range (MHz)       | 62M5D7W - 480MD7W / 17800.0 - 18600.0<br>62M5D7W - 480MD7W / 18800.0 - 19300.0 | 62M5D7W - 480MD7W / 27500.0 - 29100.0<br>62M5D7W - 480MD7W / 29500.0 - 30000.0 |
| Max Great Circle Coordination Distance | 262.0 km / 162.8 mi  | 125.0 km / 77.7 mi   |
| Precipitation Scatter Contour Radius   | 100.0 km / 62.1 mi   | 100.0 km / 62.1 mi   |



**SPACE EXPLORATION HOLDINGS**  
**Ka-Band Earth Station – Los Angeles, CA**  
**Frequency Coordination Report**  
**28 GHz**

|                                    |                            |                   |                          |
|------------------------------------|----------------------------|-------------------|--------------------------|
| <b>Coordination Values</b>         | <b>LOS ANGELES, CA</b>     |                   |                          |
| Licensee Name                      | Space Exploration Holdings |                   |                          |
| Latitude (NAD 83)                  | 34° 36' 14.5" N            |                   |                          |
| Longitude (NAD 83)                 | 117° 27' 15.7" W           |                   |                          |
| Ground Elevation (AMSL)            | 857.44 m / 2813.1 ft       |                   |                          |
| Antenna Centerline (AGL)           | 0.91 m / 3.0 ft            |                   |                          |
| Antenna Model                      | SpaceX 1.47 meter          |                   |                          |
| Antenna Mode                       | Receive 18.0 GHz           |                   | Transmit 28.0 GHz        |
| Interference Objectives: Long Term | -156.0 dBW/MHz             | 20%               | -151.0 dBW/4 kHz 20%     |
| Short Term                         | -146.0 dBW/MHz             | 0.01%             | -128.0 dBW/4 kHz 0.0025% |
| Max Available RF Power             |                            | -39.8 (dBW/4 kHz) |                          |

| Azimuth (°) | Horizon Elevation (°) | Antenna Discrimination (°) | Receive 18.0 GHz   |                            | Transmit 28.0 GHz  |                            |
|-------------|-----------------------|----------------------------|--------------------|----------------------------|--------------------|----------------------------|
|             |                       |                            | Horizon Gain (dBi) | Coordination Distance (km) | Horizon Gain (dBi) | Coordination Distance (km) |
| 0           | 0.28                  | 75.83                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 5           | 0.00                  | 71.52                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 10          | 0.00                  | 67.28                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 15          | 0.00                  | 63.10                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 20          | 0.00                  | 58.99                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 25          | 0.00                  | 54.97                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 30          | 0.00                  | 51.06                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 35          | 0.00                  | 47.29                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 40          | 0.00                  | 43.71                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 45          | 0.00                  | 40.37                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 50          | 0.00                  | 37.34                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 55          | 0.00                  | 34.69                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 60          | 0.00                  | 32.52                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 65          | 0.00                  | 30.94                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 70          | 0.00                  | 30.03                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 75          | 0.00                  | 29.87                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 80          | 0.00                  | 30.46                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 85          | 0.00                  | 31.77                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 90          | 0.00                  | 33.70                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 95          | 0.00                  | 36.16                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 100         | 0.00                  | 39.04                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 105         | 0.00                  | 42.26                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 110         | 0.00                  | 45.75                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 115         | 0.00                  | 49.44                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 120         | 0.00                  | 53.29                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 125         | 0.22                  | 57.35                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 130         | 0.27                  | 61.43                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 135         | 0.30                  | 65.58                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 140         | 0.32                  | 69.78                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 145         | 0.35                  | 74.03                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 150         | 0.38                  | 78.31                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 155         | 0.40                  | 82.61                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 160         | 0.44                  | 86.92                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 165         | 0.47                  | 91.24                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 170         | 0.50                  | 95.55                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 175         | 0.51                  | 99.85                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 180         | 0.53                  | 104.13                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 185         | 0.55                  | 108.38                     | -3.00              | 262.00                     | -3.00              | 125.00                     |



**SPACE EXPLORATION HOLDINGS**  
**Ka-Band Earth Station – Los Angeles, CA**  
**Frequency Coordination Report**  
**28 GHz**

|                                    |                            |                   |                          |
|------------------------------------|----------------------------|-------------------|--------------------------|
| <b>Coordination Values</b>         | <b>LOS ANGELES, CA</b>     |                   |                          |
| Licensee Name                      | Space Exploration Holdings |                   |                          |
| Latitude (NAD 83)                  | 34° 36' 14.5" N            |                   |                          |
| Longitude (NAD 83)                 | 117° 27' 15.7" W           |                   |                          |
| Ground Elevation (AMSL)            | 857.44 m / 2813.1 ft       |                   |                          |
| Antenna Centerline (AGL)           | 0.91 m / 3.0 ft            |                   |                          |
| Antenna Model                      | SpaceX 1.47 meter          |                   |                          |
| Antenna Mode                       | Receive 18.0 GHz           |                   | Transmit 28.0 GHz        |
| Interference Objectives: Long Term | -156.0 dBW/MHz             | 20%               | -151.0 dBW/4 kHz 20%     |
| Short Term                         | -146.0 dBW/MHz             | 0.01%             | -128.0 dBW/4 kHz 0.0025% |
| Max Available RF Power             |                            | -39.8 (dBW/4 kHz) |                          |

| Azimuth (°) | Horizon Elevation (°) | Antenna Discrimination (°) | Receive 18.0 GHz   |                            | Transmit 28.0 GHz  |                            |
|-------------|-----------------------|----------------------------|--------------------|----------------------------|--------------------|----------------------------|
|             |                       |                            | Horizon Gain (dBi) | Coordination Distance (km) | Horizon Gain (dBi) | Coordination Distance (km) |
| 190         | 0.55                  | 112.58                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 195         | 0.57                  | 116.73                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 200         | 0.58                  | 120.81                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 205         | 0.58                  | 124.80                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 210         | 0.58                  | 128.67                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 215         | 0.56                  | 132.41                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 220         | 0.54                  | 135.96                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 225         | 0.52                  | 139.28                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 230         | 0.49                  | 142.30                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 235         | 0.45                  | 144.94                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 240         | 0.41                  | 147.11                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 245         | 0.36                  | 148.72                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 250         | 0.31                  | 149.66                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 255         | 0.27                  | 149.86                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 260         | 0.23                  | 149.31                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 265         | 0.20                  | 148.05                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 270         | 0.00                  | 146.30                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 275         | 0.20                  | 143.68                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 280         | 0.49                  | 140.61                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 285         | 1.07                  | 137.06                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 290         | 1.05                  | 133.66                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 295         | 1.10                  | 130.02                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 300         | 1.05                  | 126.26                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 305         | 0.75                  | 122.45                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 310         | 0.67                  | 118.44                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 315         | 0.88                  | 114.27                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 320         | 1.10                  | 110.05                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 325         | 0.82                  | 105.89                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 330         | 1.09                  | 101.61                     | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 335         | 0.82                  | 97.36                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 340         | 0.73                  | 93.07                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 345         | 0.32                  | 88.76                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 350         | 0.00                  | 84.42                      | -3.00              | 262.00                     | -3.00              | 125.00                     |
| 355         | 0.00                  | 80.10                      | -3.00              | 262.00                     | -3.00              | 125.00                     |





## **5. Contact Information**

For questions or information regarding the 28 GHz Frequency Coordination Report, please contact:

|                 |   |
|-----------------|---|
| Contact person: | Dennis Jimeno                               |
| Title:          | Engineer III, Telecommunications            |
| Company:        | Comsearch                                   |
| Address:        | 19700 Janelia Farm Blvd., Ashburn, VA 20147 |
| Telephone:      | 703-726-5858                                |
| Fax:            | 703-726-5599                                |
| Email:          | DJimeno@Comsearch.com                       |
| Web site:       | www.comsearch.com                           |