Ka-Band Earth Station – Roll, AZ Frequency Coordination Report 28 GHz



Prepared on Behalf of SPACE EXPLORATION HOLDINGS

June 24, 2020





Table of Contents

1.	Summary of Results	- 1 -
2.	28 GHz Common Carrier and LTTS Coordination	-1-
3.	28 GHz UMFUS Coordination	- 2 -
4.	Earth Station Coordination Data	- 3 -
5.	Contact Information	-7-



1. Summary of Results

On behalf of SPACE EXPLORATION HOLDINGS, Comsearch performed a coordination notice under Section 25.203(c) and Section 25.136(a)(4) of the FCC's rules for all existing and proposed terrestrial licenses within the coordination contours of their proposed Ka-Band earth station in Roll, AZ, which will transmit at 28 GHz¹. Prior-notification letters were sent to the licensees and a copy of the notification data is provided in section four of this report. The earth station coordination was finalized on June 24, 2020.

No objections were received from any of the incumbent 28 GHz licensees.

2. 28 GHz Common Carrier and LTTS Coordination

In accordance with FCC Rules and Regulations, the Ka-Band earth station in Roll, AZ was prior-coordinated by Comsearch. A notification letter and datasheets for this earth station were sent to the following 28 GHz common carrier fixed microwave licensees. These licensees are authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis or local basis.

Licensee	Authorized Geographic Area		
Frontier Southwest Incorporated	Nationwide		

A notification letter and datasheets for the Ka-Band earth station in Roll, AZ were also sent to the following 28 GHz local television transmission licensee. This licensee is authorized to operate temporary fixed operations from 27.5 - 29.5 GHz on a nationwide basis.

Licensee	Authorized Geographic Area
Information Super Station, LLC	Continental US

No objections were received from the common carrier or local television transmission service incumbents.

 $^{^{1}}$ The proposed earth station will operate in the 27.5 – 29.1 GHz & 29.5 – 30.0 GHz portion of the KaBand.



3. 28 GHz UMFUS Coordination

There was one 28 GHz UMFUS licensee identified within the coordination distance of the proposed earth station. The proposed earth station will operate on frequencies that overlap Channel L1 & L2 of the UMFUS service. The total frequency allocation for Channels L1 & L2 of the UMFUS spectrum appears below.

Channel: L1 27.500 - 27.925 GHz

L2 27.925 - 28.350 GHz

Licensee	Authorized Geographic Area		
Verizon	Market-Based		

No objections were received from the UMFUS incumbents.



4. Earth Station Coordination Data

This section presents the data pertinent to the proposed Ka-Band earth station in Roll, AZ. This data was circulated to all incumbent licensees in the shared 28 GHz frequency ranges.

SPACE EXPLORATION HOLDINGS Ka-Band Earth Station – Roll, AZ Frequency Coordination Report 28 GHz

Job Number.		200521COMSGE05				
Administrative Inform Status	ation	ENGINEER PROPOSAL				
Call Sign Licensee Code		CDACEV				
Licensee Name		SPACEX Space Exploration Holdings				
Site Information		ROLL, AZ				
Venue Name						
Latitude (NAD 83)		32° 48' 55.8" N				
Longitude (NAD 83)		113° 47' 53.0" W				
Climate Zone		A				
Rain Zone		5				
Ground Elevation (AMS	SL)	98.24 m / 322.3 ft				
Link Information Satellite Type		Low Earth Orbit				
Mode		TR - Transmit-Receive				
Modulation		Digital				
Minimum Elevation And	ile	25.0°				
Azimuth Range	,	0.0° to 360°				
Antenna Centerline (AG	SL)	0.91 m / 3.0 ft				
Antenna Information		Receive - FCC32		Transmit - FCC32		
Manufacturer		SpaceX		SpaceX		
Model		1.47 meter		1.47 meter		
Gain / Diameter		46.9 dBi / 1.5 m		49.5 dBi / 1.5 m		
3-dB / 15-dB Beamwidt	h	0.77° / 1.70°		0.49° / 1.17°		
Max Available RF Power	(dBW/4 kH	z)		-39.8		
	(dBW/MHz)		-15.8		
Maximum EIRP	(dBW/4 kH	z)		9.7		
	(dBW/MHz)		33.7		
Interference Objectives:	Long Term	-156.0 dBW/MHz	20%	-151.0 dBW/4 kHz 20%		
	Short Term	-146.0 dBW/MHz	0.01%	-128.0 dBW/4 kHz 0.0025%		
Frequency Informatio		Receive 18.0 GHz		Transmit 28.0 GHz		
Emission / Frequency Range	e (MHz)	62M5D7W - 480MD7W / 17800.0 - 18600.0 62M5D7W - 480MD7W / 18800.0 - 19300.0		62M5D7W - 480MD7W / 27500.0 - 29100.0 62M5D7W - 480MD7W / 29500.0 - 30000.0		
Max Great Circle Coordination	on Distance	262.0 km / 162.8 m		9.7 km / 6.0 mi		
Precipitation Scatter Contour	Radius	100.0 km / 62.1 mi		100.0 km / 62.1 mi		

SPACE EXPLORATION HOLDINGS Ka-Band Earth Station – Roll, AZ Frequency Coordination Report 28 GHz

Coordination Values

ROLL, AZ

Licensee Name

Space Exploration Holdings

Latitude (NAD 83) Longitude (NAD 83) 32° 48' 55.8" N 113° 47' 53.0" W

Ground Elevation (AMSL) Antenna Centerline (AGL) 98.24 m / 322.3 ft 0.91 m / 3.0 ft

Antenna Model

SpaceX 1.47 meter

Antenna Model Antenna Mode ceX 1.47 meter Receive 18.0 GHz

Transmit 28.0 GHz

Interference Objectives: Long Term Short Term -156.0 dBW/MHz -146.0 dBW/MHz

20% 0.01% -151.0 dBW/4 kHz 20% -128.0 dBW/4 kHz 0.0025%

Max Available RF Power

-39.8 (dBW/4 kHz)

Receive 18.0 GHz Transmit 28.0 GHz

	Maria	******	1211-	Personal Hansini		A
Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
0	0.38	78.15	-3.00	262.00	-3.00	9.7
5	0.41	73.77	-3.00	262.00	-3.00	9.7
10	0.41	69.43	-3.00	262.00	-3.00	9.7
15	0.40	65.12	-3.00	262.00	-3.00	9.7
20	0.34	60.85	-3.00	262.00	-3.00	9.7
25	0.33	56.66	-3.00	262.00	-3.00	9.7
30	0.41	52.60	-3.00	262.00	-3.00	9.7
35	0.50	48.66	-3.00	262.00	-3.00	9.7
40	0.49	44.84	-3.00	262.00	-3.00	9.7
45	0.45	41.19	-3.00	262.00	-3.00	9.7
50	0.42	37.80	-3.00	262.00	-3.00	9.7
55	0.41	34.75	-3.00	262.00	-3.00	9.7
60	0.30	32.04	-3.00	262.00	-3.00	9.7
65	0.24	29.91	-3.00	262.00	-3.00	9.7
70	0.00	28.24	-3.00	262.00	-3.00	9.7
75	0.00	27.57	-3.00	262.00	-3.00	9.7
80	0.00	27.73	-3.00	262.00	-3.00	9.7
85	0.00	28.70	-3.00	262.00	-3.00	9.7
90	0.00	30.40	-3.00	262.00	-3.00	9.7
95	0.00	32.73	-3.00	262.00	-3.00	9.7
100	0.00	35.55	-3.00	262.00	-3.00	9.7
105	0.00	38.76	-3.00	262.00	-3.00	9.7
110	0.00	42.27	-3.00	262.00	-3.00	9.7
115	0.00	46.01	-3.00	262.00	-3.00	9.7
120	0.00	49.92	-3.00	262.00	-3.00	9.7
125	0.00	53.96	-3.00	262.00	-3.00	9.7
130	0.00	58.11	-3.00	262.00	-3.00	9.7
135	0.00	62.35	-3.00	262.00	-3.00	9.7
140	0.00	66.64	-3.00	262.00	-3.00	9.7
145	0.00	70.98	-3.00	262.00	-3.00	9.7
150	0.94	75.49	-3.00	262.00	-3.00	9.7
155	3.37	80.10	-3.00	262.00	-3.00	9.7
160	3.13	84.36	-3.00	262.00	-3.00	9.7
165	2.28	88.65	-3.00	262.00	-3.00	9.7
170	1.12	93.02	-3.00	262.00	-3.00	9.7
175	0.33	97.45	-3.00	262.00	-3.00	9.7
180 185	0.00	101.89 106.29	-3.00 -3.00	262.00 262.00	-3.00 -3.00	9.7 9.7

SPACE EXPLORATION HOLDINGS Ka-Band Earth Station – Roll, AZ Frequency Coordination Report 28 GHz

Coordination Values

ROLL, AZ Licensee Name Space Exploration Holdings

Latitude (NAD 83) Longitude (NAD 83) Ground Elevation (AMSL) Antenna Centerline (AGL) 32° 48' 55.8" N 113° 47' 53.0" W 98.24 m / 322.3 ft 0.91 m / 3.0 ft

Antenna Model Antenna Mode

SpaceX 1.47 meter Receive 18.0 GHz -156.0 dBW/MHz

Transmit 28.0 GHz -151.0 dBW/4 kHz 20% -128.0 dBW/4 kHz 0.0025%

Interference Objectives: Long Term Short Term

-146.0 dBW/MHz 0.01% -39.8 (dBW/4 kHz)

20%

Max Available RF Power

Describe 40 0 CUla Terrenit 20 0 CUla

200 12000	Horizon	Antenna	Horizon	Coordination	Horizon	Coordination
Azimuth (°)	Elevation (°)	Discrimination (°)	Gain (dBi)	Distance (km)	Gain (dBi)	Distance (km
0	0.38	78.15	-3.00	262.00	-3.00	9.7
5	0.41	73.77	-3.00	262.00	-3.00	9.7
10	0.41	69.43	-3.00	262.00	-3.00	9.7
15	0.40	65.12	-3.00	262.00	-3.00	9.7
20	0.34	60.85	-3.00	262.00	-3.00	9.7
25	0.33	56.66	-3.00	262.00	-3.00	9.7
30	0.41	52.60	-3.00	262.00	-3.00	9.7
35	0.50	48.66	-3.00	262.00	-3.00	9.7
40	0.49	44.84	-3.00	262.00	-3.00	9.7
45	0.45	41.19	-3.00	262.00	-3.00	9.7
50	0.42	37.80	-3.00	262.00	-3.00	9.7
55	0.41	34.75	-3.00	262.00	-3.00	9.7
60	0.30	32.04	-3.00	262.00	-3.00	9.7
65	0.24	29.91	-3.00	262.00	-3.00	9.7
70	0.00	28.24	-3.00	262.00	-3.00	9.7
75	0.00	27.57	-3.00	262.00	-3.00	9.7
80	0.00	27.73	-3.00	262.00	-3.00	9.7
85	0.00	28.70	-3.00	262.00	-3.00	9.7
90	0.00	30.40	-3.00	262.00	-3.00	9.7
95	0.00	32.73	-3.00	262.00	-3.00	9.7
100	0.00	35.55	-3.00	262.00	-3.00	9.7
105	0.00	38.76	-3.00	262.00	-3.00	9.7
110	0.00	42.27	-3.00	262.00	-3.00	9.7
115	0.00	46.01	-3.00	262.00	-3.00	9.7
120	0.00	49.92	-3.00	262.00	-3.00	9.7
125	0.00	53.96	-3.00	262.00	-3.00	9.7
130	0.00	58.11	-3.00	262.00	-3.00	9.7
135	0.00	62.35	-3.00	262.00	-3.00	9.7
140	0.00	66.64	-3.00	262.00	-3.00	9.7
145	0.00	70.98	-3.00	262.00	-3.00	9.7
150	0.94	75.49	-3.00	262.00	-3.00	9.7
155	3.37	80.10	-3.00	262.00	-3.00	9.7
160	3.13	84.36	-3.00	262.00	-3.00	9.7
165	2.28	88.65	-3.00	262.00	-3.00	9.7
170	1.12	93.02	-3.00	262.00	-3.00	9.7
175	0.33	97.45	-3.00	262.00	-3.00	9.7
180	0.00	101.89	-3.00	262.00	-3.00	9.7
185	0.00	106.29	-3.00	262.00	-3.00	9.7



5. Contact Information

For questions or information regarding the 28 GHz Frequency Coordination Report, please contact:

Contact person: Dennis Jimeno

Title: Engineer III, Telecommunications

Company: Comsearch

Address: 19700 Janelia Farm Blvd., Ashburn, VA 20147

Telephone: 703-726-5858 Fax: 703-726-5599

Email: DJimeno@Comsearch.com

Web site: www.comsearch.com