Ka-Band Earth Station – Sherrodsville, OH Frequency Coordination Report 28 GHz



Prepared on Behalf of ViaSat, Inc.

February 27, 2021





Table of Contents

1.	Summary of Results	- 8 -
2.	28 GHz Common Carrier and LTTS Coordination	- 8 -
3.	28 GHz UMFUS Coordination	- 9 -
4.	Earth Station Coordination Data	- 10 -
5.	Contact Information	- 11 -



1. Summary of Results

On behalf of ViaSat. Inc., Comsearch issued coordination notice under Section 25.203(c) and Section 25.136(a)(4) of the FCC's rules for all existing and proposed terrestrial licenses within the coordination contours of their proposed Ka-Band earth station in Sherrodsville-OH, which will transmit at 28 GHz¹. Prior-notification emails were sent to the licensees and a copy of the notification data is provided in section four of this report. The earth station coordination was finalized on December 17, 2020.

No objections were received from any of the incumbent 28 GHz licensees.

2. 28 GHz Common Carrier and LTTS Coordination

In accordance with FCC Rules and Regulations, the Ka-Band earth station in Sherrodsville, OH was prior-coordinated by Comsearch. A notification email, datasheet and Google Earth file showing the area around the site outside which the -77.6 dBm/m2 per MHz threshold value is not exceeded for this earth station were sent to the following 28 GHz common carrier fixed microwave licensees. These licensees are authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis or local basis.

Licensee	Authorized Geographic Area
AT&T	Statewide: OH
Frontier	Nationwide

A notification email, datasheet and Google Earth file showing the area around the site outside which the -77.6 dBm/m2 per MHz threshold value is not exceeded for the Ka-Band earth station in Sherrodsville, OH were also sent to the following 28 GHz local television transmission licensee. This licensee is authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis.

Licensee	Authorized Geographic Area
Information Super Station, LLC	Continental US

No objections were received from the common carrier or local television transmission service incumbents.

.

 $^{^{1}}$ The proposed earth station will operate in the 27.5 – 29.1 GHz & 29.5 – 30.0 GHz portion of the Ka-Band.



3. 28 GHz UMFUS Coordination

Two 28 GHz UMFUS licensees were identified within the coordination distance of the proposed earth station. The proposed earth station will operate on frequencies that overlap Channel L1 & L2 of the UMFUS service. The total frequency allocation for Channels L1 & L2 of the UMFUS spectrum appears below.

Channel: L1 27.500 - 27.925 GHz

L2 27.925 - 28.350 GHz

Licensee	Authorized Geographic Area
T-Mobile License LLC	Market Based

No objections were received from the UMFUS incumbents within coordination distance.



4. Earth Station Coordination Data

This section presents the data pertinent to the proposed Ka-Band earth station in Sherrodsville, OH. This data was circulated to all incumbent licensees in the shared 28 GHz frequency ranges.

Date:	11/1	17/2020	
		01117COMSNR46	
A desirate tradition to the			
Administrative Information		NINEER BRODOOM	
		SINEER PROPOSAL	
Call Sign		TAT	
		ASAT aSat. Inc	
Site Information	SHE	ERRODSVILL, OH	
Venue Name			
Latitude (NAD 83)		40° 30' 19.2" N	
Longitude (NAD 83)		81° 14' 58.2" W	
Climate Zone Rain Zone	A 2		
Ground Elevation (AM		98 m / 938.2 ft	
	JE, 203.	30 III 7 000.E II	
Link Information			
Satellite Type		stationary	
Mode		TO - Transmit-Only	
Modulation		Digital	
Satellite Arc		W to 91° West Longitude 0° to 194.8°	
Azimuth Range 175. Corresponding Elevation Angles 43.0			
Antenna Centerline (A		m / 3.9 ft	
Antenna Informatio	n	Transmit - VES000	
Manufacturer		VIASAT INC.	
Model		13138XX	
Gain / Diameter		52.0 dBi / 1.8 m	
3-dB / 15-dB Beamwidth		0.40° / 0.80°	
Max Available RF Power	(dBW/4 kHz)	42.5	
	(dBW/MHz)	-18.5	
Maximum EIRP	(dBW/4 kHz)	9.5	
	(dBW/MHz)	33.5	
Interference Objectives:	Long Term	-141.0 dBW/4 kHz 20%	
interiorence Objectives.	Short Term	-141.0 dBW/4 kHz 20% -118.0 dBW/4 kHz 0.0025%	
Frequency Information		Transmit 28.0 GHz	
Emission / Frequency Range (MHz)		464MG7D / 27500.0 - 29500.0	
Coordination Distance		3 km / 1.86 mi	
Coordination Distance		3 KIII 7 1.00 IIII	



5. Contact Information

For questions or information regarding the 28 GHz Frequency Coordination Report, please contact:

Contact person: Naveen Raghavan
Title: Engineering Manager

Company: Comsearch

Address: 19700 Janelia Farm Blvd., Ashburn, VA 20147

Telephone: 703-726-5648

Email: nraghavan@Comsearch.com

Web site: www.comsearch.com