Ka-Band Earth Station – New Braunfels, TX Frequency Coordination Report 28 GHz



Prepared on Behalf of SPACE EXPLORATION HOLDINGS

April 15, 2021





Table of Contents

1.	Summary of Results	- 1 -
2.	28 GHz Common Carrier and LTTS Coordination	- 1 -
3.	28 GHz UMFUS Coordination	- 2 -
4.	Earth Station Coordination Data	- 3 -
5.	Contact Information	- 7 -



1. Summary of Results

On behalf of SPACE EXPLORATION HOLDINGS, Comsearch performed a coordination notice under Section 25.203(c) and Section 25.136(a)(4) of the FCC's rules for all existing and proposed terrestrial licenses within the coordination contours of their proposed Ka-Band earth station in New Braunfels, TX, which will transmit at 28 GHz¹. Prior-notification letters were sent to the licensees and a copy of the notification data is provided in section four of this report. The earth station coordination was finalized on April 15, 2021.

No objections were received from any of the incumbent 28 GHz licensees.

2. 28 GHz Common Carrier and LTTS Coordination

In accordance with FCC Rules and Regulations, the Ka-Band earth station in New Braunfels, TX was prior-coordinated by Comsearch. A notification letter and datasheets for this earth station were sent to the following 28 GHz common carrier fixed microwave licensees. These licensees are authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis or local basis.

Licensee	Authorized Geographic Area
Frontier	Nationwide

A notification letter and datasheets for the Ka-Band earth station in New Braunfels, TX were also sent to the following 28 GHz local television transmission licensee. This licensee is authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis.

Licensee	Authorized Geographic Area
Information Super Station, LLC	Continental US

No objections were received from the common carrier or local television transmission service incumbents.

 $^{^{\}rm 1}$ The proposed earth station will operate in the 27.5 – 29.1 GHz & 29.5 – 30.0 GHz portion of the Ka-Band.



3. 28 GHz UMFUS Coordination

There were three 28 GHz UMFUS licensees identified within the coordination distance of the proposed earth station. The proposed earth station will operate on frequencies that overlap Channel L1 & L2 of the UMFUS service. The total frequency allocation for Channels L1 & L2 of the UMFUS spectrum appears below.

Channel:	L1	27.500 - 27.925 GHz
	L2	27.925 - 28.350 GHz

Licensee	Authorized Geographic Area
Central Texas Communications	Market Based
T-Mobile	Market Based
Verizon	Market Based

No objections were received from the UMFUS incumbents within coordination distance.



4. Earth Station Coordination Data

This section presents the data pertinent to the proposed Ka-Band earth station in New Braunfels, TX. This data was circulated to all incumbent licensees in the shared 28 GHz frequency ranges.



Job Number:		210316COMSGE02				
Administrative Informat	ion	Search Second Second				
Status		ENGINEER PROPOSAL				
Call Sign						
Licensee Code		SPACEX				
Licensee Name		Space Exploration Holding	5			
Site Information		NEW BRAUNFELS, TX	_			
Venue Name		- manual and the second				
Latitude (NAD 83)		29° 47' 2.6" N				
Longitude (NAD 83)		98° 3' 2.8" W				
Climate Zone		A				
Rain Zone		2				
Ground Elevation (AMSL)		213.48 m / 700.4 ft				
Link Information						
Satellite Type		Low Earth Orbit				
Mode		TR - Transmit-Receive				
Modulation		Digital				
Minimum Elevation Angle		25.0°				
Azimuth Range		0.0° to 360°				
Antenna Centerline (AGL)		0.91 m / 3.0 ft				
Antenna Information		Receive - FCC32	_	Transmit - FCC32		
Manufacturer		SpaceX		SpaceX		
Model		1.47 meter		1.47 meter		
Gain / Diameter		46.9 dBi / 1.5 m		49.5 dBi / 1.5 m		
3-dB / 15-dB Beamwidth		0.77°/1.70°		0.49° / 1.17°		
J-0D/ 15-0D Deanimuti		0.11 / 1.10		0.40 / 1.17		
Max Available RF Power (dBW/4 kH		Z)		-39.8		
	(dBW/MHz)		-15.8		
Maximum EIRP	(dBW/4 kH	7)		9.7		
(dBW/MHz)				33.7		
	APARAMINE.			50.7		
Interference Objectives:	Long Term	-156.0 dBW/MHz	20%	-151.0 dBW/4 kHz 20%		
Carlos and a straight part	Short Term	-146.0 dBW/MHz	0.01%	-128.0 dBW/4 kHz 0.0025%		
Frequency Information		Receive 18.0 GHz		Transmit 28.0 GHz		
Emission / Frequency Range (MHz)		62M5D7W - 480MD7W / 17800.0 - 18600.0		62M5D7W - 480MD7W / 27500.0 - 29100.0		
		62M5D7W - 480MD7W / 18800	.0 - 19300.0	62M5D7W - 480MD7W / 29500.0 - 30000.0		
Man Owned Oracle Owned on the	Distance	202 0 hm / 102 0		105 0 km / 77 7 mi		
Max Great Circle Coordination I	Distance	262.0 km / 162.8 m		125.0 km / 77.7 mi		
Precipitation Scatter Contour R	n divin	100.0 km / 62.1 mi		100.0 km / 62.1 mi		



Coordination	Values	NEW BRAUNFEL, TX	(
icensee Nan	1	Space Exploration Ho				
atitude (NAE		29° 47' 2.6" N	lanigo			
ongitude (N/		98° 3' 2.8" W				
Ground Eleva		213.48 m / 700.4 ft				
Antenna Cent		0.91 m / 3.0 ft				
Antenna Mod	el	SpaceX 1.47 meter				
Antenna Mod	e	Receive 18.0 (GHz	Transmit	28.0 GHz	
Interference (Objectives: Long Ter	-156.0 dBW/M	Hz 20%	-151.0 df	BW/4 kHz 20%	
	Short			-128 0 df	BW/4 kHz 0.0025%	
Max Available	e RF Power	Vertication		BW/4 kHz)		
			Receiv	Receive 18.0 GHz Transm		
	Horizon	Antenna	Horizon	Coordination	Horizon	Coordination
Azimuth (°)	Elevation (°)	Discrimination (°)	Gain (dBi)	Distance (km)	Gain (dBi)	Distance (km
0						
	1.83	86.16	-3.00	262.00	-3.00	125.00
5	1.45	81.37	-3.00	262.00	-3.00	125.00
10	1.32	76.59	-3.00	262.00	-3.00	125.00
15	1.09	71.79	-3.00	262.00	-3.00	125.00
20	1.29	67.05	-3.00	262.00	-3.00	125.00
25	0.88	62.25	-3.00	262.00	-3.00	125.00
30	0.51	57.45	-3.00	262.00	-3.00	125.00
35	0.47	52.72	-3.00	262.00	-3.00	125.00
40	0.35	48.02	-3.00	262.00	-3.00	125.00
40	0.26	43.36	-3.00	262.00	-3.00	125.00
50	0.00	38.72	-3.00	262.00	-3.00	125.00
55	0.00	34.24	-3.00	262.00	-3.00	125.00
60	0.00	29.91	-3.00	262.00	-3.00	125.00
65	0.00	25.80	-3.00	262.00	-3.00	125.00
70	0.00	22.03	-3.00	262.00	-3.00	125.00
75	0.00	18.81	-3.00	262.00	-3.00	125.00
80	0.00	16.46	-3.00	262.00	-3.00	125.00
85	0.00	15.40	-3.00	262.00	-3.00	125.00
90	0.00	15.87	-3.00	262.00	-3.00	125.00
95	0.00	17.76	-3.00	262.00	-3.00	125.00
100	0.00	20.69	-3.00	262.00	-3.00	125.00
105	0.00	24.27	-3.00	262.00	-3.00	125.00
110	0.00	28.26	-3.00	262.00	-3.00	125.00
115	0.00	32.52	-3.00	262.00	-3.00	125.00
120	0.00	36.94	-3.00	262.00	-3.00	125.00
125	0.00	41.48	-3.00	262.00	-3.00	125.00
130	0.00	46.10	-3.00	262.00	-3.00	125.00
135	0.00	50.77	-3.00	262.00	-3.00	125.00
140	0.00	55.49	-3.00	262.00	-3.00	125.00
145	0.00	60.24	-3.00	262.00	-3.00	125.00
150	0.00	65.01	-3.00	262.00	-3.00	125.00
155	0.00	69.80	-3.00	262.00	-3.00	125.00
160	0.24	74.62	-3.00	262.00	-3.00	125.00
165	0.21	79.42	-3.00	262.00	-3.00	125.00
170	0.00	84.23	-3.00	262.00	-3.00	125.00
175	0.21	89.05	-3.00	262.00	-3.00	125.00
180	0.34	93.87	-3.00	262.00	-3.00	125.00
185	0.26	98.68	-3.00	262.00	-3.00	125.00
105	0.20	30.00	-0.00	202.00	-5.00	120.00



Coordination Licensee Nan Latitude (NAE Longitude (NJ Ground Eleva Antenna Cen Antenna Mod Antenna Mod Interference (ne 0 83) AD 83) ation (AMSL) terline (AGL) el		2	-151.0 dl	28.0 GHz 3W/4 kHz 20% 3W/4 kHz 0.0025%	
Max Availabl	e RF Power		-39.8 (d	BW/4 kHz)		
			Deres	- 10.0.011-	Tables	
	Horizon	Antenna	Horizon	e 18.0 GHz Coordination	Horizon	nit 28.0 GHz Coordination
Azimuth (°)	Elevation (°)	Discrimination (°)	Gain (dBi)	Distance (km)	Gain (dBi)	Distance (km)
190	0.28	103.49	-3.00	262.00	-3.00	125.00
195	0.21	108.29	-3.00	262.00	-3.00	125.00
200	0.00	113.11	-3.00	262.00	-3.00	125.00
205	0.00	117.89	-3.00	262.00	-3.00	125.00
210	0.21	122.61	-3.00	262.00	-3.00	125.00
215	0.27	127.32	-3.00	262.00	-3.00	125.00
220	0.25	132.01	-3.00	262.00	-3.00	125.00
225	0.29	136.62	-3.00	262.00	-3.00	125.00
230	0.44	141.13	-3.00	262.00	-3.00	125.00
235	0.64	145.50	-3.00	262.00	-3.00	125.00
240	0.99	149.60	-3.00	262.00	-3.00	125.00
245	1.16	153.52	-3.00	262.00	-3.00	125.00
250	1.23	157.11	-3.00	262.00	-3.00	125.00
255	1.40	160.04	-3.00	262.00	-3.00	125.00
260	1.71	161.94	-3.00	262.00	-3.00	125.00
265	2.06	162.54	-3.00	262.00	-3.00	125.00
270	2.13	162.06	-3.00	262.00	-3.00	125.00
275	2.15	160.36	-3.00	262.00	-3.00	125.00
280	2.10	157.74	-3.00	262.00	-3.00	125.00
285	2.07	154.42	-3.00	262.00	-3.00	125.00
290	2.28	150.51	-3.00	262.00	-3.00	125.00
295	2.57	146.30	-3.00	262.00	-3.00	125.00
300	2.88	141.92	-3.00	262.00	-3.00	125.00
305	2.98	137.51	-3.00	262.00	-3.00	125.00
310	2.44	133.21	-3.00	262.00	-3.00	125.00
315	2.35	128.66	-3.00	262.00	-3.00	125.00
320	2.49	124.00	-3.00	262.00	-3.00	125.00
325 330	2.85 2.73	119.27 114.61	-3.00	262.00 262.00	-3.00 -3.00	125.00 125.00
335	2.75	109.90	-3.00	262.00	-3.00	125.00
335 340	2.74	105.17	-3.00	262.00	-3.00	125.00
345	2.55	100.44	-3.00	262.00	-3.00	125.00
350	2.55	95.70	-3.00	262.00	-3.00	125.00
355	2.45	90.94	-3.00	262.00	-3.00	125.00



5. Contact Information

For questions or information regarding the 28 GHz Frequency Coordination Report, please contact:

Contact person:	Dennis Jimeno
Title:	Engineer III, Telecommunications
Company:	Comsearch
Address:	19700 Janelia Farm Blvd., Ashburn, VA 20147
Telephone:	703-726-5858
Fax:	703-726-5599
Email:	DJimeno@Comsearch.com
Web site:	www.comsearch.com