Ka-Band Earth Station – Waterloo, IN Frequency Coordination Report 28 GHz



Prepared on Behalf of ViaSat, Inc.

July 31, 2021





Table of Contents

1.	Summary of Results	- 2 -
2.	28 GHz UMFUS Coordination	- 2 -
3.	Earth Station Coordination Data	- 3 -
4.	Contact Information	- 4 -



1. Summary of Results

On behalf of ViaSat. Inc., Comsearch issued coordination notice under Section 25.203(c) and Section 25.136(a)(4) of the FCC's rules for all existing and proposed terrestrial licenses within the coordination contours of their proposed Ka-Band earth station in Waterloo-IN, which will transmit at 28 GHz¹. Prior-notification emails were sent to the licensees and a copy of the notification data is provided in section four of this report. The earth station coordination was finalized on July 29, 2021.

No objections were received from any of the incumbent 28 GHz licensees.

2. 28 GHz UMFUS Coordination

All 28 GHz UMFUS licensees within the coordination distance of the proposed earth station were identified. The proposed earth station will operate on frequencies that overlap Channel L1 & L2 of the UMFUS service. The total frequency allocation for Channels L1 & L2 of the UMFUS spectrum appears below.

Channel:	L1	27.500 - 27.925 GHz
	L2	27.925 - 28.350 GHz

Licensee	Authorized Geographic Area
MetaLINK Technologies	Market Based
Verizon	Market Based

No objections were received from the UMFUS incumbents within coordination distance.

¹ The proposed earth station will operate in the 27.5 – 29.1 GHz & 29.5 – 30.0 GHz portion of the Ka-Band.



3. Earth Station Coordination Data

This section presents the data pertinent to the proposed Ka-Band earth station in Waterloo, IN. This data was circulated to all incumbent licensees in the shared 28 GHz frequency ranges.

		29/2021 629COMSNR49	
		SINEER PROPOSAL	
		SAT Sat, Inc	
Site Information	WA	TERLOO, IN	
		26' 11.04" N 02' 41.37" W	
Climate Zone	A	62 41.57 VV	
Rain Zone Ground Elevation (AMSL)		77 m / 931.0 ft	
Link Information Satellite Type Mode		stationary Transmit-Only	
Modulation Satellite Arc	Digit		
Azimuth Range		W to 91° West Longitude 4° to 189.0°	
Corresponding Elevation		°/41.7°	
Antenna Centerline (A	GL) 1.5 m	n / 4.9 ft	
Antenna Informatio	n	Transmit - VES001	
Manufacturer		VIASAT INC.	
Model Gain / Diameter		13001XX 52.6 dBi / 2.4 m	
3-dB / 15-dB Beamwidth		0.40° / 0.80°	
Max Available RF Power	(dBW/4 kHz)	42.5	
	(dBW/MHz)	-18.5	
Maximum EIRP	(dBW/4 kHz) (dBW/MHz)	9.5 33.5	
Interference Objectives:	Long Term Short Term	-141.0 dBW/4 kHz 20% -118.0 dBW/4 kHz 0.0025%	
Frequency Informa Emission / Frequency Rang		Transmit 28.0 GHz 464MG7D / 27500.0 - 29500.0	
Coordination Distance		0.45 km / 0.28 mi	



4. Contact Information

For questions or information regarding the 28 GHz Frequency Coordination Report, please contact:

Contact person:	Naveen Raghavan
Title:	Engineering Manager
Company:	Comsearch
Address:	19700 Janelia Farm Blvd., Ashburn, VA 20147
Telephone:	703-726-5648
Email:	nraghavan@Comsearch.com
Web site:	www.comsearch.com