

S1. GENERAL INFORMATION Complete for all satellite applications.

a. Space Station or Satellite Network Name: DIRECTV 1		e. Estimated Date of Placement into Service: 12/1/1993		i. Will the space station(s) operate on a Common Carrier Basis: N	
b. Construction Commencement Date:		f. Estimated Lifetime of Satellite(s): 15.5 Years		j. Number of transponders offered on a common carrier basis:	
c. Construction Completion Date:		g. Total Number of Transponders: 16		k. Total Common Carrier Transponder Bandwidth: MHz	
d1. Est Launch Date Begin:	d2. Est Launch Date End:	h. Total Transponder Bandwidth (no. transponders x Bandwidth) 384 MHz		i. Orbit Type: Mark all boxes that apply: <input checked="" type="checkbox"/> GSO <input type="checkbox"/> NGSO	

S2. OPERATING FREQUENCY BANDS Identify the frequency range and transmit/receive mode for all frequency bands in which this station will oper
Also indicate the nature of service(s) for each frequency band.

Frequency Band Limits				e. T/R Mode	f. Nature of Service(s): List all that apply to this band
Lower Frequency (Hz)		Upper Frequency (Hz)			
a. Numeric	b. Unit (K/M/G)	c. Numeric	d. Unit (K/M/G)		
17.3	G	17.8	G	R	Feeder Link for Broadcasting Satellite Service in FSS
12.2	G	12.7	G	T	Broadcasting Satellite Service - Video

S3. ORBITAL INFORMATION FOR GEOSTATIONARY SATELLITES ONLY:

a. Nominal Orbital Longitude (Degrees E/W): 72.5 W		b. Alternate Orbital Longitude (Degrees E/W):		c. Reason for orbital location selection:			
Longitudinal Tolerance or E/W Station-Keeping:		f. Inclination Excursion or N/S Station-Keeping Tolerance:				Range of orbital are in which adequate service can be provided (Optional): Degrees E/W	
d. Toward West: 0.05 Degrees	e. Toward East: 0.05 Degrees		g. Westernmost:			h. Easternmost:	
i. Reason for service are selection (Optional):							

**FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)**

S4. ORBITAL INFORMATION FOR NON-GEOSTATIONARY SATELLITES ONLY

S4a. Total Number of Satellites in Network or System:

S4c. Celestial Reference Body (Earth, Sun, Moon, etc.):

S4b. Total Number of Orbital Planes in Network or System:

S4d. Orbit Epoch Date:

For each Orbital Plane Provide:

(e) Orbital Plane No.	(f) No. of Satellites in Plane	(g) Inclination Angle (degrees)	(h) Orbital Period (Seconds)	(i) Apogee (km)	(j) Perigee (km)	(k) Right Ascension of the Ascending Node (Deg.)	(l) Argument of Perigee (Degrees)	Active Service Arc Range (Degrees)		
								(m) Begin Angle	(n) End Angle	(o) Other

S5. INITIAL SATELLITE PHASE ANGLE For each satellite in each orbital plane, provide the initial phase angle.

(a) Orbital Plane No.	(b) Satellite Number	(c) Initial Phase Angle (Degrees)

NO NGSO DATA FILED

**FEDERAL COMMUNICATIONS COMMISSION
 SATELLITE SPACE STATION AUTHORIZATIONS
 FCC Form 312 - Schedule S: (Technical and Operational Description)**

S6. SERVICE AREA CHARACTERISTICS for each service area provide:

(a) Service Area ID	(b) Type of Associated Station (Earth or Space)	(c) Service Area Diagram File Name (GXT File)	(d) Service Area Description. Provide list of geographic areas (state postal codes or ITU 3-ltr codes), satellites or Figure No. of Service Area Diagram.
CONUSRX	S		CONUS
CONUSTX	S		CONUS

FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)

S7. SPACE STATION ANTENNA BEAM CHARACTERISTICS For each antenna beam provide:

(a) Beam ID	(b) T/R Mode	Isotropic Antenna Gain		(e) Pointing Error (Degrees)	(f) Rotational Error (Degrees)	(g) Min. Cross- Polar Iso- lation (dB)	(h) Polar- ization Switch- able? (Y/N)	(i) Polarization Alignment Rel. Equatorial Plane (Degrees)	(j) Service Area ID	Transmit			Receive			Input Attenuator (dB)	
										(k) Input Losses (dB)	(l) Effective Output Power (W)	(m) Max. EIRP (dBW)	(n) System Noise Temp (k)	(o) G/T Max. Gain Pt. (db/K)	(p) Min. Saturation Flux Density (dBW/m2)	(q) Max. Value	(r) Step Size
		(c) Peak (dBi)	(d) Edge (dBi)														
UL	R	32	29	0.35		27	N		CONUSR				708	3.5	-94	7	1
DL	T	35.1	29.1	0.35		27	N		CONUSTX	1.2	120	54.7					

**FEDERAL COMMUNICATIONS COMMISSION
 SATELLITE SPACE STATION AUTHORIZATIONS
 FCC Form 312 - Schedule S: (Technical and Operational Description)**

S8. ANTENNA BEAM DIAGRAMS For each beam pattern provide the reference to the graphic image and numerical data:
 Also provide the power flux density levels in each beam that result from the emission with the highest power flux density.

(a) Beam ID	(b) T/R Mode	(c) Co-or Cross Polar Mode ("C" or" X")	(d) GSO Ref. Orbital Longitude (Deg. E/W)	(e) NGSO Antenna Gain Contour Description (Figure/Table/ Exhibit)	(f) GSO Antenna Gain Contour Data (GXT File)	Max. Power Flux Density (dBW/M2/Hz)				
						At Angle of Arrival above horizontal (for emission with highest PFD)				
						(g) 5 Deg	(h) 10 Deg	(i) 15 Deg	(j) 20 Deg	(k) 25 Deg
UL	R	C	-72		D1_72.5_RX_CO.gxt					
DL	T	C	-72		D1_72.5_TX_CO.gxt					

**FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)**

S9. SPACE STATION CHANNELS For each frequency channel provide: S10. SPACE STATION TRANSPONDERS For each transponder provide:

(a) Channel No.	(B) Assigned Bandwidth (kHz)	(c) T/R Mode	(d) Center Frequency (MHz)	(e) Polarization (H, V, L, R)	(f) TTC or Comm Channel (T or C)
16R	24000	R	17524.7	L	C
2R	24000	R	17338.58	L	C
18R	24000	R	17571.86	L	C
4R	24000	R	17367.74	L	C
20R	24000	R	17601.02	L	C
6R	24000	R	17396.9	L	C
22R	24000	R	17630.18	L	C
8R	24000	R	17426.06	L	C
24R	24000	R	17659.34	L	C
10R	24000	R	17455.22	L	C
26R	24000	R	17688.5	L	C
12R	24000	R	17484.38	L	C
14R	24000	R	17513.54	L	C
28R	24000	R	17717.66	L	C
30R	24000	R	17746.82	L	C
32R	24000	R	17775.98	L	C
2T	24000	T	12238.58	L	C
4T	24000	T	12267.74	L	C
6T	24000	T	12296.9	L	C
8T	24000	T	12326.06	L	C
10T	24000	T	12355.22	L	C
12T	24000	T	12384.38	L	C
14T	24000	T	12413.54	L	C
16T	24000	T	12442.7	L	C
18T	24000	T	12471.86	L	C
20T	24000	T	12501.02	L	C
22T	24000	T	12530.18	L	C
24T	24000	T	12559.34	L	C
26T	24000	T	12588.5	L	C
28T	24000	T	12617.66	L	C

(a) Transponder ID	(b) Transponder Gain (dB)	Receive Band		Transmit Band	
		(c) Channel No.	(d) Beam ID	(e) Channel No.	(f) Beam ID
2	120	2R	RX	2T	TX1
4	120	4R	RX	4T	TX1
6	120	6R	RX	6T	TX1
8	120	8R	RX	8T	TX1
10	120	10R	RX	10T	TX1
12	120	12R	RX	12T	TX1
14	120	14R	RX	14T	TX1
16	120	16R	RX	16T	TX1
18	120	18R	RX	18T	TX1
20	120	20R	RX	20T	TX1
22	120	22R	RX	22T	TX1
24	120	24R	RX	24T	TX1
26	120	26R	RX	26T	TX1
28	120	28R	RX	28T	TX1
30	120	30R	RX	30T	TX1
32	120	32R	RX	32T	TX1
CMD		CMD	RX		
TLM1				TLM1	TX1
TLM2				TLM2	TX1

30T	24000	T	12646.82	L	C
32T	24000	T	12675.98	L	C
CMD	1000	R	17303	R	T
TLM1	1000	T	12200.5	R	T
TLM2	1000	T	12201.75	R	T

FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)

S11. DIGITAL MODULATION PARAMETERS For each digital emission provide:

(a) Digital Mod. ID	(b) Emission Designator	(c) Assigned Bandwidth (kHz)	(d) No. of Phases	(e) Uncoded Data Rate (kbps)	(f) FEC Error Correction Coding Rate	(g) CDMA Processing Gain (dB)	(h) Total C/N Performance Objective (dB)	(i) Single Entry C/I Objective (dB)
DTH	24M0G7W	24000	4	30320	0.758		6.8	28

FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)

Page 8: Analog Modulation

S12. ANALOG MODULATION PARAMETERS For each analog emission provide:

(a) Analog Mod. ID	(b) Emission Designator	(c) Assigned Bandwidth (kHz)	(d) Signal Type	(e) Channels per Carrier	Multi-channel Telephony				(j) Video Standard NTSC, PAL, etc.	(k) Video Noise- Weighting (dB)	(l) Video and SCPC/FM Modulation Index	(m) SCPC/FM Compander, Preemphasis, and Noise Weighting (dB)	(n) Total C/N Performance Objective (dB)	(o) Single Entry C/I Objective (dB)
					(f) Ave. Companded Talker Level (dBm0)	(g) Bottom Baseband Freq. (MHz)	(h) Top Baseband Freq. (MHz)	(i) RMS Modulation Index						
CMD	800KF2D	800		1									7.6	28
TLM	800KF2D	800		1									7.6	28

FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)

S13. TYPICAL EMISSIONS For each planned type of emission provide:

Associated Transponder ID Range (a) Start (b) End		Modulation ID		(e) Carriers per Transponder	(f) Carrier Spacing (kHz)	(g) Noise Budget Reference (Table No.)	(h) Energy Dispersal Bandwidth (kHz)	Receive Band (Assoc. Transmit Stn)			Transmit Band (This Space Station)			
		(c) Digital (Table S11)	(d) Analog (Table S12)					(i) Assoc. Stn. Max. Antenna Gain (dBi)	Assoc. Station Transmit Power (dBW) (j) Min. (k) Max.		EIRP (dBW) (l) Min. (m) Max.		(n) Max. Power Flux Density (dBW/m ² /Hz)	(o) Assoc. Stn Rec. G/T (dB/K)
2	32	DTH		1							48	54		13
CMD	CMD		CMD	1				65	-7.5	22.4				
TLM1	TLM2		TLM	1							5	14		39

**FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)**

Page 10: TT and C

S14. Is the space station(s) controlled and monitored remotely? If Yes, provide the location and telephone number of the TT and C control point(s): Yes

Remote Control (TT C) Location(s):

S14a: Street Address: 5454 E. Garton Rd			
S14b. City: Castle Rock	S14c. County: Douglas	S14d. State/Country CO	S14e. Zip Code: 80104
S14f. Telephone Number: 303-660-7001		S14g. Call Sign of Control Station (if appropriate): E930191	

**FEDERAL COMMUNICATIONS COMMISSION
SATELLITE SPACE STATION AUTHORIZATIONS
FCC Form 312 - Schedule S: (Technical and Operational Description)**

S15. SPACECRAFT PHYSICAL CHARACTERISTICS:

S15a. Mass of spacecraft without fuel (kg): 1259	Spacecraft Dimensions (meters)	Probability of Survival to End of Life (0.0 - 1.0)
S15b. Mass of fuel and disposables at launch (kg): 1607		
S15c. Mass of spacecraft and fuel at launch (kg): 2866	S15f. Length (m): 26.2	S15i. Payload: 0.93
S15d. Mass of fuel, in orbit, at beginning of life (kg): 477	S15g. Width (m): 2.29	S15j. Bus: 0.89
S15e. Deployed Area of Solar Array (square meters): 43.9	S15h. Height (m): 6.87	S15k. Total: 0.83

S16. SPACECRAFT ELECTRICAL CHARACTERISTICS:

Spacecraft Subsystem	Electrical Power (Watts) At Beginning of Life		Electrical Power (Watts) At End of Life	
	At Equinox	At Solstice	At Equinox	At Solstice
Payload (Watts):	(a): 3720	(f): 3720	(k): 3749	(p): 3749
Bus (Watts):	(b):	(g):	(l): 770	(q): 403
Total (Watts):	(c):	(h):	(m) 4519	(r): 4152
Solar Array (Watts):	(d): 5332	(i): 4930	(n): 4872	(s): 4436
Depth of Battery Discharge (%):	(e) 78.5 %	(j) 78.5 %	(o) 79.4 %	(t) 79.4 %

S17. CERTIFICATIONS:

a. Are the power flux density limits of § 25.208 met?	<input type="checkbox"/> YES	<input type="checkbox"/> NO	<input checked="" type="checkbox"/> N/A
b. Are the appropriate service area coverage requirements of § 25.143(b)(ii) and (iii), or § 25.145(c)(1) and (2) met?	<input type="checkbox"/> YES	<input type="checkbox"/> NO	<input checked="" type="checkbox"/> N/A
c. Are the frequency tolerances of § 25.202(e) and the out-of-band emission limits of § 25.202(f)(1), (2) and (3) met?	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> NO	<input type="checkbox"/> N/A

In addition to the information required in this Form, the space station applicant is required to provide all the information specified in Section 25.114 of the Commission's rules, 47 C.F.R § 25.114.