

| General | Unit | |
|--|-------------|---------|
| User terminal type | | INM-C |
| Emission Designator | | 5K00G1D |
| Modulation | | BPSK |
| Uplink | | |
| Frequency | GHz | 1.6 |
| User terminal elevation angle | (deg) | 20.0 |
| User terminal EIRP towards satellite | (dBW) | 1.2 |
| Path Loss | (dB) | 188.8 |
| Mean atmospheric loss | (dB) | 0.1 |
| Satellite G/T | (dB/K) | 2.2 |
| Adjacent channel interference allocation | (dB) | 0.2 |
| Up-path C/No | (dBW/Hz) | 42.9 |
| Downlink | | |
| Frequency | GHz | 3.6 |
| LES elevation angle | (deg) | 5.0 |
| Satellite EIRP | (dBW) | -25.4 |
| Path Loss | (dB) | 195.7 |
| Mean atmospheric loss | (dB) | 0.1 |
| LES G/T | (dB/K) | 30.7 |
| Random loss | (dB) | 1.0 |
| Down-path C/No | (dBW/Hz) | 37.1 |
| Total | | |
| Mean satellite C/IMo | (dB/Hz) | 39.6 |
| Co-channel interference | (dB/Hz) | 45.3 |
| Adjacent sat. interference allocation | (dB) | 1.0 |
| Mean overall C/No | (dB/Hz) | 33.1 |
| Mean overall C/N | (dB) | 4.4 |
| Margin | | |
| C/N objective | (dB) | 3.5 |
| C/N margin | (dB) | 0.8 |