

<b>General</b>	<b>Unit</b>	
User terminal type		RBGAN
Emission Designator Modulation		30K0G1X QPSK
<b>Uplink</b>		
Frequency	GHz	1.6
User terminal elevation angle	(deg)	20.0
User terminal EIRP towards satellite	(dBW)	13.3
Path Loss	(dB)	188.8
Mean atmospheric loss	(dB)	0.1
Satellite G/T	(dB/K)	12.7
Adjacent channel interference allocation	(dB)	0.2
Up-path C/No	(dBW/Hz)	65.5
<b>Downlink</b>		
Frequency	GHz	3.6
SAS elevation angle	(deg)	5.0
Satellite EIRP	(dBW)	4.2
Path Loss	(dB)	195.7
Mean atmospheric loss	(dB)	0.1
SAS G/T	(dB/K)	32.3
Random loss	(dB)	1.0
Down-path C/No	(dBW/Hz)	68.3
<b>Total</b>		
Mean satellite C/IMo	(dB/Hz)	76.2
Co-channel interference	(dB/Hz)	62.1
Adjacent sat. interference allocation	(dB)	1.0
Mean overall C/No	(dB/Hz)	58.7
Mean overall C/N	(dB)	14.0
<b>Margin</b>		
C/N objective	(dB)	6.8
C/N margin	(dB)	7.2