

General	Unit	
User terminal type	-	Class-3
Modulation ID / Designator	-	C3F2/ 200KD7W
Data rate (kbps)	(kbps)	384
Coding rate	-	0.642
Modulation	-	16-QAM
Carrier bandwidth	(kHz)	189
Allocated bandwidth	(kHz)	200
Uplink		
Frequency	(GHz)	6.5
Earth Station EIRP	(dBW)	62.3
Antenna diameter	m	19.0
Antenna tx gain	dBi	59.6
Uplink power	(dBW)	2.7
Uplink p.s.d. avgd. in 4 kHz	(dBW/4kHz)	-14.1
Path loss	(dB)	200.9
Mean Atmospheric loss	(dB)	0.4
Satellite G/T	(dB/K)	-10.4
Up-path C/No	(dBHz)	79.2
Downlink		
Frequency	(GHz)	1.5
Satellite EIRP	(dBW)	41.5
Path loss	(dB)	188.4
Mean Atmospheric loss	(dB)	0.1
User terminal G/T	(dB/K)	-16.9
Down-path C/No	(dBHz)	64.7
Total		
Mean satellite C/IMo	(dBHz)	73.9
Co-Channel Interference	(dBHz)	74.0
Other system interference allocation	(dB)	1.0
Mean Overall C/No	(dBHz)	62.7
Mean Overall C/N	(dB)	9.9
Margin		
C/N objective	(dB)	9.1
C/N margin	(dB)	0.8