

Request for Routine Processing of Non-Compliant Antenna

The antenna at issue is a C-band Seatel 9797 (“Antenna”). This Antenna does not strictly comply with Section 25.209 of the Regulations. However, according to Section 25.218 of the Regulations, an applicant may request routine processing of an application if it meets the applicable off-axis EIRP envelopes.

Furthermore, an application pursuant to Section 25.218 must file the corresponding tables outlined in Section 25.115(h) of the Regulations. Applicant presents below the tables outlined in Section 25.115(h) and therefore requests routine processing of this application.

| EIRP DENSITY TABLE, AZIMUTH - §25.115 (h) (1) |           |                         |               |
|---|-----------|-------------------------|---------------|
| <b>Antenna Manufacturer</b>                   | Seatel    | <b>Antenna Diameter</b> | 2.4 m         |
| <b>Antenna Model</b>                          | 9797      | <b>Antenna Gain</b>     | 41.7 dBi      |
| <b>Transmit Frequency</b>                     | 6.175 GHz | <b>Max EIRP Density</b> | 22.8 dBW/4KHz |

| Off-Axis degrees | §25.218 SD (dBW/4KHz) | Actual SD (dBW/4KHz) | Margin (dB) |
|------------------|-----------------------|----------------------|-------------|
| 1.5              | 21.9                  | 6.1                  | -15.8       |
| 1.6              | 21.2                  | 3.6                  | -17.6       |
| 1.7              | 20.5                  | 1.1                  | -19.4       |
| 1.8              | 19.9                  | -1.9                 | -21.8       |
| 1.9              | 19.3                  | -4.9                 | -24.2       |
| 2.0              | 18.8                  | -7.4                 | -26.2       |
| 2.1              | 18.2                  | -10.4                | -28.6       |
| 2.2              | 17.7                  | -13.9                | -31.6       |
| 2.3              | 17.3                  | -14.9                | -32.1       |
| 2.4              | 16.8                  | -13.9                | -30.7       |
| 2.5              | 16.4                  | -12.8                | -29.1       |
| 2.6              | 15.9                  | -11.5                | -27.4       |
| 2.7              | 15.5                  | -11.4                | -26.9       |
| 2.8              | 15.1                  | -11.5                | -26.6       |
| 2.9              | 14.7                  | -12.8                | -27.5       |
| 3.0              | 14.4                  | -14.9                | -29.3       |
| 3.1              | 14.0                  | -17.8                | -31.8       |
| 3.2              | 13.7                  | -21.4                | -35.1       |
| 3.3              | 13.3                  | -22.9                | -36.2       |
| 3.4              | 13.0                  | -18.9                | -31.9       |
| 3.5              | 12.7                  | -14.9                | -27.6       |
| 3.6              | 12.4                  | -13.9                | -26.3       |
| 3.7              | 12.1                  | -13.1                | -25.2       |
| 3.8              | 11.8                  | -12.9                | -24.7       |
| 3.9              | 11.5                  | -13.9                | -25.4       |
| 4.0              | 11.2                  | -14.9                | -26.1       |
| 4.1              | 11.0                  | -16.4                | -27.4       |
| 4.2              | 10.7                  | -17.8                | -28.5       |
| 4.3              | 10.5                  | -20.0                | -30.5       |
| 4.4              | 10.2                  | -23.9                | -34.1       |
| 4.5              | 10.0                  | -30.0                | -40.0       |
| 4.6              | 9.7                   | -35.9                | -45.6       |
| 4.7              | 9.5                   | -35.9                | -45.4       |

| Off-Axis degrees | §25.218 SD (dBW/4KHz) | Actual SD (dBW/4KHz) | Margin (dB) |
|------------------|-----------------------|----------------------|-------------|
| 7.5              | 5.3                   | -25.0                | -30.3       |
| 7.6              | 5.3                   | -23.9                | -29.2       |
| 7.7              | 5.3                   | -20.0                | -25.3       |
| 7.8              | 5.3                   | -21.4                | -26.7       |
| 7.9              | 5.3                   | -20.9                | -26.2       |
| 8.0              | 5.3                   | -20.9                | -26.2       |
| 8.1              | 5.3                   | -19.9                | -25.2       |
| 8.2              | 5.3                   | -19.9                | -25.2       |
| 8.3              | 5.3                   | -19.9                | -25.2       |
| 8.4              | 5.3                   | -21.4                | -26.7       |
| 8.5              | 5.3                   | -21.9                | -27.2       |
| 8.6              | 5.3                   | -22.4                | -27.7       |
| 8.7              | 5.3                   | -23.9                | -29.2       |
| 8.8              | 5.3                   | -25.0                | -30.3       |
| 8.9              | 5.3                   | -25.9                | -31.2       |
| 9.0              | 5.3                   | -26.4                | -31.7       |
| 9.1              | 5.3                   | -26.9                | -32.2       |
| 9.2              | 5.3                   | -27.9                | -33.2       |
| 9.3              | 5.1                   | -28.9                | -34.0       |
| 9.4              | 5.0                   | -29.4                | -34.4       |
| 9.5              | 4.9                   | -30.4                | -35.2       |
| 9.6              | 4.7                   | -30.9                | -35.6       |
| 9.7              | 4.6                   | -31.4                | -36.0       |
| 9.8              | 4.5                   | -31.4                | -35.9       |
| 9.9              | 4.4                   | -30.9                | -35.3       |
| 10.0             | 4.3                   | -29.9                | -34.2       |
| 15.0             | -0.1                  | -30.9                | -30.8       |
| 20.0             | -3.2                  | -34.9                | -31.7       |
| 25.0             | -5.6                  | -36.9                | -31.2       |
| 30.0             | -7.6                  | -33.9                | -26.3       |
| 35.0             | -9.3                  | -36.4                | -27.1       |
| 40.0             | -10.8                 | -33.9                | -23.1       |
| 45.0             | -12.0                 | -36.4                | -24.4       |

ITC Global USA, LLC  
Form 312, Schedule B

|     |     |       |       |
|-----|-----|-------|-------|
| 4.8 | 9.3 | -30.0 | -39.3 |
| 4.9 | 9.0 | -25.0 | -34.0 |
| 5.0 | 8.8 | -23.9 | -32.7 |
| 5.1 | 8.6 | -21.4 | -30.0 |
| 5.2 | 8.4 | -19.9 | -28.3 |
| 5.3 | 8.2 | -18.9 | -27.1 |
| 5.4 | 8.0 | -17.8 | -25.8 |
| 5.5 | 7.8 | -16.9 | -24.7 |
| 5.6 | 7.6 | -16.4 | -24.0 |
| 5.7 | 7.4 | -16.9 | -24.3 |
| 5.8 | 7.2 | -16.4 | -23.6 |
| 5.9 | 7.0 | -17.8 | -24.8 |
| 6.0 | 6.8 | -18.9 | -25.7 |
| 6.1 | 6.7 | -20.9 | -27.6 |
| 6.2 | 6.5 | -21.9 | -28.4 |
| 6.3 | 6.3 | -23.9 | -30.2 |
| 6.4 | 6.1 | -24.9 | -31.0 |
| 6.5 | 6.0 | -24.9 | -30.9 |
| 6.6 | 5.8 | -24.9 | -30.7 |
| 6.7 | 5.6 | -24.9 | -30.5 |
| 6.8 | 5.5 | -24.9 | -30.4 |
| 6.9 | 5.3 | -25.9 | -31.2 |
| 7.0 | 5.2 | -26.4 | -31.6 |
| 7.1 | 5.3 | -27.4 | -32.7 |
| 7.2 | 5.3 | -27.9 | -33.2 |
| 7.3 | 5.3 | -26.2 | -31.5 |
| 7.4 | 5.3 | -26.4 | -31.7 |

|       |       |       |       |
|-------|-------|-------|-------|
| 50.0  | -12.7 | -36.9 | -24.2 |
| 55.0  | -12.7 | -33.9 | -21.2 |
| 60.0  | -12.7 | -39.9 | -27.2 |
| 65.0  | -12.7 | -41.9 | -29.2 |
| 70.0  | -12.7 | -41.4 | -28.7 |
| 75.0  | -12.7 | -41.9 | -29.2 |
| 80.0  | -12.7 | -41.4 | -28.7 |
| 85.0  | -12.7 | -40.9 | -28.2 |
| 90.0  | -12.7 | -38.9 | -26.2 |
| 95.0  | -12.7 | -39.9 | -27.2 |
| 100.0 | -12.7 | -38.9 | -26.2 |
| 105.0 | -12.7 | -28.9 | -16.2 |
| 110.0 | -12.7 | -31.4 | -18.7 |
| 115.0 | -12.7 | -28.9 | -16.2 |
| 120.0 | -12.7 | -28.9 | -16.2 |
| 125.0 | -12.7 | -28.9 | -16.2 |
| 130.0 | -12.7 | -28.9 | -16.2 |
| 135.0 | -12.7 | -28.9 | -16.2 |
| 140.0 | -12.7 | -29.9 | -17.2 |
| 145.0 | -12.7 | -29.9 | -17.2 |
| 150.0 | -12.7 | -28.9 | -16.2 |
| 155.0 | -12.7 | -31.4 | -18.7 |
| 160.0 | -12.7 | -32.9 | -20.2 |
| 165.0 | -12.7 | -28.4 | -15.7 |
| 170.0 | -12.7 | -31.4 | -18.7 |
| 175.0 | -12.7 | -36.4 | -23.7 |
| 180.0 | -12.7 | -38.9 | -26.2 |

Exhibit D

| EIRP DENSITY TABLE, ELEVATION - §25.115 (h) (2) |           |                  |               |
|---|-----------|------------------|---------------|
| Antenna Manufacturer                            | Seatel    | Antenna Diameter | 2.4 m         |
| Antenna Model                                   | 9797      | Antenna Gain     | 41.4 dBi      |
| Transmit Frequency                              | 6.175 GHz | Max EIRP Density | 22.8 dBW/4KHz |

| Off-Axis degrees | §25.218 SD (dBW/4KHz) | Actual SD (dBW/4KHz) | Margin (dB) |
|------------------|-----------------------|----------------------|-------------|
| 1.5              | 24.9                  | 11.5                 | -13.4       |
| 1.6              | 24.2                  | 9.6                  | -14.6       |
| 1.7              | 23.5                  | 7.6                  | -15.9       |
| 1.8              | 22.9                  | 5.4                  | -17.5       |
| 1.9              | 22.3                  | 2.7                  | -19.7       |
| 2.0              | 21.8                  | -0.2                 | -22.0       |
| 2.1              | 21.2                  | -3.7                 | -24.9       |
| 2.2              | 20.7                  | -7.2                 | -28.0       |
| 2.3              | 20.3                  | -9.7                 | -29.9       |
| 2.4              | 19.8                  | -10.3                | -30.1       |
| 2.5              | 19.4                  | -10.1                | -29.4       |
| 2.6              | 18.9                  | -10.0                | -28.9       |
| 2.7              | 18.5                  | -10.5                | -29.0       |
| 2.8              | 18.1                  | -11.7                | -29.9       |
| 2.9              | 17.7                  | -13.9                | -31.6       |
| 3.0              | 17.4                  | -17.4                | -34.8       |
| 3.1              | 17.0                  | -24.3                | -41.3       |
| 3.2              | 16.7                  | -32.4                | -49.1       |
| 3.3              | 16.3                  | -21.9                | -38.2       |
| 3.4              | 16.0                  | -17.4                | -33.4       |
| 3.5              | 15.7                  | -15.4                | -31.1       |
| 3.6              | 15.4                  | -14.2                | -29.6       |
| 3.7              | 15.1                  | -13.9                | -29.0       |
| 3.8              | 14.8                  | -14.3                | -29.1       |
| 3.9              | 14.5                  | -15.3                | -29.9       |
| 4.0              | 14.2                  | -17.3                | -31.5       |
| 4.1              | 14.0                  | -20.9                | -34.9       |
| 4.2              | 13.7                  | -27.0                | -40.7       |
| 4.3              | 13.5                  | -36.2                | -49.7       |
| 4.4              | 13.2                  | -23.5                | -36.7       |
| 4.5              | 13.0                  | -19.0                | -31.9       |
| 4.6              | 12.7                  | -16.1                | -28.9       |
| 4.7              | 12.5                  | -14.4                | -26.9       |

| Off-Axis degrees | §25.218 SD (dBW/4KHz) | Actual SD (dBW/4KHz) | Margin (dB) |
|------------------|-----------------------|----------------------|-------------|
| 6.1              | 9.7                   | -17.7                | -27.4       |
| 6.2              | 9.5                   | -16.9                | -26.4       |
| 6.3              | 9.3                   | -16.7                | -26.0       |
| 6.4              | 9.1                   | -17.1                | -26.2       |
| 6.5              | 9.0                   | -18.0                | -27.0       |
| 6.6              | 8.8                   | -19.8                | -28.6       |
| 6.7              | 8.6                   | -22.1                | -30.7       |
| 6.8              | 8.5                   | -25.8                | -34.3       |
| 6.9              | 8.3                   | -29.1                | -37.4       |
| 7.0              | 8.2                   | -26.4                | -34.6       |
| 7.1              | 8.0                   | -22.7                | -30.8       |
| 7.2              | 7.9                   | -20.2                | -28.0       |
| 7.3              | 7.7                   | -18.4                | -26.1       |
| 7.4              | 7.6                   | -17.4                | -24.9       |
| 7.5              | 7.4                   | -16.9                | -24.3       |
| 7.6              | 7.3                   | -16.8                | -24.1       |
| 7.7              | 7.1                   | -17.2                | -24.4       |
| 7.8              | 7.0                   | -18.1                | -25.1       |
| 7.9              | 6.9                   | -19.5                | -26.4       |
| 8.0              | 6.7                   | -21.6                | -28.3       |
| 8.1              | 6.6                   | -24.4                | -31.0       |
| 8.2              | 6.5                   | -26.8                | -33.3       |
| 8.3              | 6.3                   | -26.9                | -33.2       |
| 8.4              | 6.2                   | -24.4                | -30.6       |
| 8.5              | 6.1                   | -22.1                | -28.1       |
| 8.6              | 5.9                   | -20.3                | -26.3       |
| 8.7              | 5.8                   | -19.1                | -25.0       |
| 8.8              | 5.7                   | -18.4                | -24.1       |
| 8.9              | 5.6                   | -18.2                | -23.7       |
| 9.0              | 5.4                   | -18.3                | -23.7       |
| 9.1              | 5.3                   | -18.7                | -24.0       |
| 9.2              | 5.2                   | -19.4                | -24.7       |
| 9.3              | 5.1                   | -20.3                | -25.3       |

ITC Global USA, LLC  
Form 312, Schedule B

|     |      |       |       |
|-----|------|-------|-------|
| 4.8 | 12.3 | -13.4 | -25.6 |
| 4.9 | 12.0 | -12.9 | -24.9 |
| 5.0 | 11.8 | -12.8 | -24.6 |
| 5.1 | 11.6 | -13.2 | -24.8 |
| 5.2 | 11.4 | -14.1 | -25.5 |
| 5.3 | 11.2 | -15.4 | -26.6 |
| 5.4 | 11.0 | -17.6 | -28.5 |
| 5.5 | 10.8 | -21.0 | -31.8 |
| 5.6 | 10.6 | -26.9 | -37.5 |
| 5.7 | 10.4 | -44.0 | -54.4 |
| 5.8 | 10.2 | -27.6 | -37.8 |
| 5.9 | 10.0 | -22.1 | -32.1 |
| 6.0 | 9.8  | -19.2 | -29.1 |

|      |       |       |                    |
|------|-------|-------|--------------------|
| 9.4  | 5.0   | -20.8 | Exhibit D<br>-25.8 |
| 9.5  | 4.9   | -20.8 | -25.7              |
| 9.6  | 4.7   | -20.2 | -24.9              |
| 9.7  | 4.6   | -19.0 | -23.6              |
| 9.8  | 4.5   | -17.8 | -22.3              |
| 9.9  | 4.4   | -16.8 | -21.2              |
| 10.0 | 4.3   | -16.1 | -20.4              |
| 15.0 | -0.1  | -26.8 | -26.7              |
| 20.0 | -3.2  | -35.5 | -32.3              |
| 25.0 | -5.6  | -36.1 | -30.5              |
| 30.0 | -7.6  | -40.5 | -32.9              |
| 35.0 | -9.3  | -33.2 | -23.9              |
| 40.0 | -10.8 | -34.6 | -23.9              |
| 45.0 | -12.0 | -38.1 | -26.1              |

| EIRP DENSITY TABLE, AZIMUTH - §25.115 (h) (3) |           |                         |               |
|---|-----------|-------------------------|---------------|
| <b>Antenna Manufacturer</b>                   | Seatel    | <b>Antenna Diameter</b> | 2.4 m         |
| <b>Antenna Model</b>                          | 9797      | <b>Antenna Gain</b>     | 41.4 dBi      |
| <b>Transmit Frequency</b>                     | 6.175 GHz | <b>Max EIRP Density</b> | 22.8 dBW/4KHz |

| Off-Axis degrees | §25.218 SD (dBW/4KHz) | Actual SD (dBW/4KHz) | Margin (dB) |
|------------------|-----------------------|----------------------|-------------|
| 1.5              | 21.9                  | 0.6                  | -21.3       |
| 1.6              | 21.2                  | -1.9                 | -23.1       |
| 1.7              | 20.5                  | -4.4                 | -24.9       |
| 1.8              | 19.9                  | -7.4                 | -27.3       |
| 1.9              | 19.3                  | -10.4                | -29.7       |
| 2.0              | 18.8                  | -12.9                | -31.6       |
| 2.1              | 18.2                  | -15.9                | -34.1       |
| 2.2              | 17.7                  | -19.4                | -37.1       |
| 2.3              | 17.3                  | -20.4                | -37.6       |
| 2.4              | 16.8                  | -19.4                | -36.2       |
| 2.5              | 16.4                  | -18.3                | -34.6       |
| 2.6              | 15.9                  | -17.0                | -32.9       |
| 2.7              | 15.5                  | -16.9                | -32.4       |
| 2.8              | 15.1                  | -17.0                | -32.1       |
| 2.9              | 14.7                  | -18.3                | -33.0       |
| 3.0              | 14.4                  | -20.4                | -34.7       |
| 3.1              | 14.0                  | -23.3                | -37.3       |
| 3.2              | 13.7                  | -26.9                | -40.5       |
| 3.3              | 13.3                  | -28.4                | -41.7       |
| 3.4              | 13.0                  | -24.4                | -37.4       |
| 3.5              | 12.7                  | -20.4                | -33.1       |
| 3.6              | 12.4                  | -19.4                | -31.8       |
| 3.7              | 12.1                  | -18.6                | -30.7       |
| 3.8              | 11.8                  | -18.4                | -30.2       |
| 3.9              | 11.5                  | -19.4                | -30.9       |
| 4.0              | 11.2                  | -20.4                | -31.6       |
| 4.1              | 11.0                  | -21.9                | -32.8       |
| 4.2              | 10.7                  | -23.3                | -34.0       |
| 4.3              | 10.5                  | -25.5                | -35.9       |
| 4.4              | 10.2                  | -29.4                | -39.6       |
| 4.5              | 10.0                  | -35.5                | -45.4       |
| 4.6              | 9.7                   | -41.4                | -51.1       |
| 4.7              | 9.5                   | -41.4                | -50.9       |

| Off-Axis degrees | §25.218 SD (dBW/4KHz) | Actual SD (dBW/4KHz) | Margin (dB) |
|------------------|-----------------------|----------------------|-------------|
| 7.5              | 5.3                   | -30.5                | -35.8       |
| 7.6              | 5.3                   | -29.4                | -34.7       |
| 7.7              | 5.3                   | -25.5                | -30.8       |
| 7.8              | 5.3                   | -26.9                | -32.2       |
| 7.9              | 5.3                   | -26.4                | -31.7       |
| 8.0              | 5.3                   | -26.4                | -31.7       |
| 8.1              | 5.3                   | -25.4                | -30.7       |
| 8.2              | 5.3                   | -25.4                | -30.7       |
| 8.3              | 5.3                   | -25.4                | -30.7       |
| 8.4              | 5.3                   | -26.9                | -32.2       |
| 8.5              | 5.3                   | -27.4                | -32.7       |
| 8.6              | 5.3                   | -27.9                | -33.2       |
| 8.7              | 5.3                   | -29.4                | -34.7       |
| 8.8              | 5.3                   | -30.5                | -35.8       |
| 8.9              | 5.3                   | -31.4                | -36.7       |
| 9.0              | 5.3                   | -31.9                | -37.2       |
| 9.1              | 5.3                   | -32.4                | -37.7       |
| 9.2              | 5.3                   | -33.4                | -38.7       |
| 9.3              | 5.1                   | -34.4                | -39.4       |
| 9.4              | 5.0                   | -34.9                | -39.8       |
| 9.5              | 4.9                   | -35.9                | -40.7       |
| 9.6              | 4.7                   | -36.4                | -41.1       |
| 9.7              | 4.6                   | -36.9                | -41.5       |
| 9.8              | 4.5                   | -36.9                | -41.4       |
| 9.9              | 4.4                   | -36.4                | -40.8       |
| 10.0             | 4.3                   | -35.4                | -39.7       |
| 15.0             | -0.1                  | -36.4                | -36.3       |
| 20.0             | -3.2                  | -40.4                | -37.1       |
| 25.0             | -5.6                  | -42.4                | -36.7       |
| 30.0             | -7.6                  | -39.4                | -31.7       |
| 35.0             | -9.3                  | -41.9                | -32.6       |
| 40.0             | -10.8                 | -39.4                | -28.6       |
| 45.0             | -12.0                 | -41.9                | -29.8       |

ITC Global USA, LLC  
Form 312, Schedule B

|     |     |       |       |
|-----|-----|-------|-------|
| 4.8 | 9.3 | -35.5 | -44.7 |
| 4.9 | 9.0 | -30.5 | -39.5 |
| 5.0 | 8.8 | -29.4 | -38.2 |
| 5.1 | 8.6 | -26.9 | -35.5 |
| 5.2 | 8.4 | -25.4 | -33.8 |
| 5.3 | 8.2 | -24.4 | -32.6 |
| 5.4 | 8.0 | -23.3 | -31.3 |
| 5.5 | 7.8 | -22.4 | -30.2 |
| 5.6 | 7.6 | -21.9 | -29.5 |
| 5.7 | 7.4 | -22.4 | -29.8 |
| 5.8 | 7.2 | -21.9 | -29.1 |
| 5.9 | 7.0 | -23.3 | -30.3 |
| 6.0 | 6.8 | -24.4 | -31.2 |
| 6.1 | 6.7 | -26.4 | -33.0 |
| 6.2 | 6.5 | -27.4 | -33.9 |
| 6.3 | 6.3 | -29.4 | -35.7 |
| 6.4 | 6.1 | -30.4 | -36.5 |
| 6.5 | 6.0 | -30.4 | -36.3 |
| 6.6 | 5.8 | -30.4 | -36.2 |
| 6.7 | 5.6 | -30.4 | -36.0 |
| 6.8 | 5.5 | -30.4 | -35.8 |
| 6.9 | 5.3 | -31.4 | -36.7 |
| 7.0 | 5.2 | -31.9 | -37.0 |
| 7.1 | 5.3 | -32.9 | -38.2 |
| 7.2 | 5.3 | -33.4 | -38.7 |
| 7.3 | 5.3 | -31.7 | -37.0 |
| 7.4 | 5.3 | -31.9 | -37.2 |

|       |       |       |       |
|-------|-------|-------|-------|
| 50.0  | -12.7 | -42.4 | -29.7 |
| 55.0  | -12.7 | -39.4 | -26.7 |
| 60.0  | -12.7 | -45.4 | -32.7 |
| 65.0  | -12.7 | -47.4 | -34.7 |
| 70.0  | -12.7 | -46.9 | -34.2 |
| 75.0  | -12.7 | -47.4 | -34.7 |
| 80.0  | -12.7 | -46.9 | -34.2 |
| 85.0  | -12.7 | -46.4 | -33.7 |
| 90.0  | -12.7 | -44.4 | -31.7 |
| 95.0  | -12.7 | -45.4 | -32.7 |
| 100.0 | -12.7 | -44.4 | -31.7 |
| 105.0 | -12.7 | -34.4 | -21.7 |
| 110.0 | -12.7 | -36.9 | -24.2 |
| 115.0 | -12.7 | -34.4 | -21.7 |
| 120.0 | -12.7 | -34.4 | -21.7 |
| 125.0 | -12.7 | -34.4 | -21.7 |
| 130.0 | -12.7 | -34.4 | -21.7 |
| 135.0 | -12.7 | -34.4 | -21.7 |
| 140.0 | -12.7 | -35.4 | -22.7 |
| 145.0 | -12.7 | -35.4 | -22.7 |
| 150.0 | -12.7 | -34.4 | -21.7 |
| 155.0 | -12.7 | -36.9 | -24.2 |
| 160.0 | -12.7 | -38.4 | -25.7 |
| 165.0 | -12.7 | -33.9 | -21.2 |
| 170.0 | -12.7 | -36.9 | -24.2 |
| 175.0 | -12.7 | -41.9 | -29.2 |
| 180.0 | -12.7 | -44.4 | -31.7 |

Exhibit D