

**ISAT US Inc. FCC
Form 312 Exhibit C
Radiation Hazard Analysis**

1.0 Introduction

This Exhibit analyzes the non-ionizing radiation levels for the ATOM-99 earth station included in this application. The analysis and calculations performed in this Exhibit comply with the methods described in the FCC Office of Engineering and Technology Bulletin, No. 65 first published in 1985 and revised in 1997 in Edition 97-01.

Bulletin No. 65 and the FCC R&O 96-326 specifies two Maximum Permissible Exposure (MPE) limits that are dependent on the situation in which the exposure takes place and/or the status of the individuals who are subject to the exposure. These are described below:

- General Population/Uncontrolled environment MPE limit is 1 mW/cm^2 . The General Population / Uncontrolled MPE is a function of transmit frequency and is for an exposure period of thirty minutes or less.
- Occupational/Controlled environment MPE limit is 5 mW/cm^2 . The Occupational MPE is a function of transmit frequency and is for an exposure period of six minutes or less.

The analysis determined the power flux density levels of the earth station in the 1) far-field, 2) near-field, 3) transition region, 4) region between the feed and main reflector surface, 5) at the main reflector surface, and 6) between the antenna edge and the ground. The summary of results and discussion is provided in Section 2 and the detailed analyses is provided in Section 3.

Section 2.0 – Summary of Results

The terminal proposed in this application is for commercial and government uses and intended to be operated by professional personnel. The analysis of the non-ionizing radiation levels provided in Section 3 assumed the maximum allowed input power to antenna of 5W and a 100% duty cycle resulting in worst case radiation levels. In a significant number of deployments the terminal duty cycle would be below 100% and the actual power required would be lower than the 5W maximum resulting in lower radiation levels than those calculated. As with any directional antenna the maximum level of non-ionizing radiation is in the main beam of the antenna that is pointed to the satellite. As one moves around the antenna to the side lobes and back lobes the radiation levels decrease significantly. Thus, the maximum radiation level from an antenna occurs in a limited area in the direction the antenna is pointed to. The terminal proposed in this application is designed to cease transmitting if the receive signal from the satellite is blocked, which could be caused by a person standing in front of the terminal or from other blockage. If the receive signal is blocked, the transmitter is shut down and will not resume operating until the signal from the satellite is reacquired. This operational feature of the terminal minimizes the potential for human radiation exposure. The terminals will be turned off prior to any maintenance being conducted when a person may need to be in close proximity to the feed flange and main reflector.

The Table below summarize the result for the proposed terminal.

ATOM-99

Region	Distance (m)	Calculated Power Density (mW/cm ²)	Limit Controlled Environment ≤ 5 mW/cm ²	Limit Uncontrolled Environment ≤ 1 mW/cm ²
Near Field	19.8	2.31	Meets Limit	Exceeds Limit
Far Field	47.5	0.99	Meets Limit	Meets Limit
Transition Region	19.8	2.31	Meets Limit	Exceeds Limit
Feed Flange	NA	1640.44	Exceeds Limit	Exceeds Limit
Main Reflector	NA	3.21	Meets Limit	Exceeds Limit

As shown the antenna terminal meets the controlled environment limit of ≤ 5 mW/cm² except at the feed flange. The feed flange is a very small area of the terminal antenna and it is extremely unlikely that a person would be near the feed flange or the main reflector while the terminal is in operation. Any blockage of the signal from the satellite in these areas would cause the terminal to cease transmitting until the blockage is removed and the signal from the satellite is reacquired. Also, in a controlled environment technicians are trained and procedures are put in place to ensure that a safe distance is maintained from the antenna while in operation.

The terminal when operating with maximum input power and a 100% duty cycle varies in meeting the uncontrolled environment limit of ≤ 1 mW/cm². As described above, the maximum radiation levels occur in a limited area in the direction the antenna is pointed. The automatic shut off capability of the terminal when the satellite receive signal is blocked will reduce potential human exposure. In addition, the terminal proposed in this application is for commercial and government use and, given the price points, are not intended to be used by consumers or widely deployed for use by the general public. Personnel operating these terminals will be trained in how to operate the terminal safely. Furthermore, the manuals for these terminals will explicitly indicate that precautions, such as not standing in front of the terminal, that are necessary to limit potential exposure.

Section 3.0 – Detailed calculations

Input Parameter	Value	Units	Symbol
Antenna Diameter	0.89	m	D
Antenna Transmit Gain	47.5	dBi	G
Transmit Frequency	30000	MHz	f
Antenna Feed Flange Diameter	3.94	cm	d
Power Input to the Antenna	5	Watts	P

Calculated Parameters	Value	Units	Symbol	Formula
Calculated Parameter	0.6221	m ²	A	$\pi D^2/4$
Antenna Surface Area	12.1918	cm ²	a	$\pi d^2/4$
Area of Antenna Flange	0.7194	real	η	$g\lambda^2/(\pi^2 D^2)$
Antenna Efficiency	56234.1325	real	g	$10^{(G/10)}$
Gain Factor	0.0100	m	λ	$300/f$
Wavelength				

Antenna Field Definitions	Value	Units	Symbol	Formula
Calculated Parameter	19.8025	m	Rnf	$D^2/(4\lambda)$
Near-Field Distance	47.526	m	Rff	$0.6D^2/\lambda$
Distance to Far-Field	19.8025	m	Rt	$Rt=Rnf$
Distance of Transition Range				

Power Flux Density	Value	Units	Symbol	Formula
Calculated Parameter	2.3127	mW/cm ²	Snf	$16\eta P/(\pi D^2)$
Power Density in the Near Field	0.9906	mW/cm ²	Sff	$gP/(4\pi Rff^2)$
Power Density in the Far Field	2.3127	mW/cm ²	St	$Snf*Rnf/Rt$
Power Density in the Transition Region				

Flange Power Density	Value	Units	Symbol	Formula
Calculated Parameter	1640.4405	mW/cm ²	Sfa	$4P/a$
Power Density at the Feed Flange				

Main Reflector Power Density	Value	Units	Symbol	Formula
Calculated Parameter	3.2149	mW/cm ²	Ssurface	$4P/A$
Power Density at Main Reflector				

Main Reflector Power Density	Value	Units	Symbol	Formula
Calculated Parameter	0.8037	mW/cm ²	Sg	P/A
Power Density between Reflector and Ground				