FCC 312 Schedule S

FEDERAL COMMUNICATIONS COMMISSION SATELLITE SPACE STATION AUTHORIZATIONS (Technical and Operational Description)

Page 1: General, Frequency Bands, and GSO Orbit

S1. GENERAL	_ INFORMATION	Complete for	all satellite	applications
-------------	---------------	--------------	---------------	--------------

a. Space Station or Satellite No EXPRESS 3A	etwork Name:	e. Estimated Date of Placement into Service: 8/22/2000		i Will the space station(s) operate on a Common Carrier Basis:		
b. Construction Commenceme 2/1/1998	nt Date:	f. Estimated Lifetime of Satellite(s): 7	j. Number of transponders offered on a comm 0	non carrier basis:		
c. Construction Completion Date: 5/21/2000		g. Total Number of Transponders: 17		k. Total Common Carrier Transponder Bandwidth: 0 MHz		
d1. Est Launch Date Begin: 6/24/2000	d2. Est Launch Date End: 6/24/2000	h. Total Transponder Bandwidth (no. transponder 616	rs x Bandwidth) MHz	I. Orbit Type: Mark all boxes that apply: X GSO No.	GSO	

S2. OPERATING FREQUENCY BANDS Identify the frequency range and transmit/receive mode for all frequency bands in which this station will oper Also indicate the nature of service(s) for each frequency band.

	Frequency	Band Limits						
Lower Frequency (_Hz) Upper Frequency (_Hz)		_Hz)	e. T/R Mode	f. Nature of Service(s): List all that apply to this band				
a. Numeric	b. Unit (K/M/G)	c. Numeric	d. Unit (K/M/G)		.,			
6432	M	6468	M	R	Fixed Satellite Service			
4107	М	4143	М	Т	Fixed Satellite Service			
6482	M	6518	M	R	Fixed Satellite Service			
4157	M	4193	M	Τ	Fixed Satellite Service			

S3. ORBITAL INFORMATION FOR GEOSTATIONARY SATELLITES ONLY:

a. Nominal Orbital Longitude (Degrees E/W): 11 W	b. Alternate Orbital Longitude (Degrees E/W):	c. Reason for orbital location selection:							
Longitudinal Tolerance or E/W Station-Keeping:	f. Inclination Excursion or Range of orbital are in which adequate service can be N/S Station-Keeping provided (Optional):	Replacement satellite for prior Intersputnik space station.							
d. Toward West: 0.05 Degrees	Tolerance: q. Westernmost:								
e. Toward East: 0.05 Degrees	0.05 Degrees h. Easternmost:								
i. Reason for service are selection (Optional):	Reason for service are selection (Optional):								

Page 2: NGSO Orbits

FCC Form 312 - Schedule S: (Technical and Operational Description)

S4. ORBITAL INFORMATION FOR NON-GEOSTATIONARY SATELLITES ONLY

S4a. Total Number of Satellites in Network or System:

S4c. Celestial Reference Body (Earth, Sun, Moon, etc.):

S4b. Total Number of Orbital Planes in Network or System: S4d. Orbit Epoch Date:

For each Orbital Plane Provide:

(e) Orbital	(f) No. of	(g) Inclination	(h) Orbital	(i) Apogee (km)	(j) Perigee (km)	(k) Right Ascension	(I) Argument of	Active Service Arc Range (De		e (Degrees)
Plane No.	Satellites in	Angle (degrees)	Period			of the Ascending	Perigee	(m) Begin	(n) End	(o) Other
	Plane		(Seconds)			Node (Deg.)	(Degrees)	Angle	Ångle	. ,
			(=====)			(9-)	(5,000)	,g.o	gio	

S5. INITIAL SATELLITE PHASE ANGLE For each satellite in each orbital plane, provide the intital phase angle.

(a) Orbital	(b) Satellite	(c) Initial
Plane No.	Number	Phase Angle
		(Degrees)

NO NGSO DATA FILED

FCC Form 312 - Schedule S: (Technical and Operational Description)

S6. SERVICE AREA CHARACTERISTICS for each service area provide:

	(a) Service Area ID	(b) Type of Associated Station (Earth or Space)	()	(d) Service Area Description. Provide list of geographic areas (state postal codes or ITU 3-ltr codes), satellites or Figure No. of Service Area Diagram.
Ī	1	E	Express 3A Service Are	

Page 3: Service Areas

Page 4: Antenna Beams

FCC Form 312 - Schedule S: (Technical and Operational Description)

S7. SPACE STATION ANTENNA BEAM CHARACTERISTICS For each antenna beam provide:

(a)	(b)	Isotropic	Antenna	(e)	(f)	(g) Min.	(h) Polar-	(i) Polarization	(j) Service		Transmit				Receive		
Beam	T/R	Ga	ain		Rotational	Cross-	ization	Alignment Rel.	Area ID	(k)	(I) Effective	(m)	(n)	(o) G/T	(p) Min.	Input Attent	uator (dB)
ID	Mode		(d) Edge	Error		Polar Iso-	Switch-	Equatorial		Input	Output	Max.	System	Max.	Saturation	(q) Max.	(r) Step
		(dBi)	(dBi)	(Degrees)	(Degrees)	lation (dB)	able? (Y/N)	Plane (Degrees)		Losses	Power (W)	EIRP			Flux Density	Value	Size
							(T/IN)			(dB)		(dBW)	Temp (k)	(db/K)	(dBW/m2)		
17	Т	27	17	0.1		22	N		1		20	39					
17R	R	28	18	0.1		22	N		1				500	1	-93	5	1
18	Т	27	17	0.1		22	N		1		20	39					
18R	R	28	18	0.1		22	N		1				500	1	-93	5	1

Page 5: Beam Diagrams

FCC Form 312 - Schedule S: (Technical and Operational Description)

S8. ANTENNA BEAM DIAGRAMS For each beam pattern provide the reference to the graphic image and numerical data:
Also provide the power flux density levels in each beam that result from the emission with the highest power flux density.

(a)	(b)	(c) Co-or	(d) GSO	(e) NGSO Antenna Gain	(f) GSO Antenna	Max. Power Flux Density (dBW/M2/Hz)						
Beam	T/R	Cross	Ref.	Contour Description								
ID	Mode	Polar Mode ("C" or" X")	Orbital Longitude (Deg. E/W)	(Figure/Table/ Exhibit)	(GXT File)	(g) 5 Deg	(h) 10 Deg	(i) 15 Deg	(j) 20 Deg	(k) 25 Deg		
17	Т	С	11		17.gxt	-153	-150.5	-148	-145.5	-143		
17R	R	С	11		17R.gxt							
18	Т	С	11		18.gxt	-153	-150.5	-148	-145.5	-143		
18R	R	С	11		18R.gxt							

Page 6: Channels and Transponders

FCC Form 312 - Schedule S: (Technical and Operational Description)

S9. SPACE STATION CHANNELS For each frequency channel provide: S10. SPACE STATION TRANSPONDERS For each transponder provide:

(a) Channel No.	(B) Assigned Bandwidth (kHz)	(c) T/R Mode	(d) Center Frequency (MHz)	(e) Polarization (H, V, L, R)	(f) TTC or Comm Channel (T or C)
3	36000	Т	4125	R	С
4	36000	R	6450	L	С
5	36000	Т	4175	R	С
6	36000	R	6500	L	С

	(a)	(b)	Receive	Band	Transmit Band		
	Transponder ID	Transponder Gain (dB)	(c) Channel No.	(d) Beam ID	(e) Channel No.	(f) Beam ID	
Į	17	110	4	17R	3	17	
	18	110	6	18R	5	18	

Page 7: Digital Modulation

FCC Form 312 - Schedule S: (Technical and Operational Description)

S11. DIGITAL MODULATION PARAMETERS For each digital emission provide:

(a) Digital Mod. ID	(b) Emission Designator	(c) Assigned Bandwidth (kHz)	(d) No. of Phases	(e)Uncoded Data Rate (kbps)	(f) FEC Error Correction Coding Rate	(g) CDMA Processing Gain (dB)	(h) Total C/N Performance Objective (dB)	(i) Single Entry C/I Objective (dB)
QPSK	36M0G7W	35555	4	40	0.875		12.4	16.8
8PSK	12M0G7W	11939	8	20	0.75		15.5	23.2

Page 8: Analog Modulation

FCC Form 312 - Schedule S: (Technical and Operational Description)

S12. ANALOG MODULATION PARAMETERS For each analog emission provide:

(a)	(b) Emission	(c)	(d) Signal	(e)	Multi-channel Telephony			(j) Video	(k) Video	(I) Video	(m) SCPC/FM	(n) Total C/N	(o) Single	
Analog Mod. ID		Assigned Bandwidth (kHz)	Туре	Channels per Carrier	(f) Ave. Companded Talker Level (dBm0)	(g) Bottom Baseband Freq. (MHz)		(i) RMS Modulation Index	Standard NTSC, PAL, etc.	Noise- Weighting (dB)	and SCPC/FM Modulation Index	Compander, Preemphasis, and Noise Weighting (dB)	Performance Objective (dB)	Entry C/I Objective (dB)

Page 9: Typical Emissions

FCC Form 312 - Schedule S: (Technical and Operational Description)

S13. TYPICAL EMISSIONS For each planned type of emission provide:

I	Assoc		Modulation ID		(e) Carriers (f) Carrier		(3)	(h) Energy	Receive Band (Assoc. Transmit Stn)			Transmit Band (This Space Station)			
ŀ	Transponder ID Range (a) Start (b) End		(C) Digital (d) An (Table	(d) Analog (Table S12)	per Transponder	-1	Reference (Table No.)	Dispersal Bandwidth (kHz)	(i)Assoc. Stn. Max.	Assoc. Station Transmit Power (dBW)		EIRP (dBW)		Power Flux	(o)Assoc. Stn
	(0)		S11)	,	Antenna Gain (dBi)	(j) Min.	(k) Max.	(I) Min.	(m) Max.	Density (dBW/m2/Hz)	Rec. G/T (dB/K)				

FEDERAL COMMUNICATIONS COMMISSION SATELLITE SPACE STATION AUTHORIZATIONS FCC Form 312 - Schedule S: (Technical and Operational Description)

Page 10: TT and C

S14. Is the space station(s) controlled and monitored remotely? If Yes, provide the location and telephone number of the TT and C control point(s): Yes

Remote Control (TT C) Location(s):

S14a: Street Address: 21, Octyabvskaya				
S14b. City: Gus-Khrustalny	S14c. County: Russia	_	S14d. State/Country	S14e. Zip Code: 801501
\$14f. Telephone Number: +70959569526	S14g. Call Sign of Control Stat	ion (if appropriate):		

FEDERAL COMMUNICATIONS COMMISSION SATELLITE SPACE STATION AUTHORIZATIONS FCC Form 312 - Schedule S: (Technical and Operational Description)

Page 11: Characteristics and Certifications

S15. SPACECRAFT PHYSICAL CHARACTERISTICS:

S16. SPACECRAFT ELECTRICAL CHARACTERISTICS:

Spacecraft Subsystem		ver (Watts) At ng of Life	Electrical Power (Watts) At End of Life						
	At Equinox	At Solstice	At Equinox	At Solstice					
Payload (Watts):	^{(a):} 1450	(f):	(k):	(p):					
Bus (Watts):	^{(b):} 920	(g):	(I):	(q):					
Total (Watts):	(c): 2370	^{(h):} 2360	(m)	(r):					
Solar Array (Watts):	^{(d):} 5200	^{(i):} 4460	^{(n):} 3570	^{(s):} 3065					
Depth of Battery Discharge (%):	(e) %	(j) %	⁽⁰⁾ 10 %	^(t) 20 %					

S17. CERTIFICATIONS:

a. Are the power flux density limits of § 25.208 met?:	Χ	YES	NO	N/A	
b. Are the appropriate service area coverage requirements of § 25.143(b)(ii) and (iii), or § 25.145(c)(1) and (2) met?	Χ	YES	NO	N/A	
c. Are the frequency tolerances of § 25.202(e) and the out-of-band emission limits of § 25.202(f)(1), (2) and (3) met	, X	YES	NO	N/A	

In addition to the information required in this Form, the space station applicant is required to provide all the information specified in Section 25.114 of the Commission's rules, 47 C.F.R § 25.114.