Exhibit 3 Micronet Communications, Inc. 720 F Avenue, Suite 100

720 F Avenue, Suite 100 Plano, Texas 75074 972-422-7200

SUPPLEMENTAL SHOWING PART 101.103(D)

File Number: M1220503 5.93 GHz Licensee: GCI COMMUNICATIONS CORPORATION

Page 1

Pursuant to Parts 25.203 and 101.103(d) of the FCC Rules and Regulations, a frequency coordination study was conducted by Micronet Communications, Inc. for the following proposed earth station:

Unalakleet ES, AK

The results of the study indicate that no unacceptable interference will result with existing, proposed or prior coordinated radio facilities.

Coordination was performed with existing, proposed and prior coordinated carriers within coordination range on the following dates:

02/06/2013 Major Mod (Expedited response requested by 02/20/2013) There were no unresolved interference objections.

The attached coordination data was forwarded on the latest date to the following parties within coordination range or their authorized coordination agents:

COMSEARCH INC GCI COMMUNICATION CORP UNICOM INC UNITED UTILITIES INC

Respectfully Submitted,

Jeremy Boyce Systems Engineer

Attached: 1 data sheet

Exhibit 3 Micronet Communications, Inc. 720 F Avenue, Suite 100 Plano, Texas 75074 972-422-7200

File: M1220503

TECHNICAL CHARACTERISTICS OF TRANSMIT RECEIVE EARTH STATION Company: GCI COMMUNICATIONS CORPORATION Site Name, State: Unalakleet ES, AK Call Sign: E020176 Latitude (NAD83) 63 52 37.2 N Longitude (NAD83) 160 47 20.2 W Elevation ANSL (ft/m) 8.01 2.44 Receive Frequency Range (MHz) 5925-6425 Range of Satellite Orbital Long. (deg) 119.50 156.00 Antenna Centerline (ft/m) 6.00 1.83 Antenna Elevation Angles (deg) 4.92 15.78		=======================================	===========	=======================================	
Company:GCI COMMUNICATIONS CORPORATIONSite Name, State:Unalakleet ES, AKCall sign:E020176Latitude(NAD83)63 52 37.2 NLongitude(NAD83)160 47 20.2 WElevation AMSL(ft/m)8.012.44Receive Frequency Range(MHz)5700-4200Transmit Frequency Range(MHz)5925-6425Range of Satellite Orbital Long.(deg)119.50156.00Antenna Centerline(ft/m)6.001.83Antenna Elevation Angles(deg)4.9215.78	TECHNICAL CHARACTERIS	TICS OF TRANSMI	T RECEIVE	EARTH STATION	
Site Name, State:Unalakleet ES, AKCall Sign:E020176Latitude(NAD83)635237.2 NLongitude(NAD83)1604720.2 WElevation AMSL(ft/m)8.012.44Receive Frequency Range(MHz)5925-6425Range of Satellite Orbital Long.(deg W)103.00139.00Range of Azimuths from North(deg)119.50156.00Antenna Centerline(ft/m)6.001.83Antenna Elevation Angles(deg)4.9215.78	=======================================	===================			
Site Name, State:Unalakleet ES, AKCall Sign:E020176Latitude(NAD83)635237.2 NLongitude(NAD83)1604720.2 WElevation AMSL(ft/m)8.012.44Receive Frequency Range(MHz)5925-6425Range of Satellite Orbital Long.(deg W)103.00139.00Range of Azimuths from North(deg)119.50156.00Antenna Centerline(ft/m)6.001.83Antenna Elevation Angles(deg)4.9215.78	Company.	COT COMMINICAT	TANG CODDO	σλψτοΝ	
Call Sign: E020176 Latitude (NAD83) 63 52 37.2 N Longitude (NAD83) 160 47 20.2 W Elevation AMSL (ft/m) 8.01 2.44 Receive Frequency Range (MHz) 3700-4200 Transmit Frequency Range (MHz) 5925-6425 Range of Satellite Orbital Long. (deg) 119.50 156.00 Antenna Centerline (ft/m) 6.00 1.83 Antenna Elevation Angles (deg) 4.92 15.78				RATION	
Latitude(NAD83)635237.2 NLongitude(NAD83)1604720.2 WElevation AMSL(ft/m)8.012.44Receive Frequency Range(MHz)5700-4200Transmit Frequency Range(MHz)5925-6425Range of Satellite Orbital Long.(deg W)103.00139.00Range of Azimuths from North(deg)119.50156.00Antenna Centerline(ft/m)6.001.83Antenna Elevation Angles(deg)4.9215.78			AK		
Longitude(NAD83)1604720.2 WElevation AMSL(ft/m)8.012.44Receive Frequency Range(MHz)3700-4200Transmit Frequency Range(MHz)5925-6425Range of Satellite Orbital Long.(deg W)103.00139.00Range of Azimuths from North(deg)119.50156.00Antenna Centerline(ft/m)6.001.83Antenna Elevation Angles(deg)4.9215.78Equipment ParametersEquipment ParametersReceiveTransmitAntenna Gain, Main Beam(dbl)42.1046.2015 DB Half Beamwidth(deg)1.400.90AntennasReceive: PATRIOT ANTENNA SYSTEMS 3.8 METER Transmit: PATRIOT ANTENNA SYSTEMS INTTX-380AZMax Transmitter Power(dbW/4KHz)50.00Modulation / Emission DesignatorDIGITAL6K72G7D	5		63 52	37 2 N	
Elevation AMSL(ft/m)8.012.44Receive Frequency Range(MHz)3700-4200Transmit Frequency Range(MHz)5925-6425Range of Satellite Orbital Long.(deg W)103.00139.00Range of Azimuths from North(deg)119.50156.00Antenna Centerline(ft/m)6.001.83Antenna Elevation Angles(deg)4.9215.78		(NAD83)			
Receive Frequency Range(MHz)3700-4200Transmit Frequency Range(MHz)5925-6425Range of Satellite Orbital Long.(degW)103.00139.00Range of Azimuths from North(deg)119.50156.00Antenna Centerline(ft/m)6.001.83Antenna Elevation Angles(deg)4.9215.78Equipment ParametersReceive TransmitAntenna Gain, Main Beam(dbI)42.1046.2015 DB Half Beamwidth(deg)1.400.90AntennasReceive: PATRIOT ANTENNA SYSTEMS 3.8 METER Transmit: PATRIOT ANTENNA SYSTEMS INTTX-380AZMax Transmitter Power(dbW/4KHz)3.80Max EIRP Main Beam(dbW/4KHz)50.00Modulation / Emission DesignatorDIGITAL6K72G7DMax Greater Circle DistancesMax Rain Scatter Distances(km)400.02295.57Max Rain Scatter Distances(km)313.61106.83Max Interference Power Long Term(dbW)-140.60-151.80Max Interference Power Short Term (dbW)-118.40-130.80	5				
Transmit Frequency Range(MHz)5925-6425Range of Satellite Orbital Long.(deg W)103.00139.00Range of Azimuths from North(deg)119.50156.00Antenna Centerline(ft/m)6.001.83Antenna Elevation Angles(deg)4.9215.78					
Range of Satellite Orbital Long. (deg W)103.00139.00Range of Azimuths from North(deg)119.50156.00Antenna Centerline(ft/m)6.001.83Antenna Elevation Angles(deg)4.9215.78					
Antenna Centerline(ft/m)6.001.83Antenna Elevation Angles(deg)4.9215.78Equipment ParametersReceiveTransmitAntenna Gain, Main Beam(dbI)42.1046.2015 DB Half Beamwidth(deg)1.400.90AntennasReceive: PATRIOT ANTENNA SYSTEMS 3.8 METER Transmit: PATRIOT ANTENNA SYSTEMS INTTX-380AZMax Transmitter Power(dbW/4KHz)3.80Max EIRP Main Beam(dbW/4KHz)50.00Modulation / Emission DesignatorDIGITAL6K72G7DCoordination ParametersReceiveTransmitMax Greater Circle Distances(km)400.02295.57Max Interference Power Long Term(dbW)-140.60-151.80Max Interference Power Short Term (dbW)-118.40-130.80		(deg W)	103.00	139.00	
Antenna Centerline(ft/m)6.001.83Antenna Elevation Angles(deg)4.9215.78Equipment ParametersReceiveTransmitAntenna Gain, Main Beam(dbI)42.1046.2015 DB Half Beamwidth(deg)1.400.90AntennasReceive: PATRIOT ANTENNA SYSTEMS 3.8 METER Transmit: PATRIOT ANTENNA SYSTEMS INTTX-380AZMax Transmitter Power(dbW/4KHz)3.80Max EIRP Main Beam(dbW/4KHz)50.00Modulation / Emission DesignatorDIGITAL6K72G7DCoordination ParametersReceiveTransmitMax Greater Circle Distances(km)400.02295.57Max Rain Scatter Distances(km)313.61106.83Max Interference Power Long Term(dbW)-140.60-151.80Max Interference Power Short Term (dbW)-118.40-130.80	Range of Azimuths from North	(deg)	119.50	156.00	
Antenna Elevation Angles(deg)4.9215.78Equipment ParametersReceiveTransmitEquipment ParametersReceiveTransmitAntenna Gain, Main Beam(dbI)42.1046.2015 DB Half Beamwidth(deg)1.400.90AntennasReceive: PATRIOT ANTENNA SYSTEMS 3.8 METER Transmit: PATRIOT ANTENNA SYSTEMS INTTX-380AZMax Transmitter Power(dbW/4KHz)3.80Max EIRP Main Beam(dbW/4KHz)50.00Modulation / Emission DesignatorDIGITAL6K72G7DCoordination ParametersReceiveTransmitMax Greater Circle Distances(km)400.02295.57Max Rain Scatter Distances(km)313.61106.83Max Interference Power Long Term(dbW)-140.60-151.80Max Interference Power Short Term (dbW)-118.40-130.80		(ft/m)	6.00		
Equipment ParametersReceiveTransmitAntenna Gain, Main Beam(dbI)42.1046.2015 DB Half Beamwidth(deg)1.400.90AntennasReceive: PATRIOT ANTENNA SYSTEMS 3.8 METER Transmit: PATRIOT ANTENNA SYSTEMS INTTX-380AZMax Transmitter Power(dbW/4KHz)3.80Max EIRP Main Beam(dbW/4KHz)50.00Modulation / Emission DesignatorDIGITAL6K72G7DMax Greater Circle DistancesMax Greater Circle Distances(km)400.02Max Interference Power Long Term(dbW)-140.60Max Interference Power Short Term-118.40-130.80					
Equipment ParametersReceiveTransmitAntenna Gain, Main Beam(dbI)42.1046.2015 DB Half Beamwidth(deg)1.400.90AntennasReceive: PATRIOT ANTENNA SYSTEMS 3.8 METER Transmit: PATRIOT ANTENNA SYSTEMS INTTX-380AZMax Transmitter Power(dbW/4KHz)3.80Max EIRP Main Beam(dbW/4KHz)50.00Modulation / Emission DesignatorDIGITAL6K72G7DMax Greater Circle DistancesMax Greater Circle Distances(km)400.02295.57Max Rain Scatter Distances(km)313.61106.83Max Interference Power Long Term(dbW)-140.60-151.80Max Interference Power Short Term-118.40-130.80		(ucg)	1.72	10.70	
Antenna Gain, Main Beam 15 DB Half Beamwidth(dbI)42.1046.2015 DB Half Beamwidth(deg)1.400.90AntennasReceive: PATRIOT ANTENNA SYSTEMS 3.8 METER Transmit: PATRIOT ANTENNA SYSTEMS INTTX-380AZMax Transmitter Power(dbW/4KHz)3.80Max EIRP Main Beam(dbW/4KHz)50.00Modulation / Emission DesignatorDIGITAL6K72G7DCoordination ParametersReceiveTransmitMax Greater Circle Distances(km)400.02295.57Max Rain Scatter Distances(km)313.61106.83Max Interference Power Long Term(dbW)-140.60-151.80Max Interference Power Short Term (dbW)-118.40-130.80					
15 DB Half Beamwidth(deg)1.400.90AntennasReceive: PATRIOT ANTENNA SYSTEMS 3.8 METER Transmit: PATRIOT ANTENNA SYSTEMS INTTX-380AZMax Transmitter Power(dbW/4KHz)3.80Max EIRP Main Beam(dbW/4KHz)50.00Modulation / Emission DesignatorDIGITAL6K72G7DCoordination ParametersReceiveTransmitMax Greater Circle Distances(km)400.02295.57Max Rain Scatter Distances(km)313.61106.83Max Interference Power Long Term(dbW)-140.60-151.80Max Interference Power Short Term-118.40-130.80	Equipment Parameters		Receive	Transmit	
15 DB Half Beamwidth(deg)1.400.90AntennasReceive: PATRIOT ANTENNA SYSTEMS 3.8 METER Transmit: PATRIOT ANTENNA SYSTEMS INTTX-380AZMax Transmitter Power(dbW/4KHz)3.80Max EIRP Main Beam(dbW/4KHz)50.00Modulation / Emission DesignatorDIGITAL6K72G7DCoordination ParametersReceiveTransmitMax Greater Circle Distances(km)400.02295.57Max Rain Scatter Distances(km)313.61106.83Max Interference Power Long Term(dbW)-140.60-151.80Max Interference Power Short Term-118.40-130.80					
15 DB Half Beamwidth(deg)1.400.90AntennasReceive: PATRIOT ANTENNA SYSTEMS 3.8 METER Transmit: PATRIOT ANTENNA SYSTEMS INTTX-380AZMax Transmitter Power(dbW/4KHz)3.80Max EIRP Main Beam(dbW/4KHz)50.00Modulation / Emission DesignatorDIGITAL6K72G7DCoordination ParametersReceiveTransmitMax Greater Circle Distances(km)400.02295.57Max Rain Scatter Distances(km)313.61106.83Max Interference Power Long Term(dbW)-140.60-151.80Max Interference Power Short Term-118.40-130.80	Antonno Coin Main Boom	(dht)	12 10	46.20	
AntennasReceive: PATRIOT ANTENNA SYSTEMS 3.8 METER Transmit: PATRIOT ANTENNA SYSTEMS INTTX-380AZMax Transmitter Power(dbW/4KHz)3.80Max EIRP Main Beam(dbW/4KHz)50.00Modulation / Emission DesignatorDIGITAL6K72G7DCoordination ParametersReceiveTransmitMax Greater Circle Distances(km)400.02295.57Max Rain Scatter Distances(km)313.61106.83Max Interference Power Long Term(dbW)-140.60-151.80Max Interference Power Short Term(dbW)-118.40-130.80					
Transmit: PATRIOT ANTENNA SYSTEMS INTTX-380AZMax Transmitter Power(dbW/4KHz)3.80Max EIRP Main Beam(dbW/4KHz)50.00Modulation / Emission DesignatorDIGITAL6K72G7DCoordination ParametersReceiveTransmitMax Greater Circle Distances(km)400.02295.57Max Rain Scatter Distances(km)313.61106.83Max Interference Power Long Term(dbW)-140.60-151.80Max Interference Power Short Term(dbW)-118.40-130.80	15 DB Hall Beallwidth	(deg)	1.40	0.90	
Transmit: PATRIOT ANTENNA SYSTEMS INTTX-380AZMax Transmitter Power(dbW/4KHz)3.80Max EIRP Main Beam(dbW/4KHz)50.00Modulation / Emission DesignatorDIGITAL6K72G7DCoordination ParametersReceiveTransmitMax Greater Circle Distances(km)400.02295.57Max Rain Scatter Distances(km)313.61106.83Max Interference Power Long Term(dbW)-140.60-151.80Max Interference Power Short Term(dbW)-118.40-130.80	Antennas Receive: PATRIO	T ANTENNA SYSTE	MS 3.8 MET	FR	
Max EIRP Main Beam(dbW/4KHz)50.00Modulation / Emission DesignatorDIGITAL6K72G7DCoordination ParametersReceiveTransmitMax Greater Circle Distances(km)400.02295.57Max Rain Scatter Distances(km)313.61106.83Max Interference Power Long Term(dbW)-140.60-151.80Max Interference Power Short Term(dbW)-118.40-130.80	Transmit: PATRIOT ANTENNA SYSTEMS INTTX-380AZ				
Max EIRP Main Beam(dbW/4KHz)50.00Modulation / Emission DesignatorDIGITAL6K72G7DCoordination ParametersReceiveTransmitMax Greater Circle Distances(km)400.02295.57Max Rain Scatter Distances(km)313.61106.83Max Interference Power Long Term(dbW)-140.60-151.80Max Interference Power Short Term(dbW)-118.40-130.80					
Modulation / Emission DesignatorDIGITAL6K72G7DCoordination ParametersReceiveTransmitMax Greater Circle Distances(km)400.02295.57Max Rain Scatter Distances(km)313.61106.83Max Interference Power Long Term(dbW)-140.60-151.80Max Interference Power Short Term(dbW)-118.40-130.80	Max Transmitter Power	(dbW/4KHz)		3.80	
Coordination ParametersReceiveTransmitMax Greater Circle Distances(km)400.02295.57Max Rain Scatter Distances(km)313.61106.83Max Interference Power Long Term(dbW)-140.60-151.80Max Interference Power Short Term(dbW)-118.40-130.80	Max EIRP Main Beam	(dbW/4KHz)		50.00	
Max Greater Circle Distances(km)400.02295.57Max Rain Scatter Distances(km)313.61106.83Max Interference Power Long Term(dbW)-140.60-151.80Max Interference Power Short Term(dbW)-118.40-130.80	Modulation / Emission Designato:	r DIGITAL 6	K72G7D		
Max Greater Circle Distances(km)400.02295.57Max Rain Scatter Distances(km)313.61106.83Max Interference Power Long Term(dbW)-140.60-151.80Max Interference Power Short Term(dbW)-118.40-130.80					
Max Greater Circle Distances(km)400.02295.57Max Rain Scatter Distances(km)313.61106.83Max Interference Power Long Term(dbW)-140.60-151.80Max Interference Power Short Term(dbW)-118.40-130.80	Condination Deventors				
Max Rain Scatter Distances(km)313.61106.83Max Interference Power Long Term(dbW)-140.60-151.80Max Interference Power Short Term(dbW)-118.40-130.80	Coordination parameters		Receive		
Max Rain Scatter Distances(km)313.61106.83Max Interference Power Long Term(dbW)-140.60-151.80Max Interference Power Short Term(dbW)-118.40-130.80					
Max Rain Scatter Distances (km) 313.61 106.83 Max Interference Power Long Term (dbW) -140.60 -151.80 Max Interference Power Short Term (dbW) -118.40 -130.80	Max Greater Circle Distances	(km)	400.02	295.57	
Max Interference Power Long Term (dbW)-140.60-151.80Max Interference Power Short Term (dbW)-118.40-130.80					
Max Interference Power Short Term (dbW) -118.40 -130.80		· · ·			
		. ,			