

FREQUENCY COORDINATION AND INTERFERENCE ANALYSIS REPORT

Prepared for

**Alascom Inc
Chignik, Alaska
(Call Sign: E4150)**

Satellite Earth Station

Prepared By:
COMSEARCH
19700 Janelia Farm Boulevard
Ashburn, Virginia 20147
July 8, 2015

TABLE OF CONTENTS

1. CONCLUSIONS	3
2. SUMMARY OF RESULTS	4
3. SUPPLEMENTAL SHOWING	5
4. EARTH STATION COORDINATION DATA.....	6
5. CERTIFICATION.....	10

1. CONCLUSIONS

An interference study considering all existing, proposed and prior coordinated microwave facilities within the coordination contours of the proposed earth station demonstrates that this site will operate satisfactorily with the common carrier microwave environment. Further, there will be no restrictions of its operation due to interference considerations.

2. SUMMARY OF RESULTS

A number of great circle interference cases were identified during the interference study of the proposed earth station. Each of the cases, which exceeded the interference objective on a line-of-sight basis, was profiled and the propagation losses estimated using NBS TN101 (Revised) techniques. The losses were found to be sufficient to reduce the signal levels to acceptable magnitudes in every case.

The following companies reported potential great circle interference conflicts that did not meet the objectives on a line-of-sight basis. When over-the-horizon losses are considered on the interfering paths, sufficient blockage exists to negate harmful interference from occurring with the proposed transmit-receive earth station.

Company

None

No carriers reported potential interference cases.

3. SUPPLEMENTAL SHOWING

Pursuant to Part 25.203(c) of the FCC Rules and Regulations, the satellite earth station proposed in this application was coordinated by Comsearch using computer techniques and in accordance with Part 25 of the FCC Rules and Regulations.

Expedited coordination data for this earth station was emailed and sent to the below listed carriers with a letter dated June 24, 2015.

Company

Comsearch

4. EARTH STATION COORDINATION DATA

This section presents the data pertinent to frequency coordination of the proposed earth station that was circulated to all carriers within its coordination contours.

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Date: 07/08/2015
Job Number: 150624COMSJC01

Administrative Information

Status ENGINEER PROPOSAL
Call Sign E4150
Licensee Code P1040
Licensee Name Alascom Inc

Site Information CHIGNIK, ALASKA

Venue Name
Latitude (NAD 83) 56° 18' 6.3" N
Longitude (NAD 83) 158° 24' 46.3" W
Climate Zone B
Rain Zone 2
Ground Elevation (AMSL) 11.89 m / 39.0 ft

Link Information

Satellite Type Geostationary
Mode TR - Transmit-Receive
Modulation Digital
Satellite Arc 94° W to 143° West Longitude
Azimuth Range 111.7° to 161.7°
Corresponding Elevation Angles 5.2° / 24.4°
Antenna Centerline (AGL) 5.36 m / 17.6 ft

Antenna Information

	Receive	Transmit
Manufacturer	Andrew Corporation	Andrew Corporation
Model	ESA5-46A	ESA5-46A
Gain / Diameter	43.7 dBi / 4.5 m	46.8 dBi / 4.5 m
3-dB / 15-dB Beamwidth	1.22° / 2.47°	0.85° / 1.90°

29K0G7W to 15M0G7W

Max Available RF Power	(dBW/4 kHz)	-2.7	-21.7		
	(dBW/MHz)	21.3	2.3		
Maximum EIRP	(dBW/4 kHz)	44.1	25.1		
	(dBW/MHz)	68.1	49.1		
	(dBW)	52.7	60.8		
Interference Objectives:	Long Term	-156.0 dBW/MHz	20%	-154.0 dBW/4 kHz	20%
	Short Term	-146.0 dBW/MHz	0.01%	-131.0 dBW/4 kHz	0.0025%

Frequency Information

	Receive 4.0 GHz	Transmit 6.1 GHz
Emission / Frequency Range (MHz)	29K0G7W - 15M0G7W / 3700.0 - 4200.0	29K0G7W - 15M0G7W / 5925.0 - 6425.0

Max Great Circle Coordination Distance	574.0 km / 356.6 mi	330.1 km / 205.1 mi
Precipitation Scatter Contour Radius	615.6 km / 382.5 mi	101.5 km / 63.1 mi

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Coordination Values

CHIGNIK, AK

Licensee Name Alascom Inc
Latitude (NAD 83) 56° 18' 6.3" N
Longitude (NAD 83) 158° 24' 46.3" W
Ground Elevation (AMSL) 11.89 m / 39.0 ft
Antenna Centerline (AGL) 5.36 m / 17.6 ft
Antenna Model Andrew Corporation ESA5-46A
Antenna Mode Receive 4.0 GHz Transmit 6.1 GHz
Interference Objectives: Long Term -156.0 dBW/MHz 20% -154.0 dBW/4 kHz 20%
Short Term -146.0 dBW/MHz 0.01% -131.0 dBW/4 kHz 0.0025%
Max Available RF Power -2.7 (dBW/4 kHz)

Azimuth (°)	Receive 4.0 GHz		Transmit 6.1 GHz			
	Horizon Elevation (°)	Antenna Discrimination (°)	Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
0	13.78	111.47	-10.00	100.00	-10.00	100.00
5	13.53	106.54	-10.00	100.00	-10.00	100.00
10	13.53	101.60	-10.00	100.00	-10.00	100.00
15	10.05	96.70	-10.00	113.53	-10.00	100.00
20	5.24	91.72	-10.00	128.82	-10.00	100.00
25	0.00	86.74	-10.00	412.20	-10.00	200.77
30	0.00	81.76	-10.00	412.20	-10.00	200.77
35	0.00	76.78	-10.00	412.20	-10.00	200.77
40	0.00	71.80	-10.00	412.20	-10.00	200.77
45	0.00	66.83	-10.00	412.20	-10.00	200.77
50	0.00	61.85	-10.00	412.20	-10.00	200.77
55	0.00	56.88	-10.00	412.20	-10.00	200.77
60	0.00	51.91	-10.00	412.20	-10.00	200.77
65	1.49	46.84	-9.76	227.42	-9.76	111.86
70	2.82	41.78	-8.52	178.13	-8.52	100.00
75	4.13	36.74	-7.13	151.09	-7.13	100.00
80	3.45	31.77	-5.55	174.89	-5.55	100.00
85	3.86	26.76	-3.69	173.27	-3.69	100.00
90	4.16	21.75	-1.44	179.63	-1.44	100.00
95	4.47	16.74	1.41	191.52	1.41	100.00
100	4.28	11.76	5.24	217.99	5.24	105.93
105	4.73	6.74	11.28	252.68	11.28	118.34
110	5.46	1.74	25.97	573.97	25.97	330.12
115	5.11	1.76	25.88	486.60	25.88	258.78
120	6.05	3.39	18.76	347.16	18.76	172.51
125	7.21	4.68	15.25	247.57	15.25	116.64
130	10.04	4.33	16.08	237.79	16.08	114.75
135	11.47	5.05	14.41	211.90	14.41	103.83
140	12.76	5.72	13.07	191.79	13.07	100.00
145	14.16	6.06	12.44	176.49	12.44	100.00
150	13.32	8.32	9.00	165.58	9.00	100.00
155	13.85	9.07	8.05	157.15	8.05	100.00
160	11.22	12.71	4.39	158.65	4.39	100.00
165	9.67	15.11	2.52	159.73	2.52	100.00
170	7.94	18.41	0.37	155.93	0.37	100.00
175	7.39	21.51	-1.31	150.26	-1.31	100.00
180	11.05	22.55	-1.83	133.81	-1.83	100.00

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Coordination Values


CHIGNIK, AK

Licensee Name	Alascom Inc				
Latitude (NAD 83)	56° 18' 6.3" N				
Longitude (NAD 83)	158° 24' 46.3" W				
Ground Elevation (AMSL)	11.89 m / 39.0 ft				
Antenna Centerline (AGL)	5.36 m / 17.6 ft				
Antenna Model	Andrew Corporation ESA5-46A				
Antenna Mode	Receive 4.0 GHz			Transmit 6.1 GHz	
Interference Objectives: Long Term	-156.0 dBW/MHz	20%	-154.0 dBW/4 kHz 20%		
Short Term	-146.0 dBW/MHz	0.01%	-131.0 dBW/4 kHz 0.0025%		
Max Available RF Power				-2.7 (dBW/4 kHz)	

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 4.0 GHz		Transmit 6.1 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
185	11.85	26.33	-3.51	123.49	-3.51	100.00
190	10.14	31.46	-5.44	125.49	-5.44	100.00
195	10.63	35.76	-6.84	118.61	-6.84	100.00
200	10.23	40.49	-8.18	118.10	-8.18	100.00
205	10.34	45.13	-9.36	114.13	-9.36	100.00
210	7.28	50.56	-10.00	118.06	-10.00	100.00
215	6.41	55.39	-10.00	120.07	-10.00	100.00
220	6.22	60.08	-10.00	120.54	-10.00	100.00
225	6.24	64.76	-10.00	120.48	-10.00	100.00
230	6.75	69.40	-10.00	119.29	-10.00	100.00
235	6.36	74.17	-10.00	120.19	-10.00	100.00
240	6.15	78.93	-10.00	120.70	-10.00	100.00
245	6.45	83.66	-10.00	119.99	-10.00	100.00
250	7.75	88.40	-10.00	118.77	-10.00	100.00
255	9.51	93.22	-10.00	114.84	-10.00	100.00
260	8.17	98.00	-10.00	117.83	-10.00	100.00
265	7.55	102.75	-10.00	117.45	-10.00	100.00
270	7.55	107.52	-10.00	117.45	-10.00	100.00
275	9.56	112.51	-10.00	114.73	-10.00	100.00
280	9.56	117.30	-10.00	114.74	-10.00	100.00
285	9.56	122.08	-10.00	114.73	-10.00	100.00
290	10.83	127.07	-10.00	110.03	-10.00	100.00
295	10.84	131.84	-10.00	110.02	-10.00	100.00
300	11.00	136.60	-10.00	109.28	-10.00	100.00
305	11.75	141.50	-10.00	105.94	-10.00	100.00
310	15.98	147.34	-10.00	100.00	-10.00	100.00
315	15.99	152.12	-10.00	100.00	-10.00	100.00
320	15.99	149.90	-10.00	100.00	-10.00	100.00
325	15.99	145.21	-10.00	100.00	-10.00	100.00
330	13.37	140.99	-10.00	100.00	-10.00	100.00
335	13.37	136.11	-10.00	100.00	-10.00	100.00
340	13.37	131.21	-10.00	100.00	-10.00	100.00
345	14.39	126.18	-10.00	100.00	-10.00	100.00
350	14.39	121.27	-10.00	100.00	-10.00	100.00
355	14.20	116.37	-10.00	100.00	-10.00	100.00

5. CERTIFICATION

I HEREBY CERTIFY THAT I AM THE TECHNICALLY QUALIFIED PERSON RESPONSIBLE FOR THE PREPARATION OF THE FREQUENCY COORDINATION DATA CONTAINED IN THIS APPLICATION, THAT I AM FAMILIAR WITH PARTS 101 AND 25 OF THE FCC RULES AND REGULATIONS, THAT I HAVE EITHER PREPARED OR REVIEWED THE FREQUENCY COORDINATION DATA SUBMITTED WITH THIS APPLICATION, AND THAT IT IS COMPLETE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.



Jeffrey E. Cowles
Engineer III, Telecommunications
COMSEARCH
19700 Janelia Farm Boulevard
Ashburn, Va. 20147

DATED: July 8, 2015