

# FREQUENCY COORDINATION AND INTERFERENCE ANALYSIS REPORT

Prepared for

**Alascom Inc.**  
**Chignik Lake, Alaska**  
**(Call Sign: E2227)**

**Satellite Earth Station**

Prepared By:  
COMSEARCH  
19700 Janelia Farm Boulevard  
Ashburn, Virginia 20147  
July 8, 2015

## TABLE OF CONTENTS

1. CONCLUSIONS .....	3
2. SUMMARY OF RESULTS .....	4
3. SUPPLEMENTAL SHOWING .....	5
4. EARTH STATION COORDINATION DATA.....	6
5. CERTIFICATION.....	10

## 1. CONCLUSIONS

An interference study considering all existing, proposed and prior coordinated microwave facilities within the coordination contours of the proposed earth station demonstrates that this site will operate satisfactorily with the common carrier microwave environment. Further, there will be no restrictions of its operation due to interference considerations.

## 2. SUMMARY OF RESULTS

A number of great circle interference cases were identified during the interference study of the proposed earth station. Each of the cases, which exceeded the interference objective on a line-of-sight basis, was profiled and the propagation losses estimated using NBS TN101 (Revised) techniques. The losses were found to be sufficient to reduce the signal levels to acceptable magnitudes in every case.

The following companies reported potential great circle interference conflicts that did not meet the objectives on a line-of-sight basis. When over-the-horizon losses are considered on the interfering paths, sufficient blockage exists to negate harmful interference from occurring with the proposed transmit-receive earth station.

Company

None

No carriers reported potential interference cases.

### 3. SUPPLEMENTAL SHOWING

Pursuant to Part 25.203(c) of the FCC Rules and Regulations, the satellite earth station proposed in this application was coordinated by Comsearch using computer techniques and in accordance with Part 25 of the FCC Rules and Regulations.

Expedited coordination data for this earth station was emailed and sent to the below listed carriers with a letter dated June 24, 2015.

Company

Comsearch

## **4. EARTH STATION COORDINATION DATA**

This section presents the data pertinent to frequency coordination of the proposed earth station that was circulated to all carriers within its coordination contours.

# COMSEARCH

## Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147  
(703)726-5500 <http://www.comsearch.com>

Date: 07/08/2015  
Job Number: 150624COMSJC02

---

### Administrative Information

Status ENGINEER PROPOSAL  
Call Sign E2227  
Licensee Code P1040  
Licensee Name Alascom Inc

---

### Site Information CHIGNIK LAKE, ALASKA

Venue Name  
Latitude (NAD 83) 56° 15' 17.6" N  
Longitude (NAD 83) 158° 46' 4.7" W  
Climate Zone A  
Rain Zone 2  
Ground Elevation (AMSL) 14.33 m / 47.0 ft

---

### Link Information

Satellite Type Geostationary  
Mode TR - Transmit-Receive  
Modulation Digital  
Satellite Arc 94° W to 143° West Longitude  
Azimuth Range 111.4° to 161.2°  
Corresponding Elevation Angles 5.0° / 24.4°  
Antenna Centerline (AGL) 5.36 m / 17.6 ft

---

### Antenna Information

	Receive	Transmit
Manufacturer	Andrew Corporation	Andrew Corporation
Model	ESA45-39239	ESA45-39239
Gain / Diameter	43.0 dBi / 4.5 m	46.5 dBi / 4.5 m
3-dB / 15-dB Beamwidth	1.22° / 2.47°	0.85° / 1.90°

29K0G7W to 15M0G7W

Max Available RF Power	(dBW/4 kHz)	-2.7	-21.7		
	(dBW/MHz)	21.3	2.3		
Maximum EIRP	(dBW/4 kHz)	43.8	24.8		
	(dBW/MHz)	67.8	48.8		
	(dBW)	52.4	60.5		
Interference Objectives:	Long Term	-156.0 dBW/MHz	20%	-154.0 dBW/4 kHz	20%
	Short Term	-146.0 dBW/MHz	0.01%	-131.0 dBW/4 kHz	0.0025%

---

### Frequency Information

	Receive 4.0 GHz	Transmit 6.1 GHz
Emission / Frequency Range (MHz)	29K0G7W - 15M0G7W / 3700.0 - 4200.0	29K0G7W - 15M0G7W / 5925.0 - 6425.0

Max Great Circle Coordination Distance	574.1 km / 356.7 mi	334.3 km / 207.7 mi
Precipitation Scatter Contour Radius	619.3 km / 384.8 mi	101.7 km / 63.2 mi

# COMSEARCH

## Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147  
(703)726-5500 <http://www.comsearch.com>

### Coordination Values

### CHIGNIK LAKE, AK

Licensee Name Alascom Inc  
Latitude (NAD 83) 56° 15' 17.6" N  
Longitude (NAD 83) 158° 46' 4.7" W  
Ground Elevation (AMSL) 14.33 m / 47.0 ft  
Antenna Centerline (AGL) 5.36 m / 17.6 ft  
Antenna Model Andrew Corporation ESA45-39239  
Antenna Mode Receive 4.0 GHz Transmit 6.1 GHz  
Interference Objectives: Long Term -156.0 dBW/MHz 20% -154.0 dBW/4 kHz 20%  
Short Term -146.0 dBW/MHz 0.01% -131.0 dBW/4 kHz 0.0025%  
Max Available RF Power -2.7 (dBW/4 kHz)

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 4.0 GHz		Transmit 6.1 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
0	7.26	111.38	-10.00	111.55	-10.00	100.00
5	6.91	106.39	-10.00	115.30	-10.00	100.00
10	7.12	101.39	-10.00	113.03	-10.00	100.00
15	7.01	96.40	-10.00	114.20	-10.00	100.00
20	7.09	91.40	-10.00	113.41	-10.00	100.00
25	7.26	86.40	-10.00	111.60	-10.00	100.00
30	5.85	81.40	-10.00	126.67	-10.00	100.00
35	5.29	76.40	-10.00	132.04	-10.00	100.00
40	4.41	71.40	-10.00	141.69	-10.00	100.00
45	3.79	66.41	-10.00	152.18	-10.00	100.00
50	2.76	61.42	-10.00	176.99	-10.00	100.00
55	2.43	56.44	-10.00	184.74	-10.00	100.00
60	1.89	51.47	-10.00	197.38	-10.00	100.00
65	1.53	46.50	-9.69	206.27	-9.69	104.95
70	1.39	41.53	-8.46	215.91	-8.46	112.03
75	0.65	36.63	-7.10	257.50	-7.10	141.32
80	0.00	31.76	-5.55	315.81	-5.55	187.89
85	0.93	26.69	-3.66	260.96	-3.66	139.45
90	0.78	21.80	-1.46	286.35	-1.46	156.18
95	0.58	16.98	1.25	321.27	1.25	181.02
100	0.86	12.13	4.90	330.37	4.90	182.01
105	2.46	6.90	11.03	318.49	11.03	160.07
110	4.38	1.55	27.27	574.14	27.27	334.34
115	5.61	1.36	28.65	496.25	28.65	267.98
120	6.16	3.30	19.05	349.01	19.05	168.48
125	6.56	5.29	13.91	250.88	13.91	112.90
130	8.26	5.98	12.58	217.17	12.58	100.00
135	9.21	7.16	10.63	198.46	10.63	100.00
140	9.08	9.18	7.93	183.59	7.93	100.00
145	9.97	10.06	6.93	165.56	6.93	100.00
150	9.15	12.35	4.71	160.10	4.71	100.00
155	7.49	15.28	2.39	165.40	2.39	100.00
160	6.99	16.89	1.31	165.57	1.31	100.00
165	5.29	19.46	-0.23	180.83	-0.23	100.00
170	4.74	21.45	-1.29	182.70	-1.29	100.00
175	5.28	23.41	-2.23	169.58	-2.23	100.00
180	6.05	26.00	-3.38	152.17	-3.38	100.00



# COMSEARCH

## Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147  
(703)726-5500 <http://www.comsearch.com>

### Coordination Values


### CHIGNIK LAKE, AK

Licensee Name Alascom Inc  
Latitude (NAD 83) 56° 15' 17.6" N  
Longitude (NAD 83) 158° 46' 4.7" W  
Ground Elevation (AMSL) 14.33 m / 47.0 ft  
Antenna Centerline (AGL) 5.36 m / 17.6 ft  
Antenna Model Andrew Corporation ESA45-39239  
Antenna Mode Receive 4.0 GHz Transmit 6.1 GHz  
Interference Objectives: Long Term -156.0 dBW/MHz 20% -154.0 dBW/4 kHz 20%  
Short Term -146.0 dBW/MHz 0.01% -131.0 dBW/4 kHz 0.0025%  
Max Available RF Power -2.7 (dBW/4 kHz)

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 4.0 GHz		Transmit 6.1 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
185	5.87	29.79	-4.85	146.93	-4.85	100.00
190	6.41	33.50	-6.13	135.01	-6.13	100.00
195	3.50	39.04	-7.79	171.30	-7.79	100.00
200	1.02	44.29	-9.16	224.13	-9.16	119.76
205	1.22	48.39	-10.00	213.63	-10.00	111.93
210	1.22	52.69	-10.00	213.63	-10.00	111.94
215	1.92	56.88	-10.00	196.65	-10.00	100.00
220	3.77	60.96	-10.00	152.49	-10.00	100.00
225	5.43	65.28	-10.00	130.65	-10.00	100.00
230	5.38	69.97	-10.00	131.17	-10.00	100.00
235	5.75	74.63	-10.00	127.58	-10.00	100.00
240	5.34	79.38	-10.00	131.57	-10.00	100.00
245	3.94	84.15	-10.00	149.19	-10.00	100.00
250	4.25	88.83	-10.00	144.15	-10.00	100.00
255	3.64	93.51	-10.00	155.24	-10.00	100.00
260	2.04	98.09	-10.00	193.66	-10.00	100.00
265	3.61	102.84	-10.00	155.94	-10.00	100.00
270	3.79	107.51	-10.00	152.05	-10.00	100.00
275	1.97	111.86	-10.00	195.39	-10.00	100.00
280	0.55	116.10	-10.00	246.28	-10.00	136.67
285	0.00	120.40	-10.00	285.28	-10.00	170.66
290	0.00	124.75	-10.00	285.28	-10.00	170.66
295	0.71	129.29	-10.00	236.88	-10.00	130.83
300	0.72	133.52	-10.00	235.99	-10.00	130.15
305	1.23	137.85	-10.00	213.34	-10.00	111.69
310	2.56	142.52	-10.00	181.77	-10.00	100.00
315	3.92	147.16	-10.00	149.46	-10.00	100.00
320	4.96	151.40	-10.00	134.07	-10.00	100.00
325	5.15	146.40	-10.00	133.34	-10.00	100.00
330	5.31	141.40	-10.00	131.83	-10.00	100.00
335	5.95	136.39	-10.00	125.69	-10.00	100.00
340	5.73	131.40	-10.00	127.83	-10.00	100.00
345	5.48	126.40	-10.00	130.19	-10.00	100.00
350	6.47	121.39	-10.00	120.03	-10.00	100.00
355	7.06	116.38	-10.00	113.73	-10.00	100.00

## 5. CERTIFICATION

I HEREBY CERTIFY THAT I AM THE TECHNICALLY QUALIFIED PERSON RESPONSIBLE FOR THE PREPARATION OF THE FREQUENCY COORDINATION DATA CONTAINED IN THIS APPLICATION, THAT I AM FAMILIAR WITH PARTS 101 AND 25 OF THE FCC RULES AND REGULATIONS, THAT I HAVE EITHER PREPARED OR REVIEWED THE FREQUENCY COORDINATION DATA SUBMITTED WITH THIS APPLICATION, AND THAT IT IS COMPLETE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.



Jeffrey E. Cowles  
Engineer III, Telecommunications  
COMSEARCH  
19700 Janelia Farm Boulevard  
Ashburn, Va. 20147

DATED: July 8, 2015