EXHIBIT 3

EXHIBIT WITH DECLARATIONS ON COMPLIANCE WITH 25.221(A)(1) AND 25.222(A)(1) OF THE COMMISSION'S RULES FOR EARTH STATIONS ON VESSELS

INCLUDES DECLARATIONS FOR –

ORBIT 2.2 METER C-BAND ANTENNA (MODELS OCEAN TRX 7-300-C AND ORBAND AL-7107-C)

SEA TEL 2.4 METER KU-BAND ANTENNA (MODELS 9797, 9711 AND 9711IMAKU)

INTELLIAN 2.4 METER MULTI-BAND ANTENNA (MODELS V240M C-BAND FOR C-BAND SIDE AND V24MKU-BAND FOR KU-BAND SIDE)

ORBIT 2.4 METER C-BAND ANTENNA (MODEL ORBAND AL-7108-C)

INTELLIAN 1.5 METER KU-BAND ANTENNA (MODEL V150)

ORBIT
COMMUNICATION WITHOUT BOUNDARIES

Declaration of Orbit Communication Systems Ltd

1. This Declaration is referred to the following marine stabilized antenna systems for satellite communications at sea, model:

   OrBand AL-7107-C VSAT system, 2.2 meter C-band antenna and the OceanTRx 7-300-C VSAT system, 2.2 meter C-band antenna models, are electronically identical to each other.

2. This declaration covers the requirements on off-axis EIRP spectral density limitations as well as pointing accuracy and cessation of transmission as described in FCC regulation 47 CFR of September 2015, Section 25.221, paragraphs (a)(1)(i), (a)(1)(ii) and (a)(1)(iii).

3. Orbit Communication Systems Ltd hereby declares that the antenna reference in 1 Above, will meet the off-axis EIRP spectral density requirements of Section 25.221 (a)(1)(i) with an N value of 1 when the input power spectral density is limited to -10.20 dBW/4kHz.

4. Orbit Communication Systems Ltd hereby declares that the antenna reference in 1. above will maintain a stabilization pointing accuracy of 0.2 degrees RMS or less under specified ship motion conditions, thus meeting the requirements of § 25.221 (a)(1)(iii).

5. Orbit Communication Systems Ltd hereby declares that the antenna reference in 1. above will automatically cease transmission within 100 milliseconds if the pointing error should exceed 0.5 degrees and will not resume transmission until the pointing error drops below 0.2 degrees, thus meeting the requirements of § 25.221 (a)(1)(iii).

Date: 18/11/2017

Satcom Regulations Director – Orbit Communication Systems Ltd.

Sea Tel Inc.
4030 Nelson Ave., Concord
California, 94520, USA
T: +1 (925) 798-7979
F: +1 (925) 798-7986

FCC Declaration of Conformity

1. Sea Tel, Inc. designs, develops, manufactures and services marine stabilized antenna systems for satellite communication at sea. These products are in turn used by our customers as part of their Ku-band Earth Station on Vessels (ESV) networks.

2. FCC regulation 47 C.F.R. § 25.222 defines the provisions for blanket licensing of ESV antennas operating in the Ku Band. This declaration covers the requirements for meeting § 25.222 (a)(1) by the demonstrations outlined in paragraphs (b)(1)(i) and (b)(1)(iii). The requirements for meeting § 25.222 (a)(3)-(a)(7) are left to the applicant. The paragraph numbers in this declaration refer to the 2009 version of FCC 47 C.F.R. § 25.222.

3. Sea Tel hereby declares that the antennas listed below will meet the off-axis EIRP spectral density requirements of § 25.222 (a)(1)(i) with an N value of 1, when the following Input Power spectral density limitations are met:

*0.6 Meter Ku Band, Models 2406 and USAT-24 are limited to	-21.6 dBW/4kHz
*0.75 Meter Ku Band, Models 3011 and USAT-30 are limited to	-21.6 dBW/4kHz
0.9 Meter Ku Band, Model 3612 is limited to	-20.3 dBW/4kHz
1.0 Meter Ku Band, Models 4003/4006/4009/4010 are limited to	-16.3 dBW/4kHz
1.0 Meter Ku Band Model 4012 is limited to	-16.6 dBW/4kHz
1.2 Meter Ku Band, Models 4996/5009/5010/5012 are limited to	-14.0 dBW/4kHz
1.5 Meter Ku Band, Models 6006/6009/6012 are limited to	-14.0 dBW/4kHz
2.4 Meter Ku Band, Models 9797/9711/ 9711IMA are limited to	-14.0 dBW/4kHz

4. Sea Tel hereby declares that the antennas referenced in paragraph 3 above, will maintain a stabilization pointing accuracy of better than 0.2 degrees under specified ship motion conditions, thus meeting the requirements of § 25.222 (a)(1)(ii)(A). Those antennas marked with * will maintain a stabilization pointing accuracy of better than 0.3 degrees. The Input Power spectral density limits for these antenna have been adjusted to meet the requirements of§ 25.222 (a)(1)(ii)(B).

5. Sea Tel hereby declares that the antennas referenced in paragraph 3 above, will automatically cease transmission within 100 milliseconds if the pointing error should exceed 0.5 degrees and will not resume transmission until the error drops below 0.2 degrees, thus meeting the requirements of § 25.222 (a)(1)(iii).

6. Sea Tel maintains all relevant test data, which is available upon request, to verify these declarations.

Peter Blaney, Chief Engineer
Sea Tel, Inc
Concord, CA

FCC Declaration of Conformity

Intellian Technologies, manufactures of stabilized maritime VSAT antenna systems for satellite communication at sea, supplies stabilized maritime VSAT antenna systems to the satellite communication service providers for their ESV (Earth Station on Vessels) networks.

FCC §25.221 defines the provisions for blanket licensing of ESV antennas operation in the C-band. It defines the antennas radiation, and each article regulates the followings;

§25.221 (a)(1)(i)(A):	Regulation for Azimuth Direction & Co Polarization
§25.221 (a)(1)(i)(B):	Regulation for Other Direction & Co Polarization
§25.221 (a)(1)(i)(C):	Regulation for Cross Polarization

FCC §25.222 defines the provisions for blanket licensing of ESV antennas operation in the Ku-band. It defines the antennas radiation, and each article regulates the followings;

§25.222 (a)(1)(i)(A):	Regulation for Azimuth Direction & Co Polarization
§25.222 (a)(1)(i)(B):	Regulation for Other Direction & Co Polarization
§25.222 (a)(1)(i)(C):	Regulation for Cross Polarization

Intellian Technologies, Inc. declares that v240M complies with the threshold level as defined in §25.221(a)(1)(i)(A):/ §25.222(a)(1)(i)(A):, and declares that v240M is in accordance with all defined regulations from §25.221(a)(1)(i)(B) to §25.221(a)(1)(i)(C) / from §25.222(a)(1)(i)(B) to §25.222(a)(1)(i)(C) at the below stated input power spectral density, with an N value of 1.

Product description	Intellian v240M, 2.4m Multi-band maritime VSAT antenna system
EIRP spectral density limit	C-band: -7.415dBW/ 4KHz
	Ku-band: -14.0dBW/ 4KHz

Intellian Technologies, Inc. declares that the above antenna will maintain a pointing error of less than or equal to 0.2 degree under specified ship motion conditions in accordance with the requirements of §25.221 (a)(1)(ii) / §25.222 (a)(1)(ii).

Intellian Technologies, Inc. declares that the above antennas will automatically cease the transmission with a mute command to the modem within 100 milliseconds if the target satellite and the axis of the main lobe of the ESV antenna exceeds 0.5 degree and will not resume until such angle is less than or equal to 0.2 degree in accordance with the requirements of §25.221 (a)(1)(iii) / §25.222 (a)(1)(iii).

Radiation pattern data is available upon request to verify the conformance.

Authority: **Steve Cha**
Vice President, Research & Development

Signature: _____

Date: June 2, 2014

Intellian Technologies, Inc.
US Headquarters
9004 Research Dr.
Irvine, CA 92618 USA
Tel: +1 949 727 4498

Intellian Technologies, Inc.
EMEA & APAC Headquarters
2F Dongik Bldg., 98 Nonhyun-dong
Kangnam-gu, Seoul 135-080, Korea
Tel: +82 2 511 2244

DECLARATION OF ORBIT COMMUNICATION LTD

Model "AL-7108" (C-Band)

I, Guy Naym, Director R&D Satcom Systems, hereby declare, that the following statements are true and correct:

1. Orbit Communication Ltd. Designs, develops and manufactures marine stabilized antenna systems for satellite communications at sea.

2. The Model "AL-7108" (C-Band) meets the shape of the off-axis EIRP spectral density mask provided for in 47 CFR Section 25.221.

3. Anyone using the Model "AL-7108" (C-Band) antenna will comply with U.S. Federal Communications Commission (FCC) off-axis EIRP spectral density limits provided that, the transmit power density at the antenna input is kept below -9.9 dBW/4KHz (0.102 Watts/4KHz) of occupied bandwidth (the worst case is at 6.4 GHz X-Pol).

4. Orbit Communication Ltd "AL-7108" (C-Band) Marine Stabilized System will maintain a stabilization tracking accuracy of better than 0.2 degrees under specified ship motion conditions. The internal controller software continuously monitor the instantaneous antenna tracking error and will cease the Tx of the BUC within 100ms (using M&C of the BUC) if an unexpected even occurs that causes the tracking error to exceed 0.5 degrees. Transmissions will not restart until the tracking error is less than 0.2 degrees of the target satellite.

5. Orbit Communication Ltd maintains all relevant test & analyzed data, which is available upon request.

Executed on December 13, 2011

Guy Naym

Director R&D SatCom Systems

Orbit Communication Ltd

FCC Declaration of Conformity

Intellian Technologies, manufactures of stabilized maritime VSAT antenna systems for satellite communication at sea, supplies stabilized maritime VSAT antenna systems to the satellite communication service providers for their ESV (Earth Station on Vessels) networks.

FCC §25.222 defines the provisions for blanket licensing of ESV antennas operation in the Ku-band. It defines the antennas radiation, and each article regulates the followings;

§25.222 (a)(1)(i)(A):	Regulation for Azimuth Direction & Co Polarization
§25.222 (a)(2)(i)(B):	Regulation for Other Direction & Co Polarization
§25.222 (a)(1)(i)(C):	Regulation for Cross Polarization

Intellian Technologies, Inc. declares that v150 complies with the threshold level as defined in §25.222(a)(1)(i)(A):, and declares that v150 is in accordance with all defined regulations from §25.222(a)(1)(i)(B) to §25.222(a)(1)(i)(C) at the below stated input power spectral density, with an N value of 1.

Product description	Intellian v150, 150cm Ku-band maritime VSAT antenna system
EIRP spectral density limit	-14.0 dBW/ 4KHz

Intellian Technologies, Inc. declares that the above antenna will maintain a pointing error of less than or equal to 0.2 degree under specified ship motion conditions in accordance with the requirements of §25.222 (a)(1)(ii).

Intellian Technologies, Inc. declares that the above antennas will automatically cease the transmission with a mute command to the modem within 100 milliseconds if the target satellite and the axis of the main lobe of the ESV antenna exceeds 0.5 degree and will not resume until such angle is less than or equal to 0.2 degree in accordance with the requirements of §25.222 (a)(1)(iii)

Radiation pattern data is available upon request to verify the conformance.

Authority: **Steve Cha**
VP of Engineering/ R&D

Signature: _____

Date: March 01, 2017

Intellian Technologies, Inc.
US Headquarters
9004 Research Dr.
Irvine, CA 92618 USA
Tel: +1 949 727 4498

Intellian Technologies, Inc.
EMEA & APAC Headquarters
5F IDIS Tower, 344, Pangyo-ro (Sampyeong-dong),
Bundang-gu, Seongnam-si, Gyeonggi-do 13493 Korea
Tel: +82 2 511 2244