

E020130 – Modification Corrections

Please change the following values in Schedule B:

- Field E38: Total Input Power at antenna flange (Watts) from 400 to 200
- Field E40: Total EIRP for all carriers (dBW) from 74.82 to 71.81
- Field E48: Maximum EIRP per Carrier (dBW) from 74.8206 to 71.81
- Field E49: Maximum EIRP Density per Carrier (dBW/4kHz) from 35.2782 to 32.27

Eφ2φ13φ MOD.

E26. Common Name:	E27. Country: USA
-------------------	-------------------

ANTENNA

Site ID	E28. Antenna Id	E29. Quantity	E30. Manufacturer	E31. Model	E32. Antenna Size<meters>	E41/42. Antenna Gain Transmint and/or Recieve (____ dBi at ____ GHz)	
SLY	SLY	1	AVL Technologies	2400 Ku 2-Port	2.4	48.8 dBi at 14.25	

E28. Antenna Id	E33/34. Diameter Minor/Major (meters)	E35. Above Ground Level (meters)	E36. Above Sea Level(meters)	E37. Building Height Above Ground Level (meters)	E38. Total Input Power at antenna flange (Watts)	E39. Maximum Antenna Height Above Rooftop (meters)	E40. Total EIRP for al carriers(dBW)
SLY	0.0/0.0	6.1	0.0	0.0	400.0 200	0.0	74.82 71.81

FREQUENCY

E28. Antenna Id	E43/44. Frequency Bands (MHz)	E45. T/R Mode	E46. Antenna Polarization(H,V, L,R)	E47. Emission Designator	E48. Maximum EIRP per Carrier (dBW)	E49. Maximum ERIP Density per Carrier (dBW/4kHz)
SLY	14000 14500	T	Horizontal and Vertical	36M0G7W	74.8206 71.81	35.2782 32.27