

FREQUENCY COORDINATION AND INTERFERENCE ANALYSIS REPORT

Prepared for
Alascom Inc
NIGHTMUTE, AK
Satellite Earth Station

Prepared By:
COMSEARCH
21515 Ridgetop Circle, Suite 300
Sterling, VA 20166
October 06, 2022

TABLE OF CONTENTS

1. CONCLUSIONS.....	3
2. SUMMARY OF RESULTS	4
3. SUPPLEMENTAL SHOWING	5
4. EARTH STATION COORDINATION DATA	6
5. CERTIFICATION.....	10

1. CONCLUSIONS

An interference study considering all existing, proposed and prior coordinated microwave facilities within the coordination contours of the proposed earth station demonstrates that this site will operate satisfactorily with the common carrier microwave environment. Further, there will be no restrictions of its operation due to interference considerations.

2. SUMMARY OF RESULTS

A number of great circle interference cases were identified during the interference study of the proposed earth station. Each of the cases, which exceeded the interference objective on a line-of-sight basis, was profiled and the propagation losses estimated using NBS TN101 (Revised) techniques. The losses were found to be sufficient to reduce the signal levels to acceptable magnitudes in every case.

3. SUPPLEMENTAL SHOWING

Pursuant to Part 25.203(c) of the FCC Rules and Regulations, the satellite earth station proposed in this application was coordinated by Comsearch using computer techniques and in accordance with Part 25 of the FCC Rules and Regulations.

Coordination data for this earth station was sent to the below listed carriers with a letter dated 09/22/2022.

Company

United Utilities, Inc.

United2, LLC

Comsearch

4. EARTH STATION COORDINATION DATA

This section presents the data pertinent to frequency coordination of the proposed earth station that was circulated to all carriers within its coordination contours.

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Date: 10/06/2022
Job Number: 220922COMSPI02

Administrative Information

Status: ENGINEER PROPOSAL
Call Sign: E2245
Licensee Code: P1040
Licensee Name: Alascom Inc

Site Information NIGHTMUTE, AK

Venue Name
Latitude (NAD 83): 60° 28' 29.9" N
Longitude (NAD 83): 164° 43' 26.1" W
Climate Zone: A
Rain Zone: 2
Ground Elevation (AMSL): 3.0 m / 9.8 ft

Link Information

Satellite Type: Geostationary
Mode: TR - Transmit-Receive
Modulation: Digital
Satellite Arc: 104° W to 226° West Longitude
Azimuth Range: 116.0° to 244.5°
Corresponding Elevation Angles: 5.3° / 5.0°
Antenna Centerline (AGL): 4.57 m / 15.0 ft

Antenna Information

Receive - A4045B

Transmit - A6045B

Manufacturer: ANDREW CORPORATION
Model: ESA45-46
Gain / Diameter: 43.9 dBi / 4.5 m
3-dB / 15-dB Beamwidth: 1.20° / 2.40°

ANDREW CORPORATION
ESA45-46
46.2 dBi / 4.5 m
0.94° / 1.90°

Max Available RF Power (dBW/4 kHz)
(dBW/MHz)

-2.7
21.3

Maximum EIRP (dBW/4 kHz)
(dBW/MHz)

43.5
67.5

Interference Objectives: Long Term -162.0 dBW/MHz 20%
Short Term -140.0 dBW/MHz 0.01%

-154.0 dBW/4 kHz 20%
-131.0 dBW/4 kHz 0.0025%

Frequency Information

Receive 4.0 GHz

Transmit 6.1 GHz

Emission / Frequency Range (MHz): 29K0G7W - 4M50G7W / 3700.0 - 4200.0

29K0G7W - 4M50G7W / 5925.0 - 6425.0

Max Great Circle Coordination Distance: 517.7 km / 321.7 mi
Precipitation Scatter Contour Radius: 610.3 km / 379.2 mi

331.8 km / 206.1 mi
101.7 km / 63.2 mi

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Coordination Values

NIGHTMUTE, AK

Licensee Name Alascom Inc
Latitude (NAD 83) 60° 28' 29.9" N
Longitude (NAD 83) 164° 43' 26.1" W
Ground Elevation (AMSL) 3.0 m / 9.8 ft
Antenna Centerline (AGL) 4.57 m / 15.0 ft
Antenna Model Andrew Corporation ESA45-46
Antenna Mode Receive 4.0 GHz Transmit 6.1 GHz
Interference Objectives: Long Term -162.0 dBW/MHz 20% -154.0 dBW/4 kHz 20%
Short Term -140.0 dBW/MHz 0.01% -131.0 dBW/4 kHz 0.0025%
Max Available RF Power -2.7 (dBW/4 kHz)

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 4.0 GHz		Transmit 6.1 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
0	8.18	115.46	-13.28	100.00	-18.26	100.00
5	8.20	110.98	-10.69	100.00	-15.39	100.00
10	8.31	105.98	-6.89	100.00	-10.78	100.00
15	8.28	100.99	-6.10	100.00	-9.80	100.00
20	8.30	96.00	-6.10	100.00	-9.80	100.00
25	7.85	91.01	-6.10	100.00	-9.80	100.00
30	6.87	86.01	-6.10	107.28	-9.80	100.00
35	5.58	81.01	-6.10	120.84	-9.80	100.00
40	4.53	76.01	-6.10	132.63	-9.80	100.00
45	3.40	71.02	-6.10	150.38	-9.80	100.00
50	2.67	66.03	-6.10	166.53	-9.80	100.00
55	1.73	61.07	-6.10	192.01	-9.80	100.00
60	1.10	56.11	-6.10	207.32	-9.80	115.70
65	0.41	51.17	-6.10	247.89	-9.80	148.36
70	0.00	46.24	-6.10	272.28	-9.80	171.44
75	0.00	41.29	-6.10	272.28	-9.80	171.44
80	0.00	36.34	-6.10	272.28	-9.80	171.44
85	0.00	31.41	-5.38	276.64	-6.21	185.34
90	0.00	26.50	-4.40	282.75	-4.10	193.45
95	0.00	21.63	-2.75	293.34	-2.45	199.75
100	0.00	16.83	-0.83	306.22	-1.17	204.65
105	0.00	12.20	-0.10	311.30	-0.80	206.04
110	0.00	7.99	4.91	348.35	4.21	224.93
115	0.00	5.38	10.14	508.44	9.44	324.80
120	0.00	6.50	7.90	444.33	6.71	279.17
125	0.00	8.61	3.68	368.70	3.59	235.10
130	0.00	10.62	-0.10	316.11	1.96	216.74
135	0.00	12.50	-0.10	311.30	-0.80	206.04
140	0.00	14.25	-0.10	311.30	-0.80	206.04
145	0.00	15.85	-0.44	308.94	-0.97	205.40
150	0.00	17.27	-1.01	305.02	-1.25	204.31
155	0.00	18.51	-1.50	301.66	-1.50	203.37
160	0.00	19.54	-1.92	298.88	-1.71	202.59
165	0.00	20.36	-2.24	296.70	-1.94	201.69
170	0.00	20.95	-2.48	295.12	-2.18	200.78
175	0.00	21.32	-2.63	294.17	-2.33	200.23
180	0.00	21.43	-2.67	293.86	-2.37	200.05
185	0.00	21.31	-2.62	294.18	-2.32	200.24

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Coordination Values

NIGHTMUTE, AK

Licensee Name	Alascom Inc				
Latitude (NAD 83)	60° 28' 29.9" N				
Longitude (NAD 83)	164° 43' 26.1" W				
Ground Elevation (AMSL)	3.0 m / 9.8 ft				
Antenna Centerline (AGL)	4.57 m / 15.0 ft				
Antenna Model	Andrew Corporation ESA45-46				
Antenna Mode	Receive 4.0 GHz				
Interference Objectives: Long Term	-162.0 dBW/MHz	20%	Transmit 6.1 GHz	-154.0 dBW/4 kHz	20%
Short Term	-140.0 dBW/MHz	0.01%		-131.0 dBW/4 kHz	0.0025%
Max Available RF Power				-2.7 (dBW/4 kHz)	

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 4.0 GHz		Transmit 6.1 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
190	0.00	20.95	-2.48	295.12	-2.18	200.78
195	0.00	20.36	-2.25	296.68	-1.95	201.68
200	0.00	19.54	-1.92	298.88	-1.71	202.59
205	0.00	18.51	-1.50	301.66	-1.50	203.38
210	0.00	17.27	-1.01	305.03	-1.25	204.32
215	0.00	15.85	-0.44	308.94	-0.97	205.40
220	0.00	14.26	-0.10	311.30	-0.80	206.04
225	0.00	12.51	-0.10	311.30	-0.80	206.04
230	0.00	10.61	-0.10	318.97	1.97	217.73
235	0.00	8.61	3.67	372.95	3.59	237.39
240	0.00	6.49	7.91	438.54	6.72	275.19
245	0.00	5.06	10.78	517.74	10.08	331.78
250	0.00	7.45	6.00	356.62	4.75	227.34
255	0.00	11.63	-0.10	311.30	-0.06	207.26
260	0.00	16.28	-0.61	307.76	-1.06	205.07
265	0.00	21.08	-2.53	294.79	-2.23	200.59
270	0.00	25.96	-4.29	283.43	-3.99	193.86
275	0.00	30.87	-5.27	277.31	-5.67	187.41
280	0.00	35.81	-6.10	272.28	-9.80	171.44
285	0.00	40.76	-6.10	272.28	-9.80	171.44
290	0.00	45.71	-6.10	272.28	-9.80	171.44
295	0.00	50.68	-6.10	272.28	-9.80	171.44
300	0.67	55.61	-6.10	227.88	-9.80	133.18
305	1.45	60.56	-6.10	199.83	-9.80	106.54
310	2.49	65.52	-6.10	172.80	-9.80	100.00
315	3.43	70.51	-6.10	149.56	-9.80	100.00
320	4.18	75.50	-6.10	136.07	-9.80	100.00
325	4.55	80.50	-6.10	132.40	-9.80	100.00
330	4.73	85.50	-6.10	130.02	-9.80	100.00
335	5.04	90.50	-6.10	126.03	-9.80	100.00
340	6.01	95.50	-6.10	116.73	-9.80	100.00
345	6.80	100.49	-6.10	108.01	-9.80	100.00
350	7.29	105.49	-6.49	101.25	-10.29	100.00
355	7.78	110.47	-10.38	100.00	-15.08	100.00

5. CERTIFICATION

I HEREBY CERTIFY THAT I AM THE TECHNICALLY QUALIFIED PERSON RESPONSIBLE FOR THE PREPARATION OF THE FREQUENCY COORDINATION DATA CONTAINED IN THIS APPLICATION, THAT I AM FAMILIAR WITH PARTS 101 AND 25 OF THE FCC RULES AND REGULATIONS, THAT I HAVE EITHER PREPARED OR REVIEWED THE FREQUENCY COORDINATION DATA SUBMITTED WITH THIS APPLICATION, AND THAT IT IS COMPLETE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

BY: *Pirouz Ebadirad*

Pirouz Ebadirad
Microwave Engineer I
COMSEARCH
21515 Ridgetop Circle, Suite 300
Sterling, VA 20166

DATED: October 06, 2022