ATTACHMENT A

Ka-Band Earth Station – Lindon, UT Frequency Coordination Report 28 GHz



Prepared on Behalf of HUGHES NETWORK SYSTEMS LIMITED

November 5, 2020





Table of Contents

1.	Summary of Results	- 1 -
2.	28 GHz Common Carrier and LTTS Coordination	- 1 -
3.	28 GHz UMFUS Coordination	- 2 -
4.	Earth Station Coordination Data	- 3 -
5.	Contact Information	- 7 -



1. Summary of Results

On behalf of HUGHES NETWORK SYSTEMS LIMITED, Comsearch performed a coordination notice under Section 25.203(c) and Section 25.136(a)(4) of the FCC's rules for all existing and proposed terrestrial licenses within the coordination contours of their proposed Ka-Band earth station in Lindon, UT, which will transmit at 28 GHz¹. Prior-notification letters were sent to the licensees with the latest antenna information and a copy of the notification data is provided in section four of this report. The earth station coordination was finalized on November 5, 2020.

No objections were received from any of the incumbent 28 GHz licensees.

2. 28 GHz Common Carrier and LTTS Coordination

In accordance with FCC Rules and Regulations, the Ka-Band earth station in Lindon, UT was prior-coordinated by Comsearch. A notification letter and datasheets for this earth station were sent to the following 28 GHz common carrier fixed microwave licensees. These licensees are authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis or local basis.

Licensee	Authorized Geographic Area
Frontier	Nationwide

A notification letter and datasheets for the Ka-Band earth station in Lindon, UT were also sent to the following 28 GHz local television transmission licensee. This licensee is authorized to operate temporary fixed operations from 27.5 – 29.5 GHz on a nationwide basis.

Licensee	Authorized Geographic Area
Information Super Station, LLC	Continental US

No objections were received from the common carrier or local television transmission service incumbents.

¹ The proposed earth station will operate in the 27.5 – 28.35 GHz & 28.35 – 29.1 GHz portion of the Ka-Band.



3. 28 GHz UMFUS Coordination

There was one 28 GHz UMFUS licensee identified within the coordination distance of the proposed earth station. The proposed earth station will operate on frequencies that overlap Channel L1 & L2 of the UMFUS service. The total frequency allocation for Channels L1 & L2 of the UMFUS spectrum appears below.

Channel:	L1	27.500 - 27.925 GHz
	L2	27.925 - 28.350 GHz

Licensee	Authorized Geographic Area	
Verizon	Market-Based	

No objections were received from the UMFUS incumbents.



4. Earth Station Coordination Data

This section presents the data pertinent to the proposed Ka-Band earth station in Lindon, UT. This data was circulated to all incumbent licensees in the shared 28 GHz frequency ranges.



Administrative Info	rmation			
Status	E	ENGINEER PROPOSAL		
Call Sign	E	E170165		
		HUNESY		
Licensee Name	ł	HUGHES NETWORK SYSTEMS LIMITED		
Site Information	1	LINDON, UT		
Venue Name				
Latitude (NAD 83))° 19' 46.2" N		
Longitude (NAD 83)		1° 43' 36.8" W		
Climate Zone	1			
Rain Zone	1.000.00	5		
Ground Elevation (AM	SL)	1410.5 m / 4627.6 ft		
Link Information				
Satellite Type		Geostationary		
Mode		TO - Transmit-Only		
Modulation		Digital		
Satellite Arc		5.2° W to 95.2° West Longitude		
Azimuth Range		155.4° to 155.4°		
Corresponding Elevati		40.3° / 40.3°		
Antenna Centerline (A	.GL) 7	7.0 m / 23.0 ft		
Antenna Informatio	on	Transmit - FCC32		
Manufacturer		SED		
Model		10.0 meter		
Gain / Diameter		67.9 dBi / 10.0 m		
3-dB / 15-dB Beamwid	ith	0.08°/0.16°		
Max Available RF Power	(dBW/4 kH:	z) -41.8		
	(dBW/MHz)) -17.8		
Maximum EIRP	(dBW/4 kHz	z) 26.1		
	(dBW/MHz)	50.1		
Interference Objectives: Long Term		-151.0 dBW/4 kHz 20%		
	Short Term	-128.0 dBW/4 kHz 0.0025%		
Frequency Informa	tion	Transmit 28.0 GHz		
Emission / Frequency Range (MHz)		455MG7W - 470MG7W / 27500.0 - 28350.0 455MG7W - 470MG7W / 28350.0 - 29100.0		
Max Great Circle Coordination Distance		100.0 km / 62.1 mi		
Precipitation Scatter Conto	Deditor	100.0 km / 62.1 mi		



HUGHES NETWORK SYSTEMS LIMITED Ka-Band Earth Station – Lindon, UT Frequency Coordination Report 28 GHz

Coordination Values	LINDON, UT	
Licensee Name	HUGHES NETWORK SYSTEMS LIMITED	
Latitude (NAD 83)	40° 19' 46.2" N	
Longitude (NAD 83)	111° 43' 36.8" W	
Ground Elevation (AMSL)	1410.5 m / 4627.6 ft	
Antenna Centerline (AGL)	7.0 m / 23.0 ft	
Antenna Model	10.0 m / 32.8 ft	
Antenna Mode	Transmit 28.0 GHz	
Interference Objectives: Long Ter	m -151.0 dBW/4 kHz 20%	
Short Ter	m -128.0 dBW/4 kHz 0.0025%	
Max Available RF Power	-41.8 (dBW/4 kHz)	

		Transmit 28.0 GHz			
	Horizon	Antenna	Horizon	Coordination	
Azimuth (°)	Elevation (°)	Discrimination (°)	Gain (dBi)	Distance (km)	
0	3.36	136.57	-10.00	100.00	
5	6.07	135.92	-10.00	100.00	
10	7.49	133.73	-10.00	100.00	
15	8.38	130.80	-10.00	100.00	
20	5.87	125.93	-10.00	100.00	
25	7.30	122.89	-10.00	100.00	
30	7.35	119.05	-10.00	100.00	
35	7.22	115.06	-10.00	100.00	
40	7.76	111.17	-10.00	100.00	
45	8.57	107.22	-10.00	100.00	
50	10.01	103.23	-10.00	100.00	
55	10.19	98.96	-10.00	100.00	
60	7.87	94.53	-10.00	100.00	
65	7.33	90.31	-10.00	100.00	
70	6.10	86.18	-10.00	100.00	
75	5.93	82.07	-10.00	100.00	
80	5.18	78.08	-10.00	100.00	
85	4.10	74.28	-10.00	100.00	
90	3.56	70.50	-10.00	100.00	
95	2.94	66.87	-10.00	100.00	
100	2.43	63.36	-10.00	100.00	
105	2.48	59.76	-10.00	100.00	
110	2.48	56.32	-10.00	100.00	
115	2.46	53.03	-10.00	100.00	
120	2.42	49.96	-10.00	100.00	
125	2.37	47.15	-9.84	100.00	
130	2.30	44.63	-9.24	100.00	
135	2.19	42.50	-8.71	100.00	
140	1.96	40.90	-8.29	100.00	
145	1.68	39.81	-8.00	100.00	
150	1.38	39.26	-7.85	100.00	
155	1.13	39.21	-7.83	100.00	
160	0.88	39.68	-7.96	100.00	
165	0.76	40.54	-8.20	100.00	
170	0.53	41.99	-8.58	100.00	
175	0.00	44.11	-9.11	100.00	
180	0.00	46.14	-9.60	100.00	
185	0.00	48.50	-10.00	100.00	

Comsearch Proprietary



Coordination Values		LINDON, UT			
Licensee Nan		HUGHES NETWORK SYSTEMS LIMITED			
Latitude (NAD		40° 19' 46.2" N			
Longitude (N/		111° 43' 36.8" W			
Ground Eleva		1410.5 m / 4627.6 ft			
Antenna Cent		7.0 m / 23.0 ft			
Antenna Mod		10.0 m / 32.8 ft			
Antenna Mod	e	Transmit 28.0	GHz		
Interference (Objectives: Long T				
	Short T			6	
Max Available	e RF Power	-41.8 (dBW/4 kHz)			
			Transm	nit 28.0 GHz	
	Horizon	Antenna	Horizon	Coordination	
Azimuth (°)	Elevation (°)	Discrimination (°)	Gain (dBi)	Distance (km)	
190	0.00	51.16	-10.00	100.00	
195	0.00	54.05	-10.00	100.00	
200	0.00	57.15	-10.00	100.00	
205	0.00	60.41	-10.00	100.00	
210	0.00	63.82	-10.00	100.00	
215	0.00	67.33	-10.00	100.00	
220	0.00	70.94	-10.00	100.00	
225	0.00	74.61	-10.00	100.00	
230	0.00	78.34	-10.00	100.00	
235	0.00	82.11	-10.00	100.00	
240	0.00	85.91	-10.00	100.00	
245	0.00	89.72	-10.00	100.00	
250	0.00	93.53	-10.00	100.00	
255	0.00	97.32	-10.00	100.00	
260	0.00	101.10	-10.00	100.00	
265	0.00	104.84	-10.00	100.00	
270	0.00	108.52	-10.00	100.00	
275	0.00	112.14	-10.00	100.00	
280	0.00	115.67	-10.00	100.00	
285	0.00	119.09	-10.00	100.00	
290	0.00	122.38	-10.00	100.00	
295	0.00	125.50	-10.00	100.00	
000					

128.43

131.12

133.53

135.61

137.30

138.57

139.37

139.88

139.67

138.98

138.17

137.40

300

305

310

315

320

325

330

335

340

345

350

355

0.00

0.00

0.00

0.00

0.00

0.00

0.00

0.22

0.23

0.27

0.70

1.74

-10.00

-10.00

-10.00

-10.00

-10.00

-10.00

-10.00

-10.00

-10.00

-10.00

-10.00

-10.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00



5. Contact Information

For questions or information regarding the 28 GHz Frequency Coordination Report, please contact:

Contact person:	Dennis Jimeno
Title:	Engineer III, Telecommunications
Company:	Comsearch
Address:	19700 Janelia Farm Blvd., Ashburn, VA 20147
Telephone:	703-726-5858
Fax:	703-726-5599
Email:	DJimeno@Comsearch.com
Web site:	www.comsearch.com

Ka-Band Earth Station – Lindon, UT Frequency Coordination Report 48 GHz



Prepared on Behalf of HUGHES NETWORK SYSTEMS LIMITED

November 5, 2020





Table of Contents

1.	Summary of Results	- 1 -
2.	48 GHz UMFUS Coordination	- 1 -
3.	Earth Station Coordination Data	- 2 -
4.	Contact Information	- 7 -



1. Summary of Results

On behalf of HUGHES NETWORK SYSTEMS LIMITED, Comsearch performed a coordination notice under Section 25.203(c) and Section 25.136(a)(4) of the FCC's rules for all existing and proposed terrestrial licenses within the coordination contours of their proposed Ka-Band earth station in Lindon, UT, which will transmit at 48 GHz¹. Prior-notification letters were sent to the licensees with the antenna update and a copy of the notification data is provided in section four of this report. The earth station coordination was finalized on November 5, 2020.

No objections were received from any of the incumbent 48 GHz licensees.

2. 48 GHz UMFUS Coordination

There were four 48 GHz UMFUS licensees identified within the coordination distance of the proposed earth station. The proposed earth station will operate on frequencies that overlap the UMFUS service band of 47.2 - 48.2 GHz.

Licensee	Authorized Geographic Area
DISH Network	Market-Based
Sprint	Market-Based
Union Telephone	Market-Based
Verizon	Market-Based

No objections were received from the UMFUS incumbents.

¹ The proposed earth station will operate in the 47.2 – 48.2 GHz portion of the Ka-Band.



3. Earth Station Coordination Data

This section presents the data pertinent to the proposed Ka-Band earth station in Lindon, UT. This data was circulated to all incumbent licensees in the shared 48 GHz frequency ranges.



Job Number:		200707COMSDJ02.48GHZ – Revision				
Administrative Info	rmation					
Status		NGINEER PROPOSAL				
Call Sign		170165				
Licensee Code		HUNESY				
Licensee Name		HUGHES NETWORK SYSTEMS LIMITED				
Site Information	LI	NDON, UT				
Venue Name						
Latitude (NAD 83)		40° 19' 46.2" N				
Longitude (NAD 83)	11 A	111° 43' 36.8" W				
Climate Zone						
Rain Zone	5	the service data taken				
Ground Elevation (AMSL)		1410.5 m / 4627.6 ft				
Link Information		(and free free free free free free free fre				
Satellite Type		eostationary				
Mode		TO - Transmit-Only				
Modulation		gital				
Satellite Arc		95.2° W to 95.2° West Longitude				
Azimuth Range		155.4° to 155.4°				
Corresponding Elevati		40.3° / 40.3°				
Antenna Centerline (AGL)		7.0 m / 23.0 ft				
Antenna Informatio	on	Transmit - FCC32				
Manufacturer		SED				
Model		10.0 meter				
Gain / Diameter		71.6 dBi / 10.0 m				
3-dB / 15-dB Beamwidth		0.08°/0.16°				
Max Available RF Power	(dBW/4 kHz)	-46.5				
	(dBW/MHz)	-22.5				
Maximum EIRP	(dBW/4 kHz)	25.1				
	(dBW/MHz)	49.1				
Interference Objectives:	Long Term	-151.0 dBW/4 kHz 20%				
Short Term		-128.0 dBW/4 kHz 0.0025%				
Frequency Informa	tion	Transmit 48.0 GHz				
Emission / Frequency Range (MHz)		455MG7W - 470MG7W /47200.0 - 48200.0				
Max Great Circle Coordination Distance Precipitation Scatter Contour Radius		100.0 km / 62.1 mi				
		100.0 km / 62.1 mi				



Coordinatic Licensee Nar Latitude (NAE Longitude (NA Ground Eleva Antenna Cen Antenna Mod	ne D 83) AD 83) ation (AMSL) terline (AGL)	LINDON, UT HUGHES NETWORH 40° 19' 46.2" N 111° 43' 36.8" W 1410.5 m / 4627.6 ft 7.0 m / 23.0 ft SED 10.0 meter	K SYSTEMS LI	MITED	
Antenna Mod	e Objectives: Long T Short T	Transmit 48.0 erm -151.0 dBW/4	kHz 20% kHz 0.0025%	6	
		Transmit 48.0 GHz			
	Horizon	Antenna	Horizon	Coordination	
Azimuth (°)	Elevation (°)	Discrimination (°)	Gain (dBi)	Distance (km)	
0	3.37	136.57	-10.00	100.00	_
5	6.08	135.93	-10.00	100.00	
10	7.50	133.74	-10.00	100.00	
15	8.39	130.81	-10.00	100.00	
20	5.88	125.93	-10.00	100.00	
25	7.31	122.89	-10.00	100.00	
30	7.36	119.05	-10.00	100.00	
35	7.23	115.06	-10.00	100.00	
40	7.77	111.17	-10.00	100.00	
45	8.58	107.22	-10.00	100.00	
50	10.02	103.23	-10.00	100.00	
55	10.20	98.96	-10.00	100.00	
60	7.88	94.53	-10.00	100.00	
65	7.33	90.31	-10.00	100.00	

86.17

82.07

78.08

74.28

70.50

66.87

63.29

59.67

56.24

52.95

49.87

47.05

44.52

42.39

40.77

39.71

39.16

39.13

39.63

40.50

41.96

44.11

46.14

48.50

Comsearch Proprietary

70

75

80

85

90

95

100

105

110

115

120

125

130

135

140

145

150

155

160

165

170

175

180

185

6.11

5.94

5.19

4.11

3.57

2.95

2.61

2.69

2.61

2.60

2.56

2.50

2.44

2.33

2.10

1.78

1.49

1.21

0.93

0.81

0.56

0.00

0.00

0.00

-10.00

-10.00

-10.00

-10.00

-10.00

-10.00

-10.00

-10.00

-10.00

-10.00

-10.00

-9.81

-9.21

-8.68

-8.26

-7.97

-7.82

-7.81

-7.95

-8.19

-8.57

-9.11

-9.60

-10.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00

100.00



Coordination Values	LINE	DON, UT	
Licensee Name	HUG	SHES NETWORK SYSTEMS LIMIT	ED
Latitude (NAD 83)		19' 46.2" N	
Longitude (NAD 83)	111° 43' 36.8" W		
Ground Elevation (AMSL)	1410	0.5 m / 4627.6 ft	
Antenna Centerline (AGL)	7.0 n	n / 23.0 ft	
Antenna Model	SED	10.0 meter	
Antenna Mode		Transmit 48.0 GHz	
Interference Objectives: Long Term		-151.0 dBW/4 kHz 20%	
Short Term		-128.0 dBW/4 kHz 0.0025%	
Max Available RF Power		-45.7 (dBW/4 kHz)	

		Transmit 48.0 GHz				
	Horizon	Antenna	Horizon	Coordination		
Azimuth (°)	Elevation (°)	Discrimination (°)	Gain (dBi)	Distance (km)		
190	0.00	51.16	-10.00	100.00		
195	0.00	54.05	-10.00	100.00		
200	0.00	57.15	-10.00	100.00		
205	0.00	60.41	-10.00	100.00		
210	0.00	63.82	-10.00	100.00		
215	0.00	67.33	-10.00	100.00		
220	0.00	70.94	-10.00	100.00		
225	0.00	74.61	-10.00	100.00		
230	0.00	78.34	-10.00	100.00		
235	0.00	82.11	-10.00	100.00		
240	0.00	85.91	-10.00	100.00		
245	0.00	89.72	-10.00	100.00		
250	0.00	93.53	-10.00	100.00		
255	0.00	97.32	-10.00	100.00		
260	0.00	101.10	-10.00	100.00		
265	0.00	104.84	-10.00	100.00		
270	0.00	108.52	-10.00	100.00		
275	0.00	112.14	-10.00	100.00		
280	0.00	115.67	-10.00	100.00		
285	0.00	119.09	-10.00	100.00		
290	0.00	122.38	-10.00	100.00		
295	0.00	125.50	-10.00	100.00		
300	0.00	128.43	-10.00	100.00		
305	0.00	131.12	-10.00	100.00		
310	0.00	133.53	-10.00	100.00		
315	0.00	135.61	-10.00	100.00		
320	0.00	137.30	-10.00	100.00		
325	0.00	138.57	-10.00	100.00		
330	0.00	139.37	-10.00	100.00		
335	0.23	139.89	-10.00	100.00		
340	0.24	139.68	-10.00	100.00		
345	0.27	138.98	-10.00	100.00		
350	0.70	138.17	-10.00	100.00		
355	1.75	137.41	-10.00	100.00		



4. Contact Information

For questions or information regarding the 48 GHz Frequency Coordination Report, please contact:

Contact person:	Dennis Jimeno
Title:	Engineer III, Telecommunications
Company:	Comsearch
Address:	19700 Janelia Farm Blvd., Ashburn, VA 20147
Telephone:	703-726-5858
Fax:	703-726-5599
Email:	DJimeno@Comsearch.com
Web site:	www.comsearch.com