

FREQUENCY COORDINATION AND INTERFERENCE ANALYSIS REPORT

Prepared for
LAC COURTE OREILLES OJIBWA PBC (WOJB)
HAYWARD, WI
Satellite Earth Station

Prepared By:
COMSEARCH
19700 Janelia Farm Boulevard
Ashburn, VA 20147
August 29, 2003

TABLE OF CONTENTS

1. CONCLUSIONS	3
2. SUMMARY OF RESULTS	4
3. SUPPLEMENTAL SHOWING	5
4. EARTH STATION COORDINATION DATA	6
5. CERTIFICATION	10

1. CONCLUSIONS

An interference study considering all existing, proposed and prior coordinated microwave facilities within the coordination contours of the proposed earth station demonstrates that this site will operate satisfactorily with the common carrier microwave environment. Further, there will be no restrictions of its operation due to interference considerations.

2. SUMMARY OF RESULTS

A number of great circle interference cases were identified during the interference study of the proposed earth station. Each of the cases, which exceeded the interference objective on a line-of-sight basis, was profiled and the propagation losses estimated using NBS TN101 (Revised) techniques. The losses were found to be sufficient to reduce the signal levels to acceptable magnitudes in every case.

The following companies reported potential great circle interference conflicts that did not meet the objectives on a line-of-sight basis. When over-the-horizon losses are considered on the interfering paths, sufficient blockage exists to negate harmful interference from occurring with the proposed receive-only earth station.

Company

AT&T Communications of the Midwest

No Other Carriers Reported Potential Interference Cases.

3. SUPPLEMENTAL SHOWING

Pursuant to Part 25.203(c) of the FCC Rules and Regulations, the satellite earth station proposed in this application was coordinated by Comsearch using computer techniques and in accordance with Part 25 of the FCC Rules and Regulations.

Coordination data for this earth station was sent to the below listed carriers with a letter dated 08/27/2003.

Company

AT&T COMMUNICATIONS OF MICHIGAN
AT&T COMMUNICATIONS OF THE MIDWEST INC
AT&T COMMUNICATIONS OF WISCONSIN, INC
AT&T CORP
BELL CANADA - ONTARIO REGION
MANITOBA TELEPHONE COMPANY

4. EARTH STATION COORDINATION DATA

This section presents the data pertinent to frequency coordination of the proposed earth station that was circulated to all carriers within its coordination contours.

SATELLITE EARTH STATION
 FREQUENCY COORDINATION DATA
 08/25/2003

Company	LAC COURTE OREILLES OJIBWA PBC (WOJB)
Owner code	WOJB
Earth Station Name, State	HAYWARD, WI
Latitude (DMS) (NAD83)	45 56 35.5 N
Longitude (DMS) (NAD83)	91 21 39.5 W
Ground Elevation AMSL (Ft/m)	1345.47 / 410.08
Antenna Centerline AGL (Ft/m)	9.00 / 2.74
Receive Antenna Type:	C40381 COMTECH ANTENNA SY
	3.8 METER PF
4.0 GHz Gain (dBi) / Diameter (m)	42.9 / 3.8
3 dB / 15 dB Half Beamwidth	0.70 / 1.40
Operating Mode	RECEIVE ONLY
Modulation	ANALOG & DIGITAL
Emission / Receive Band (MHz)	30K0F1D - 10M3G7W / 3700.0000 - 4200.0000
Max permissible Interference Power	
4.0 GHz, 20% (dBW/1 MHz)	-156.0
4.0 GHz, 0.0100% (dBW/1 MHz)	-146.0
Range of Satellite Arc (Geostationary)	
Degrees Longitude	60.0 W / 143.0 W
Azimuth Range (Min/Max)	139.7 / 240.4
Corresponding Elevation Angles	28.8 / 17.3
Radio Climate	A
Rain Zone	2
Max Great Circle Coordination Distance (Mi/Km)	
4.0 GHz	224.6 / 361.5
Precipitation Scatter Contour Radius (Mi/Km)	
4.0 GHz	317.7 / 511.3

Table of Earth Station Coordination Values
08/25/2003

Earth Station Name HAYWARD WI
 Owner LAC COURTE OREILLES OJIBWA PBC
 Latitude (DMS) (NAD83) 45 56 35.5 N
 Longitude (DMS) (NAD83) 91 21 39.5 W
 Ground Elevation (Ft/m) 1345.47 / 410.08 AMSL
 Antenna Centerline (Ft/m) 9.00 / 2.74 AGL
 Antenna Model COMTECH ANTENNA SY 3.8 METER PF
 Objectives: Receive -156.0 (dBW /1 MHz)

Azimuth (Deg)	Horizon Elevation Angle (Deg)	Antenna Disc. Angle (Deg)	Antenna Gain (dBi)	4.0 GHz Coordination Distance (Km)
0	0.00	118.18	-9.37	289.3
5	0.00	122.87	-10.67	281.0
10	0.00	124.04	-10.91	279.5
15	0.00	119.92	-10.07	284.8
20	0.00	115.73	-8.39	295.7
25	0.00	111.48	-8.10	297.6
30	0.00	107.18	-8.10	297.6
35	0.00	102.85	-8.10	297.6
40	0.00	98.49	-8.10	297.6
45	0.00	94.12	-8.10	297.6
50	0.00	89.74	-8.10	297.6
55	0.00	85.36	-8.10	297.6
60	0.00	80.99	-8.10	297.6
65	0.00	76.63	-8.10	297.6
70	0.00	72.30	-8.10	297.6
75	0.48	67.91	-8.10	263.5
80	0.40	63.66	-8.10	273.2
85	0.57	59.40	-8.10	256.4
90	0.44	55.31	-8.10	267.5
95	0.68	51.19	-8.10	249.5
100	0.72	47.26	-8.10	246.9
105	0.55	43.60	-8.10	257.5
110	0.51	40.11	-7.15	266.5
115	0.53	36.86	-6.47	269.2
120	0.57	33.96	-6.10	268.9
125	0.58	31.55	-6.10	268.6
130	0.44	29.85	-6.04	281.1
135	0.36	28.81	-5.62	293.9
140	0.35	28.47	-5.49	296.6
145	0.00	29.25	-5.80	314.0
150	0.45	30.03	-6.10	280.2
155	0.30	31.98	-6.10	298.1
160	0.33	33.65	-6.10	294.8
165	0.43	34.91	-6.10	282.0
170	0.48	35.84	-6.27	274.8
175	0.51	36.42	-6.38	271.2
180	0.49	36.65	-6.43	273.0


Table of Earth Station Coordination Values
08/25/2003

Earth Station Name HAYWARD WI
 Owner LAC COURTE OREILLES OJIBWA PBC
 Latitude (DMS) (NAD83) 45 56 35.5 N
 Longitude (DMS) (NAD83) 91 21 39.5 W
 Ground Elevation (Ft/m) 1345.47 / 410.08 AMSL
 Antenna Centerline (Ft/m) 9.00 / 2.74 AGL
 Antenna Model COMTECH ANTENNA SY 3.8 METER PF
 Objectives: Receive -156.0 (dBW /1 MHz)

Azimuth (Deg)	Horizon Elevation Angle (Deg)	Antenna Disc. Angle (Deg)	Antenna Gain (dBi)	4.0 GHz Coordination Distance (Km)
185	0.39	36.54	-6.41	285.3
190	0.00	36.32	-6.36	309.4
195	0.00	35.32	-6.16	310.8
200	0.00	33.95	-6.10	311.3
205	0.00	32.26	-6.10	311.3
210	0.00	30.26	-6.10	311.3
215	0.00	28.00	-5.30	317.5
220	0.00	25.51	-4.30	324.6
225	0.00	22.82	-3.23	332.4
230	0.00	20.05	-2.12	340.6
235	0.00	18.05	-0.15	355.4
240	0.00	17.27	0.63	361.4
245	0.00	17.86	0.04	356.9
250	0.00	19.70	-1.80	343.0
255	0.00	22.49	-3.09	333.4
260	0.00	25.92	-4.47	323.4
265	0.00	29.77	-6.01	311.9
270	0.00	33.90	-6.10	311.3
275	0.00	38.21	-6.74	306.8
280	0.00	42.65	-8.10	297.6
285	0.00	47.19	-8.10	297.6
290	0.00	51.79	-8.10	297.6
295	0.00	56.45	-8.10	297.6
300	0.00	61.13	-8.10	297.6
305	0.00	65.85	-8.10	297.6
310	0.00	70.59	-8.10	297.6
315	0.28	75.32	-8.10	287.6
320	0.00	80.11	-8.10	297.6
325	0.23	84.87	-8.10	294.0
330	0.32	89.65	-8.10	282.0
335	0.00	94.42	-8.10	297.6
340	0.00	99.20	-8.10	297.6
345	0.00	103.96	-8.10	297.6
350	0.00	108.72	-8.10	297.6
355	0.00	113.46	-8.10	297.6

5. CERTIFICATION

I HEREBY CERTIFY THAT I AM THE TECHNICALLY QUALIFIED PERSON RESPONSIBLE FOR THE PREPARATION OF THE FREQUENCY COORDINATION DATA CONTAINED IN THIS APPLICATION, THAT I AM FAMILIAR WITH PARTS 101 AND 25 OF THE FCC RULES AND REGULATIONS, THAT I HAVE EITHER PREPARED OR REVIEWED THE FREQUENCY COORDINATION DATA SUBMITTED WITH THIS APPLICATION, AND THAT IT IS COMPLETE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

BY: 

GARY K. EDWARDS
SENIOR MANAGER
COMSEARCH
19700 Janelia Farm Boulevard
Ashburn, VA 20147

DATED: August 29, 2003