# FREQUENCY COORDINATION AND INTERFERENCE ANALYSIS REPORT

Prepared for
PACIFICA FOUNDATION
BERKELEY, CA
Satellite Earth Station

Prepared By: COMSEARCH 19700 Janelia Farm Boulevard Ashburn, VA 20147 October 23, 2003

## TABLE OF CONTENTS

1. CONCLUSIONS	3
2. SUMMARY OF RESULTS	
3. SUPPLEMENTAL SHOWING	
4. EARTH STATION COORDINATION DATA	
5. CERTIFICATION	

### 1. CONCLUSIONS

An interference study considering all existing, proposed and prior coordinated microwave facilities within the coordination contours of the proposed earth station demonstrates that this site will operate satisfactorily with the common carrier microwave environment. Further, there will be no restrictions of its operation due to interference considerations.

#### 2. SUMMARY OF RESULTS

A number of great circle interference cases were identified during the interference study of the proposed earth station. Each of the cases, which exceeded the interference objective on a line-of-sight basis, was profiled and the propagation losses estimated using NBS TN101 (Revised) techniques. The losses were found to be sufficient to reduce the signal levels to acceptable magnitudes in every case.

The following companies reported potential great circle interference conflicts that did not meet the objectives on a line-of-sight basis. When over-the-horizon losses are considered on the interfering paths, sufficient blockage exists to negate harmful interference from occurring with the proposed receive-only earth station.

No Carriers Reported Potential Interference Cases.

#### 3. SUPPLEMENTAL SHOWING

Pursuant to Part 25.203(c) of the FCC Rules and Regulations, the satellite earth station proposed in this application was coordinated by Comsearch using computer techniques and in accordance with Part 25 of the FCC Rules and Regulations.

Coordination data for this earth station was sent to the below listed carriers with a letter dated 09/29/2003.

#### Company

AT&T COMMUNICATIONS OF CALIFORNIA, INC. American Towers, Inc. CAL ONE CELLULAR LP MCI NETWORK SERVICES INC PACIFIC BELL SACRAMENTO REGION

4. EARTH STATION COORDINATION DATA									
This section presents the data pertinent to frequency coordination of the proposed earth station that was circulated to all carriers within its coordination contours.									

Date: 09/29/2003

Job Number:

**Administrative Information** 

Status ENGINEER PROPOSAL

Call Sign

Licensee Code KPFA

Licensee Name PACIFICA FOUNDATION

Site Information BERKELEY, CA

Venue Name

Latitude (NAD 83) 37° 52′ 19.7″ N Longitude (NAD 83) 122° 16′ 21.8″ W

Climate Zone B Rain Zone 4

Ground Elevation (AMSL) 53.20 m / 174.6 ft

**Link Information** 

Satellite Type Geostationary
Mode RO - Receive-Only
Modulation Analog and Digital

Satellite Arc 60° W to 143° West Longitude

Azimuth Range 107.9° to 211.6° Corresponding Elevation Angles 13.1° / 41.0° Antenna Centerline (AGL) 11.89 m / 39.0 ft

Antenna Information Receive - C40381

Manufacturer COMTECH ANTENNA SYSTEMS

 Model
 3.8 METER PF

 Gain / Diameter
 42.9 dBi / 3.8 m

 3-dB / 15-dB Beamwidth
 1.4° / 2.8°

Interference Objectives: Long Term -156.0 dBW/MHz 20%

Short Term -146.0 dBW/MHz 0.01%

Frequency Information Receive 4.0 GHz

Emission / Frequency Range (MHz) 30K0F1D - 10M3G7W / 3700.0 - 4200.0

Max Great Circle Coordination Distance 457.2 km / 284.1 mi Precipitation Scatter Contour Radius 381.2 km / 236.8 mi **Coordination Values** 

BERKELEY, CA

Licensee Name Latitude (NAD 83) Longitude (NAD 83) Ground Elevation (AMSL) PACIFICA FOUNDATION 37° 52' 19.7" N 122° 16' 21.8" W 53.20 m / 174.6 ft 11.89 m / 39.0 ft

Antenna Centerline (AGL) Antenna Model

COMTECH ANTENNA SYSTEMS 3.8 METER PF

Antenna Mode

Receive 4.0 GHz

Interference Objectives: Long Term Short Term

-156.0 dBW/MHz 20% -146.0 dBW/MHz 0.01% Receive 4.0 GHz

		Receive 4.0 GHz				
	Horizon	Antenna	Horizon	Coordination		
Azimuth (°)	Elevation (°)	Discrimination (°)	Gain (dBi)	Distance (km)		
0	2.71	107.58	-8.10	184.33		
5	3.22	102.69	-8.10	168.26		
10	3.77	97.78	-8.10	153.55		
15	4.28	92.85	-8.10	145.56		
20	4.48	87.91	-8.10	143.60		
25	5.39	82.95	-8.10	134.13		
30	5.51	77.99	-8.10	132.72		
35	5.59	73.04	-8.10	131.87		
40	5.73	68.08	-8.10	130.35		
45	6.26	63.09	-8.10	126.71		
50	6.51	58.12	-8.10	126.06		
55	6.81	53.14	-8.10	125.28		
60	7.26	48.15	-8.10	124.13		
65	6.88	43.25	-8.10	125.10		
70	6.91	38.31	-6.76	129.70		
75	6.48	33.47	-6.10	133.37		
80	6.10	28.68	<b>-</b> 5.57	136.51		
85	5.67	23.99	-3.70	148.81		
90	4.92	19.60	-1.70	168.85		
95	5.20	15.07	2.83	189.10		
100	5.36	11.02	8.87	223.65		
105	4.18	9.35	10.55	256.88		
110	3.81	9.50	10.40	265.11		
115	2.93	12.37	6.53	273.10		
120	2.76	15.86	2.04	248.55		
125	2.25	19.80	-1.90	243.17		
130	1.48	23.82	-3.63	271.56		
135	1.46	27.21	-4.98	262.29		
140	1.07	30.69	<b>−</b> 6.10	278.10		
145	0.42	34.19	<b>−</b> 6.10	385.02		
150	0.00	37.30	-6.56	457.23		
155	0.00	39.80	-7.06	450.37		
160	0.00	41.96	-7.89	439.31		
165	0.00	43.72	-8.59	430.08		
170	0.00	45.03	-9.11	423.44		
175	0.00	45.84	-9.27	421.39		
180	0.00	46.11	-9.32	420.70		
185	0.00	45.84	-9.27	421.39		

**Coordination Values** 

**BERKELEY, CA** 

Licensee Name Latitude (NAD 83) Longitude (NAD 83) Ground Elevation (AMSL) Antenna Centerline (AGL) PACIFICA FOUNDATION 37° 52' 19.7" N 122° 16' 21.8" W 53.20 m / 174.6 ft 11.89 m / 39.0 ft

Antenna Model Antenna Mode COMTECH ANTENNA SYSTEMS 3.8 METER PF

enna Mode Receive 4.0 GHz

Interference Objectives: Long Term -156.0 dBW/MHz 20% Short Term -146.0 dBW/MHz 0.01%

		Antenna	Receive 4	4.0 GHz	
	Horizon	Discrimination	Horizon	Coordination	
Azimuth (°)	Elevation (°)	(°)	Gain (dBi)	Distance (km)	
190	0.00	45.03	-9.11	423.44	
195	0.00	43.72	-8.59	430.09	
200	0.00	42.37	-8.05	437.14	
205	0.00	41.48	-7.69	441.90	
210	0.00	41.06	-7.53	444.11	
215	0.00	41.15	-7.56	443.65	
220	0.00	41.73	-7.79	440.55	
225	0.00	42.79	-8.10	436.48	
230	0.00	44.28	-8.10	436.48	
235	0.00	46.17	-8.10	436.48	
240	0.00	48.41	-8.10	436.48	
245	0.00	50.95	-8.10	436.48	
250	0.00	53.74	-8.10	436.48	
255	0.00	56.74	-8.10	436.48	
260	0.00	59.92	-8.10	436.48	
265	0.00	63.24	-8.10	436.48	
270	0.00	66.69	-8.10	436.48	
275	0.00	70.23	-8.10	436.48	
280	0.00	73.84	-8.10	436.48	
285	0.00	77.52	-8.10	436.48	
290	0.00	81.24	-8.10	436.48	
295	0.00	84.99	-8.10	436.48	
300	0.00	88.76	-8.10	436.48	
305	0.00	92.53	-8.10	436.48	
310	0.00	96.29	-8.10	436.48	
315	0.00	100.03	-8.10	436.48	
320	0.00	103.74	-8.10	436.48	
325	0.00	107.40	-8.10	436.48	
330	0.00	110.99	-8.10	436.48	
335	0.76	114.80	-8.10	299.11	
340	1.44	118.56	-9.53	231.64	
345	2.12	122.21	-10.54	191.89	
350	2.04	117.33	-9.03	204.11	
355	2.13	112.45	-8.10	206.06	

#### 5. CERTIFICATION

I HEREBY CERTIFY THAT I AM THE TECHNICALLY QUALIFIED PERSON RESPONSIBLE FOR THE PREPARATION OF THE FREQUENCY COORDINATION DATA CONTAINED IN THIS APPLICATION, THAT I AM FAMILIAR WITH PARTS 101 AND 25 OF THE FCC RULES AND REGULATIONS, THAT I HAVE EITHER PREPARED OR REVIEWED THE FREQUENCY COORDINATION DATA SUBMITTED WITH THIS APPLICATION, AND THAT IT IS COMPLETE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

Rocio Palomo Engineer II COMSEARCH 19700 Janelia Farm Boulevard

Ashburn, VA 20147

DATED: October 23, 2003