

# FREQUENCY COORDINATION AND INTERFERENCE ANALYSIS REPORT

Prepared for

**PIONEER LONG DISTANCE INC.  
KINGFISHER EAST, OKLAHOMA**

**Satellite Earth Station**

Prepared By:  
COMSEARCH

19700 JANELIA FARM BOULEVARD  
ASHBURN, VIRGINIA 20147

APRIL 6, 2004

## TABLE OF CONTENTS

1. CONCLUSIONS .....	3
2. SUMMARY OF RESULTS .....	4
3. SUPPLEMENTAL SHOWING .....	5
4. EARTH STATION COORDINATION DATA .....	6
5. CERTIFICATION .....	10

## **1. CONCLUSIONS**

An interference study considering *all existing, proposed and prior coordinated microwave facilities within the coordination contours of the proposed earth station demonstrates that this site will operate satisfactorily with the common carrier microwave environment. Further, there will be no restrictions of its operation due to interference considerations.*

## 2. SUMMARY OF RESULTS

A number of great circle interference cases were identified during the interference study of the proposed earth station. Each of the cases, which exceeded the interference objective on a line-of-sight basis, was profiled and the propagation losses estimated using NBS TN101 (Revised) techniques. The losses were found to be sufficient to reduce the signal levels to acceptable magnitudes in every case.

The following companies reported potential great circle interference conflicts that did not meet the objectives on a line-of-sight basis. When over-the-horizon losses are considered on the interfering paths, sufficient blockage exists to negate harmful interference from occurring with the proposed receive-only earth station.

Company

NONE

No Carriers Reported Potential Interference Cases.

### 3. SUPPLEMENTAL SHOWING

Pursuant to Part 25.203(c) of the FCC Rules and Regulations, the satellite earth station proposed in this application was coordinated by Comsearch using computer techniques and in accordance with Part 25 of the FCC Rules and Regulations.

Coordination data for this earth station was sent to the below listed carriers with a letter dated February 29, 2004.

Company

Comsearch

## **4. EARTH STATION COORDINATION DATA**

This section presents the data pertinent to frequency coordination of the proposed earth station that was circulated to all carriers within its coordination contours.

Date: 02/29/2004  
Job Number:

---

**Administrative Information**

Status ENGINEER PROPOSAL  
Call Sign  
Licensee Code PIOLON  
Licensee Name Pioneer Long Distance Inc.

---

**Site Information KINGFISHER EAST, OKLAHOMA**

Venue Name  
Latitude (NAD 83) 35° 52' 4.5" N  
Longitude (NAD 83) 97° 54' 15.2" W  
Climate Zone A  
Rain Zone 2  
Ground Elevation (AMSL) 342.29 m / 1123.0 ft

---

**Link Information**

Satellite Type Geostationary  
Mode RO - Receive-Only  
Modulation Analog and Digital  
Satellite Arc 60° W to 143° West Longitude  
Azimuth Range 127.0° to 239.7°  
Corresponding Elevation Angles 32.4° / 27.2°  
Antenna Centerline (AGL) 5.49 m / 18.0 ft

---

**Antenna Information**

**Receive - T40503**  
ANTENNA TECH CORP  
SIMULSAT 5M  
44.0 dBi / 5.0 m  
0.8° / 1.6°

Interference Objectives: Long Term -156.0 dBW/MHz 20%  
Short Term -146.0 dBW/MHz 0.01%

---

**Frequency Information**

**Receive 4.0 GHz**  
36M0F8F / 3700.0 - 4200.0  
36M0G7F / 3700.0 - 4200.0

Max Great Circle Coordination Distance 327.8 km / 203.7 mi  
Precipitation Scatter Contour Radius 492.5 km / 306.0 mi

---

**Coordination Values**

Licensee Name KINGFISHER EAST, OK  
Pioneer Long Distance Inc.

Latitude (NAD 83) 35° 52' 4.5" N  
 Longitude (NAD 83) 97° 54' 15.2" W  
 Ground Elevation (AMSL) 342.29 m / 1123.0 ft  
 Antenna Centerline (AGL) 5.49 m / 18.0 ft  
 Antenna Model ANTENNA TECH CORP SIMULSAT 5M  
 Antenna Mode Receive 4.0 GHz  
 Interference Objectives: Long Term -156.0 dBW/MHz 20%  
 Short Term -146.0 dBW/MHz 0.01%

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 4.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)
0	0.00	116.66	-10.00	285.28
5	0.00	116.55	-10.00	285.28
10	0.00	112.51	-10.00	285.28
15	0.00	108.41	-10.00	285.28
20	0.00	104.26	-10.00	285.28
25	0.00	100.08	-10.00	285.28
30	0.00	95.88	-10.00	285.28
35	0.00	91.66	-10.00	285.28
40	0.00	87.44	-10.00	285.28
45	0.00	83.22	-10.00	285.28
50	0.00	79.02	-10.00	285.28
55	0.00	74.85	-10.00	285.28
60	0.00	70.71	-10.00	285.28
65	0.00	66.62	-10.00	285.28
70	0.00	62.60	-10.00	285.28
75	0.00	58.66	-10.00	285.28
80	0.00	54.82	-10.00	285.28
85	0.00	51.12	-10.00	285.28
90	0.00	47.58	-9.52	288.37
95	0.00	44.26	-8.85	292.69
100	0.00	41.20	-8.24	296.72
105	0.00	38.47	-7.69	300.37
110	0.00	36.15	-7.23	303.51
115	0.00	34.32	-6.73	306.93
120	0.00	33.07	-6.23	310.40
125	0.00	32.47	-5.99	312.72
130	0.00	32.54	-6.02	311.89
135	0.00	33.29	-6.32	309.80
140	0.00	34.67	-6.87	305.99
145	0.00	36.61	-7.32	302.89
150	0.00	39.02	-7.80	299.63
155	0.00	41.64	-8.33	296.13
160	0.00	43.93	-8.79	293.11
165	0.00	45.81	-9.16	290.66
170	0.00	47.21	-9.44	288.85
175	0.00	48.08	-9.62	287.74
180	0.00	48.37	-9.67	287.37
185	0.00	48.07	-9.61	287.74




<b>Coordination Values</b>	<b>KINGFISHER EAST, OK</b>		
Licensee Name	Pioneer Long Distance Inc.		
Latitude (NAD 83)	35° 52' 4.5" N		
Longitude (NAD 83)	97° 54' 15.2" W		
Ground Elevation (AMSL)	342.29 m / 1123.0 ft		
Antenna Centerline (AGL)	5.49 m / 18.0 ft		
Antenna Model	ANTENNA TECH CORP SIMULSAT 5M		
Antenna Mode	Receive 4.0 GHz		
Interference Objectives: Long Term	-156.0 dBW/MHz	20%	
Short Term	-146.0 dBW/MHz	0.01%	

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 4.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)
190	0.00	47.21	-9.44	288.85
195	0.00	45.81	-9.16	290.67
200	0.00	43.93	-8.79	293.11
205	0.00	41.64	-8.33	296.13
210	0.00	39.00	-7.80	299.66
215	0.00	36.07	-7.21	303.62
220	0.00	33.12	-6.25	310.28
225	0.00	30.62	-5.25	317.91
230	0.00	28.72	-4.49	323.33
235	0.00	27.54	-4.01	326.74
240	0.00	27.16	-3.87	327.82
245	0.00	27.63	-4.05	326.46
250	0.00	28.90	-4.56	322.81
255	0.00	30.88	-5.35	317.19
260	0.00	33.43	-6.37	309.40
265	0.00	36.44	-7.29	303.12
270	0.00	39.80	-7.96	298.59
275	0.00	43.43	-8.69	293.78
280	0.00	47.26	-9.45	288.79
285	0.00	51.25	-10.00	285.28
290	0.00	55.35	-10.00	285.28
295	0.00	59.56	-10.00	285.28
300	0.00	63.83	-10.00	285.28
305	0.00	68.16	-10.00	285.28
310	0.00	72.53	-10.00	285.28
315	0.00	76.94	-10.00	285.28
320	0.00	81.37	-10.00	285.28
325	0.00	85.81	-10.00	285.28
330	0.00	90.25	-10.00	285.28
335	0.00	94.70	-10.00	285.28
340	0.00	99.14	-10.00	285.28
345	0.00	103.57	-10.00	285.28
350	0.00	107.97	-10.00	285.28
355	0.00	112.34	-10.00	285.28

## 5. CERTIFICATION

I HEREBY CERTIFY THAT I AM THE TECHNICALLY QUALIFIED PERSON RESPONSIBLE FOR THE PREPARATION OF THE FREQUENCY COORDINATION DATA CONTAINED IN THIS APPLICATION, THAT I AM FAMILIAR WITH PARTS 101 AND 25 OF THE FCC RULES AND REGULATIONS, THAT I HAVE EITHER PREPARED OR REVIEWED THE FREQUENCY COORDINATION DATA SUBMITTED WITH THIS APPLICATION, AND THAT IT IS COMPLETE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.



JEFFREY E. COWLES  
PRINCIPAL FREQUENCY PLANNER  
COMSEARCH  
19700 JANELIA FARM BLVD.  
ASHBURN, VA. 20147

DATED: APRIL 6, 2004