

FREQUENCY COORDINATION AND INTERFERENCE ANALYSIS REPORT

Prepared for

**Fox Broadcasting Company
Alpena, Michigan**

Satellite Earth Station

Prepared By:
COMSEARCH

19700 Janelia Farm Boulevard
Ashburn, Virginia 20147
December 1, 2010

TABLE OF CONTENTS

1. CONCLUSIONS.....	3
2. SUMMARY OF RESULTS.....	4
3. SUPPLEMENTAL SHOWING	5
4. EARTH STATION COORDINATION DATA	6
5. CERTIFICATION	10

1. CONCLUSIONS

An interference study considering all existing, proposed and prior coordinated microwave facilities within the coordination contours of the proposed earth station demonstrates that this site will operate satisfactorily with the common carrier microwave environment. Further, there will be no restrictions of its operation due to interference considerations.

2. SUMMARY OF RESULTS

A number of great circle interference cases were identified during the interference study of the proposed earth station. Each of the cases, which exceeded the interference objective on a line-of-sight basis, was profiled and the propagation losses estimated using NBS TN101 (Revised) techniques. The losses were found to be sufficient to reduce the signal levels to acceptable magnitudes in every case.

The following companies reported potential great circle interference conflicts that did not meet the objectives on a line-of-sight basis. When over-the-horizon losses are considered on the interfering paths, sufficient blockage exists to negate harmful interference from occurring with the proposed receive-only earth station.

Company

None

No carriers reported potential interference cases.

3. SUPPLEMENTAL SHOWING

Pursuant to Part 25.203(c) of the FCC Rules and Regulations, the satellite earth station proposed in this application was coordinated by Comsearch using computer techniques and in accordance with Part 25 of the FCC Rules and Regulations.

Coordination data for this earth station was sent to the below listed carriers with a letter dated October 31, 2010.

Company

AT&T COMMUNICATIONS OF MICHIGAN

4. EARTH STATION COORDINATION DATA

This section presents the data pertinent to frequency coordination of the proposed earth station that was circulated to all carriers within its coordination contours.

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Date: 12/01/2010
Job Number: 101031COMSJC01

Administrative Information

Status ENGINEER PROPOSAL
Call Sign
Licensee Code FOXBRO
Licensee Name Fox Broadcasting Company

Site Information ALPENA, MICHIGAN

Venue Name
Latitude (NAD 83) 45° 3' 53.4" N
Longitude (NAD 83) 83° 28' 22.2" W
Climate Zone A
Rain Zone 2
Ground Elevation (AMSL) 193.24 m / 634.0 ft

Link Information

Satellite Type Geostationary
Mode RO - Receive-Only
Modulation Analog and Digital
Satellite Arc 60° W to 143° West Longitude
Azimuth Range 148.5° to 247.4°
Corresponding Elevation Angles 33.1° / 12.5°
Antenna Centerline (AGL) 3.05 m / 10.0 ft

Antenna Information

Receive

Manufacturer Andrew Corporation
Model 4.5 Meter
Gain / Diameter 43.8 dBi / 4.5 m
3-dB / 15-dB Beamwidth 1.10° / 2.10°

Interference Objectives: Long Term -156.0 dBW/MHz 20%
Short Term -146.0 dBW/MHz 0.01%

Frequency Information

Receive 4.0 GHz

Emission / Frequency Range (MHz)
36M0F8W / 3700.0 - 4200.0
36M0G7W / 3700.0 - 4200.0

Max Great Circle Coordination Distance 352.6 km / 219.1 mi
Precipitation Scatter Contour Radius 528.5 km / 328.4 mi

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Coordination Values

ALPENA, MI

Licensee Name Fox Broadcasting Company
Latitude (NAD 83) 45° 3' 53.4" N
Longitude (NAD 83) 83° 28' 22.2" W
Ground Elevation (AMSL) 193.24 m / 634.0 ft
Antenna Centerline (AGL) 3.05 m / 10.0 ft
Antenna Model Andrew Corporation 4.5 Meter
Antenna Mode Receive 4.0 GHz
Interference Objectives: Long Term -156.0 dBW/MHz 20%
Short Term -146.0 dBW/MHz 0.01%

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 4.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)
0	0.00	112.05	-10.00	285.28
5	0.00	116.91	-10.00	285.28
10	0.00	121.75	-10.00	285.28
15	0.00	125.20	-10.00	285.28
20	0.00	121.41	-10.00	285.28
25	0.00	117.52	-10.00	285.28
30	0.00	113.54	-10.00	285.28
35	0.00	109.49	-10.00	285.28
40	0.00	105.40	-10.00	285.28
45	0.00	101.26	-10.00	285.28
50	0.00	97.09	-10.00	285.28
55	0.00	92.91	-10.00	285.28
60	0.00	88.72	-10.00	285.28
65	0.00	84.54	-10.00	285.28
70	0.00	80.37	-10.00	285.28
75	0.00	76.22	-10.00	285.28
80	0.00	72.10	-10.00	285.28
85	0.00	68.03	-10.00	285.28
90	0.00	64.02	-10.00	285.28
95	0.00	60.10	-10.00	285.28
100	0.00	56.27	-10.00	285.28
105	0.00	52.56	-10.00	285.28
110	0.00	49.02	-10.00	285.28
115	0.00	45.67	-9.49	288.53
120	0.00	42.58	-8.73	293.49
125	0.00	39.79	-8.00	298.35
130	0.00	37.39	-7.32	302.91
135	0.00	35.45	-6.74	306.86
140	0.00	34.05	-6.30	309.89
145	0.00	33.26	-6.05	311.65
150	0.00	33.13	-6.01	311.95
155	0.00	33.67	-6.18	310.74
160	0.00	34.83	-6.55	308.17
165	0.00	36.23	-6.98	305.24
170	0.00	37.26	-7.28	303.16
175	0.00	37.89	-7.46	301.93
180	0.00	38.10	-7.52	301.52
185	0.00	37.89	-7.46	301.93

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Coordination Values

ALPENA, MI

Licensee Name Fox Broadcasting Company
Latitude (NAD 83) 45° 3' 53.4" N
Longitude (NAD 83) 83° 28' 22.2" W
Ground Elevation (AMSL) 193.24 m / 634.0 ft
Antenna Centerline (AGL) 3.05 m / 10.0 ft
Antenna Model Andrew Corporation 4.5 Meter
Antenna Mode Receive 4.0 GHz
Interference Objectives: Long Term -156.0 dBW/MHz 20%
Short Term -146.0 dBW/MHz 0.01%

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 4.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)
190	0.00	37.26	-7.28	303.16
195	0.00	36.23	-6.98	305.24
200	0.00	34.83	-6.55	308.18
205	0.00	33.08	-5.99	312.69
210	0.00	31.04	-5.30	317.57
215	0.00	28.72	-4.46	323.57
220	0.29	25.93	-3.35	319.22
225	0.41	23.09	-2.09	312.76
230	0.48	20.14	-0.60	316.20
235	0.51	17.06	1.20	326.54
240	0.57	14.00	3.34	339.06
245	0.57	12.16	4.87	351.56
250	0.55	12.23	4.81	352.57
255	0.56	14.13	3.24	339.00
260	0.48	17.36	1.01	328.41
265	0.45	21.23	-1.17	314.76
270	0.44	25.48	-3.16	301.65
275	0.50	29.92	-4.90	282.31
280	0.40	34.55	-6.46	282.78
285	0.29	39.27	-7.85	288.14
290	0.00	44.07	-9.10	291.04
295	0.30	48.79	-10.00	273.32
300	0.24	53.61	-10.00	280.13
305	0.23	58.44	-10.00	280.86
310	0.25	63.29	-10.00	279.29
315	0.23	68.15	-10.00	282.01
320	0.00	73.04	-10.00	285.28
325	0.00	77.91	-10.00	285.28
330	0.00	82.79	-10.00	285.28
335	0.00	87.67	-10.00	285.28
340	0.00	92.55	-10.00	285.28
345	0.00	97.43	-10.00	285.28
350	0.00	102.31	-10.00	285.28
355	0.00	107.19	-10.00	285.28

5. CERTIFICATION

I HEREBY CERTIFY THAT I AM THE TECHNICALLY QUALIFIED PERSON RESPONSIBLE FOR THE PREPARATION OF THE FREQUENCY COORDINATION DATA CONTAINED IN THIS APPLICATION, THAT I AM FAMILIAR WITH PARTS 101 AND 25 OF THE FCC RULES AND REGULATIONS, THAT I HAVE EITHER PREPARED OR REVIEWED THE FREQUENCY COORDINATION DATA SUBMITTED WITH THIS APPLICATION, AND THAT IT IS COMPLETE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.



Jeffrey E. Cowles
Engineer III, Telecommunications
COMSEARCH
19700 Janelia Farm Boulevard
Ashburn, Va 20147

DATED: December 1, 2010