Micronet Communications, Inc.

720 F Avenue, Suite 100 Plano, Texas 75074 972-422-7200

SUPPLEMENTAL SHOWING PART 101.103(D)

File Number: N1213608 3.70 GHz

Licensee: KMEX LICENSE PARTNERSHIP GP (UNIVISION TELEVISION GROUP) Page 1

Pursuant to Parts 25.203 and 101.103(d) of the FCC Rules and Regulations, a frequency coordination study was conducted by Micronet Communications, Inc. for the following proposed earth station:

Los Angeles, CA

The results of the study indicate that no unacceptable interference will result with existing, proposed or prior coordinated radio facilities.

Coordination was performed with existing, proposed and prior coordinated carriers within coordination range on the following dates:

07/18/2012 Original PCN There were no unresolved interference objections.

The attached coordination data was forwarded on the latest date to the following parties within coordination range or their authorized coordination agents:

AT&T COMMUNICATIONS OF CALIFORNIA INC
AT&T CORP
COMSEARCH INC
MCI COMMUNICATION SERVICES INC
RADIO DYNAMICS

Respectfully Submitted,

Jeremy B. Lewis

Jeremy Lewis Systems Engineer

Attached: 1 data sheet

Micronet Communications, Inc. 720 F Avenue, Suite 100 Plano, Texas 75074 972-422-7200

File: N1213608

Max Rain Scatter Distances

Rain Zone / Radio Zone

Max Interference Power Long Term (dbW)

Max Interference Power Short Term (dbW)

TECHNICAL CHARACTERISTICS OF RECEIVE ONLY EARTH STATION		
Company: GROUP)	KMEX LICENSE	PARTNERSHIP GP (UNIVISION TELEVISION
Site Name, State: Call Sign:	Los Angeles,	CA
Latitude		33 58 35.2 N
Longitude		118 23 16.1 W
Elevation AMSL		100.07 30.50
Receive Frequency Range		3700-4200
Transmit Frequency Range		
Range of Satellite Orbital Long		74.00 139.00
Range of Azimuths from North	_	119.72 213.94
Antenna Centerline		49.21 15.00
Antenna Elevation Angles	(deg)	28.74 44.76
Equipment Parameters		Receive
Antenna Gain, Main Beam	(dbI)	43.50
15 DB Half Beamwidth		
Antennas Receive: EASI 4	.5 METER	
Max Transmitter Power Max EIRP Main Beam	(dbW/4KHz) (dbW/4KHz)	
Modulation / Emission Designato: 2M50G7D1M20G7D		
Coordination Parameters		Receive
Max Greater Circle Distances	(km)	253.34
	(/	

(km)

168.77

-140.60

-118.40

В

4