Micronet Communications, Inc.

720 F Avenue, Suite 100 Plano, Texas 75074 972-422-7200

SUPPLEMENTAL SHOWING PART 101.103(D)

File Number: D1213608 3.70 GHz

Licensee: KUVI LICENSE PARTNERSHIP GP (UNIVISION TELEVISION GROUP INC) Page 1

Pursuant to Parts 25.203 and 101.103(d) of the FCC Rules and Regulations, a frequency coordination study was conducted by Micronet Communications, Inc. for the following proposed earth station:

Bakersfield, CA

The results of the study indicate that no unacceptable interference will result with existing, proposed or prior coordinated radio facilities.

Coordination was performed with existing, proposed and prior coordinated carriers within coordination range on the following dates:

07/19/2012 Original PCN There were no unresolved interference objections.

The attached coordination data was forwarded on the latest date to the following parties within coordination range or their authorized coordination agents:

AMERICAN TOWER LLC
AT&T COMMUNICATIONS OF CALIFORNIA INC
COMSEARCH INC
MCI COMMUNICATION SERVICES INC
RADIO DYNAMICS

Respectfully Submitted,

Jeremy B. Lewis

Jeremy Lewis Systems Engineer

Attached: 1 data sheet

Micronet Communications, Inc. 720 F Avenue, Suite 100 Plano, Texas 75074 972-422-7200

File: D1213608

Max Rain Scatter Distances

Rain Zone / Radio Zone

Max Interference Power Long Term (dbW)

Max Interference Power Short Term (dbW)

TECHNICAL CHARACTERISTICS OF RECEIVE ONLY EARTH STATION

(km)

=======================================		========	========	====
Company:	KUVI LICENSE	PARTNERSHIP	GP (UNIVISION	TELEVISION GROUP
INC)				
Site Name, State:	Bakersfield,	CA		
Call Sign:				
Latitude	(NAD83)	35 21	47.4 N	
Longitude	/	119 4		
Elevation AMSL		393.00		
Receive Frequency Range	(MHz)	3700-4200		
Transmit Frequency Range	(MHz)			
Range of Satellite Orbital Long.				
Range of Azimuths from North				
Antenna Centerline	(ft/m)	393.70	120.00	
Antenna Elevation Angles	(deg)	27.47	43.80	
Equipment Parameters		Receive		
Antenna Gain, Main Beam	(dhT)	43 00		
15 DB Half Beamwidth				
13 DB Hall Beallwidth	(deg)	2.00		
Antennas Receive: SIMULSA	\Т 5М			
1.0001.00	011			
Max Transmitter Power	(dbW/4KHz)			
Max EIRP Main Beam				
Modulation / Emission Designator				
Coordination Parameters		Receive		
Max Greater Circle Distances	(km)	255.77		

168.93

-140.60

-118.40

4

Α