Micronet Communications, Inc.

720 F Avenue, Suite 100 Plano, Texas 75074 972-422-7200

SUPPLEMENTAL SHOWING PART 101.103(D)

File Number: P1213608 3.70 GHz

Licensee: WXTV LICENSE PARTNERSHIP G P (UNIVISION TELEVISION GROUP INC) Page 1

Pursuant to Parts 25.203 and 101.103(d) of the FCC Rules and Regulations, a frequency coordination study was conducted by Micronet Communications, Inc. for the following proposed earth station:

New York, NJ

The results of the study indicate that no unacceptable interference will result with existing, proposed or prior coordinated radio facilities.

Coordination was performed with existing, proposed and prior coordinated carriers within coordination range on the following dates:

08/06/2012 No-impact change notification pursuant to Section 101.103(d)(2)(ix) - No response required.

07/23/2012 Original PCN

There were no unresolved interference objections.

The attached coordination data was forwarded on the latest date to the following parties within coordination range or their authorized coordination agents:

COMSEARCH INC FCSA SERVICES

Respectfully Submitted,

Jeremy S. Lewis

Jeremy Lewis Systems Engineer

Attached: 1 data sheet

Micronet Communications, Inc. 720 F Avenue, Suite 100 Plano, Texas 75074 972-422-7200

File: P1213608

Max Rain Scatter Distances

Rain Zone / Radio Zone

Max Interference Power Long Term (dbW)

Max Interference Power Short Term (dbW)

TECHNICAL CHARACTERISTICS OF RECEIVE ONLY EARTH STATION			
Company:	NXTV LICENSE	PARTNERSHIP	G P (UNIVISION TELEVIS
GROUP INC)			
·	New York, NJ		
Call Sign:			
Latitude	(NAD83)	40 52	24.7 N
Longitude	(NAD83)	74 0 7.00	22.4 W
Elevation AMSL	(ft/m)	7.00	2.13
Receive Frequency Range	(MHz)	3700-4200	
Transmit Frequency Range	(MHz)		
Range of Satellite Orbital Long.	(deg W)	74.00	139.00
Range of Azimuths from North	(deg)	179.99	253.03
Antenna Centerline	(ft/m)	83.00	25.30
Antenna Elevation Angles	(deg)	42.76	10.10
Equipment Parameters		Receive	
Antenna Gain, Main Beam	(dbI)	43.50	
	(deg)		
Antennas Receive: COMMSCO	PE ES45MPJ (4	.5 METER)	
Max Transmitter Power Max EIRP Main Beam	(dbW/4KHz)		
Modulation / Emission Designator 2M50G7D1M20G7D			3G7W
Coordination Parameters		Receive	
Max Greater Circle Distances	(lem)	244 65	

(km)

251.86

-140.60 -118.40

2