Micronet Communications, Inc.

720 F Avenue, Suite 100 Plano, Texas 75074 972-422-7200

SUPPLEMENTAL SHOWING PART 101.103(D)

File Number: H1213608 3.70 GHz

Licensee: KUVN LICENSE PARTNERSHIP L P (UNIVISION TELEVISION GROUP INC) Page 1

Pursuant to Parts 25.203 and 101.103(d) of the FCC Rules and Regulations, a frequency coordination study was conducted by Micronet Communications, Inc. for the following proposed earth station:

Dallas, TX

The results of the study indicate that no unacceptable interference will result with existing, proposed or prior coordinated radio facilities.

Coordination was performed with existing, proposed and prior coordinated carriers within coordination range on the following dates:

07/18/2012 Original PCN
There were no unresolved interference objections.

The attached coordination data was forwarded on the latest date to the following parties within coordination range or their authorized coordination agents:

AT&T COMMUNICATIONS OF THE SOUTH CENTRAL STATES INC AT&T CORP COMSEARCH INC RADIO DYNAMICS

Respectfully Submitted,

Jeremy S. Lewis

Jeremy Lewis Systems Engineer

Attached: 1 data sheet

Micronet Communications, Inc. 720 F Avenue, Suite 100 Plano, Texas 75074 972-422-7200

File: H1213608

Max Interference Power Long Term (dbW)

Max Interference Power Short Term (dbW)

Rain Zone / Radio Zone

	========	
TECHNICAL CHARACTERIST	ICS OF RECEIV	/E ONLY EARTH STATION
Company:	KIIVN I.TCENSE	PARTNERSHIP L P (UNIVISION TELEVIS
GROUP INC)	NOVIV LICLINOL	THE THE CONTROL TO THE TENT OF
•	Dallas, TX	
Call Sign:	,	
Latitude	(NAD83)	32 47 14.0 N
Longitude	(NAD83)	96 47 38.6 W
Elevation AMSL	(ft/m)	472.44 144.00
Receive Frequency Range	(MHz)	3700-4200
Transmit Frequency Range	(MHz)	
Range of Satellite Orbital Long.	(deg W)	74.00 139.00
Range of Azimuths from North	(deg)	142.19 239.16
Antenna Centerline	(ft/m)	594.82 181.30
Antenna Elevation Angles		
Equipment Parameters		Receive
Antenna Gain, Main Beam		
15 DB Half Beamwidth	(deg)	2.20
Antennas Receive: EASI 4.	5 METER	
Max Transmitter Power		
Max EIRP Main Beam	(dbW/4KHz)	
Modulation / Emission Designator 2M50G7D1M20G7D		
Coordination Parameters		Receive
Max Greater Circle Distances		
Max Rain Scatter Distances		239.13
	(11 ==)	1 4 0 6 0

-140.60

-118.40

В

2