

# FREQUENCY COORDINATION AND INTERFERENCE ANALYSIS REPORT

Prepared for  
**WJW License, LLC**  
**CLEVELAND, OH**  
**Satellite Earth Station**

Prepared By:  
COMSEARCH  
19700 Janelia Farm Boulevard  
Ashburn, VA 20147  
March 27, 2018

## TABLE OF CONTENTS

1. CONCLUSIONS .....	3
2. SUMMARY OF RESULTS .....	4
3. SUPPLEMENTAL SHOWING .....	5
4. EARTH STATION COORDINATION DATA.....	6
5. CERTIFICATION.....	10

## 1. CONCLUSIONS

An interference study considering all existing, proposed and prior coordinated microwave facilities within the coordination contours of the proposed earth station demonstrates that this site will operate satisfactorily with the common carrier microwave environment. Further, there will be no restrictions of its operation due to interference considerations.

## 2. SUMMARY OF RESULTS

A number of great circle interference cases were identified during the interference study of the proposed earth station. Each of the cases, which exceeded the interference objective on a line-of-sight basis, was profiled and the propagation losses estimated using NBS TN101 (Revised) techniques. The losses were found to be sufficient to reduce the signal levels to acceptable magnitudes in every case.

### 3. SUPPLEMENTAL SHOWING

Pursuant to Part 25.203(c) of the FCC Rules and Regulations, the satellite earth station proposed in this application was coordinated by Comsearch using computer techniques and in accordance with Part 25 of the FCC Rules and Regulations.

Coordination data for this earth station was sent to the below listed carriers with a letter dated 02/19/2018.

Company

Mountain State Communications, Ilc  
Waterleaf International LLC

## **4. EARTH STATION COORDINATION DATA**

This section presents the data pertinent to frequency coordination of the proposed earth station that was circulated to all carriers within its coordination contours.

# COMSEARCH

## Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147  
(703)726-5500 <http://www.comsearch.com>

Date: 03/27/2018  
Job Number: 180219COMSGE08

---

### Administrative Information

Status ENGINEER PROPOSAL  
Call Sign  
Licensee Code WJWLIC  
Licensee Name WJW License, LLC

---

### Site Information CLEVELAND, OH

Venue Name STUDIO  
Latitude (NAD 83) 41° 31' 47.4" N  
Longitude (NAD 83) 81° 38' 55.5" W  
Climate Zone A  
Rain Zone 2  
Ground Elevation (AMSL) 183.93 m / 603.4 ft

---

### Link Information

Satellite Type Geostationary  
Mode RO - Receive-Only  
Modulation Digital  
Satellite Arc 60° W to 143° West Longitude  
Azimuth Range 149.1° to 250.1°  
Corresponding Elevation Angles 37.2° / 12.5°  
Antenna Centerline (AGL) 2.74 m / 9.0 ft

---

### Antenna Information Receive - FCC32

Manufacturer Dawnco  
Model 5 meter  
Gain / Diameter 44.5 dBi / 5.0 m  
3-dB / 15-dB Beamwidth 0.86° / 2.00°

Interference Objectives: Long Term -156.0 dBW/MHz 20%  
Short Term -146.0 dBW/MHz 0.01%

---

### Frequency Information Receive 4.0 GHz

Emission / Frequency Range (MHz) 36M0G7W / 3700.0 - 4200.0

Max Great Circle Coordination Distance 391.9 km / 243.5 mi  
Precipitation Scatter Contour Radius 528.3 km / 328.2 mi

# COMSEARCH

## Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147  
(703)726-5500 <http://www.comsearch.com>

### Coordination Values

### CLEVELAND, OH

Licensee Name WJW License, LLC  
Latitude (NAD 83) 41° 31' 47.4" N  
Longitude (NAD 83) 81° 38' 55.5" W  
Ground Elevation (AMSL) 183.93 m / 603.4 ft  
Antenna Centerline (AGL) 2.74 m / 9.0 ft  
Antenna Model Dawnco 5 meter  
Antenna Mode Receive 4.0 GHz  
Interference Objectives: Long Term -156.0 dBW/MHz 20%  
Short Term -146.0 dBW/MHz 0.01%

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 4.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)
0	0.00	109.42	-10.00	285.28
5	0.00	114.28	-10.00	285.28
10	0.00	119.13	-10.00	285.28
15	0.00	123.68	-10.00	285.28
20	0.00	120.17	-10.00	285.28
25	0.00	116.53	-10.00	285.28
30	0.00	112.80	-10.00	285.28
35	0.37	109.08	-10.00	264.46
40	0.00	105.11	-10.00	285.28
45	0.40	101.25	-10.00	260.68
50	0.39	97.27	-10.00	261.63
55	0.85	93.30	-10.00	228.43
60	0.70	89.27	-10.00	237.23
65	0.40	85.27	-10.00	260.99
70	0.58	81.26	-10.00	244.69
75	0.62	77.28	-10.00	242.38
80	0.80	73.30	-10.00	231.32
85	0.75	69.42	-10.00	234.27
90	0.74	65.59	-10.00	235.11
95	0.95	61.76	-10.00	223.03
100	1.57	57.83	-10.00	206.13
105	1.68	54.21	-10.00	203.08
110	1.68	50.81	-10.00	203.18
115	1.58	47.67	-9.96	206.10
120	1.64	44.68	-9.25	205.25
125	1.62	42.04	-8.59	208.85
130	1.72	39.67	-7.96	209.14
135	1.76	37.77	-7.43	210.46
140	1.60	36.57	-7.08	216.86
145	1.38	35.99	-6.90	224.31
150	1.45	35.73	-6.83	222.70
155	1.32	36.27	-6.99	225.78
160	1.03	37.53	-7.36	233.21
165	0.82	39.14	-7.82	242.37
170	0.97	40.13	-8.09	231.86
175	0.96	40.83	-8.27	231.72
180	1.46	40.56	-8.20	215.14
185	1.58	40.21	-8.11	212.18



# COMSEARCH

## Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147  
(703)726-5500 <http://www.comsearch.com>

### Coordination Values


### CLEVELAND, OH

Licensee Name WJW License, LLC  
Latitude (NAD 83) 41° 31' 47.4" N  
Longitude (NAD 83) 81° 38' 55.5" W  
Ground Elevation (AMSL) 183.93 m / 603.4 ft  
Antenna Centerline (AGL) 2.74 m / 9.0 ft  
Antenna Model Dawnco 5 meter  
Antenna Mode Receive 4.0 GHz  
Interference Objectives: Long Term -156.0 dBW/MHz 20%  
Short Term -146.0 dBW/MHz 0.01%

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 4.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)
190	1.58	39.54	-7.93	213.21
195	1.40	38.60	-7.66	219.80
200	2.24	36.31	-7.00	203.25
205	1.86	34.78	-6.53	212.01
210	0.62	33.62	-6.17	265.42
215	0.76	30.98	-5.28	261.84
220	1.06	27.98	-4.17	251.36
225	0.35	25.56	-3.19	313.11
230	0.29	22.46	-1.79	331.35
235	0.31	19.16	-0.06	341.21
240	0.24	15.86	1.99	367.32
245	0.00	13.52	3.72	385.90
250	0.00	12.54	4.54	391.89
255	0.00	13.46	3.78	386.31
260	0.00	15.94	1.94	371.66
265	0.00	19.40	-0.19	355.13
270	0.00	23.40	-2.23	339.80
275	0.00	27.71	-4.07	326.36
280	0.00	32.21	-5.70	314.73
285	0.00	36.83	-7.15	304.03
290	0.00	41.52	-8.46	295.28
295	0.00	46.27	-9.63	287.63
300	0.00	51.06	-10.00	285.28
305	0.00	55.87	-10.00	285.28
310	0.00	60.70	-10.00	285.28
315	0.00	65.55	-10.00	285.28
320	0.00	70.41	-10.00	285.28
325	0.00	75.28	-10.00	285.28
330	0.00	80.16	-10.00	285.28
335	0.00	85.04	-10.00	285.28
340	0.00	89.92	-10.00	285.28
345	0.00	94.80	-10.00	285.28
350	0.00	99.67	-10.00	285.28
355	0.00	104.55	-10.00	285.28

## 5. CERTIFICATION

I HEREBY CERTIFY THAT I AM THE TECHNICALLY QUALIFIED PERSON RESPONSIBLE FOR THE PREPARATION OF THE FREQUENCY COORDINATION DATA CONTAINED IN THIS APPLICATION, THAT I AM FAMILIAR WITH PARTS 101 AND 25 OF THE FCC RULES AND REGULATIONS, THAT I HAVE EITHER PREPARED OR REVIEWED THE FREQUENCY COORDINATION DATA SUBMITTED WITH THIS APPLICATION, AND THAT IT IS COMPLETE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

BY: 

Gary K. Edwards  
Senior Manager  
COMSEARCH  
19700 Janelia Farm Boulevard  
Ashburn, VA 20147

DATED: March 27, 2018