

**Micronet Communications, Inc.**

720 F Avenue, Suite 100  
Plano, Texas 75074  
972-422-7200

SUPPLEMENTAL SHOWING PART 101.103(D)

File Number: M1815813 3.70 GHz  
Licensee: Multimedia Holdings Corporation

Page 1

---

Pursuant to Parts 25.203 and 101.103(d) of the FCC Rules and Regulations, a frequency coordination study was conducted by Micronet Communications, Inc. for the following proposed earth station:

Golden Valley Studio, MN

The results of the study indicate that no unacceptable interference will result with existing, proposed or prior coordinated radio facilities.

Coordination was performed with existing, proposed and prior coordinated carriers within coordination range on the following dates:

06/26/2018 Original PCN  
There were no unresolved interference objections.

The attached coordination data was forwarded on the latest date to the following parties within coordination range or their authorized coordination agents:

COMSEARCH INC

Respectfully Submitted,



Jeremy Boyce  
Systems Engineer

Attached: 1 data sheet

Micronet Communications, Inc.  
720 F Avenue, Suite 100  
Plano, Texas 75074  
972-422-7200

File: M1815813

=====

TECHNICAL CHARACTERISTICS OF RECEIVE ONLY EARTH STATION

=====

Company:	Multimedia Holdings Corporation			
Site Name, State:	Golden Valley Studio, MN			
Call Sign:				
Latitude	(NAD83)	44	58	59.8 N
Longitude	(NAD83)	93	23	28.8 W
Elevation AMSL	(ft/m)	884.84		269.70
Receive Frequency Range	(MHz)	3700-4200		
Transmit Frequency Range	(MHz)			
Range of Satellite Orbital Long.	(deg W)	72.00		139.00
Range of Azimuths from North	(deg)	151.01		235.32
Antenna Centerline	(ft/m)	17.00		5.18
Antenna Elevation Angles	(deg)	34.00		21.59

-----

Equipment Parameters Receive

-----

Antenna Gain, Main Beam	(dbI)	39.00
15 DB Half Beamwidth	(deg)	0.00

Antennas Receive: SCIENTIFIC ATLANTA 9000 (2.8 METER)

Max Transmitter Power	(dbW/4KHz)	
Max EIRP Main Beam	(dbW/4KHz)	
Modulation / Emission Designator	DIGITAL	36M0G7W

-----

Coordination Parameters Receive

-----

Max Greater Circle Distances	(km)	264.72
Max Rain Scatter Distances	(km)	403.41
Max Interference Power Long Term	(dbW)	-140.60
Max Interference Power Short Term	(dbW)	-118.40
Rain Zone / Radio Zone		2 <span style="float: right;">A</span>

MICRONET COMMUNICATIONS, INC.  
06-26-2018

File: M1815813

page 1

=====  
Horizon Angle      Horizon Gain      Final Contour      -      3.95 GHz RECEIVE ONLY  
=====

Company:                                  Multimedia Holdings Corporation

Site Name, State:                                  Golden Valley Studio, MN

Call Sign:

Latitude (NAD83) 44 58 59.8 N                  Longitude (NAD83) 93 23 28.8 W

North Azimuth (deg)	Horizon Angle (deg)	Horizon Gain (db)	Final Contour (km)	North Azimuth (deg)	Horizon Angle (deg)	Horizon Gain (db)	Final Contour (km)
0	1.55	-10.00	173.8	180	0.30	-7.47	241.6
5	1.81	-10.00	167.1	185	0.36	-7.39	238.9
10	2.06	-10.00	160.8	190	0.45	-7.18	234.7
15	2.30	-10.00	155.4	195	0.50	-6.86	234.5
20	2.52	-10.00	150.4	200	0.52	-6.42	235.1
25	2.72	-10.00	146.3	205	0.59	-5.84	229.6
30	2.90	-10.00	143.0	210	0.56	-5.15	231.0
35	3.08	-10.00	139.6	215	0.79	-4.22	215.1
40	3.17	-10.00	138.0	220	0.66	-3.24	219.1
45	3.26	-10.00	136.3	225	0.62	-2.16	219.5
50	3.31	-10.00	135.2	230	0.55	-1.39	219.9
55	3.34	-10.00	134.7	235	0.45	-1.13	222.8
60	3.33	-10.00	134.8	240	0.28	-1.45	229.6
65	3.30	-10.00	135.4	245	0.32	-2.17	225.3
70	3.24	-10.00	136.6	250	0.38	-3.20	221.3
75	3.15	-10.00	138.3	255	0.59	-4.35	210.3
80	3.04	-10.00	143.6	260	0.73	-5.57	203.2
85	2.90	-10.00	150.6	265	0.66	-6.82	206.7
90	2.74	-10.00	159.4	270	0.40	-8.02	219.9
95	2.56	-10.00	168.5	275	0.38	-9.11	221.2
100	2.37	-10.00	177.7	280	0.34	-10.00	224.1
105	2.18	-10.00	187.6	285	0.29	-10.00	227.2
110	1.97	-10.00	197.9	290	0.38	-10.00	221.6
115	1.75	-9.70	207.3	295	0.47	-10.00	216.7
120	1.52	-8.97	215.1	300	0.26	-10.00	229.4
125	1.29	-8.25	220.2	305	0.29	-10.00	227.7
130	1.06	-7.60	224.4	310	0.22	-10.00	232.5
135	0.31	-7.17	264.7	315	0.44	-10.00	218.0
140	0.40	-6.65	253.9	320	0.21	-10.00	233.1
145	0.39	-6.31	249.0	325	0.23	-10.00	231.9
150	0.55	-6.11	234.4	330	0.36	-10.00	222.5
155	0.83	-6.09	213.9	335	0.39	-10.00	220.4
160	0.66	-6.41	220.9	340	0.44	-10.00	217.8
165	0.52	-6.85	228.4	345	0.62	-10.00	208.7
170	0.21	-7.25	247.6	350	1.03	-10.00	188.7
175	0.28	-7.41	243.0	355	1.29	-10.00	180.7