Micronet Communications, Inc.

720 F Avenue, Suite 100 Plano, Texas 75074 972-422-7200

SUPPLEMENTAL SHOWING PART 101.103(D)

File Number: M1825606 3.70 GHz Licensee: American Christian Television Services Inc.

Page 1

Pursuant to Parts 25.203 and 101.103(d) of the FCC Rules and Regulations, a frequency coordination study was conducted by Micronet Communications, Inc. for the following proposed earth station:

WTLW TV44, OH

The results of the study indicate that no unacceptable interference will result with existing, proposed or prior coordinated radio facilities.

Coordination was performed with existing, proposed and prior coordinated carriers within coordination range on the following dates:

10/03/2018 Original PCN There were no unresolved interference objections.

The attached coordination data was forwarded on the latest date to the following parties within coordination range or their authorized coordination agents:

COMSEARCH INC MOUNTAIN STATE COMMUNICATIONS, LLC WATERLEAF INTERNATIONAL LLC

Respectfully Submitted,

Jeremy B. Lewis

Jeremy Lewis Systems Engineer

Attached: 1 data sheet

Micronet Communications, Inc. 720 F Avenue, Suite 100 Plano, Texas 75074 972-422-7200

File: M1825606

TECHNICAL CHARACTERISTICS OF RECEIVE ONLY EARTH STATION
Company: American Christian Television Services Inc.

Company: Site Name, State:	American Chr: WTLW TV44, OF		ision Services	s inc.
Call Sign:	WILW IV44, OI	.1		
Latitude	(NAD83)	40 45	47 0 N	
Longitude	(NAD83)	84 11 827.00	10W	
Elevation AMSL	(ft/m)	827.00	252.07	
Receive Frequency Range	(MHz)	3700-4200	202.07	
Transmit Frequency Range		0,00 1200		
Range of Satellite Orbital Long.		76.00	125.00	
Range of Azimuths from North	(deg)	167.58	232.91	
Antenna Centerline	(ft/m)	10.00	3.05	
Antenna Centerline Antenna Elevation Angles	(deg)	42.14	27.26	
5				
Equipment Parameters		Receive		
Equipment Parameters				
Antenna Gain, Main Beam 15 DB Half Beamwidth	(dbI)	40.00		
15 DB Half Beamwidth	(deg)	2.50		
Antennas Receive: PRODEL	IN 1304-990 (3	3 M)		
Max Transmitter Power				
Max EIRP Main Beam	(dbW/4KHz)	20100714		
Modulation / Emission Designator	r digital	36MUG/W		
Coordination Parameters		Receive		
Max Greater Circle Distances	(km)	383.36		
Max Rain Scatter Distances				
Max Interference Power Long Terr				
Max Interference Power Short Ter				
Rain Zone / Radio Zone		2	А	