

1.8M C & Ku-Band Rx/Tx

Series 1183

Technical Specifications

Electrical		C-Band Linear	C-Band Circular	Ku-Band Linear
Antenna Size		1.8 M (71 in.)	1.8 M (71 in.)	1.8 M (71 in.)
Operating Frequency (GHz)	Receive	3.625 - 4.20 GHz	3.625 - 4.20 GHz	10.70 - 12.75 GHz
	Transmit	5.85 - 6.425 GHz	5.85 - 6.425 GHz	13.75 - 14.50 GHz
Midband Gain (+/- .2dB)	Receive	35.50 dBi	35.30 dBi	44.80 dBi
	Transmit	39.50 dBi	39.30 dBi	46.80 dBi
Antenna Noise Temperature				
10° Elevation		45 K	45 K	69 K
20° Elevation		41 K	41 K	64 K
30° Elevation		41 K	41 K	63 K
40° Elevation		40 K	40 K	62 K
Sidelobe Envelope, Co-Pol (dBi)				
100λ / D ≤ θ ≤ 20°		29 - 25 Logθ dBi	29 - 25 Logθ dBi	29 - 25 Logθ dBi
20° < θ ≤ 26.3°		-3.5 dBi	-3.5 dBi	-3.5 dBi
26.3° < θ ≤ 48°		32 - 25	32 - 25	32 - 25
θ > 48°		-10 dBi (averaged)	-10 dBi (averaged)	-10 dBi (averaged)
Cross Polarization Isolation	On Axis	30 dB	17.7 dB Tx 15.5 dB Rx	30 dB
	With 1.0 dB Beamwidth	26 dB	17.7 dB Tx 15.5 dB Rx	26 dB
VSWR		1.3:1 Max.	1.3:1 Max.	1.3:1 Max. Tx 1.5:1 Max. Rx
Output Waveguide Interface Flange		WR137 or N Tx WR229 Rx	WR137 or N Tx WR229 Rx	WR75 WR229 Rx
Power Handling		1 kW	1 kW	100 W

Mechanical

Reflector Material	Glass Fiber Reinforced Polyester SMC		
Antenna Optics	Prime Focus, One-Piece Offset Feed		
Mount Type	Elevation over Azimuth		
Mast Pipe Size	3.5" SCH 40 Pipe (4.00" OD) 10.16 cm.		
Elevation Adjustment Range	5° to 90°, Continuous Fine Adjustment		
Azimuth Adjustment Range	360° Continuous		
Shipping Specifications (Approx. Net Weight)	180 lbs. (82kg.)	185 lbs. (84kg.)	170 lbs. (78kg.)

Environmental Performance

Wind Loading	Operational	45 mph (72 km/h)
	Survival	125 mph (201 km/h)
Temperature	Operational	-40° to 140° F (-40° to 60° C)
Rain	Operational	1/2" (13 mm)/hr
Ice	Operational	-----
Atmospheric Conditions	Salt, Pollutants and Contaminants as Encountered in Coastal and Industrial Areas	
Relative Humidity	0 to 100% With Condensation	
Solar Radiation	360 BTU/h/ft ²	

GENERAL DYNAMICS

SATCOM Technologies

1500 Prodelin Drive • Newton, NC 28658 USA • Telephone: +1-828-464-4141 • Fax: +1-828-464-4147
 Email: vsat@gdsatcom.com • Web Site: www.gdsatcom.com

1000-013 Rev. 02/12