

19700 Janelia Farm Boulevard

Ashburn, VA 20147

(703) 726-5500

Fax (703) 726-5600



COMSEARCH®

<http://www.comsearch.com>

October 2, 2008

*** CLIENT COPY ***
*** PLEASE MAIL ***
*** TO CUSTOMER ***

Re: Universal Space Network, Inc.
Naalehu, Hawaii
2 GHz Transmit/Receive Earth Station
Job Number: 081002COMSJC01

***** EXPEDITED FREQUENCY COORDINATION *****
***** RESPONSE REQUESTED BY OCTOBER 9, 2008 *****

Dear Frequency Coordinator:

This notice is being provided in accordance with Section 25.203(c) of the FCC Rules and Regulations. We are forwarding the attached expedited coordination data on behalf of Universal Space Network, Inc. for the purpose of obtaining an STA to provide support services during the launch and early orbit testing of a new satellite from their existing transmit/receive earth station located near Naalehu, Hawaii.

The coordination notice is being circulated to the owners (or their protection agents) of all existing or proposed terrestrial facilities operating in a shared frequency band within the coordination contours of the earth station(s).

We respectfully request that you examine this data for its interference potential with your system(s). In the event that your analysis identifies potential interference cases that have not been resolved, please contact Comsearch by October 9, 2008.

If there are any questions concerning this coordination notice, please contact Comsearch.

Sincerely,

COMSEARCH

Jeffrey E. Cowles
Principal Frequency Planner

Enclosure(s)

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5660 <http://www.comsearch.com>

Date: 10/02/2008
Job Number: 081002COMSJC01

Administrative Information

Status ENGINEER PROPOSAL
Call Sign NAALEHU
Licensee Code UNSPNE
Licensee Name Universal Space Network, Inc.

Site Information

NAALEHU, HAWAII
Venue Name
Latitude (NAD 83) 19° 0' 50.3" N
Longitude (NAD 83) 155° 39' 46.6" W
Climate Zone C
Rain Zone 4
Ground Elevation (AMSL) 378.0 m / 1240.2 ft

Link Information

Satellite Type Low Earth Orbit
Mode TR – Transmit/Receive
Modulation Digital
Minimum Elevation Angle 5.0°
Azimuth Range 0.0° to 360°
Antenna Centerline (AGL) 8.53 m / 28.0 ft

Antenna Information

	Receive	Transmit
Manufacturer	Datron	Datron
Model	1453	1453
Gain / Diameter	46.9 dBi / 13.0 m	45.9 dBi / 13.0 m
3-dB / 15-dB Beamwidth	0.78° / 1.46°	0.76° / 1.46°
Max Available RF Power		
(dBW/4 kHz)		5.1
(dBW/MHz)		22.1
Maximum EIRP		
(dBW/4 kHz)		51.0
(dBW/MHz)		68.0
(dBW)		68.0
Interference Objectives:		
Long Term	-156.0 dBW/MHz 20%	-154.0 dBW/4 kHz 20%
Short Term	-146.0 dBW/MHz 0.01%	-131.0 dBW/4 kHz 0.0025%

Frequency Information

	Receive 2.2 GHz	Transmit 2.0 GHz
Emission / Frequency Range (MHz)	200KG2D / 2217.12 200KG2D / 2230.8	200KG2D / 2041.958 200KG2D / 2054.195
Max Great Circle Coordination Distance	1050.1 km / 652.4 mi	760.0 km / 472.2 mi
Precipitation Scatter Contour Radius	100.0 km / 62.1 mi	100.0 km / 62.1 mi

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5660 <http://www.comsearch.com>

Coordination Values		NAALEHU, HI			
Licensee Name		Universal Space Network, Inc.			
Latitude (NAD 83)		19° 0' 50.3" N			
Longitude (NAD 83)		155° 39' 46.6" W			
Ground Elevation (AMSL)		378.0 m / 1240.2 ft			
Antenna Centerline (AGL)		8.53 m / 28.0 ft			
Antenna Model		Datron 1453			
Antenna Mode		Receive 2.2 GHz		Transmit 2.0 GHz	
Interference Objectives: Long Term		-156.0 dBW/MHz	20%	-154.0 dBW/4 kHz	20%
Short Term		-146.0 dBW/MHz	0.01%	-131.0 dBW/4 kHz	0.0025%
Max Available RF Power		5.1 (dBW/4 kHz)			

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 2.2 GHz		Transmit 2.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
0	2.78	5.0	4.50	662.10	4.50	365.00
5	2.62	5.0	4.50	671.20	4.50	374.40
10	2.39	5.0	4.50	685.10	4.50	388.60
15	2.30	5.0	4.50	690.80	4.50	394.30
20	2.17	5.0	4.50	699.20	4.50	403.00
25	2.03	5.0	4.50	708.80	4.50	412.70
30	1.68	5.0	4.50	734.80	4.50	439.30
35	0.90	5.0	4.50	811.80	4.50	517.90
40	0.33	5.0	4.50	911.20	4.50	619.40
45	0.00	5.0	4.50	1050.10	4.50	760.00
50	0.00	5.0	4.50	1050.10	4.50	760.00
55	0.00	5.0	4.50	1050.10	4.50	760.00
60	0.00	5.0	4.50	1050.10	4.50	760.00
65	0.00	5.0	4.50	1050.10	4.50	760.00
70	0.00	5.0	4.50	1050.10	4.50	760.00
75	0.00	5.0	4.50	1050.10	4.50	760.00
80	0.00	5.0	4.50	1050.10	4.50	760.00
85	0.00	5.0	4.50	1050.10	4.50	760.00
90	0.00	5.0	4.50	1050.10	4.50	760.00
95	0.00	5.0	4.50	1050.10	4.50	760.00
100	0.00	5.0	4.50	1050.10	4.50	760.00
105	0.00	5.0	4.50	1050.10	4.50	760.00
110	0.00	5.0	4.50	1050.10	4.50	760.00
115	0.00	5.0	4.50	1050.10	4.50	760.00
120	0.00	5.0	4.50	1050.10	4.50	760.00
125	0.00	5.0	4.50	1050.10	4.50	760.00
130	0.00	5.0	4.50	1050.10	4.50	760.00
135	0.00	5.0	4.50	1050.10	4.50	760.00
140	0.00	5.0	4.50	1050.10	4.50	760.00
145	0.00	5.0	4.50	1050.10	4.50	760.00
150	0.00	5.0	4.50	1050.10	4.50	760.00
155	0.00	5.0	4.50	1050.10	4.50	760.00
160	0.00	5.0	4.50	1050.10	4.50	760.00
165	0.00	5.0	4.50	1050.10	4.50	760.00
170	0.00	5.0	4.50	1050.10	4.50	760.00
175	0.00	5.0	4.50	1050.10	4.50	760.00
180	0.00	5.0	4.50	1050.10	4.50	760.00
185	0.00	5.0	4.50	1050.10	4.50	760.00

COMSEARCH
Earth Station Data Sheet
 19700 Janelia Farm Boulevard, Ashburn, VA 20147
 (703)726-5660 <http://www.comsearch.com>

Coordination Values	NAALEHU, HI			
Licensee Name	Universal Space Network, Inc.			
Latitude (NAD 83)	19° 0' 50.3" N			
Longitude (NAD 83)	155° 39' 46.6" W			
Ground Elevation (AMSL)	378.0 m / 1240.2 ft			
Antenna Centerline (AGL)	8.53 m / 28.0 ft			
Antenna Model	Datron 1453			
Antenna Mode	Receive 2.2 GHz		Transmit 2.0 GHz	
Interference Objectives: Long Term	-156.0 dBW/MHz	20%	-154.0 dBW/4 kHz	20%
Short Term	-146.0 dBW/MHz	0.01%	-131.0 dBW/4 kHz	0.0025%
Max Available RF Power			5.1 (dBW/4 kHz)	

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 2.2 GHz		Transmit 2.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
190	0.00	5.0	4.50	1050.10	4.50	760.00
195	0.00	5.0	4.50	1050.10	4.50	760.00
200	0.00	5.0	4.50	1050.10	4.50	760.00
205	0.00	5.0	4.50	1050.10	4.50	760.00
210	0.00	5.0	4.50	1050.10	4.50	760.00
215	0.00	5.0	4.50	1050.10	4.50	760.00
220	0.00	5.0	4.50	1050.10	4.50	760.00
225	0.00	5.0	4.50	1050.10	4.50	760.00
230	0.00	5.0	4.50	1050.10	4.50	760.00
235	0.00	5.0	4.50	1050.10	4.50	760.00
240	0.00	5.0	4.50	1050.10	4.50	760.00
245	0.00	5.0	4.50	1050.10	4.50	760.00
250	0.00	5.0	4.50	1050.10	4.50	760.00
255	0.00	5.0	4.50	1050.10	4.50	760.00
260	0.00	5.0	4.50	1050.10	4.50	760.00
265	0.34	5.0	4.50	908.60	4.50	616.80
270	0.54	5.0	4.50	866.00	4.50	573.30
275	0.79	5.0	4.50	826.30	4.50	532.80
280	1.04	5.0	4.50	795.00	4.50	500.90
285	0.98	5.0	4.50	802.00	4.50	508.00
290	1.14	5.0	4.50	784.10	4.50	489.70
295	1.30	5.0	4.50	768.00	4.50	473.20
300	1.42	5.0	4.50	757.00	4.50	461.80
305	1.68	5.0	4.50	734.80	4.50	439.30
310	1.86	5.0	4.50	721.00	4.50	425.20
315	2.05	5.0	4.50	707.40	4.50	411.30
320	2.17	5.0	4.50	699.20	4.50	403.00
325	2.35	5.0	4.50	687.60	4.50	391.10
330	2.46	5.0	4.50	681.00	4.50	384.10
335	2.59	5.0	4.50	673.00	4.50	376.20
340	2.68	5.0	4.50	667.80	4.50	370.80
345	2.73	5.0	4.50	664.90	4.50	367.90
350	3.10	5.0	4.50	644.70	4.50	347.30
355	2.96	5.0	4.50	652.20	4.50	354.90