

APPLICATION FOR EARTH STATION SPECIAL TEMPORARY AUTHORITY

APPLICANT INFORMATION Enter a description of this application to identify it on the main menu:  
Gateway station, Phase II IOT, initial 30 days (July 2009)

1. Applicant

<b>Name:</b>	TerreStar License Inc.	<b>Phone Number:</b>	703-483-7800
<b>DBA Name:</b>		<b>Fax Number:</b>	
<b>Street:</b>	12010 Sunset Hills Road	<b>E-Mail:</b>	doug.brandon@terrestar.com
<b>City:</b>	Reston	<b>State:</b>	VA
<b>Country:</b>	USA	<b>Zipcode:</b>	20190 -
<b>Attention:</b>	Mr Douglas I Brandon		

*With Condition*



File # SES-STA-20090728-00926

Call Sign \_\_\_\_\_ Grant Date 8/11/09  
(or other identifier)

Term Dates  
From 8/11/09 To: 9/10/09

Approved: Patrick Medley

*Chief Satellite Engng Br.*

Attachment

SES-STA-20090728-00926

Condition:

All operations shall be on an unprotected and non-harmful interference basis, i.e., TerreStar License Inc. shall not cause harmful interference to, and shall not claim protection from, interference caused to it by any other lawfully operating station and it shall cease transmission(s) immediately upon notice of such interference.

*With Condition*

File # SES-STA-20090728-00926

Call Sign \_\_\_\_\_ Grant Date 8/11/09  
(or other identifier)

Term Dates  
From 8/11/09 To: 7/10/09

Approved: Kelly M. Madler

Chief, Satellite Engngs Sr.



**2. Contact**

<b>Name:</b>	Joseph A. Godles, Esq.	<b>Phone Number:</b>	202-429-4900
<b>Company:</b>	Goldberg Godles Wiener & Wright	<b>Fax Number:</b>	202-429-4912
<b>Street:</b>	1229 19th Street, NW	<b>E-Mail:</b>	jgodles@g2w2.com
<b>City:</b>	Washington	<b>State:</b>	DC
<b>Country:</b>	USA	<b>Zipcode:</b>	20036 -2413
<b>Attention:</b>		<b>Relationship:</b>	Legal Counsel

(If your application is related to an application filed with the Commission, enter either the file number or the IB Submission ID of the related application. Please enter only one.)

3. Reference File Number SESLIC2007053000732 or Submission ID

4a. Is a fee submitted with this application?

If Yes, complete and attach FCC Form 159. If No, indicate reason for fee exemption (see 47 C.F.R. Section 1.1114).

Governmental Entity  Noncommercial educational licensee

Other (please explain):

4b. Fee Classification CGX – Fixed Satellite Transmit/Receive Earth Station

5. Type Request

Use Prior to Grant

Change Station Location

Other

6. Requested Use Prior Date

08/11/2009

7. City North Las Vegas

8. Latitude

(dd mm ss.s h) 36 14 9.9 N



**FCC NOTICE REQUIRED BY THE PAPERWORK REDUCTION ACT**

The public reporting for this collection of information is estimated to average 2 hours per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the required data, and completing and reviewing the collection of information. If you have any comments on this burden estimate, or how we can improve the collection and reduce the burden it causes you, please write to the Federal Communications Commission, AMD-PERM, Paperwork Reduction Project (3060-0678), Washington, DC 20554. We will also accept your comments regarding the Paperwork Reduction Act aspects of this collection via the Internet if you send them to PRA@fcc.gov. PLEASE DO NOT SEND COMPLETED FORMS TO THIS ADDRESS.

Remember – You are not required to respond to a collection of information sponsored by the Federal government, and the government may not conduct or sponsor this collection, unless it displays a currently valid OMB control number or if we fail to provide you with this notice. This collection has been assigned an OMB control number of 3060-0678.

**THE FOREGOING NOTICE IS REQUIRED BY THE PAPERWORK REDUCTION ACT OF 1995, PUBLIC LAW 104-13, OCTOBER 1, 1995, 44 U.S.C. SECTION 3507.**

## REQUEST FOR SPECIAL TEMPORARY AUTHORITY

TerreStar License Inc. (“TerreStar”), pursuant to Section 25.120 of the Commission’s rules, hereby requests Special Temporary Authority (“STA”) to conduct in-orbit testing (“IOT”) of the TerreStar-1 satellite in the manner described below. This STA request covers IOT operations specific to the Satellite Beam-forming Network (SBN), following the successful launch of the TerreStar-1 satellite on July 1, 2009.

The Bureau previously granted TerreStar authority to conduct IOT with the TerreStar-1 satellite. In a series of applications,<sup>1</sup> TerreStar indicated that it was seeking authority under what was called Phase I operations, in which IOT would be conducted in the United States via three facilities to test the communications payload: (1) TerreStar-1, a Canadian-licensed satellite as to which TerreStar holds a letter of intent (“LOI”) authorization (Call Sign S2633) to serve the United States; (2) the 6.3-m and 9.3-m antennas associated with TerreStar’s licensed gateway earth station located in North Las Vegas, Nevada (Call Sign E070098); and (3) an unlicensed 1.8-m mobile earth terminal (“MET”)<sup>2</sup> that is co-located with TerreStar’s North Las Vegas gateway earth station. Phase I IOT is on-going consistent with the parameters sought in TerreStar’s initial STA requests.

In those same STA requests, TerreStar indicated that it would be filing a subsequent set of requests as part of Phase II operations in order to test the SBN. Accordingly, TerreStar is submitting the instant Phase II requests for that purpose. The Phase II requests cover IOT over the three facilities identified above and TerreStar’s Calibration Earth Stations (“CES”).<sup>3</sup>

This exhibit describes the operational parameters for Phase II IOT in the United States for the three facilities identified above and the CESs.

---

<sup>1</sup> The Bureau granted TerreStar an initial 30-day Special Temporary Authority until August 4, 2009, to operate, respectively, the gateway antennas licensed under Call Sign E070098 and a 1.8-m mobile earth terminal pursuant to the application requests submitted as SES-STA-20090625-00794 and SES-STA-20090523-00646. Furthermore, TerreStar filed requests seeking 60-day extensions of those STA’s pursuant to the application requests submitted as SES-STA-20090625-00795 and SES-STA-20090523-00644, which requests have been placed on Public Notice as accepted for filing.

<sup>2</sup> The 1.8-m MET, operating in a temporary fixed mode, uses a custom antenna that is designed for the express purpose of testing service link performance on TerreStar-1. The 1.8-m MET is entirely different from the MET handsets that will be used by TerreStar’s customers.

<sup>3</sup> TerreStar submitted an application (File No. SES-LIC-20090403-00405; Call Sign E090061) on April 1, 2009, seeking authority to operate a network of 15 technically identical calibration earth stations, at fixed locations which point to the TerreStar-1 satellite and dynamically calibrate the channel responses of the satellite beams. TerreStar’s application remains pending.

## Exhibit 1

A copy of this exhibit accompanies each of the STA requests TerreStar is filing in connection with the Phase II IOT. The STA request form this exhibit is attached to identifies, for each Phase II IOT STA request: (1) the time period for which an STA is sought; and (2) the facility for which an STA is sought.

Based on discussions with the FCC's staff, and in light of the fact that no FCC radio license has been issued for TerreStar-1, TerreStar is not filing any request for special temporary authority for the satellite in connection with IOT. Rather, TerreStar is identifying in the IOT STA requests relating to TerreStar's gateway earth station in North Las Vegas the parameters for TerreStar-1's operations during IOT that deviate from the parameters on which the LOI authorization for TerreStar-1 are based.

STA is required because the technical operations required for IOT go beyond the operations authorized by TerreStar's FCC licenses and authorizations. In particular, TerreStar requires authority for the following operations that are not already authorized:

- TerreStar-1: Use of unmodulated (CW) carriers not covered by the LOI authorization and use of power levels higher than are authorized by the LOI authorization
- NLV gateway: Use of unmodulated (CW) carriers in the 12.75-13.25 GHz band that are not covered by the license and use of power levels higher than are authorized by the license (this STA request includes a Comsearch report reflecting temporary coordination of the unmodulated carriers)
- NLV gateway: Use of higher power and wider bandwidth for 12.751 and 12.999 GHz command carriers than is authorized by the license and corresponding changes to the emission designators for the carriers. The EIRP, EIRP density, and bandwidth of these command carriers have been increased to 72 dBW, 48.8 dBW, and 832 KHz, respectively, from what is currently licensed (this STA request includes a Comsearch report reflecting temporary coordination of the higher power and wider bandwidth)
- NLV gateway: Feeder link transmissions on discrete frequencies in the upper half of the 12.75-13.25 GHz band (the gateway license authorizes transmissions only in the lower half of the band; this STA request includes a Comsearch report reflecting temporary coordination of the additional frequencies)

## Exhibit 1

- NLV gateway: Use of a different polarization and higher power for the 12.992 GHz CW pilot signal than is authorized by the license (the license shows right hand polarization; left hand polarization will be used). The EIRP and EIRP density of the pilot signal has been increased to 80 dBW from what is currently licensed (this STA request includes a Comsearch report reflecting temporary coordination of the CW carriers)
- NLV gateway: Use of wider bandwidth for 11.2005 GHz and 11.4495 GHz telemetry carriers than is authorized by the license and corresponding changes to the emission designators for the carriers. The bandwidth of these telemetry carriers have been increased to 400 KHz from what is currently licensed
- NLV gateway: Use of 5 MHz carriers in the 12.75-13.00 GHz band that are not covered by the license (this STA request includes a Comsearch report reflecting temporary coordination of the 5 MHz carriers)
- 1.8-m MET: Operation of this earth station, which has not been licensed
- CES terminals: Operation of TerreStar's 15 technically identical U.S. Calibration Earth Stations in accordance with the parameters specified in connection with application for a license to operate the Calibration Earth Stations
- CES terminals: Operation of unmodulated (CW) carriers (operation of these CW carriers is not requested in TerreStar's pending CES application), at higher EIRP than requested in TerreStar's CES application, by four of TerreStar's 15 U.S. CESs, located in San Manuel, AZ, Miami, FL, Austin, NV, and North Las Vegas, NV

### I. Introduction

TerreStar launched its TerreStar-1 satellite on July 1, 2009. The satellite has since its launch reached its assigned orbital slot of 111.0° W.L. Currently, all satellite systems are functioning normally and the satellite is undergoing the initial check-up of its major subsystems, including both the bus and the communication payload. TerreStar needs to perform IOT of its SBN payload, herein called Phase II IOT, which will commence near the conclusion of the



## Exhibit 1

Phase I IOT. The IOT will be performed by employees of TerreStar's satellite contractor, Space Systems Loral ("Loral"), under TerreStar's direction and supervision.

During this Phase II IOT, the components related to its Satellite Beam-forming Network will be tested as engineers check the combined payload performance with the Ground-Based Beam Forming ("GBBF") network to determine how well various S-band beams are formed. As the Commission is aware, the S-band antenna subsystem of TerreStar-1 satellite system is based on the so-called GBBF approach. As such, the ground GBBF equipment, which is housed at the TerreStar gateway sites at both North Las Vegas ("NLV"), NV and Allan Park ("AP"), Ontario, Canada, will need to be tested in a *combined* manner with the satellite S-band antenna and associated radiating elements to ascertain the actual beam-forming capabilities and performance. In addition, for the first time in orbit, TerreStar will obtain the actual beam patterns of the elemental beams which are essential to the beam-forming task and to compare them against the prediction.

The communication payload of the TerreStar-1 satellite consists of two repeater subsystems: one associated with the Forward channel and another one associated with the Return channel. The Forward channel refers to the Ku-to-S band signal path that originates from a Ku-band gateway facility to the satellite, and then traverses to an S-band device on the ground: in this instance the 1.8-m IOT antenna. The Return channel refers to the reverse link, *i.e.*, from an S-band device such as the 1.8-m IOT antenna to the satellite and then back to the Ku-band gateway on the ground.

Table 1 below summarizes the types of signals along with their characteristics that will be employed in each of the Forward payload and Return payload Phase II tests.

### II. Forward Payload Tests

With the exception of one test (noted in this section below), all test signals required in Forward payload tests will be transmitted from the GBBF equipment and gateway RF equipment located at NLV at Ku-band and converted to S-band frequencies before being downlinked by the satellite at S-band. The following key tests are planned to be conducted:

- Payload bake-out: At the beginning of the Phase II IOT, and toward the conclusion of the Phase I IOT, any residual moisture in the feed array needs to be purged in order to reduce the chances of multipaction or

## Exhibit 1

arcing inside waveguide sections carrying high power. All 64 active S-band TWTAAs will be driven near/at saturation to heat the feed array.

- Interface verification: The signal path from the GBBF equipment, through the gateway RF equipment, to the satellite forward link transponder, will be checked for connectivity for each of the 64 forward paths.
- Equalization verification: Verify that amplitude, phase, and delay equalization have been applied to two special single-element beams over NLV.
- Calibration verification: Verify that calibration circuitry can properly correct the feederlink-induced amplitude and phase errors.
- Pointing verification: Verify that GBBF equipment can correctly compensate for satellite pointing errors.
- Beamforming Accuracy test 1 (transmitted from NLV): Verify beamforming accuracy by measuring each beam response over NLV and compare it against prediction. The GBBF will be operating over the NLV band.
- Beamforming Accuracy test 1 (transmitted from AP): Verify beamforming accuracy by measuring each beam response over NLV and compare it against prediction. The GBBF will be operating over the AP band and the AP gateway RF equipment will be used.
- Frequency Response test: Verify the frequency response of a formed spot beam over NLV.
- Beamforming Advantage test: Verify the beam-forming gain of a formed spot beam over NLV compared to a single-element beam.

Regarding the S-band downlink, TerreStar is conscious of its interference-related responsibilities with respect to Fixed Service (FS) stations that are operating co-channel with TerreStar in the 2190-2200 MHz band in some locations. TerreStar has selected frequencies for S-band IOT test signals that are optimal for interference avoidance; all IOT test signals except the payload bake-out signals will be short in duration; and the number of transmissions during the test period will be limited. TerreStar has conducted a study and determined that these transmissions, including both the IOT test signals and the payload bake-out

signals, satisfy the interference-avoidance standards specified in TIA's Telecommunication System Bulletin (TSB) 86.

### III. Return Payload Tests

Most of the test signals required in Return payload tests will be transmitted from the 1.8-m IOT antenna and associated equipment located at NLV at S-band and converted to Ku-band frequencies before being downlinked by the satellite at Ku-band. As described in one of the paragraphs below, one test will involve S-band transmissions by four of TerreStar's Calibration Earth Stations ("CES"). The following key tests are planned to be conducted:

- Doppler Correction verification: Verify that the Doppler frequency shifts have been corrected for two elements over NLV with significant feederlink frequency separation. Both NLV and AP GBBF equipment will be checked.
- Calibration verification: Verify that calibration circuitry can properly correct the feederlink-induced amplitude and phase errors.
- Pointing verification: Verify that GBBF equipment can correctly compensate for satellite pointing errors.
- Beamforming Accuracy test 1: Verify beam-forming accuracy by measuring each beam response over NLV and compare it against prediction. Both NLV and AP GBBF equipment will be checked.
- Beamforming Accuracy test 2 (transmitted by CES stations): In this test, CES stations will transmit, one at a time and in addition to their normal calibration signals, a CW signal for testing purpose. The test is designed to check the beamforming accuracy using feeds that cover the CES stations used in the test. Additionally, the test will check the ATC nulling accuracy in the return channel. Up to four of TerreStar's CESs in the United States, located in in San Manuel, AZ, Miami, FL, Austin, NV, and North Las Vegas, NV, will be used in connection with this test.
- Frequency Response test: Verify the frequency response of a formed spot beam over NLV.
- Beamforming Advantage test: Verify the beam-forming gain of a formed spot beam over NLV compared to a single-element beam.

Regarding the IOT test signal transmissions at 2 GHz, TerreStar understands from Sprint's submissions to the Commission that BAS stations in both Las Vegas and the near-by Phoenix DMA clusters have been relocated from BAS channels 1 and 2 in the 1990-2025 MHz band.<sup>4</sup> TerreStar has selected 2004.90 MHz and 2008.10 MHz for S-band IOT transmissions to eliminate the possibility of interference to any BAS receiver. The frequencies selected provide 18 MHz or more of separation between the TerreStar CW test signal and BAS users in the Las Vegas or Phoenix DMAs who have migrated to the new BAS channel plan above 2025 MHz.

Similarly, there will be no interference to BAS from the S-band transmissions. TerreStar demonstrated in its CES application that its 15 CES stations are sufficiently removed from any BAS receive sites that there will be no interference to the receive sites from CES operations in accordance with the parameters specified in the application. Similarly, there will be no interference to BAS from operation of the four CES stations located in the US (at San Manuel, AZ, Miami, FL, Austin, NV, and North Las Vegas, NV) that are required in one of the return channel tests. This is because BAS channels 1 and 2 have been migrated out of the 1990-2025 MHz band in all four DMAs where the CES stations are located.

#### IV. Conclusion

TerreStar's request for STA is supported by good cause. Grant of the instant STA request is in the public interest, as it will enable TerreStar to perform in-orbit testing on its TerreStar-1 satellite and ensure the proper functioning of the satellite's communications payload in anticipation of providing service to the public over the satellite and the network's gateway antennas.

---

<sup>4</sup> Sprint's BAS Relocation web site indicates all DMAs in southern California have successfully transitioned to the BAS channel plan above 2025 MHz including Los Angeles, San Diego, Palm Springs and Bakersfield. See [http://www.2ghzrelocation.com/plugin/template/broadcast/Welcome/\\*](http://www.2ghzrelocation.com/plugin/template/broadcast/Welcome/*).

**Table 1. TerreStar SBN IOT Test Signal Characteristics**

	S-band EIRP (in dBW)	Bandwidth Used	S-band Frequency (in MHz)	Estimated Duration for each Test Signal Transmission (in minutes; see Notes 1 & 2)	Estimated Number of Instances of Test Signal Transmission (see Note 1)	Ku-band EIRP from/at NLV (in dBW)	Ku-band Frequency (in MHz)
<b><u>Forward Payload Tests</u></b>							
Payload bake-out	68	5 MHz per feed with a total of 64 feeds	2195-2200	2160	1	75	12750-13000
Interface verification	54	CW	2199.900 2193.609	1	130	80 (see Note 3)	(see Table 2)
Equalization verification	51.6	5 MHz	2195-2200	60	2	62	12750-13000
Calibration verification	72	2*CW	2199.910 2199.920	1	5	59	12750-13000
Pointing verification	72	4*CW	2199.890 2199.900 2199.910 2199.920	720	1	59	12750-13000
Beamforming Accuracy test 1 (transmitted from NLV)	72	4*CW	2199.890 2199.900 2199.910 2199.920	180	1	59	12750-13000

Exhibit 1

Beamforming Accuracy test 1 (transmitted from AP)	72	4*CW	2193.599 2193.609 2193.619 2193.629	180	1	N/A	13000-13250
Frequency Response test	62	5 MHz	2195-2200	30	1	72.5	12750-13000
Beamforming Advantage test	72	2*CW	2199.910 2199.920	5	1	59	12750-13000
<b><u>Return Payload Tests</u></b>							
Doppler Correction verification	37.8	CW	2008.1 (NLV) 2004.9 (AP)	N/A	N/A	45	10700-10950 11200-11450
Calibration verification	37.8	CW	2008.1 (NLV)	N/A	N/A	45	10700-10950 11200-11450
Pointing verification	37.8	CW	2008.1 (NLV)	N/A	N/A	45	10700-10950 11200-11450
Beamforming Accuracy test 1	37.8	CW	2008.1 (NLV) 2004.9 (AP)	N/A	N/A	45	10700-10950 11200-11450
Beamforming Accuracy test 2 (transmitted by 4 CES stations)	25	CW	2008.1 (NLV)	N/A	N/A	40	10700-10950 11200-11450
Frequency Response test	35.5	5 MHz	2005-2010 (NLV)	N/A	N/A	40	10700-10950 11200-11450

Exhibit 1

Beamforming Advantage test	30	CW	2008.1 (NLV)	N/A	N/A	35	10700- 10950 11200- 11450
-------------------------------	----	----	--------------	-----	-----	----	------------------------------------

**Note 1:** Each 10 MHz sweep or each forward path testing using a steady CW is considered as one Test Signal Transmission.

**Note 2:** Duration is the duration of the actual signal transmission and does not include the time it takes to maneuver the satellite or position the beams.

**Note 3:** Satellite is in off-nominal attitude mode.

**Note 4:** All entries are estimates.

Exhibit 1

Table 2. Ku-band Element Frequencies that correspond to Two S-band Test Signal Frequencies in Forward Payload Tests

Element No.	S-band 2199.9 MHz	S-band 2193.609 MHz
1	12764.9 MHz	13008.609 MHz
2	12771.9 MHz	13015.609 MHz
3	12778.9 MHz	13022.609 MHz
4	12785.9 MHz	13029.609 MHz
5	12792.9 MHz	13036.609 MHz
6	12799.9 MHz	13043.609 MHz
7	12806.9 MHz	13050.609 MHz
8	12813.9 MHz	13057.609 MHz
9	12820.9 MHz	13064.609 MHz
10	12827.9 MHz	13071.609 MHz
11	12834.9 MHz	13078.609 MHz
12	12841.9 MHz	13085.609 MHz
13	12848.9 MHz	13092.609 MHz
14	12855.9 MHz	13099.609 MHz
15	12862.9 MHz	13106.609 MHz
16	12869.9 MHz	13113.609 MHz
17	12876.9 MHz	13120.609 MHz
18	12883.9 MHz	13127.609 MHz
19	12890.9 MHz	13134.609 MHz
20	12897.9 MHz	13141.609 MHz
21	12904.9 MHz	13148.609 MHz
22	12911.9 MHz	13155.609 MHz
23	12918.9 MHz	13162.609 MHz
24	12925.9 MHz	13169.609 MHz
25	12932.9 MHz	13176.609 MHz
26	12939.9 MHz	13183.609 MHz
27	12946.9 MHz	13190.609 MHz
28	12953.9 MHz	13197.609 MHz
29	12960.9 MHz	13204.609 MHz
30	12967.9 MHz	13211.609 MHz
31	12974.9 MHz	13218.609 MHz
32	12981.9 MHz	13225.609 MHz



# FREQUENCY COORDINATION AND INTERFERENCE ANALYSIS REPORT

Prepared for  
TerreStar License Inc.  
N LAS VEGAS, NV  
(9.3 Meter)  
Satellite Earth Station

Prepared By:  
COMSEARCH  
19700 Janelia Farm Boulevard  
Ashburn, VA 20147  
April 20, 2009

## TABLE OF CONTENTS

1. CONCLUSIONS.....	3
2. SUMMARY OF RESULTS.....	4
3. SUPPLEMENTAL SHOWING.....	5
4. EARTH STATION COORDINATION DATA.....	6
5. CERTIFICATION.....	13

## **1. CONCLUSIONS**

An interference study for the proposed temporary testing considering all existing, proposed and prior coordinated microwave facilities within the coordination contours demonstrates that this earth station will operate satisfactorily with the common carrier microwave environment. Further, there will be no restrictions of its operation due to interference considerations.

## **2. SUMMARY OF RESULTS**

A number of great circle interference cases were identified during the interference study of the proposed earth station. Each of the cases, which exceeded the interference objective on a line-of-sight basis, was profiled and the propagation losses estimated using NBS TN101 (Revised) techniques. The losses were found to be sufficient to reduce the signal levels to acceptable magnitudes in most every case. Those cases that did not clear with terrain profiles will be resolved by either uplink power reduction, or frequency offset.

### 3. SUPPLEMENTAL SHOWING

Pursuant to Part 25.203(c) of the FCC Rules and Regulations, the satellite earth station proposed in this application was coordinated by Comsearch using computer techniques and in accordance with Part 25 of the FCC Rules and Regulations.

Coordination data for this earth station was sent to the below listed carriers with a letter dated 04/10/2009.

#### Company

Baja Broadband Operating Company, LLC  
CRANSTON ACQUISITION LLC  
Clark County School Dist., KLVX TV  
ENTRAVISION HOLDINGS, LLC  
JOURNAL BROADCASTING CORPORATION  
KUPN Licensee, LLC  
KVVU BROADCASTING CORPORATION  
LAS VEGAS TV PARTNERS LLC  
MOHAVE COUNTY BOARD OF SUPERVISORS  
NEVADA CHANNEL 3, INC  
NPG Cable, Inc dba Cablvsn Bullhead City  
Rio Virgin Telephone Company Inc  
TELEMUNDO LAS VEGAS LICENSE LLC  
TRI-STATE BROADCASTING, LLC  
UNA VEZ MAS ARIZONA, LLC  
VALLEY BROADCASTING COMPANY

## **4. EARTH STATION COORDINATION DATA**

This section presents the data pertinent to frequency coordination of the proposed earth station that was circulated to all carriers within its coordination contours.

# COMSEARCH

## Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147  
(703)726-5500 <http://www.comsearch.com>

Date:

04/10/2009

Job Number:

<PCNJobCode>

### Administrative Information

Status ENGINEER PROPOSAL  
Call Sign <PCNCallSign>  
Licensee Code TERNET  
Licensee Name TerreStar License Inc..

### Site Information

Venue Name **N LAS VEGAS, NV**  
Latitude (NAD 83) 36° 14' 9.9" N  
Longitude (NAD 83) 115° 7' 1.3" W  
Climate Zone A  
Rain Zone 5  
Ground Elevation (AMSL) 585.22 m / 1920.0 ft

### Link Information

Satellite Type Inclined Geo Orbit  
Mode TO - Transmit-Only  
Modulation Digital  
Minimum Elevation Angle 47.0° (+/- 10 degrees)  
Azimuth Range 106.5 degrees West Longitude (+/- 2 degrees)  
Antenna Centerline (AGL) 5.49 m / 18.0 ft

### Antenna Information

Manufacturer Transmit - FCC32  
Model Vertex/RSI  
Gain / Diameter 9.3 Meter  
3-dB / 15-dB Beamwidth 60.2 dBi / 9.3 m  
0.15° / 0.32°

Max Available RF Power (dBW/4 KHz) -0.2  
(dBW/MHz) 23.8  
Maximum EIRP (dBW/4 KHz) 60.0  
(dBW/MHz) 84.0

Interference Objectives: Long Term -151.0 dBW/4 KHz 20%  
Short Term -128.0 dBW/4 KHz 0.0025%

### Frequency Information

Emission / Frequency Range (MHz) Transmit 13.0 GHz  
NON / 13240.5 - 13245.5

Max Great Circle Coordination Distance  
Precipitation Scatter Contour Radius

161.6 km / 100.4 mi  
100.0 km / 62.1 mi

**COMSEARCH**  
**Earth Station Data Sheet**  
 19700 Janelia Farm Boulevard, Ashburn, VA 20147  
 (703)726-5500 <http://www.comsearch.com>

**Coordination Values**  
 License Name **N LAS VEGAS, NV**  
 Latitude (NAD 83) TerreStar License Inc..  
 36° 14' 9.9" N  
 Longitude (NAD 83) 115° 7' 1.3" W  
 Ground Elevation (AMSL) 585.22 m / 1920.0 ft  
 Antenna Centerline (AGL) 5.49 m / 18.0 ft  
 Antenna Model Vertex/RSI 9.3 meter  
 Antenna Mode  
 Interference Directives: Long Term Transmit 13.0 GHz  
 Short Term -151.0 dBW/4 KHz  
 Max Available RF Power -0.2 (dBW/4 KHz) 20%  
 -128.0 dBW/4 KHz 0.0025%

Azimuth (°)	Horizon		Antenna Discrimination (°)	Transmit 13.0 GHz	
	Elevation (°)	Gain (dbi)		Horizon Gain (dbi)	Coordination Distance (km)
0	0.00	76.33	-10.00	124.40	
5	0.00	71.95	-10.00	123.50	
10	0.00	67.61	-10.00	121.90	
15	0.00	63.31	-10.00	121.60	
20	0.00	59.08	-10.00	122.50	
25	0.00	54.92	-10.00	124.70	
30	0.00	50.86	-10.00	127.60	
35	0.00	46.93	-10.00	131.60	
40	0.00	43.16	-10.00	139.00	
45	0.00	39.61	-10.00	147.70	
50	0.00	36.35	-10.00	154.60	
55	0.00	33.45	-10.00	157.50	
60	0.00	31.02	-10.00	157.50	
65	0.00	29.18	-10.00	157.50	
70	0.00	28.05	-10.00	157.50	
75	0.00	27.72	-10.00	157.50	
80	0.00	28.21	-10.00	157.50	
85	0.00	29.49	-10.00	157.50	
90	0.00	31.45	-10.00	157.50	
95	0.00	33.98	-10.00	157.50	
100	0.00	36.95	-10.00	157.50	
105	0.00	40.28	-10.00	157.50	
110	0.00	43.88	-10.00	157.50	
115	0.00	47.68	-10.00	157.50	
120	0.00	51.64	-10.00	157.50	
125	0.00	55.72	-10.00	157.50	
130	0.00	59.89	-9.75	158.50	
135	0.00	64.14	-9.39	159.90	
140	0.00	68.45	-9.13	160.80	
145	0.00	72.80	-8.97	161.40	
150	0.00	77.18	-8.92	161.60	
155	0.00	81.59	-8.99	161.40	
160	0.00	86.00	-9.17	160.70	
165	0.00	90.43	-9.44	159.60	
170	0.00	94.85	-9.76	158.40	
175	0.00	99.27	-9.95	157.70	
180	0.00	103.67	-10.00	157.50	
185	0.00	108.05	-10.00	157.50	



# COMSEARCH

## Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147  
 (703)726-5500 <http://www.comsearch.com>

### Coordination Values

Licensee Name  
 Latitude (NAD 83)  
 Longitude (NAD 83)  
 Ground Elevation (AMSL)  
 Antenna Centerline (AGL)  
 Antenna Model  
 Antenna Mode  
 Interference Objectives: Long Term  
 Short Term  
 Max Available RF Power

**N LAS VEGAS, NV**  
 TerreStar License Inc..  
 36° 14' 9.9" N  
 115° 7' 1.3" W  
 585.22 m / 1920.0 ft  
 5.49 m / 18.0 ft  
 Vertex/RSI 9.3 meter

Transmit 13.0 GHz  
 -151.0 dBW/4 KHz  
 -128.0 dBW/4 KHz

20%  
 0.0025%

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Transmit 13.0 GHz	
			Horizon Gain (dbi)	Coordination Distance (km)
190	0.00	112.39	-10.00	157.50
195	0.00	116.69	-10.00	157.50
200	0.00	120.92	-10.00	157.50
205	0.00	125.08	-10.00	154.80
210	0.00	129.14	-10.00	151.20
215	0.00	133.07	-10.00	144.60
220	0.00	136.84	-10.00	130.70
225	0.00	140.39	-10.00	129.60
230	0.00	143.65	-10.00	128.30
235	0.00	146.55	-10.00	119.90
240	0.00	148.98	-10.00	118.00
245	0.00	150.82	-10.00	115.20
250	0.00	151.95	-10.00	114.70
255	0.00	152.28	-10.00	116.20
260	0.00	151.79	-10.00	115.70
265	0.00	150.51	-10.00	117.80
270	0.00	148.55	-10.00	120.60
275	0.00	146.02	-10.00	122.50
280	0.00	143.05	-10.00	123.60
285	0.00	139.72	-10.00	123.20
290	0.00	136.12	-10.00	121.80
295	0.00	132.32	-10.00	121.80
300	0.00	128.36	-10.00	121.70
305	0.00	124.28	-10.00	121.90
310	0.00	120.11	-10.00	120.80
315	0.00	115.86	-10.00	121.60
320	0.00	111.55	-10.00	122.60
325	0.00	107.20	-10.00	123.20
330	0.00	102.82	-10.00	123.70
335	0.00	98.41	-10.00	125.60
340	0.00	94.00	-10.00	129.90
345	0.00	89.57	-10.00	130.30
350	0.00	85.15	-10.00	127.40
355	0.00	80.73	-10.00	125.50

# COMSEARCH

## Earth Station Data Sheet

19700 Janella Farm Boulevard, Ashburn, VA 20147  
(703)726-5500 <http://www.comsearch.com>

04/09/2009

Date:  
Job Number:

<PCNJJobCode>

### Administrative Information

Status ENGINEER PROPOSAL  
Call Sign <PCNCallSign>  
Licensee Code TERNET  
Licensee Name TerreStar License Inc.

### Site Information

Venue Name **N LAS VEGAS, NV**  
Latitude (NAD 83) 36° 14' 9.9" N  
Longitude (NAD 83) 115° 7' 1.3" W  
Climate Zone A  
Rain Zone 5  
Ground Elevation (AMSL) 585.22 m / 1920.0 ft

### Link Information

Satellite Type Inclined Geo Orbit  
Mode TO - Transmit-Only  
Modulation Digital  
Minimum Elevation Angle 41.7°  
Azimuth Range 111.0 degrees West Longitude (+/- 6 degrees inclination)  
Antenna Centerline (AGL) 5.49 m / 18.0 ft

### Antenna Information

Manufacturer **Transmit - FCC32**  
Model Vertex/RSI  
Gain / Diameter 9.3 Meter  
3-dB / 15-dB Beamwidth 60.2 dBi / 9.3 m  
0.15° / 0.32°

Max Available RF Power (dBW/4 KHz) -11.38  
(dBW/MHz) 12.62  
Maximum EIRP (dBW/4 KHz) 48.82  
(dBW/MHz) 72.82

Interference Objectives: Long Term -151.0 dBW/4 KHz 20%  
Short Term -128.0 dBW/4 KHz 0.0025%

### Frequency Information

Emission / Frequency Range (MHz) **Transmit 13.0 GHz**  
832KGT0 / 12751.0 and 12999.0

Max Great Circle Coordination Distance 161.6 km / 100.4 mi  
Precipitation Scatter Contour Radius 100.0 km / 62.1 mi

**COMSEARCH**  
**Earth Station Data Sheet**  
 19700 Janelia Farm Boulevard, Ashburn, VA 20147  
 (703) 726-5500 <http://www.comsearch.com>

Coordination Values		N LAS VEGAS, NV	
License Name	TerreStar License Inc..		
Latitude (NAD 83)	36° 14' 9.9" N		
Longitude (NAD 83)	115° 7' 1.3" W		
Ground Elevation (AMSL)	585.22 m / 1920.0 ft		
Antenna Cen terline (AGL)	5.49 m / 18.0 ft		
Antenna Model	Vertex/RSI 9.3 meter		
Antenna Mode	Transmit 13.0 GHz		
Interference Objectives: Long Term	-151.0 dBW/4 KHz	20%	
Short Term	-128.0 dBW/4 KHz	0.0025%	
Max Available RF Power	-11.38 (dBW/4 KHz)		

Azimuth (°)	Horizon		Antenna Discrimination (°)	Transmit 13.0 GHz	
	Elevation (°)	Gain (dbi)		Horizon Gain (dbi)	Coordination Distance (km)
0	0.00		76.33	-10.00	124.40
5	0.00		71.95	-10.00	123.50
10	0.00		67.61	-10.00	121.90
15	0.00		63.31	-10.00	121.60
20	0.00		59.08	-10.00	122.50
25	0.00		54.92	-10.00	124.70
30	0.00		50.86	-10.00	127.60
35	0.00		46.93	-10.00	131.60
40	0.00		43.16	-10.00	139.00
45	0.00		39.61	-10.00	147.70
50	0.00		36.35	-10.00	154.60
55	0.00		33.45	-10.00	157.50
60	0.00		31.02	-10.00	157.50
65	0.00		29.18	-10.00	157.50
70	0.00		28.05	-10.00	157.50
75	0.00		27.72	-10.00	157.50
80	0.00		28.21	-10.00	157.50
85	0.00		29.49	-10.00	157.50
90	0.00		31.45	-10.00	157.50
95	0.00		33.98	-10.00	157.50
100	0.00		36.95	-10.00	157.50
105	0.00		40.28	-10.00	157.50
110	0.00		43.88	-10.00	157.50
115	0.00		47.68	-10.00	157.50
120	0.00		51.64	-10.00	157.50
125	0.00		55.72	-10.00	157.50
130	0.00		59.89	-9.75	158.50
135	0.00		64.14	-9.39	159.90
140	0.00		68.45	-9.13	160.80
145	0.00		72.80	-8.97	161.40
150	0.00		77.18	-8.92	161.60
155	0.00		81.59	-8.99	161.40
160	0.00		86.00	-9.17	160.70
165	0.00		90.43	-9.44	159.60
170	0.00		94.85	-9.76	158.40
175	0.00		99.27	-9.95	157.70
180	0.00		103.67	-10.00	157.50
185	0.00		108.05	-10.00	157.50

**COMSEARCH**  
**Earth Station Data Sheet**  
 19700 Janelia Farm Boulevard, Ashburn, VA 20147  
 (703)726-5500 <http://www.comsearch.com>

**Coordination Values**  
 License Name **N LAS VEGAS, NV**  
 Latitude (NAD 83) TerreStar License Inc..  
 Longitude (NAD 83) 36° 14' 9.9" N  
 115° 7' 1.3" W  
 Ground Elevation (AMSL) 585.22 m / 1920.0 ft  
 Antenna Centerline (AGL) 5.49 m / 18.0 ft  
 Antenna Model Vertex/RSI 9.3 meter  
 Antenna Mode  
 Interference Objectives: Long Term Transmit 13.0 GHz  
 Short Term -151.0 dBW/4 KHz  
 Max Available RF Power -11.38 (dBW/4 KHz) 20%  
 -128.0 dBW/4 KHz 0.0025%

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Transmit 13.0 GHz	
			Horizon Gain (db)	Coordination Distance (km)
190	0.00	112.39	-10.00	157.50
195	0.00	116.69	-10.00	157.50
200	0.00	120.92	-10.00	157.50
205	0.00	125.08	-10.00	154.80
210	0.00	129.14	-10.00	151.20
215	0.00	133.07	-10.00	144.60
220	0.00	136.84	-10.00	130.70
225	0.00	140.39	-10.00	129.60
230	0.00	143.65	-10.00	128.30
235	0.00	146.55	-10.00	119.90
240	0.00	148.98	-10.00	118.00
245	0.00	150.82	-10.00	115.20
250	0.00	151.95	-10.00	114.70
255	0.00	152.28	-10.00	116.20
260	0.00	151.79	-10.00	115.70
265	0.00	150.51	-10.00	117.80
270	0.00	148.55	-10.00	120.60
275	0.00	146.02	-10.00	122.50
280	0.00	143.05	-10.00	123.60
285	0.00	139.72	-10.00	123.20
290	0.00	136.12	-10.00	121.80
295	0.00	132.32	-10.00	121.80
300	0.00	128.36	-10.00	121.70
305	0.00	124.28	-10.00	121.90
310	0.00	120.11	-10.00	120.80
315	0.00	115.86	-10.00	121.60
320	0.00	111.55	-10.00	122.60
325	0.00	107.20	-10.00	123.20
330	0.00	102.82	-10.00	123.70
335	0.00	98.41	-10.00	125.60
340	0.00	94.00	-10.00	129.90
345	0.00	89.57	-10.00	130.30
350	0.00	85.15	-10.00	127.40
355	0.00	80.73	-10.00	125.50

## 5. CERTIFICATION

I HEREBY CERTIFY THAT I AM THE TECHNICALLY QUALIFIED PERSON RESPONSIBLE FOR THE PREPARATION OF THE FREQUENCY COORDINATION DATA CONTAINED IN THIS APPLICATION, THAT I AM FAMILIAR WITH PARTS 101 AND 25 OF THE FCC RULES AND REGULATIONS, THAT I HAVE EITHER PREPARED OR REVIEWED THE FREQUENCY COORDINATION DATA SUBMITTED WITH THIS APPLICATION, AND THAT IT IS COMPLETE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

BY: \_\_\_\_\_



Gary K. Edwards  
Senior Manager  
COMSEARCH  
19700 Janelia Farm Boulevard  
Ashburn, VA 20147

DATED: April 20, 2009

# FREQUENCY COORDINATION AND INTERFERENCE ANALYSIS REPORT

Prepared for  
TerreStar License Inc.  
NLAS VEGAS, NV  
(9.3 Meter)  
Satellite Earth Station

Prepared By:  
COMSEARCH  
19700 Janelia Farm Boulevard  
Ashburn, VA 20147  
May 14, 2009

## TABLE OF CONTENTS

1. CONCLUSIONS.....	3
2. SUMMARY OF RESULTS.....	4
3. SUPPLEMENTAL SHOWING.....	5
4. EARTH STATION COORDINATION DATA.....	6
5. CERTIFICATION.....	10

## **1. CONCLUSIONS**

An interference study considering all existing, proposed and prior coordinated microwave facilities within the coordination contours of the temporary proposed earth station uplink demonstrates that this site will operate satisfactorily with the common carrier microwave environment. Further, there will be no restrictions of its operation due to interference considerations.



## **2. SUMMARY OF RESULTS**

A number of great circle interference cases were identified during the interference study of the proposed temporary earth station uplink. Each of the cases, which exceeded the interference objective on a line-of-sight basis, was profiled and the propagation losses estimated using NBS TN101 (Revised) techniques. Sufficient losses were identified to reduce the signal levels to acceptable magnitudes in every case, thru terrain loss, frequency offset, or short term interference receive power level.

### 3. SUPPLEMENTAL SHOWING

Pursuant to Part 25.203(c) of the FCC Rules and Regulations, the satellite earth station proposed in this application was coordinated by Comsearch using computer techniques and in accordance with Part 25 of the FCC Rules and Regulations.

Coordination data for this earth station was sent to the below listed carriers with a letter dated 02/19/2009.

#### Company

Baja Broadband Operating Company, LLC  
CRANSTON ACQUISITION LLC  
Clark County School Dist., KLVX TV  
ENTRAVISION HOLDINGS, LLC  
JOURNAL BROADCASTING CORPORATION  
KUPN Licensee, LLC  
KVUU BROADCASTING CORPORATION  
LAS VEGAS TV PARTNERS LLC  
MOHAVE COUNTY BOARD OF SUPERVISORS  
NEVADA CHANNEL 3, INC  
NPG Cable, Inc dba Cablvsn Bullhead City  
Rio Virgin Telephone Company Inc  
SOUTHWEST MEDIA, LLC  
TELEMUNDO LAS VEGAS LICENSE LLC  
TRI-STATE BROADCASTING, LLC  
UNA VEZ MAS ARIZONA, LLC  
UNIVERSITY OF UTAH  
UTAH STATE BOARD OF REGENTS  
VALLEY BROADCASTING COMPANY

3G Wireless, LLC  
Broadcast Sports Corp  
Casper, John  
FISHMAN BROTHERS ENTERPRISES  
GOODYEAR TIRE AND RUBBER COMPANY  
Information Super Station LLC  
NSM Surveillance  
Production & Satellite Services, Inc.  
Regulus Media Services, Inc.  
REMOTE FACILITIES CONSULTING SERVICES  
RF Film, Inc  
RF Technology, LLC  
Total RF Marketing Inc  
Universal Satellite Communications Inc.  
WOLFE AIR AVIATION  
Wexler Video, Inc.  
Winged Vision Inc

## **4. EARTH STATION COORDINATION DATA**

This section presents the data pertinent to frequency coordination of the proposed earth station that was circulated to all carriers within its coordination contours.

**COMSEARCH**  
**Earth Station Data Sheet**  
19700 Janelia Farm Boulevard, Ashburn, VA 20147  
(703)726-5500 <http://www.comsearch.com>

Date: 03/09/2009  
Job Number: 090219CCOMSGE01

---

**Administrative Information**

Status ENGINEER PROPOSAL  
Call Sign E070098  
Licensee Code TERNET  
Licensee Name TerreStar License Inc..

---

**Site Information**

Venue Name **N LAS VEGAS, NV**  
Latitude (NAD 83) 36° 14' 9.9" N  
Longitude (NAD 83) 115° 7' 1.3" W  
Climate Zone A  
Rain Zone 5  
Ground Elevation (AMSL) 585.22 m / 1920.0 ft

---

**Link Information**

Satellite Type Inclined Geo Orbit  
Mode TR - Transmit-Only  
Modulation Digital  
Minimum Elevation Angle 41.7°  
Azimuth Range 111.0 degrees West Longitude (Azimuth 173.2 degrees)  
Antenna Centerline (AGL) 5.49 m / 18.0 ft

---

**Antenna Information**

Manufacturer **Transmit - FCC32**  
Model Vertex/RSI  
Gain / Diameter 9.3 Meter  
3-dB / 15-dB Beamwidth 60.2 dBi / 9.3 m  
0.30° / 0.64°

Max Available RF Power (dBW/4 KHz) (1) 19.8 (2) 1.8  
(dBW/MHz) 43.8 25.8

Maximum EIRP (dBW/4 KHz) 80.0 62.0  
(dBW/MHz) 104.0 86.0

Interference Objectives: Long Term -151.0 dBW/4 KHz 20%  
Short Term -128.0 dBW/4 KHz 0.0025%

---

**Frequency Information**

Emission / Frequency Range (MHz) **Transmit 13.0 GHz**  
(1) NON / 12750.0 - 13250.0  
(2) 5M00G7D / 12750.0 - 13000.0

Max Great Circle Coordination Distance 183.2 km / 113.8 mi  
Precipitation Scatter Contour Radius 100.0 km / 62.1 mi

**COMSEARCH**  
**Earth Station Data Sheet**  
 19700 Janella Farm Boulevard, Ashburn, VA 20147  
 (703) 726-5500 <http://www.comsearch.com>

**Coordination Values**

Licensee Name  
 Latitude (NAD 83)  
 Longitude (NAD 83)  
 Ground Elevation (AMSL)  
 Antenna Centerline (AGL)  
 Antenna Model  
 Antenna Mode  
 Interference Objectives: Long Term  
 Short Term  
 Max Available RF Power

**NLAS VEGAS, NV**

TerreStar License Inc..  
 36° 14' 9.9" N  
 115° 7' 1.3" W  
 585.22 m / 1920.0 ft  
 5.49 m / 18.0 ft  
 Vertex/RSI 9.3 meter  
 Transmit 13.0 GHz  
 -151.0 dBW/4 KHz 20%  
 -128.0 dBW/4 KHz 0.0025%  
 19.8 (dBW/4 KHz)

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Transmit 13.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)
0	0.63	76.41	-10.00	177.80
5	0.65	72.06	-10.00	177.80
10	0.69	67.76	-10.00	177.80
15	0.70	63.50	-10.00	177.80
20	0.68	59.29	-10.00	177.80
25	0.63	55.15	-10.00	177.80
30	0.56	51.10	-10.00	177.80
35	0.47	47.16	-10.00	177.80
40	0.39	43.38	-10.00	177.80
45	0.30	39.80	-10.00	177.80
50	0.23	36.51	-10.00	177.80
55	0.00	33.45	-10.00	177.80
60	0.00	31.02	-10.00	177.80
65	0.00	29.18	-10.00	177.80
70	0.00	28.05	-10.00	177.80
75	0.00	27.72	-10.00	177.80
80	0.00	28.21	-10.00	177.80
85	0.00	29.49	-10.00	177.80
90	0.00	31.45	-10.00	177.80
95	0.00	33.98	-10.00	177.80
100	0.00	36.95	-10.00	177.80
105	0.00	40.28	-10.00	177.80
110	0.00	43.88	-10.00	177.80
115	0.00	47.68	-10.00	177.80
120	0.00	51.64	-9.98	177.80
125	0.00	55.72	-9.52	179.60
130	0.00	59.89	-9.13	181.10
135	0.00	64.14	-8.82	183.20
140	0.00	68.45	-8.63	183.00
145	0.00	72.80	-8.55	183.20
150	0.00	77.18	-8.60	183.10
155	0.00	81.59	-8.78	182.40
160	0.00	86.00	-9.06	181.30
165	0.00	90.43	-9.43	179.90
170	0.00	94.85	-9.76	178.70
175	0.00	99.27	-9.95	177.80
180	0.00	103.67	-10.00	177.80
185	0.00	108.05	-10.00	177.80

**COMSEARCH**  
**Earth Station Data Sheet**  
 19700 Janelia Farm Boulevard, Ashburn, VA 20147  
 (703) 726-5500 <http://www.comsearch.com>

**Coordination Values**

Licensee Name **N LAS VEGAS, NV**  
 TerreStar License Inc..  
 Latitude (NAD 83) 36° 14' 9.9" N  
 Longitude (NAD 83) 115° 7' 1.3" W  
 Ground Elevation (AMSL) 585.22 m / 1920.0 ft  
 Antenna Centerline (AGL) 5.49 m / 18.0 ft  
 Antenna Model Vertex/RSI 9.3 meter  
 Antenna Mode Transmit 13.0 GHz  
 Interference Objectives: Long Term -151.0 dBW/4 KHz 20%  
 Short Term -128.0 dBW/4 KHz 0.0025%  
 Max Available RF Power 19.8 (dBW/4 KHz)

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Transmit 13.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)
190	0.00	112.39	-10.00	177.80
195	0.00	116.69	-10.00	177.80
200	0.00	120.92	-10.00	177.80
205	0.23	125.00	-10.00	177.80
210	0.26	129.03	-10.00	177.80
215	0.33	132.91	-10.00	177.80
220	0.50	136.56	-10.00	177.80
225	0.52	140.06	-10.00	177.80
230	0.55	143.26	-10.00	177.80
235	0.74	145.97	-10.00	177.80
240	0.78	148.30	-10.00	177.80
245	0.84	150.03	-10.00	177.80
250	0.85	151.11	-10.00	177.80
255	0.82	151.46	-10.00	177.80
260	0.83	150.97	-10.00	177.80
265	0.78	149.79	-10.00	177.80
270	0.72	147.93	-10.00	177.80
275	0.68	145.49	-10.00	177.80
280	0.65	142.59	-10.00	177.80
285	0.66	139.31	-10.00	177.80
290	0.69	135.74	-10.00	177.80
295	0.69	131.99	-10.00	177.80
300	0.69	128.07	-10.00	177.80
305	0.69	124.03	-10.00	177.80
310	0.71	119.89	-10.00	177.80
315	0.70	115.68	-10.00	177.80
320	0.67	111.41	-10.00	177.80
325	0.66	107.09	-10.00	177.80
330	0.65	102.74	-10.00	177.80
335	0.61	98.37	-10.00	177.80
340	0.52	93.98	-10.00	177.80
345	0.51	89.57	-10.00	177.80
350	0.57	85.17	-10.00	177.80
355	0.61	80.78	-10.00	177.80

## 5. CERTIFICATION

I HEREBY CERTIFY THAT I AM THE TECHNICALLY QUALIFIED PERSON RESPONSIBLE FOR THE PREPARATION OF THE FREQUENCY COORDINATION DATA CONTAINED IN THIS APPLICATION, THAT I AM FAMILIAR WITH PARTS 101 AND 25 OF THE FCC RULES AND REGULATIONS, THAT I HAVE EITHER PREPARED OR REVIEWED THE FREQUENCY COORDINATION DATA SUBMITTED WITH THIS APPLICATION, AND THAT IT IS COMPLETE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

BY: 

Gary K. Edwards  
Senior Manager  
COMSEARCH  
19700 Janelia Farm Boulevard  
Ashburn, VA 20147

DATED: May 14, 2009