

19700 Janelia Farm Boulevard

Ashburn, VA 20147

(703) 726-5500

Fax (703) 726-5600



COMSEARCH®

<http://www.comsearch.com>

July 24, 2011

*** CLIENT COPY ***
*** PLEASE MAIL ***
*** TO CUSTOMER ***

Re: Universal Space Network, Inc.
Naalehu, Hawaii
2 GHz Band Transmit/Receive Earth Station
Job Number: 110724COMSJC03

***** EXPEDITED FREQUENCY COORDINATION *****
***** RESPONSE REQUESTED BY AUGUST 5, 2011 *****

Dear Frequency Coordinator:

This notice is being provided in accordance with Section 25.203(c) of the FCC Rules and Regulations. We are forwarding the attached expedited coordination data on behalf of Universal Space Network, Inc. for the purpose of obtaining a STA to provide support services during the launch and early orbit testing of a new satellite from their existing transmit/receive earth station near Naalehu, Hawaii.

The coordination notice is being circulated to the owners (or their protection agents) of all existing or proposed terrestrial facilities operating in a shared frequency band within the coordination contours of the station(s).

Please update your database with the attached information.

We respectfully request that you examine this data for its interference potential with your system(s). In the event that your analysis identifies potential interference cases that were not previously reported, please contact Comsearch by August 5, 2011.

If there are any questions concerning this coordination notice, please contact Comsearch.

Sincerely,

COMSEARCH

Jeffrey E. Cowles
Engineer III, Telecommunications
jcowles@comsearch.com

Enclosure(s)

COMSEARCH
Earth Station Data Sheet
 19700 Janelia Farm Boulevard, Ashburn, VA 20147
 (703)726-5660 <http://www.comsearch.com>

Date: 07/24/2011
 Job Number: 110724COMSJC03

Administrative Information

Status ENGINEER PROPOSAL
 Call Sign NAALEHU
 Licensee Code UNSPNE
 Licensee Name Universal Space Network, Inc.

Site Information**NAALEHU, HAWAII**

Venue Name
 Latitude (NAD 83) 19° 0' 50.3" N
 Longitude (NAD 83) 155° 39' 46.6" W
 Climate Zone C
 Rain Zone 4
 Ground Elevation (AMSL) 378.0 m / 1240.2 ft

Link Information

Satellite Type Low Earth Orbit
 Mode TR – Transmit/Receive
 Modulation Digital
 Minimum Elevation Angle 5.0°
 Azimuth Range 0.0° to 360°
 Antenna Centerline (AGL) 8.53 m / 28.0 ft

Antenna Information**Receive****Transmit**

Manufacturer	Datron	Datron
Model	1453	1453
Gain / Diameter	46.9 dBi / 13.0 m	45.9 dBi / 13.0 m
3-dB / 15-dB Beamwidth	0.78° / 1.46°	0.76° / 1.46°
Max Available RF Power (dBW/4 kHz)		4.5
(dBW/MHz)		22.1
Maximum EIRP (dBW/4 kHz)		50.4
(dBW/MHz)		68.0
(dBW)		68.0
Interference Objectives: Long Term	-156.0 dBW/MHz 20%	-154.0 dBW/4 kHz 20%
Short Term	-146.0 dBW/MHz 0.01%	-131.0 dBW/4 kHz 0.0025%

Frequency Information**Receive 2.2 GHz****Transmit 2.0 GHz**

Emission / Frequency Range (MHz)	230KG2D / 2230.0000	230KG2D / 2053.4583
Max Great Circle Coordination Distance	1050.1 km / 652.4 mi	760.0 km / 472.2 mi
Precipitation Scatter Contour Radius	100.0 km / 62.1 mi	176.0 km / 109.3 mi

COMSEARCH**Earth Station Data Sheet**

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5660 <http://www.comsearch.com>

Coordination Values**NAALEHU, HI**

Licensee Name	Universal Space Network, Inc.			
Latitude (NAD 83)	19° 0' 50.3" N			
Longitude (NAD 83)	155° 39' 46.6" W			
Ground Elevation (AMSL)	378.0 m / 1240.2 ft			
Antenna Centerline (AGL)	8.54 m / 28.0 ft			
Antenna Model	Datron 1453			
Antenna Mode	Receive 2.2 GHz		Transmit 2.0 GHz	
Interference Objectives: Long Term	-156.0 dBW/MHz	20%	-154.0 dBW/4 kHz	20%
Short Term	-146.0 dBW/MHz	0.01%	-131.0 dBW/4 kHz	0.0025%
Max Available RF Power			4.5 (dBW/4 kHz)	

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 2.2 GHz		Transmit 2.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
0	2.78	5.0	4.50	662.10	4.50	365.00
5	2.62	5.0	4.50	671.20	4.50	374.40
10	2.39	5.0	4.50	685.10	4.50	388.60
15	2.30	5.0	4.50	690.80	4.50	394.30
20	2.17	5.0	4.50	699.20	4.50	403.00
25	2.03	5.0	4.50	708.80	4.50	412.70
30	1.68	5.0	4.50	734.80	4.50	439.30
35	0.90	5.0	4.50	811.80	4.50	517.90
40	0.33	5.0	4.50	911.20	4.50	619.40
45	0.00	5.0	4.50	1050.10	4.50	760.00
50	0.00	5.0	4.50	1050.10	4.50	760.00
55	0.00	5.0	4.50	1050.10	4.50	760.00
60	0.00	5.0	4.50	1050.10	4.50	760.00
65	0.00	5.0	4.50	1050.10	4.50	760.00
70	0.00	5.0	4.50	1050.10	4.50	760.00
75	0.00	5.0	4.50	1050.10	4.50	760.00
80	0.00	5.0	4.50	1050.10	4.50	760.00
85	0.00	5.0	4.50	1050.10	4.50	760.00
90	0.00	5.0	4.50	1050.10	4.50	760.00
95	0.00	5.0	4.50	1050.10	4.50	760.00
100	0.00	5.0	4.50	1050.10	4.50	760.00
105	0.00	5.0	4.50	1050.10	4.50	760.00
110	0.00	5.0	4.50	1050.10	4.50	760.00
115	0.00	5.0	4.50	1050.10	4.50	760.00
120	0.00	5.0	4.50	1050.10	4.50	760.00
125	0.00	5.0	4.50	1050.10	4.50	760.00
130	0.00	5.0	4.50	1050.10	4.50	760.00
135	0.00	5.0	4.50	1050.10	4.50	760.00
140	0.00	5.0	4.50	1050.10	4.50	760.00
145	0.00	5.0	4.50	1050.10	4.50	760.00
150	0.00	5.0	4.50	1050.10	4.50	760.00
155	0.00	5.0	4.50	1050.10	4.50	760.00
160	0.00	5.0	4.50	1050.10	4.50	760.00
165	0.00	5.0	4.50	1050.10	4.50	760.00
170	0.00	5.0	4.50	1050.10	4.50	760.00
175	0.00	5.0	4.50	1050.10	4.50	760.00
180	0.00	5.0	4.50	1050.10	4.50	760.00

COMSEARCH**Earth Station Data Sheet**

19700 Janelia Farm Boulevard, Ashburn, VA 20147
 (703)726-5660 <http://www.comsearch.com>

Coordination Values**NAALEHU, HI**

Licensee Name Universal Space Network, Inc.
 Latitude (NAD 83) 19° 0' 50.3" N
 Longitude (NAD 83) 155° 39' 46.6" W
 Ground Elevation (AMSL) 378.0 m / 1240.2 ft
 Antenna Centerline (AGL) 8.54 m / 28.0 ft
 Antenna Model Datron 1453

Antenna Mode	Receive 2.2 GHz		Transmit 2.0 GHz	
Interference Objectives: Long Term	-156.0 dBW/MHz	20%	-154.0 dBW/4 kHz	20%
Short Term	-146.0 dBW/MHz	0.01%	-131.0 dBW/4 kHz	0.0025%
Max Available RF Power			4.5 (dBW/4 kHz)	

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 2.2 GHz		Transmit 2.0 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
185	0.00	5.0	4.50	1050.10	4.50	760.00
190	0.00	5.0	4.50	1050.10	4.50	760.00
195	0.00	5.0	4.50	1050.10	4.50	760.00
200	0.00	5.0	4.50	1050.10	4.50	760.00
205	0.00	5.0	4.50	1050.10	4.50	760.00
210	0.00	5.0	4.50	1050.10	4.50	760.00
215	0.00	5.0	4.50	1050.10	4.50	760.00
220	0.00	5.0	4.50	1050.10	4.50	760.00
225	0.00	5.0	4.50	1050.10	4.50	760.00
230	0.00	5.0	4.50	1050.10	4.50	760.00
235	0.00	5.0	4.50	1050.10	4.50	760.00
240	0.00	5.0	4.50	1050.10	4.50	760.00
245	0.00	5.0	4.50	1050.10	4.50	760.00
250	0.00	5.0	4.50	1050.10	4.50	760.00
255	0.00	5.0	4.50	1050.10	4.50	760.00
260	0.00	5.0	4.50	1050.10	4.50	760.00
265	0.34	5.0	4.50	908.60	4.50	616.80
270	0.54	5.0	4.50	866.00	4.50	573.30
275	0.79	5.0	4.50	826.30	4.50	532.80
280	1.04	5.0	4.50	795.00	4.50	500.90
285	0.98	5.0	4.50	802.00	4.50	508.00
290	1.14	5.0	4.50	784.10	4.50	489.70
295	1.30	5.0	4.50	768.00	4.50	473.20
300	1.42	5.0	4.50	757.00	4.50	461.80
305	1.68	5.0	4.50	734.80	4.50	439.30
310	1.86	5.0	4.50	721.00	4.50	425.20
315	2.05	5.0	4.50	707.40	4.50	411.30
320	2.17	5.0	4.50	699.20	4.50	403.00
325	2.35	5.0	4.50	687.60	4.50	391.10
330	2.46	5.0	4.50	681.00	4.50	384.10
335	2.59	5.0	4.50	673.00	4.50	376.20
340	2.68	5.0	4.50	667.80	4.50	370.80
345	2.73	5.0	4.50	664.90	4.50	367.90
350	3.10	5.0	4.50	644.70	4.50	347.30
355	2.96	5.0	4.50	652.20	4.50	354.90