

COMSEARCH Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5660 <http://www.comsearch.com>

Date: 11/11/2012
Job Number: 121111COMSJC01

Administrative Information

Status: TEMPORARY (Operation from 12/07/2012 to 01/20/2013)
Call Sign: TEMP01
Licensee Code: INTELS
Licensee Name: Intelsat License LLC

Site Information

FILLMORE, CALIFORNIA

Venue Name
Latitude (NAD 83): 34° 24' 22.0" N
Longitude (NAD 83): 118° 53' 37.4" W
Climate Zone: A
Rain Zone: 4
Ground Elevation (AMSL): 313.94 m / 1030.0 ft

Link Information

Satellite Type: Low Earth Orbit
Mode: TO - Transmit-Only
Modulation: Digital
Minimum Elevation Angle: 5.0°
Azimuth Range: 0.0° to 360°
Antenna Centerline (AGL): 8.23 m / 27.0 ft

Antenna Information

Transmit

Manufacturer: Scientific-Atlanta
Model: 10.3 Meter
Gain / Diameter: 53.8 dBi / 10.3 m
3-dB / 15-dB Beamwidth: 0.40° / 0.60°

Max Available RF Power (dBW/4 kHz): 10.9
(dBW/MHz): 34.9

Maximum EIRP (dBW/4 kHz): 64.7
(dBW/MHz): 88.7
(dBW): 88.0

Interference Objectives: Long Term: -154.0 dBW/4 kHz 20%
Short Term: -131.0 dBW/4 kHz 0.0025%

Frequency Information

Transmit 6.1 GHz

Emission / Frequency Range (MHz): 850KFXD / 6420.0
850KFXD / 6421.5

Max Great Circle Coordination Distance: 347.9 km / 216.2 mi
Precipitation Scatter Contour Radius: 325.4 km / 202.2 mi

COMSEARCH**Earth Station Data Sheet**

19700 Janelia Farm Boulevard, Ashburn, VA 20147

(703)726-5660 <http://www.comsearch.com>

Coordination Values	FILLMORE, CA
Licensee Name	Intelsat License LLC
Latitude (NAD 83)	34° 24' 22.0" N
Longitude (NAD 83)	118° 53' 37.4" W
Ground Elevation (AMSL)	313.94 m / 1030.0 ft
Antenna Centerline (AGL)	8.23 m / 27.0 ft
Antenna Model	Scientific-Atlanta 10.3 Meter
Antenna Mode	Transmit 6.1 GHz
Interference Objectives: Long Term	-154.0 dBW/4 kHz 20%
Short Term	-131.0 dBW/4 kHz 0.0025%
Max Available RF Power	10.9 (dBW/4 kHz)

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Transmit 6.1 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)
0	9.45	76.90	-10.00	256.40
5	9.81	73.28	-10.00	256.40
10	11.84	70.32	-10.00	256.40
15	10.91	66.54	-10.00	256.40
20	12.89	64.07	-10.00	256.40
25	13.83	61.45	-10.00	256.40
30	11.05	56.89	-10.00	256.40
35	11.05	53.97	-10.00	256.40
40	11.16	51.36	-10.00	256.40
45	12.08	49.66	-10.00	256.40
50	12.02	47.53	-10.00	256.40
55	12.02	45.80	-10.00	256.40
60	11.89	44.32	-10.00	256.40
65	10.13	41.66	-10.00	256.40
70	10.13	41.15	-10.00	256.40
75	10.13	41.13	-7.96	269.20
80	8.91	40.41	-4.20	292.90
85	8.91	41.41	0.77	324.20
90	6.32	40.56	4.53	347.90
95	6.32	42.59	4.53	347.90
100	6.32	45.00	4.53	347.90
105	6.35	47.76	4.53	347.90
110	5.84	50.44	4.53	347.90
115	4.00	52.69	4.53	347.90
120	2.01	55.33	4.53	347.90
125	1.94	59.11	4.53	347.90
130	2.44	63.20	4.53	347.90
135	2.62	67.23	4.53	347.90
140	2.67	71.27	4.53	347.90
145	2.87	75.38	4.53	347.90
150	2.62	79.46	4.53	347.90
155	3.19	83.65	4.53	347.90
160	2.85	87.77	4.53	347.90
165	3.52	91.91	4.53	347.90
170	3.28	96.04	4.53	347.90
175	3.00	100.19	4.53	347.90
180	2.53	104.38	4.53	347.90
185	2.35	108.51	4.53	347.90

COMSEARCH**Earth Station Data Sheet**

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5660 <http://www.comsearch.com>

Coordination Values	FILLMORE, CA
Licensee Name	Intelsat License LLC
Latitude (NAD 83)	34° 24' 22.0" N
Longitude (NAD 83)	118° 53' 37.4" W
Ground Elevation (AMSL)	313.94 m / 1030.0 ft
Antenna Centerline (AGL)	8.23 m / 27.0 ft
Antenna Model	Scientific-Atlanta 10.3 Meter
Antenna Mode	Transmit 6.1 GHz
Interference Objectives: Long Term	-154.0 dBW/4 kHz 20%
Short Term	-131.0 dBW/4 kHz 0.0025%
Max Available RF Power	10.9 (dBW/4 kHz)

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Transmit 6.1 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)
190	2.28	112.57	4.53	347.90
195	0.78	117.05	4.53	347.90
200	0.41	121.18	4.53	347.90
205	1.23	124.74	4.53	347.90
210	0.97	128.61	4.53	347.90
215	0.94	132.22	4.53	347.90
220	0.00	136.21	4.53	347.90
225	0.00	139.42	4.53	347.90
230	0.00	142.31	4.53	347.90
235	0.00	144.80	4.53	347.90
240	0.00	146.79	4.53	347.90
245	0.00	148.21	4.53	347.90
250	0.00	148.95	4.53	347.90
255	0.00	148.97	4.53	347.90
260	0.00	148.28	4.53	347.90
265	0.00	146.92	4.53	347.90
270	0.00	144.96	4.53	347.90
275	1.12	141.62	0.77	324.20
280	1.30	138.71	-4.20	292.90
285	2.93	134.56	-7.96	269.20
290	4.19	130.57	-10.00	256.40
295	4.04	127.29	-10.00	256.40
300	4.42	123.56	-10.00	256.40
305	3.72	120.18	-10.00	256.40
310	3.09	116.58	-10.00	256.40
315	2.76	112.74	-10.00	256.40
320	3.33	108.58	-10.00	256.40
325	4.75	104.28	-10.00	256.40
330	5.93	100.12	-10.00	256.40
335	7.78	95.99	-10.00	256.40
340	8.25	92.08	-10.00	256.40
345	9.31	88.23	-10.00	256.40
350	9.65	84.45	-10.00	256.40
355	9.64	80.68	-10.00	256.40