

FREQUENCY COORDINATION AND INTERFERENCE ANALYSIS REPORT

Prepared for

**Anadarko Petroleum Corporation
Lucius Spar, Gulf of Mexico
(Oil Platform)**

Satellite Earth Station

Prepared By:
COMSEARCH
19700 Janelia Farm Boulevard
Ashburn, Virginia 20147
December 17, 2013

TABLE OF CONTENTS

1. CONCLUSIONS	3
2. SUMMARY OF RESULTS	4
3. SUPPLEMENTAL SHOWING	5
4. EARTH STATION COORDINATION DATA.....	6
5. CERTIFICATION.....	10

1. CONCLUSIONS

An interference study considering all existing, proposed and prior coordinated microwave facilities within the coordination contours of the proposed earth station demonstrates that this site will operate satisfactorily with the common carrier microwave environment. Further, there will be no restrictions of its operation due to interference considerations.

2. SUMMARY OF RESULTS

A number of great circle interference cases were identified during the interference study of the proposed earth station. Each of the cases, which exceeded the interference objective on a line-of-sight basis, was profiled and the propagation losses estimated using NBS TN101 (Revised) techniques. The losses were found to be sufficient to reduce the signal levels to acceptable magnitudes in every case.

The following companies reported potential great circle interference conflicts that did not meet the objectives on a line-of-sight basis. When over-the-horizon losses are considered on the interfering paths, sufficient blockage exists to negate harmful interference from occurring with the proposed transmit-receive earth station.

Company

None

No carriers reported potential interference cases.

3. SUPPLEMENTAL SHOWING

Pursuant to Part 25.203(c) of the FCC Rules and Regulations, the satellite earth station proposed in this application was coordinated by Comsearch using computer techniques and in accordance with Part 25 of the FCC Rules and Regulations.

Expedited coordination data for this earth station was faxed and sent to the below listed carriers with a letter dated November 22, 2013. An expedited revised coordination notice was faxed and sent on December 13, 2013.

Company

Comsearch

4. EARTH STATION COORDINATION DATA

This section presents the data pertinent to frequency coordination of the proposed earth station that was circulated to all carriers within its coordination contours.

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Date: 12/17/2013
Job Number: 131213COMSJC10

Administrative Information

Status ENGINEER PROPOSAL
Call Sign
Licensee Code S04815
Licensee Name Anadarko Petroleum Corporation

Site Information LUCIUS SPAR, GULF of MEXICO

Venue Name Oil Platform
Latitude (NAD 83) 26° 7' 54.8" N
Longitude (NAD 83) 92° 2' 25.1" W
Climate Zone B
Rain Zone 1
Ground Elevation (AMSL) 0.0 m / 0.0 ft

Link Information

Satellite Type Geostationary
Mode TR - Transmit-Receive
Modulation Digital
Satellite Arc 32° W to 139° West Longitude
Azimuth Range 104.2° to 247.6°
Corresponding Elevation Angles 18.4° / 30.3°
Antenna Centerline (AGL) 33.53 m / 110.0 ft

Antenna Information

	Receive	Transmit
Manufacturer	Sea Tel	Sea Tel
Model	9797	9797
Gain / Diameter	38.5 dBi / 2.4 m	41.7 dBi / 2.4 m
3-dB / 15-dB Beamwidth	2.04° / 3.80°	1.40° / 2.64°
Max Available RF Power (dBW/4 kHz)		-22.8
(dBW/MHz)		1.2
Maximum EIRP (dBW/4 kHz)		18.9
(dBW/MHz)		42.9
Interference Objectives:		
Long Term	-156.0 dBW/MHz 20%	-154.0 dBW/4 kHz 20%
Short Term	-146.0 dBW/MHz 0.01%	-131.0 dBW/4 kHz 0.0025%

Frequency Information

	Receive 4.0 GHz	Transmit 6.1 GHz
Emission / Frequency Range (MHz)	2M29G7W - 7M66G7W / 3700.0 - 4200.0	2M29G7W - 7M66G7W / 5925.0 - 6425.0
Max Great Circle Coordination Distance	562.8 km / 349.7 mi	152.3 km / 94.6 mi
Precipitation Scatter Contour Radius	585.0 km / 363.4 mi	100.0 km / 62.1 mi

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Coordination Values

LUCIUS SPAR, GM

Licensee Name Anadarko Petroleum Corporation
Latitude (NAD 83) 26° 7' 54.8" N
Longitude (NAD 83) 92° 2' 25.1" W
Ground Elevation (AMSL) 0.0 m / 0.0 ft
Antenna Centerline (AGL) 33.53 m / 110.0 ft
Antenna Model Sea Tel 9797
Antenna Mode Receive 4.0 GHz Transmit 6.1 GHz
Interference Objectives: Long Term -156.0 dBW/MHz 20% -154.0 dBW/4 kHz 20%
Short Term -146.0 dBW/MHz 0.01% -131.0 dBW/4 kHz 0.0025%
Max Available RF Power -22.8 (dBW/4 kHz)

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 4.0 GHz		Transmit 6.1 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
0	0.00	103.51	-10.00	412.20	-10.00	117.35
5	0.00	98.77	-10.00	412.20	-10.00	117.35
10	0.00	94.03	-10.00	412.20	-10.00	117.35
15	0.00	89.29	-10.00	412.20	-10.00	117.35
20	0.00	84.54	-10.00	412.20	-10.00	117.35
25	0.00	79.80	-10.00	412.20	-10.00	117.35
30	0.00	75.07	-10.00	412.20	-10.00	117.35
35	0.00	70.35	-10.00	412.20	-10.00	117.35
40	0.00	65.65	-10.00	412.20	-10.00	117.35
45	0.00	60.97	-10.00	412.20	-10.00	117.35
50	0.00	56.33	-10.00	412.20	-10.00	117.35
55	0.00	51.72	-10.00	412.20	-10.00	117.35
60	0.00	47.17	-9.84	414.16	-9.84	117.77
65	0.00	42.70	-8.76	427.87	-8.76	120.69
70	0.00	38.33	-7.59	443.25	-7.59	124.06
75	0.00	34.11	-6.32	460.52	-6.32	127.94
80	0.00	30.09	-4.96	479.17	-4.96	132.37
85	0.00	26.37	-3.53	500.33	-3.53	137.33
90	0.00	23.11	-2.09	522.49	-2.09	142.61
95	0.00	20.51	-0.80	543.28	-0.80	147.64
100	0.00	18.85	0.11	558.40	0.11	151.22
105	0.00	18.40	0.38	562.83	0.38	152.32
110	0.00	19.24	-0.10	554.76	-0.10	150.33
115	0.00	21.21	-1.16	537.38	-1.16	146.21
120	0.00	24.03	-2.52	515.81	-2.52	141.01
125	0.00	27.45	-3.97	493.79	-3.97	135.79
130	0.00	31.27	-5.38	473.15	-5.38	130.98
135	0.00	35.34	-6.71	455.20	-6.71	126.74
140	0.00	39.35	-7.87	439.47	-7.87	123.23
145	0.00	43.20	-8.89	426.24	-8.89	120.34
150	0.00	46.85	-9.77	415.09	-9.77	117.96
155	0.00	50.23	-10.00	412.20	-10.00	117.35
160	0.00	53.25	-10.00	412.20	-10.00	117.35
165	0.00	55.81	-10.00	412.20	-10.00	117.35
170	0.00	57.78	-10.00	412.20	-10.00	117.35
175	0.00	59.03	-10.00	412.20	-10.00	117.35
180	0.00	59.46	-10.00	412.20	-10.00	117.35
185	0.00	59.03	-10.00	412.20	-10.00	117.35

COMSEARCH

Earth Station Data Sheet

19700 Janelia Farm Boulevard, Ashburn, VA 20147
(703)726-5500 <http://www.comsearch.com>

Coordination Values


LUCIUS SPAR, GM

Licensee Name Anadarko Petroleum Corporation
Latitude (NAD 83) 26° 7' 54.8" N
Longitude (NAD 83) 92° 2' 25.1" W
Ground Elevation (AMSL) 0.0 m / 0.0 ft
Antenna Centerline (AGL) 33.53 m / 110.0 ft
Antenna Model Sea Tel 9797
Antenna Mode Receive 4.0 GHz Transmit 6.1 GHz
Interference Objectives: Long Term -156.0 dBW/MHz 20% -154.0 dBW/4 kHz 20%
Short Term -146.0 dBW/MHz 0.01% -131.0 dBW/4 kHz 0.0025%
Max Available RF Power -22.8 (dBW/4 kHz)

Azimuth (°)	Horizon Elevation (°)	Antenna Discrimination (°)	Receive 4.0 GHz		Transmit 6.1 GHz	
			Horizon Gain (dBi)	Coordination Distance (km)	Horizon Gain (dBi)	Coordination Distance (km)
190	0.00	57.78	-10.00	412.20	-10.00	117.35
195	0.00	55.81	-10.00	412.20	-10.00	117.35
200	0.00	53.25	-10.00	412.20	-10.00	117.35
205	0.00	50.23	-10.00	412.20	-10.00	117.35
210	0.00	46.85	-9.77	415.09	-9.77	117.96
215	0.00	43.35	-8.93	425.76	-8.93	120.24
220	0.00	40.10	-8.08	436.78	-8.08	122.63
225	0.00	37.16	-7.25	447.80	-7.25	125.07
230	0.00	34.62	-6.48	458.27	-6.48	127.43
235	0.00	32.58	-5.83	466.83	-5.83	129.52
240	0.00	31.15	-5.33	473.79	-5.33	131.13
245	0.00	30.39	-5.07	477.62	-5.07	132.01
250	0.00	30.37	-5.06	477.73	-5.06	132.04
255	0.00	31.08	-5.31	474.09	-5.31	131.20
260	0.00	32.49	-5.79	467.29	-5.79	129.63
265	0.00	34.49	-6.44	458.83	-6.44	127.56
270	0.00	37.00	-7.21	448.41	-7.21	125.21
275	0.00	39.92	-8.03	437.41	-8.03	122.77
280	0.00	43.16	-8.88	426.37	-8.88	120.37
285	0.00	46.66	-9.72	415.65	-9.72	118.08
290	0.00	50.35	-10.00	412.20	-10.00	117.35
295	0.00	54.20	-10.00	412.20	-10.00	117.35
300	0.00	58.17	-10.00	412.20	-10.00	117.35
305	0.00	62.24	-10.00	412.20	-10.00	117.35
310	0.00	66.38	-10.00	412.20	-10.00	117.35
315	0.00	70.58	-10.00	412.20	-10.00	117.35
320	0.00	74.83	-10.00	412.20	-10.00	117.35
325	0.00	79.11	-10.00	412.20	-10.00	117.35
330	0.00	83.41	-10.00	412.20	-10.00	117.35
335	0.00	87.72	-10.00	412.20	-10.00	117.35
340	0.00	92.04	-10.00	412.20	-10.00	117.35
345	0.00	96.35	-10.00	412.20	-10.00	117.35
350	0.00	100.65	-10.00	412.20	-10.00	117.35
355	0.00	104.93	-10.00	412.20	-10.00	117.35

5. CERTIFICATION

I HEREBY CERTIFY THAT I AM THE TECHNICALLY QUALIFIED PERSON RESPONSIBLE FOR THE PREPARATION OF THE FREQUENCY COORDINATION DATA CONTAINED IN THIS APPLICATION, THAT I AM FAMILIAR WITH PARTS 101 AND 25 OF THE FCC RULES AND REGULATIONS, THAT I HAVE EITHER PREPARED OR REVIEWED THE FREQUENCY COORDINATION DATA SUBMITTED WITH THIS APPLICATION, AND THAT IT IS COMPLETE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.



Jeffrey E. Cowles
Engineer III, Telecommunications
COMSEARCH
19700 Janelia Farm Boulevard
Ashburn, Va. 20147

DATED: December 17, 2013